

Produkte
Products

Prüfbericht - Nr.: 14026821 001

Test Report No.:

Seite 1 von 11

Page 1 of 11

Auftraggeber: Stadlbauer Marketing + Vertrieb GmbH
Client:
 Rennbahn Allee 1
 5412 Puch, Salzburg
 Austria

Gegenstand der Prüfung: Short Range Device - Low Power Transmitter (26.995MHz)
Test Item:

Bezeichnung: 900005 **Serien-Nr.:** Engineering sample
Identification: **Serial No.:**

Wareneingangs-Nr.: 00110512210-001 **Eingangsdatum:** 12.05.2011
Receipt No.: 00110613079-001 **Date of Receipt:** 16.06.2011

Prüfort: Hong Kong Productivity Council
Testing Location: HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

Prüfgrundlage: FCC Part 15, Subpart C
Test Specification:
 ANSI C63.4-2003
 CISPR 22:1997

Prüfergebnis: Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n).
Test Result: The test item passed the test specification(s).

Prüflaboratorium: TÜV Rheinland Hong Kong Ltd.
Testing Laboratory: 9th Floor, Emperor International Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

geprüft / tested by:

kontrolliert / reviewed by:

18.07.2011 Joey Leung
 Test Engineer



Datum Name/Stellung
 Date Name/Position

Unterschrift
 Signature

18.07.2011 Sharon Li
 Test Engineer



Datum Name/Stellung
 Date Name/Position

Unterschrift
 Signature

Sonstiges / Other Aspects:

FCCID: YFA900005-4

Abkürzungen: P(pass) = entspricht Prüfgrundlage
 F(fail) = entspricht nicht Prüfgrundlage
 N/A = nicht anwendbar
 N/T = nicht getestet

Abbreviations: P(pass) = passed
 F(fail) = failed
 N/A = not applicable
 N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
 This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

www.tuv.com

Test Summary

Radiated Emission of Carrier Frequency

Result: Pass

Spurious Radiated Emissions

Result: Pass

Bandwidth Measurement

Result: Pass

Contents

List of Test and Measurement Instruments.....	4
General Product Information	5
Product Function and Intended Use.....	5
Ratings and System Details.....	5
Independent Operation Modes.....	6
Submitted Documents	6
Related Submittal(s) Grants	6
Test Set-up and Operation Mode.....	7
Principle of Configuration Selection	7
Test Operation and Test Software	7
Special Accessories and Auxiliary Equipment.....	7
Countermeasures to achieve EMC Compliance.....	7
Test Methodology	8
Radiated Emission.....	8
Field Strength Calculation	8
Test Results	9
Radiated Emission of Carrier Frequency Subclause 15.227(a)	9
Spurious Radiated Emissions Subclause 15.227(b).....	10
Bandwidth Measurement.....	11
Appendix 1 Test Protocol	
Appendix 2 Test Setup	
Appendix 3 EUT External Photo	
Appendix 4 EUT Internal Photo	
Appendix 5 FCCID Label, Block Diagram, Schematics, BOM and User manual	

List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

Equipment	Manufacturer	Type	S/N	Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	25-May-12
Test Receiver	R & S	ESU26	100050	26-May-12
Bi-conical Antenna	R & S	HK116	100241	05-May-13
Log Periodic Antenna	R & S	HL223	841516/020	06-May-13
Coaxial cable 50ohm	Rosenberger	RTK081-05S-05S-10m	LA2-001-10M / 001	08-Dec-11
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	3950M00241	03-Oct-11
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	30-Oct-11
Horn Antenna	EMCO	3115	9002-3351	11-May-13
FSP 30 Spectrum Analyser	R & S	FSP 30	100286	17-Sep-12
Active Loop Antenna	EMCO	6502	9107-2651	19-Apr-12

General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a transmitter for a RC toy car operating at 26.995MHz. The EUT has a throttle control and a steering wheel. Throttle control is used to command the forward and backward movement while steering wheel is used to command left and right movement of the associated receiver.

Ratings and System Details

	Transmitter
Frequency range	: 26.995MHz
Number of channels	: 1
Type of antenna	: External Telescopic Antenna
Power supply	: Battery operated 9V
Ports	: none
Protection Class	: III

www.tuv.com

Independent Operation Modes

The basic operation modes are:

- Transmitting control signal for the RC toy car.

For further information refer to User Manual

Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork
- Bill of material

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Test Results

Radiated Emission of Carrier Frequency

Subclause 15.227(a)

RESULT:

Pass

Test Specification	:	FCC Part 15 Subclause 15.227(a)
Test Method	:	ANSI 63.4-2003
Measurement Location	:	Semi Anechoic Chamber
Measurement Distance	:	3m
Detector Function	:	Peak and Average
Measurement BW	:	120 kHz
Supply Voltage	:	DC 9V

Polarization: Vertical

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB μ V/m)	Delta to Limit (dB)
Peak	26.995	61.7	-38.3
Average	26.995	60.2	-19.8

Polarization: Horizontal

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB μ V/m)	Delta to Limit (dB)
Peak	26.995	44.3	-55.7
Average	26.995	42.5	-37.5

Limit	Subclause 15.227(a)			
Frequency within the band	Peak Emission		Average Emission	
	(μ V/m)	dB μ V/m	(μ V/m)	dB μ V/m
26.96-27.28 MHz	100,000	100.0	10,000	80.0

According to section 15.35(b), when average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Spurious Radiated Emissions
Subclause 15.227(b)
RESULT:
Pass

Test Specification	:	FCC Part 15 Subclause 15.209
Test Method	:	ANSI 63.4-2003
Measurement Location	:	Semi Anechoic Chamber
Measurement Distance	:	3m
Detector Function	:	Quasi Peak
Measurement BW	:	120 kHz
Supply Voltage	:	DC 9V
Measuring Frequency Range	:	30-1000MHz

Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Delta to Limit (dB)
40.487	30.7	40.0	-9.3
148.455	29.6	43.5	-13.9
175.474	28.1	43.5	-15.4
202.470	30.4	43.5	-13.1
215.968	27.7	43.5	-15.8

Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Delta to Limit (dB)
175.474	24.5	43.5	-19.0
188.972	21.7	43.5	-21.8
202.470	38.0	43.5	-5.5
215.968	33.9	43.5	-9.6

Remark: (1) '*' indicates the frequency of the emissions fall into the restricted band as defined in Section 15.205(a). They comply with the radiated emission limits specified in Section 15.209.
 (2) There is no spurious emission found between lowest oscillating frequency to 30 MHz.

Limit
Subclause 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

Limit for Radiated Emission under Section 15.209:

Frequency (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
30-88	100	$20 \log(100) = 40.0$	3
88-216	150	$20 \log(150) = 43.5$	3
216-960	200	$20 \log(200) = 46.0$	3
960-2500	500	$20 \log(500) = 54.0$	3

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

www.tuv.com

Bandwidth Measurement

Port of Testing : Antenna port
Detector Function : Peak
Supply Voltage : DC 9V

The field strength of any emissions appearing at the lower edge 26.96 MHz and upper edge 27.28 MHz are 45.07dB and 47.42dB below the carrier respectively.

For test results refer to Appendix 1.