

Prüfbericht - Nr.: 14032330 001

Test Report No.:

 Seite 1 von 11
 Page 1 of 11

Auftraggeber: Stadlbauer Marketing + Vertrieb Ges.M.B.H.
Client:
 Rennbahnallee 1
 5412 Puch, Salzburg
 Austria

Gegenstand der Prüfung: Short Range Device – Low Power Transmitter (27.145MHz)
Test Item:

Bezeichnung: 900022 **Serien-Nr.:** Engineering sample
Identification: **Serial No.:**

Wareneingangs-Nr.: 00130204157-004 **Eingangsdatum:** 04.02.2013
Receipt No.: **Date of Receipt:**

Zustand des Prüfgegenstandes bei Anlieferung: Test samples received are sufficient for testing
Condition of test item at delivery: and not damaged.

Prüfort: Global United Technology Services Co., Ltd.
Testing Location: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, China

Prüfgrundlage: FCC Part 15, Subpart C
Test Specification: ANSI C63.4-2003
 CISPR 22:1997

Prüfergebnis: Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n).
Test Result: The test item passed the test specification(s).

Prüflaboratorium: TÜV Rheinland Hong Kong Ltd.
Testing Laboratory: 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

geprüft / tested by:

 06.06.2013 Hugo Wan
 Senior Project Manager

 Datum Name/Stellung
 Date Name/Position



 06.06.2013 Sharon Li
 Assistant Manager

 Datum Name/Stellung
 Date Name/Position



Sonstiges / Other Aspects:

FCC ID: YFA900022

Abkürzungen: P(ass) = entspricht Prüfgrundlage
 Fail) = entspricht nicht Prüfgrundlage
 N/A = nicht anwendbar
 N/T = nicht getestet

Abbreviations: P(ass) = passed
 Fail) = failed
 N/A = not applicable
 N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
 This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Test Summary

Radiated Emission of Carrier Frequency

Result: Pass

Spurious Radiated Emissions

Result: Pass

Bandwidth Measurement

Result: Pass

Contents

List of Test and Measurement Instruments.....	4
General Product Information	5
Product Function and Intended Use.....	5
Ratings and System Details.....	5
Independent Operation Modes.....	6
Submitted Documents	6
Related Submittal(s) Grants	6
Test Set-up and Operation Mode.....	7
Principle of Configuration Selection	7
Test Operation and Test Software	7
Special Accessories and Auxiliary Equipment	7
Countermeasures to achieve EMC Compliance	7
Test Methodology	8
Radiated Emission.....	8
Field Strength Calculation	8
Test Results	9
Radiated Emission of Carrier Frequency Subclause 15.227(a).....	9
Spurious Radiated Emissions Subclause 15.227(b)	10
Bandwidth Measurement Subclause 15.215(c)	11
Appendix 1 Test Protocol	
Appendix 2 Test Setup	
Appendix 3 EUT External Photo	
Appendix 4 EUT Internal Photo	
Appendix 5 FCCID Label, Block Diagram, Schematics, BOM and User manual	

List of Test and Measurement Instruments

Global United Technology Services Co., Ltd. (Registration number: 600491)

Radiated Emission

Equipment	Manufacturer	Type	S/N	Cal Due Date
3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	--	5 Apr 2015
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	--	N/A
ESU EMI Test Receiver	R&S	ESU26	--	06 Jul 2013
Loop Antenna	Zhinan	ZN30900A	--	25 Jul 2013
Bi-log Hybrid Antenna	SCHWARZBECK	VULB9163	--	17 Mar 2014
Double-ridged horn antenna	SCHWARZBECK	9120D	--	17 Mar 2014
Horn Antenna	ETS-LINDGREN	3160-09	--	17 Mar 2014
RF Amplifier	HP	8347A	--	06 Jul 2013
RF Amplifier	HP	8349B	--	06 Jul 2013
EMI Test Software	AUDIX	E3	--	N/A
Coaxial cable	GTS	N/A	--	06 Jul 2013
Coaxial Cable	GTS	N/A	--	06 Jul 2013
Thermo meter	N/A	N/A	--	05 Jul 2013

General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a transmitter for a RC toy car operating at 27.145MHz. The EUT has 2 control rods to command the forward, backward, left and right movement of the associated receiver.

FCC ID: YFA900022

Model	Product description
900022	Radio Control Toy Transmitter

Ratings and System Details

	Transmitter
Frequency range	: 27.145MHz
Number of channels	: 1
Type of antenna	: External Telescopic Antenna
Antenna length	: 36 cm
Power supply	: 2 x AA size batteries, 3.0V DC
Ports	: none
Protection Class	: III

www.tuv.com

Independent Operation Modes

The basic operation modes are:

- Transmitting control signal for the RC toy Car.

For further information refer to User Manual

Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork
- Bill of materials

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Test Results

Radiated Emission of Carrier Frequency

Subclause 15.227(a)

RESULT:

Pass

Test Specification : FCC Part 15 Subclause 15.227(a)
 Test Method : ANSI 63.4-2003
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Peak and Average
 Measurement BW : 120 kHz
 Supply Voltage : 3.0V DC

Polarization: Vertical

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB μ V/m)	Delta to Limit (dB)
Peak	27.145	74.4	-25.6
Average	27.145	67.3	-12.7

Polarization: Horizontal

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB μ V/m)	Delta to Limit (dB)
Peak	27.145	59.6	-40.4
Average	27.145	49.9	-30.1

Limit

Subclause 15.227(a)

Frequency within the band	Peak Emission		Average Emission	
	(μ V/m)	dB μ V/m	(μ V/m)	dB μ V/m
26.96-27.28 MHz	100,000	100.0	10,000	80.0

According to section 15.35(b), when average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Spurious Radiated Emissions

Subclause 15.227(b)

RESULT:

Pass

Test Specification	:	FCC Part 15 Subclause 15.209
Test Method	:	ANSI 63.4-2003
Measurement Location	:	Semi Anechoic Chamber
Measurement Distance	:	3m
Detector Function	:	Quasi Peak
Measurement BW	:	120 kHz
Supply Voltage	:	3.0V DC
Measuring Frequency Range	:	30-1000MHz

Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dB _u V/m)	Limit at 3m (dB _u V/m)	Delta to Limit (dB)
No peak found	--	40.0	--

Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dB _u V/m)	Limit at 3m (dB _u V/m)	Delta to Limit (dB)
No peak found	--	40.0	--

Remark: (1) '*' indicates the frequency of the emissions fall into the restricted band as defined in Section 15.205(a). They comply with the radiated emission limits specified in Section 15.209.
 (2) There is no spurious emission found between lowest oscillating frequency to 30 MHz.

Limit

Subclause 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

Limit for Radiated Emission under Section 15.209:

Frequency (MHz)	Field strength (μ V/m)	Field strength (dB _u V/m)	Measurement distance (m)
30-88	100	$20 \log(100) = 40.0$	3
88-216	150	$20 \log(150) = 43.5$	3
216-960	200	$20 \log(200) = 46.0$	3
960-2500	500	$20 \log(500) = 54.0$	3

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

Bandwidth Measurement**Subclause 15.215(c)**

Port of Testing : Antenna port
Detector Function : Peak
Supply Voltage : 3.0V DC

The field strength of any emissions appearing at the lower edge 26.96 MHz and upper edge 27.28 MHz are 53.86 dB and 51.19 dB below the carrier respectively.

For test results refer to Appendix 1.

Limit**Subclause 15.215(c)**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in Section 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.