

FCC PART 15 CLASS B  
EMI MEASUREMENT AND TEST REPORT  
For

Whitebox International Limited  
Unit 04, 7/F, BRIGHT WAY TOWER, NO.33 MONG KOK ROAD, KOWLOON, HK

**FCC ID:YFDWH-NR-5502**

May 13, 2010

This Report Concerns: Original Report	Equipment Type : High Speed Wireless Router
Test Engineer:	Jack Liu
Report No.:	BST10050138ER-3
Receive EUT Date/Test Date:	May. 06,2010/ May 06-May 13,2010
Reviewed By:	Christina <i>Christina</i>
Prepared By:	 <p>Shenzhen BST Technology Co.,Ltd. 3F,Weames Technology Building, No. 10 Kefa Road,Science Park, Nanshan District,Shenzhen,Guangdong,China Tel: 0755-26747751 ~ 3 Fax: 0755-26747751 ~ 3 ext.826</p>

**Note:** The test report is specially limited to the above company and this particular sample only.  
It may not be duplicated without prior written consent of Shenzhen BST Technology Co.,Ltd.  
This report must not be used by the client to claim product certification,approval,or  
endorsement by NVLAP, NIST or any agency of the US Government.

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>3</b>
1.1. Report information.....	3
1.2. Measurement Uncertainty.....	3
<b>2. PRODUCT DESCRIPTION .....</b>	<b>4</b>
2.1. EUT Description .....	4
2.2. Block Diagram of EUT Configuration .....	4
2.3. Support Equipment List .....	4
2.4. Test Conditions .....	4
<b>3. FCC ID LABEL.....</b>	<b>5</b>
<b>4. TEST RESULTS SUMMARY .....</b>	<b>6</b>
Modifications .....	6
<b>5. TEST EQUIPMENT USED .....</b>	<b>7</b>
5.1. For Conducted Emission Test.....	7
5.2. For Radiated Emission Measurement .....	7
<b>6. CONDUCTED EMISSION TEST.....</b>	<b>8</b>
6.1. Block Diagram of Test Setup.....	8
6.2. Test Standard .....	8
6.3. Conducted Emission Limit(Class B) .....	8
6.4. EUT Configuration on Test .....	8
6.5. Operating Condition of EUT .....	8
6.6. Test Procedure .....	9
6.7. Test Result .....	9
<b>7. RADIATED EMISSION MEASUREMENT .....</b>	<b>10</b>
7.1. Block Diagram of EUT Configuration .....	10
7.2. Test Standard .....	10
7.3. Radiated Emission Limit(Class B) .....	10
7.4. EUT Configuration on Test .....	11
7.5. Operating Condition of EUT .....	11
7.6. Test Procedure .....	11
7.7. Test Result .....	11
<b>APPENDIX I .....</b>	<b>12</b>
<b>APPENDIX II.....</b>	<b>16</b>

## 1. GENERAL INFORMATION

### 1.1. Report information

1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BST approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BST in any way guarantees the later performance of the product/equipment.

1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BST therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BST, unless the applicant has authorized BST in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of  
Shenzhen Academy of Metrology & Quality Inspection  
(FCC Registered Test Site Number: 274801) on  
Bldg. Metrology & Quality Inspection, Longzhu Road, Nanshan,  
Shenzhen, Guangdong, China  
The Test Site is constructed and calibrated to meet the FCC requirements.

### 1.2. Measurement Uncertainty

Available upon request.

## 2. PRODUCT DESCRIPTION


### 2.1. EUT Description

Description : High Speed Wireless Router  
Applicant : Whitebox International Limited  
Unit 04, 7/F, BRIGHT WAY TOWER, NO.33 MONG KOK ROAD,  
KOWLOON, HK  
Model Number : WH-NR-5502, WH-NR-5502K, WH-NR-5502W, WH-NR-5502N,  
WH-NR-5502G, WH-NR-5502A, WH-NR-5502B, WH-NR-5502C,  
WH-NR-5502D

### Additional Information

Power Supply : DC 5V Power supply by adapter

### 2.2. Block Diagram of EUT Configuration



### 2.3. Support Equipment List

Adapter :  
MODEL: T10W-PA05A

### 2.4. Test Conditions

Temperature: 23~25

Relative Humidity: 55~63 %

### 3. FCC ID LABEL

**FCC ID:YFDWH-NR-5502**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: 1. This device may not cause harmful interference, and 2. This device must accept any interference received, including interference that may cause undesired operation.

#### Label Location on EUT

#### EUT Bottom View/ FCC ID Label Location



## 4. TEST RESULTS SUMMARY

**Table 1 Test Results Summary**

Test Items	Test Results
Conducted disturbance	Pass
Radiated disturbance	Pass

Remark: "N/A" means "Not applicable."

### Modifications

No modification was made.

## 5. TEST EQUIPMENT USED

### 5.1. For Conducted Emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESHS30	828985/018	Jun. 01, 09	1 Year
2.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	Jun. 01, 09	1 Year
3.	L.I.S.N.	Rohde & Schwarz	ESH2-Z5	834549/005	Jun. 01, 09	1 Year
4.	Conical	Emtek	N/A	N/A	N/A	N/A
5.	Voltage Probe	Schwarzbeck	TK9416	N/A	Jun. 01.09	1 Year
6.	Coaxial Switch	Anritsu	MP59B	6100214550	Jun. 01, 09	1 Year


### 5.2. For Radiated Emission Measurement

Anechoic Chamber

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	ANRITSU	MS2661C	6200140915	Jun 01,09	1 Year
2.	Test Receiver	Rohde&Schwarz	ESC830	828982/018	Jun 01,09	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	142	Jun 01,09	1 Year
4.	50 Coaxial Switch	Anritsu Corp	MP59B	6100237248	Jun 01,09	1 Year
5.	Cable	Schwarzbeck	AK9513	ACRX1	Jun 01,09	1 Year
6.	Cable	Rosenberger	N/A	FR2RX2	Jun 01,09	1 Year
7.	Cable	Schwarzbeck	AK9513	CRRX2	Jun 01,09	1 Year
8.	Cable	Schwarzbeck	AK9513	CRRX2	Jun 01,09	1 Year
9.	Single Phase Power Line Filter	MPE	23332C	N/A	Jun 01,09	1 Year
10.	Single Phase Power Line Filter	MPE	23333C	N/A	Jun 01,09	1 Year
11.	Signal Generator	HP	864A	3625U00573	Jun 01,09	1 Year

## 6. CONDUCTED EMISSION TEST

### 6.1. Block Diagram of Test Setup



### 6.2. Test Standard

FCC Part 15 CLASS B

### 6.3. Conducted Emission Limit(Class B)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. \*Decreasing linearly with logarithm of frequency.

### 6.4. EUT Configuration on Test

The following equipments are installed on conducted emission test to meet Part 15 requirement and operating in a manner, which tends to maximize its emission characteristics in a normal application.

#### 6.4.1. EUT Information

Model Number : **WH-NR-5502**  
 Serial Number : **N/A**

### 6.5. Operating Condition of EUT

6.5.1. Setup the EUT and simulators as shown in Section 5.1.

6.5.2. Turn on the power of all equipments.

6.5.3. Let the EUT work in test modes (EUT Working) and test it.

## **6.6. Test Procedure**

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions form both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

The bandwidth of the test receiver (R&S Test Receiver ESHS30) is set at 10KHz. and all the scanning waveform are attached within **Appendix I**.


## **6.7. Test Result**

**PASS**


## 7. RADIATED EMISSION MEASUREMENT

### 7.1. Block Diagram of EUT Configuration

7.1.1. Block Diagram of connection between the EUT and the simulators



7.1.2. Anechoic Chamber Test Setup Diagram



### 7.2. Test Standard

FCC Part 15 CLASS B

### 7.3. Radiated Emission Limit(Class B)

FREQUEN CY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMITS (dB $\mu$ V/m)
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
960 ~ 1000	3	54.0

Note:(1) The smaller limit shall apply at the edge between two frequency bands.

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT or system.

#### 7.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Measurement to meet the Commission requirements and operating regulations in a manner which tends to maximize Its emission characteristics in normal application.

#### 7.5. Operating Condition of EUT

7.5.1. Setup the EUT as shown on Section 6.1.2

7.5.2. Turn on the power of all equipments.

7.5.3. Let the EUT work in test mode(EUT working) and measure it.

#### 7.6. Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.

The bandwidth setting on the test receiver (R&S TEST RECEIVER ESCS20) is 120 KHz. The EUT is tested in Anechoic Chamber. The frequency range from 30MHz to 1000 MHz is checked. All the test results are listed in Section 7.7. and all the scanning waveform are attached within **Appendix II**.

#### 7.7. Test Result


**PASS**


## **APPENDIX I**

*Test Mode: operating(worse case mode)*

Line Conducted Emissions				FCC Part 15 CLASS B	
Frequency (MHz)	Amplitude (dB $\mu$ V)	Detector (QP/AV)	Conductor (Line/Neutral)	Limit (dB $\mu$ V)	Margin (dB)
3.800	41.20	AV	Hot	46.00	4.80
0.400	41.80	AV	Hot	47.85	6.05
1.500	39.50	AV	Hot	46.00	6.50
3.800	37.20	AV	Neutral	46.00	8.80
0.200	43.50	AV	Hot	53.61	10.11
23.590	39.40	AV	Hot	50.00	10.60
3.800	45.00	QP	Hot	56.00	11.00
0.200	50.60	QP	Hot	63.61	13.01
23.390	36.70	AV	Neutral	50.00	13.30
23.580	46.60	QP	Hot	60.00	13.40
0.200	39.50	AV	Neutral	53.61	14.11
7.490	35.70	AV	Hot	50.00	14.30
1.000	31.50	AV	Neutral	46.00	14.50
0.400	43.30	QP	Hot	57.85	14.55
0.500	41.10	QP	Neutral	56.00	14.90
1.500	40.90	QP	Hot	56.00	15.10
23.480	44.80	QP	Neutral	60.00	15.20
3.800	40.00	QP	Neutral	56.00	16.00
0.200	47.50	QP	Neutral	63.61	16.11
2.200	28.70	AV	Neutral	46.00	17.30
0.200	35.50	AV	Neutral	53.61	18.11
7.490	40.30	QP	Hot	60.00	19.70
1.000	34.60	QP	Neutral	56.00	21.40
2.200	32.00	QP	Neutral	56.00	24.00


Plot(s) of Test Data is presented hereinafter as reference.





## **APPENDIX II**

Test Mode: *operating* (worse case mode)



Frequency (MHz)	Corrected Amplitude (dB $\mu$ V/m)	Ant. Height (cm)	Ant. Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dB $\mu$ V/m)	Margin (dB)
551.995425	44.6	178.0	H	2.0	-5.8	46.0	1.4*
368.002200	43.3	105.0	H	269.0	-9.2	46.0	2.7*
54.949375	34.6	105.0	V	147.0	-17.7	40.0	5.4
276.007250	40.2	106.0	H	243.0	-11.1	46.0	5.8
64.167150	32.5	104.0	V	125.0	-17.1	40.0	7.5
73.188575	31.1	103.0	V	0.0	-16.9	40.0	8.9