AquaCheck (Pty) LTD

TEST REPORT FOR

Basic II Wireless Probe Model: ACBPROBE_xM

Tested To The Following Standards:

FCC Part 15 Subpart C Section 15.247

Report No.: 94367-6

Date of issue: April 14, 2014



This test report bears the accreditation symbol indicating that the testing performed herein meets the test and reporting requirements of ISO/IEC 17025 under the applicable scope of EMC testing for CKC Laboratories, Inc.

We strive to create long-term, trust based relationships by providing sound, adaptive, customer first testing services. We embrace each of our customers' unique EMC challenges, not as an interruption to set processes, but rather as the reason we are in business.

This report contains a total of 58 pages and may be reproduced in full only. Partial reproduction may only be done with the written consent of CKC Laboratories, Inc.



TABLE OF CONTENTS

Administrative Information	3
Test Report Information	3
Report Authorization	3
Test Facility Information	4
Software Versions	4
Site Registration & Accreditation Information	4
Summary of Results	5
Conditions During Testing	5
Equipment Under Test	6
Peripheral Devices	6
FCC Part 15 Subpart C	7
15.31(e) Voltage Variations	7
15.247(a)(2) Occupied Bandwidth	8
15.247(b)(3) RF Power Output	12
15.247(d) Antenna Conducted Emissions	16
15.247(d) Field Strength of Radiated Spurious Emissions and Band Edge	24
15. 247(e) Power Spectral Density	53
Supplemental Information	57
Measurement Uncertainty	57
Emissions Test Details	57



ADMINISTRATIVE INFORMATION

Test Report Information

REPORT PREPARED FOR: REPORT PREPARED BY:

AquaCheck (Pty) LTD Morgan Tramontin
1325 Hackberry St. CKC Laboratories, Inc.
Bennet, NE 68317 5046 Sierra Pines Drive
Mariposa, CA 95338

REPRESENTATIVE: Arthur Pickworth Project Number: 94367

DATE OF EQUIPMENT RECEIPT: March 17, 2014

DATE(S) OF TESTING: March 17 - April 9, 2014

Report Authorization

The test data contained in this report documents the observed testing parameters pertaining to and are relevant for only the sample equipment tested in the agreed upon operational mode(s) and configuration(s) as identified herein. Compliance assessment remains the client's responsibility. This report may not be used to claim product endorsement by A2LA or any government agencies. This test report has been authorized for release under quality control from CKC Laboratories, Inc.

Steve Behm

Director of Quality Assurance & Engineering Services CKC Laboratories, Inc.

Steve 7 Be



Test Facility Information



Our laboratories are configured to effectively test a wide variety of product types. CKC utilizes first class test equipment, anechoic chambers, data acquisition and information services to create accurate, repeatable and affordable test results.

TEST LOCATION(S): CKC Laboratories, Inc. 1120 Fulton Place Fremont, CA 94539

Software Versions

CKC Laboratories Proprietary Software	Version
EMITest Emissions	5.00.14
Immunity	5.00.07

Site Registration & Accreditation Information

Location	CB #	TAIWAN	CANADA	FCC	JAPAN
Fremont	US0082	SL2-IN-E-1148R	3082B-1	958979	A-0149



SUMMARY OF RESULTS

Standard / Specification: FCC Part 15 Subpart C

Test Procedure/Method	Description	Results
15.31(e)	Voltage Variation	Pass
15.247(a)(2) / DA 00-705	Occupied Bandwidth	Pass
15.247(b)(3) / DA 00-705	RF Power Output	Pass
15.247(d) / DA 00-705	Antenna Conducted Emissions	Pass
15.247(d) / DA 00-705	Field Strength of Radiated Spurious Emissions and Band Edge	Pass
15.247(e) / DA 00-705	Power Spectral Density	Pass

Conditions During Testing

This list is a summary of the conditions noted for or modifications made to the equipment during testing.

Sum	nmary of Conditions
Non	ne



EQUIPMENT UNDER TEST (EUT)

EQUIPMENT UNDER TEST

Basic II Wireless Probe

Manuf: AquaCheck (Pty) LTD Model: ACBPROBE_xM

Serial: 21648

900MHz Band Antenna

Manuf: SkyWare Antennas

Model: 16-1003-A Serial: None

PERIPHERAL DEVICES

The EUT was not tested with peripheral devices.

Batteries Lithium Pack

Manuf: QC Model: SB6044 Serial: None

GSW Wide Band Antenna

Manuf: RF Design

Model: ANT-GSM-ST-SM-M5

Serial: None

Page 6 of 58 Report No.: 94367-6



FCC PART 15 SUBPART C

This report contains EMC emissions test results under United States Federal Communications Commission (FCC) CFR 47 Section 15 Subpart C requirements for Intentional Radiators.

15.31(e) Voltage Variations

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: 15.31e Work Order #: 94367

Work Order #: 94367 Date: 3/28/2014
Test Type: Conducted Power Measurement Time: 08:25:41
Equipment: Basic II Wireless Probe Sequence#: 1

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE xM

S/N: 21648

Test Equipment:

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP01211	Attenuator	PE7002-10	4/2/2013	4/2/2015
T2	ANP06138	Cable	32022-29094K- 29094K-72TC	8/2/2013	8/2/2015
	AN03471	RF Characteristics Analyzer	E4440A	12/19/2013	12/19/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None

Support Devices:

Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

RF output power =10mW and attenuator "1"

RBW = 1MHzVBW = 3MHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is set to continuously transmit

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power

15.31e: Using the new batteries

Test Setup Photo(s)

Note: For section 15.31(e) it is not required to have a test setup photo.

Page 7 of 58 Report No.: 94367-6



15.247(a)(2) Occupied Bandwidth

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: **OBW**

Work Order #: 94367 Date: 3/28/2014
Test Type: Conducted Power Measurement Time: 08:25:41

Equipment: Basic II Wireless Probe Sequence#: 1

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE xM

S/N: 21648

Test Equipment:

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP01211	Attenuator	PE7002-10	4/2/2013	4/2/2015
T2	ANP06138	Cable	32022-29094K-	8/2/2013	8/2/2015
			29094K-72TC		
	AN03471	RF Characteristics Analyzer	E4440A	12/19/2013	12/19/2015

Equipment Under Test (* = EUT):

	•			
Function	Manufacturer	Model #	S/N	
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648	
Batteries Lithium Pack	OC	SB6044	None	

Support Devices:

WIFF THE THIRD				
Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

OBW Set up

RF output power =10mW and attenuator "1"

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz


The EUT is set to continuously transmit.

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.


Page 8 of 58 Report No.: 94367-6



Test Data




Low Channel



Middle Channel






High Channel



Test Setup Photo(s)



Test Setup



Test Setup - Close View



15.247(b)(3) RF Power Output

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: 15.247(b) Power Output (902-928 MHz DTS)

Work Order #: 94367 Date: 3/28/2014
Test Type: Conducted Power Measurement Time: 08:25:41

Equipment: Basic II Wireless Probe Sequence#: 1

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP01211	Attenuator	PE7002-10	4/2/2013	4/2/2015
T2	ANP06138	Cable	32022-29094K-	8/2/2013	8/2/2015
			29094K-72TC		
	AN03471	RF Characteristics Analyzer	E4440A	12/19/2013	12/19/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None

Support Devices:

WIFF THE THIRD				
Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

Fundamental of the EUT

RF output power =10mW and attenuator "1"

RBW = 1MHzVBW = 3MHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is set to continuously transmit.

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.

Page 12 of 58 Report No.: 94367-6




Ext Attn: 0 dB

Measu	rement Data:	Re	eading lis	ted by ma	argin.		Те	st Distand	ce: None		
#	Freq	Rdng	T1	T2			Dist	Corr	Spec	Margin	Polar
	MHz	dΒμV	dB	dB	dB	dB	Table	dΒμV	dΒμV	dB	Ant
1	918.992M	84.2	+9.9	+0.7			+0.0	94.8	137.0	-42.2	None
									High Char	nnel	
2	910.810M	82.9	+9.9	+0.7			+0.0	93.5	137.0	-43.5	None
									Middle Ch	annel	
3	902.768M	81.5	+9.9	+0.7			+0.0	92.1	137.0	-44.9	None
									Low Chan	nel	

Convert equivalent electric field strength to the resultant power level


Frequency (MHz)	Measured Power in Watts	Power Limit in Watts	Pass/Fail
Low Channel	0.000032359	1.00	Pass
Middle Channel	0.000044668	1.00	Pass
High Channel	0.000060256	1.00	Pass

Test Data




Low Channel





Middle Channel



High Channel



Test Setup Photo(s)



Test Setup



Test Setup - Close View



15.247(d) Antenna Conducted Emissions

The Reference level measurement for Emission is non restricted frequency bands were made using the methods set out in KDB "558704 D01 DTS Meas. Guidance v03r01", Section 11 Emissions in non-restricted frequency band Note: The Reference Level is the limit line for Radiated Spurious Emission and Conducted Spurious Emission.

	Reference level measurement in 100kHz Table								
Channel	Power Level (dBm)	Power Level (dBuV)	Reference level for Conducted	Power Level (dBuV/m)	Reference level for Radiated				
	(ubiii)	(ubuv)	(dBuV)	(ubuv/iii)	(dBuV/m)				
LO	-14.9	92.1	72.1	80.3	60.3				
MID	-13.5	93.5	73.5	81.7	61.7				
HI	-12.2	94.8	74.8	83.1	63.1				

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) Conducted Spurious Emissions

Work Order #: 94367 Date: 3/28/2014
Test Type: Conducted Spurious Emission Time: 11:00:12 AM

Equipment: Basic II Wireless Probe Sequence#: 4

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE xM

S/N: 21648

Test Equipment:

T Cot Equi	pintenti				
ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP01211	Attenuator	PE7002-10	4/2/2013	4/2/2015
T2	ANP06138	Cable	32022-29094K- 29094K-72TC	8/2/2013	8/2/2015
	AN03471	RF Characteristics Analyzer	E4440A	12/19/2013	12/19/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None

Support Devices:

Function Manufacturer Model #	S/N
-------------------------------	-----

Page 16 of 58 Report No.: 94367-6



Test Conditions / Notes:

Conducted Spurious Emission

Frequency Range: 9kHz to 10000MHz

RF output power =10mW and attenuator "1"

RBW = 100kHzVBW = 300kHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is set to continuously transmit.

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.

Low Channel


Ext Attn: 0 dB

Meas	urement Data:	Re	eading lis	ted by ma	argin.		Te	st Distance	e: None		
#	Freq	Rdng	T1	T2			Dist	Corr	Spec	Margin	Polar
	MHz	$dB\mu V$	dB	dB	dΒ	dB	Table	$dB\mu V$	dΒμV	dB	Ant
1	5416.341M	59.8	+10.1	+1.6			+0.0	71.5	72.1	-0.6	None
2	901.024M	42.0	+9.9	+0.7			+0.0	52.6	72.1	-19.5	None
3	6318.549M	38.4	+10.0	+1.8			+0.0	50.2	72.1	-21.9	None

Page 17 of 58 Report No.: 94367-6



CKC Laboratories, Inc. Date: 3/28/2014 Time: 11:00:12 AM AquaCheck (Pty) LTD WO#: 94367 Test Distance: None Sequence#: 4





Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) Conducted Spurious Emissions

Work Order #: 94367 Date: 3/28/2014
Test Type: Conducted Spurious Emission Time: 11:45:59

Equipment: Basic II Wireless Probe Sequence#: 5

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP01211	Attenuator	PE7002-10	4/2/2013	4/2/2015
T2	ANP06138	Cable	32022-29094K-	8/2/2013	8/2/2015
			29094K-72TC		
	AN03471	RF Characteristics Analyzer	E4440A	12/19/2013	12/19/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None

Support Devices:

Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

Conducted Spurious Emission

Frequency Range: 9kHz to 10000MHz

RF output power =10mW and attenuator "1"

RBW = 100kHzVBW = 300kHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is set to continuously transmit.

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.

Middle Channel


Page 19 of 58 Report No.: 94367-6



Ext Attn: 0 dB

Measurement Data: Reading listed by margin. Test Distance: None											
#	Freq	Rdng	T1	T2			Dist	Corr	Spec	Margin	Polar
	MHz	$dB\mu V$	dB	dB	dB	dB	Table	dΒμV	dΒμV	dB	Ant
	1 5464.809M	61.0	+10.1	+1.6			+0.0	72.7	73.5	-0.8	None
	2 6373.943M	34.6	+10.0	+1.8			+0.0	46.4	73.5	-27.1	None
	3 7286.989M	32.0	+10.0	+1.9			+0.0	43.9	73.5	-29.6	None

CKC Laboratories, Inc. Date: 3/28/2014 Time: 11:45:59 AquaCheck (Pty) LTD WO#: 94367 Test Distance: None Sequence#: 5





Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) Conducted Spurious Emissions

Work Order #: 94367 Date: 3/28/2014
Test Type: Conducted Spurious Emission Time: 9:38:51 AM

Equipment: **Basic II Wireless Probe** Sequence#: 3

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP01211	Attenuator	PE7002-10	4/2/2013	4/2/2015
T2	ANP06138	Cable	32022-29094K-	8/2/2013	8/2/2015
			29094K-72TC		
	AN03471	RF Characteristics Analyzer	E4440A	12/19/2013	12/19/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None

Support Devices:

Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

Conducted Spurious Emission

Frequency Range: 9kHz to 10000MHz

RF output power =10mW and attenuator "1"

RBW = 100kHzVBW = 300kHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is set to continuously transmit.

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.

High Channel


Page 21 of 58 Report No.: 94367-6



Ext Attn: 0 dB

Meas	urement Data:	Re	eading lis	ted by ma	argin.		Te	st Distance	e: None		
#	Freq	Rdng	T1	T2			Dist	Corr	Spec	Margin	Polar
	MHz	dΒμV	dB	dB	dB	dB	Table	dΒμV	dΒμV	dB	Ant
1	5510.976M	60.8	+10.0	+1.6			+0.0	72.4	74.8	-2.4	None
2	2 5513.979M	60.1	+10.0	+1.6			+0.0	71.7	74.8	-3.1	None
3	5513.378M	54.8	+10.0	+1.6			+0.0	66.4	74.8	-8.4	None

CKC Laboratories, Inc. Date: 3/28/2014 Time: 9:38:51 AM AquaCheck (Pty) LTD WO#: 94367 Test Distance: None Sequence#: 3





Test Setup Photo(s)



Test Setup



Test Setup - Close View



15.247(d) Field Strength of Radiated Spurious Emissions and Band Edge

The Reference level measurement for Emission is non restricted frequency bands were made using the methods set out in KDB "558704 D01 DTS Meas. Guidance v03r01", Section 11 Emissions in non-restricted frequency band Note: The Reference Level is the limit line for Radiated Spurious Emission and Conducted Spurious Emission. Choose the worst reference level for the limit line for Radiated Emission only.

	Reference level measurement in 100kHz Table							
Channel	Power Level (dBm)	Power Level (dBuV)	Reference level for Conducted (dBuV)	Power Level (dBuV/m)	Reference level for Radiated (dBuV/m)			
LO	-14.9	92.1	72.1	80.3	60.3			
MID	-13.5	93.5	73.5	81.7	61.7			
HI	-12.2	94.8	74.8	83.1	63.1			

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) / 15.209 Radiated Spurious Emissions

Work Order #: 94367 Date: 4/3/2014
Test Type: Radiated Scan Time: 13:44:17
Equipment: Basic II Wireless Probe Sequence#: 46

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE xM

S/N: 21648

Test Equipment:

1 cst Lqu	upinent.				
ID	Asset #	Description	Model	Calibration Date	Cal Due Date
	AN00432	Loop Antenna	6502	4/2/2013	4/2/2015
	ANP00880	Cable	RG214U	7/30/2012	7/30/2014
	ANP05300	Cable	RG214/U	3/25/2013	3/25/2015
	AN02668	Spectrum Analyzer	E4446A	2/22/2013	2/22/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None
900MHz Band Antenna	SkyWave Antennas	16-1003-A	None

Support Devices:

Function	Manufacturer	Model #	S/N	

Page 24 of 58 Report No.: 94367-6



Test Conditions / Notes:

Radiated Emission

Frequency Range: 9kHz to 30MHz

RF output power =10mW and attenuator "1"

Resolution bandwidth for restricted band

9 kHz -150 kHz;RBW=200 Hz,VBW=200 Hz; 150 kHz-30 MHz;RBW=9 kHz,VBW=9 kHz; 30 MHz-1000 MHz;RBW=120 kHz,VBW=120 kHz, 1000 MHz-10,000 MHz;RBW=1 MHz,VBW=1 MHz.

Resolution bandwidth for non-restricted band

RBW=100kHz, VBW=300kHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is placed on 80cm Styrofoam table. It is powered by 3.6VDC internal Batteries Lithium Package and set continuously transmit.

900MHz Band Antenna = 5.25dBi gain

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.

Low Channel

NO EMISSION HAS BEEN FOUND

Page 25 of 58 Report No.: 94367-6



Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) / 15.209 Radiated Spurious Emissions

 Work Order #:
 94367
 Date: 4/2/2014

 Test Type:
 Radiated Scan
 Time: 09:42:13

Equipment: Basic II Wireless Probe Sequence#: 8

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN00730	Preamp	8447D	1/17/2013	1/17/2015
T2	AN00852	Biconilog Antenna	CBL 6111C	11/28/2012	11/28/2014
Т3	ANP00880	Cable	RG214U	7/30/2012	7/30/2014
T4	ANP01183	Cable	CNT-195	9/3/2013	9/3/2015
T5	ANP05300	Cable	RG214/U	3/25/2013	3/25/2015
	AN02668	Spectrum Analyzer	E4446A	2/22/2013	2/22/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N	
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648	
900MHz Band Antenna	SkyWare Antennas	16-1003-A	None	
Batteries Lithium Pack	QC	SB6044	None	

Support Devices:

Support Derives				
Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

Radiated Emission

Frequency Range: 30MHz to 1000MHz RF output power =10mW and attenuator "1" Resolution bandwidth for restricted band

9 kHz -150 kHz;RBW=200 Hz,VBW=200 Hz; 150 kHz-30 MHz;RBW=9 kHz,VBW=9 kHz; 30 MHz-1000 MHz;RBW=120 kHz,VBW=120 kHz, 1000 MHz-10,000 MHz;RBW=1 MHz,VBW=1 MHz.

Resolution bandwidth for non-restricted band

RBW=100kHz, VBW=300kHz Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is placed on 80cm Styrofoam table. It is powered by 3.6VDC internal Batteries Lithium Package and set

continuously transmit

900MHz Band Antenna = 5.25dBi gain

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power

Low Channel


Page 26 of 58 Report No.: 94367-6



Ext Attn: 0 dB

Measur	rement Data:	Re	eading lis	ted by ma	argin.		Тє	est Distance	e: 3 Meters	1	
#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5								
	MHz	$dB\mu V$	dB	dB	dB	dB	Table	$dB\mu V/m$	$dB\mu V/m$	dB	Ant
1	110.363M	40.2	-27.0	+10.9	+1.0	+0.2	+0.0	25.6	43.5	-17.9	Vert
			+0.3								
2	115.528M	38.7	-26.9	+11.3	+1.0	+0.3	+0.0	24.7	43.5	-18.8	Vert
			+0.3								
3	129.942M	37.6	-27.0	+11.3	+1.1	+0.5	+0.0	23.8	43.5	-19.7	Vert
			+0.3								
4	611.864M	29.2	-26.9	+19.5	+2.7	+1.0	+0.0	26.2	46.0	-19.8	Horiz
			+0.7								
5	612.344M	28.6	-26.9	+19.5	+2.7	+1.0	+0.0	25.6	46.0	-20.4	Horiz
			+0.7								
6	990.734M	28.9	-27.3	+24.5	+3.6	+1.3	+0.0	32.0	54.0	-22.0	Horiz
			+1.0								

CKC Laboratories, Inc. Date: 4/2/2014 Time: 09:42:13 AquaCheck (Pty) LTD WO#: 94367 Test Distance: 3 Meters. Sequence#: 8





Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) / 15.209 Radiated Spurious Emissions

Work Order #: 94367 Date: 4/3/2014
Test Type: Radiated Scan Time: 10:28:49
Equipment: Basic II Wireless Probe Sequence#: 35

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

_ rest =qttq					
ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN03114	Preamp	AMF-7D-	4/11/2013	4/11/2015
			00101800-30-10P		
T2	AN02157	Horn Antenna-ANSI	3115	1/23/2013	1/23/2015
		C63.5			
Т3	AN03302	Cable	32026-29094K-	3/24/2014	3/24/2016
			29094K-72TC		
T4	ANP01210	Cable	FSJ1P-50A-4A	2/19/2013	2/19/2015
T5	ANP06125	Cable	32022-29094K-	5/6/2013	5/6/2015
			29094K-72TC		
	AN02668	Spectrum Analyzer	E4446A	2/22/2013	2/22/2015
T6	AN03172	High Pass Filter	HM1155-11SS	1/15/2014	1/15/2016
T7	ANDuty Cycle	<-Select Sub Type->	_	5/29/2013	5/29/2015
	Correct Factor				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None
900MHz Band Antenna	SkyWave Antennas	16-1003-A	None

Support Devices:

			~	
Function	Manufacturer	Model #	C/N	
Tunction	Manufacturei	1 VIOUCI π	5/19	

Test Conditions / Notes:

Radiated Emission

Frequency Range: 1000MHz to 10000MHz

RF output power =10mW and attenuator "1" Resolution bandwidth for restricted band

9 kHz -150 kHz;RBW=200 Hz,VBW=200 Hz; 150 kHz-30 MHz;RBW=9 kHz,VBW=9 kHz; 30 MHz-1000 MHz;RBW=120 kHz,VBW=120 kHz, 1000 MHz-10,000 MHz;RBW=1 MHz,VBW=1 MHz.

Resolution bandwidth for non-restricted band

RBW=100kHz, VBW=300kHz Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

> Page 28 of 58 Report No.: 94367-6



The EUT is placed on 80cm Styrofoam table. It is powered by 3.6VDC internal Batteries Lithium Package and set continuously transmit.

900MHz Band Antenna = 5.25dBi gain

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power. Low Channel


Ext Attn: 0 dB

Measi	irement Data:	Re	eading lis	ted by ma	argin.		Т	est Distance	e: 3 Meters		
#	Freq	Rdng	T1	T2	Т3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7						
	MHz	$dB\mu V$	dB	dB	dB	dB	Table	$dB\mu V/m$	$dB\mu V/m$	dB	Ant
1	5414.410M	87.2	-56.8	+34.7	+1.8	+4.0	+0.0	52.9	54.0	-1.1	Horiz
	Ave		+1.6	+0.1	-19.7						
^	5414.410M	87.4	-56.8	+34.7	+1.8	+4.0	+0.0	53.1	54.0	-0.9	Horiz
			+1.6	+0.1	-19.7						
3	4513.510M	80.3	-59.2	+32.5	+1.6	+3.7	+0.0	41.0	54.0	-13.0	Vert
			+1.6	+0.2	-19.7						
4	9027.840M	68.0	-56.7	+38.2	+2.3	+6.0	+0.0	40.5	54.0	-13.5	Vert
			+2.3	+0.1	-19.7						
5	3611.609M	79.1	-59.7	+31.4	+1.4	+3.1	+0.0	37.0	54.0	-17.0	Vert
			+1.3	+0.1	-19.7						
6	8122.115M	60.9	-57.4	+37.0	+2.2	+5.5	+0.0	31.0	54.0	-23.0	Horiz
			+2.4	+0.1	-19.7						
7	2707.706M	65.7	-59.0	+29.3	+1.2	+2.8	+0.0	21.9	54.0	-32.1	Horiz
			+1.4	+0.2	-19.7						

Page 29 of 58 Report No.: 94367-6



CKC Laboratories, Inc. Date: 4/3/2014 Time: 10:28:49 AquaCheck (Pty) LTD WO#: 94367 Test Distance: 3 Meters. Sequence#: 35





Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) / 15.209 Radiated Spurious Emissions

 Work Order #:
 94367
 Date: 4/3/2014

 Test Type:
 Radiated Scan
 Time: 13:45:13

Equipment: **Basic II Wireless Probe** Sequence#: 47

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

ĺ	ID	Asset #	Description	Model	Calibration Date	Cal Due Date
		AN00432	Loop Antenna	6502	4/2/2013	4/2/2015
ĺ		ANP00880	Cable	RG214U	7/30/2012	7/30/2014
ĺ		ANP05300	Cable	RG214/U	3/25/2013	3/25/2015
ĺ		AN02668	Spectrum Analyzer	E4446A	2/22/2013	2/22/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None
900MHz Band Antenna	SkyWave Antennas	16-1003-A	None

Support Devices:

Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

Radiated Emission

Frequency Range: 9kHz to 30MHz

RF output power =10mW and attenuator "1" Resolution bandwidth for restricted band

9 kHz -150 kHz;RBW=200 Hz,VBW=200 Hz; 150 kHz-30 MHz;RBW=9 kHz,VBW=9 kHz; 30 MHz-1000 MHz;RBW=120 kHz,VBW=120 kHz,

1000 MHz-10,000 MHz;RBW=1 MHz,VBW=1 MHz.

Resolution bandwidth for non-restricted band

RBW=100kHz, VBW=300kHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is placed on 80cm Styrofoam table. It is powered by 3.6VDC internal Batteries Lithium Package and set continuously transmit.

900MHz Band Antenna = 5.25dBi gain

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.

Middle Channel

NO EMISSION HAS BEEN FOUND

Page 31 of 58 Report No.: 94367-6



Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) / 15.209 Radiated Spurious Emissions

Work Order #: 94367 Date: 4/2/2014
Test Type: Radiated Scan Time: 10:17:42
Equipment: Basic II Wireless Probe Sequence#: 11

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE xM

S/N: 21648

Test Equipment:

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN00730	Preamp	8447D	1/17/2013	1/17/2015
T2	AN00852	Biconilog Antenna	CBL 6111C	11/28/2012	11/28/2014
T3	ANP00880	Cable	RG214U	7/30/2012	7/30/2014
T4	ANP01183	Cable	CNT-195	9/3/2013	9/3/2015
T5	ANP05300	Cable	RG214/U	3/25/2013	3/25/2015
	AN02668	Spectrum Analyzer	E4446A	2/22/2013	2/22/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N	
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648	
900MHz Band Antenna	SkyWare Antennas	16-1003-A	None	
Batteries Lithium Pack	QC	SB6044	None	

Support Devices:

Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

Radiated Emission

Frequency Range: 30MHz to 1000MHz RF output power =10mW and attenuator "1" Resolution bandwidth for restricted band

9 kHz -150 kHz;RBW=200 Hz,VBW=200 Hz; 150 kHz-30 MHz;RBW=9 kHz,VBW=9 kHz; 30 MHz-1000 MHz;RBW=120 kHz,VBW=120 kHz, 1000 MHz-10,000 MHz;RBW=1 MHz,VBW=1 MHz.

Resolution bandwidth for non-restricted band

RBW=100kHz, VBW=300kHz Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is placed on 80cm Styrofoam table. It is powered by 3.6VDC internal Batteries Lithium Package and set

continuously transmit.

900MHz Band Antenna = 5.25dBi gain

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.

Middle Channel


Page 32 of 58 Report No.: 94367-6



Ext Attn: 0 dB

Measur	rement Data:	Re	eading lis	ted by ma	argin.		Те	est Distance	e: 3 Meters		
#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5								
	MHz	dΒμV	dB	dB	dB	dB	Table	$dB\mu V/m$	dBμV/m	dB	Ant
1	132.825M	43.7	-27.0	+11.4	+1.1	+0.5	+0.0	30.0	43.5	-13.5	Vert
			+0.3								
2	120.333M	37.3	-27.0	+11.3	+1.1	+0.3	+0.0	23.3	43.5	-20.2	Vert
			+0.3								
3	611.143M	28.7	-26.9	+19.4	+2.7	+1.0	+0.0	25.6	46.0	-20.4	Horiz
			+0.7								
4	115.047M	36.7	-26.9	+11.3	+1.0	+0.3	+0.0	22.7	43.5	-20.8	Vert
			+0.3								
5	608.020M	28.3	-26.9	+19.1	+2.7	+1.0	+0.0	24.9	46.0	-21.1	Horiz
			+0.7								
6	974.142M	29.0	-27.2	+24.4	+3.6	+1.3	+0.0	32.0	54.0	-22.0	Horiz
			+0.9								

CKC Laboratories, Inc. Date: 4/2/2014 Time: 10:17:42 AquaCheck (Pty) LTD WO#: 94367 Test Distance: 3 Meters Sequence#: 11





Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) / 15.209 Radiated Spurious Emissions

Work Order #: 94367 Date: 4/3/2014
Test Type: Radiated Scan Time: 11:14:51
Equipment: Basic II Wireless Probe Sequence#: 38

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

1 ем Едигриен:							
ID	Asset #	Description	Model	Calibration Date	Cal Due Date		
T1	AN03114	Preamp	AMF-7D-	4/11/2013	4/11/2015		
			00101800-30-10P				
T2	AN02157	Horn Antenna-ANSI	3115	1/23/2013	1/23/2015		
		C63.5					
Т3	AN03302	Cable	32026-29094K-	3/24/2014	3/24/2016		
			29094K-72TC				
T4	ANP01210	Cable	FSJ1P-50A-4A	2/19/2013	2/19/2015		
T5	ANP06125	Cable	32022-29094K-	5/6/2013	5/6/2015		
			29094K-72TC				
	AN02668	Spectrum Analyzer	E4446A	2/22/2013	2/22/2015		
Т6	AN03172	High Pass Filter	HM1155-11SS	1/15/2014	1/15/2016		
T7	ANDuty Cycle	<-Select Sub Type->		5/29/2013	5/29/2015		
	Correct Factor						

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None
900MHz Band Antenna	SkyWave Antennas	16-1003-A	None

Support Devices:

E atian	Manuela atuman	Madal #	C/NI	
Function	Manufacturer	Model #	3 /1 N	

Test Conditions / Notes:

Radiated Emission

Frequency Range: 1000MHz to 10000MHz RF output power =10mW and attenuator "1" Resolution bandwidth for restricted band

9 kHz -150 kHz;RBW=200 Hz,VBW=200 Hz; 150 kHz-30 MHz;RBW=9 kHz,VBW=9 kHz; 30 MHz-1000 MHz;RBW=120 kHz,VBW=120 kHz, 1000 MHz-10,000 MHz;RBW=1 MHz,VBW=1 MHz.

Resolution bandwidth for non-restricted band

RBW=100kHz, VBW=300kHz Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

> Page 34 of 58 Report No.: 94367-6



The EUT is placed on 80cm Styrofoam table. It is powered by 3.6VDC internal Batteries Lithium Package and set continuously transmit.

900MHz Band Antenna = 5.25dBi gain

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power. Middle Channel


Ext Attn: 0 dB

Measurement Data:		Re	eading lis	ted by ma	argin.		Тє	est Distance	e: 3 Meters		
#	Freq	Rdng	T1	T2	Т3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7						
	MHz	dΒμV	dB	dB	dB	dB	Table	$dB\mu V/m$	$dB\mu V/m$	dB	Ant
1	5446.442M	59.6	-56.8	+34.7	+1.8	+4.0	+0.0	45.0	54.0	-9.0	Horiz
			+1.6	+0.1	+0.0						
2	7286.280M	75.4	-59.2	+36.5	+2.1	+5.4	+0.0	42.7	54.0	-11.3	Horiz
			+2.0	+0.2	-19.7						
3	9103.232M	65.8	-56.7	+38.2	+2.3	+6.0	+0.0	38.2	54.0	-15.8	Vert
			+2.2	+0.1	-19.7						
4	4551.548M	76.3	-59.1	+32.5	+1.6	+3.7	+0.0	37.1	54.0	-16.9	Vert
			+1.6	+0.2	-19.7						
5	3641.639M	78.3	-59.4	+31.6	+1.4	+3.2	+0.0	36.9	54.0	-17.1	Vert
			+1.4	+0.1	-19.7						
6	8196.189M	58.9	-57.2	+37.0	+2.2	+5.6	+0.0	29.4	54.0	-24.6	Horiz
			+2.5	+0.1	-19.7						

Page 35 of 58 Report No.: 94367-6



CKC Laboratories, Inc. Date: 4/3/2014 Time: 11:14:51 AquaCheck (Pty) LTD WO#: 94367 Test Distance: 3 Meters. Sequence#: 38





Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) / 15.209 Radiated Spurious Emissions

Work Order #: 94367 Date: 4/3/2014
Test Type: Radiated Scan Time: 13:30:10
Equipment: Basic II Wireless Probe Sequence#: 45

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

ĺ	ID	Asset #	Description	Model	Calibration Date	Cal Due Date
		AN00432	Loop Antenna	6502	4/2/2013	4/2/2015
ĺ		ANP00880	Cable	RG214U	7/30/2012	7/30/2014
ĺ		ANP05300	Cable	RG214/U	3/25/2013	3/25/2015
ĺ		AN02668	Spectrum Analyzer	E4446A	2/22/2013	2/22/2015

Equipment Under Test (* = EUT):

1 1	- /-		
Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None
900MHz Band Antenna	SkyWave Antennas	16-1003-A	None

Support Devices:

Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

Radiated Emission

Frequency Range: 9kHz to 30MHz

RF output power =10mW and attenuator "1" Resolution bandwidth for restricted band

9 kHz -150 kHz;RBW=200 Hz,VBW=200 Hz; 150 kHz-30 MHz;RBW=9 kHz,VBW=9 kHz; 30 MHz-1000 MHz;RBW=120 kHz,VBW=120 kHz,

1000 MHz-10,000 MHz;RBW=1 MHz,VBW=1 MHz.

Resolution bandwidth for non-restricted band

RBW=100kHz, VBW=300kHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is placed on 80cm Styrofoam table. It is powered by 3.6VDC internal Batteries Lithium Package and set continuously transmit.

900MHz Band Antenna = 5.25dBi gain

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.

High Channel

NO EMISSION HAS BEEN FOUND

Page 37 of 58 Report No.: 94367-6



Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) / 15.209 Radiated Spurious Emissions

Work Order #: 94367 Date: 4/2/2014
Test Type: Radiated Scan Time: 10:58:36
Equipment: Basic II Wireless Probe Sequence#: 14

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

	T				
ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN00730	Preamp	8447D	1/17/2013	1/17/2015
T2	AN00852	Biconilog Antenna	CBL 6111C	11/28/2012	11/28/2014
T3	ANP00880	Cable	RG214U	7/30/2012	7/30/2014
T4	ANP01183	Cable	CNT-195	9/3/2013	9/3/2015
T5	ANP05300	Cable	RG214/U	3/25/2013	3/25/2015
	AN02668	Spectrum Analyzer	E4446A	2/22/2013	2/22/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N	
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648	
900MHz Band Antenna	SkyWare Antennas	16-1003-A	None	
Batteries Lithium Pack	OC	SB6044	None	

Support Devices:

Support Bertees.				
Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

Radiated Emission

Frequency Range: 30MHz to 1000MHz RF output power =10mW and attenuator "1" Resolution bandwidth for restricted band

9 kHz -150 kHz;RBW=200 Hz,VBW=200 Hz; 150 kHz-30 MHz;RBW=9 kHz,VBW=9 kHz; 30 MHz-1000 MHz;RBW=120 kHz,VBW=120 kHz, 1000 MHz-10,000 MHz;RBW=1 MHz,VBW=1 MHz.

Resolution bandwidth for non-restricted band

RBW=100kHz, VBW=300kHz Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is placed on 80cm Styrofoam table. It is powered by 3.6VDC internal Batteries Lithium Package and set continuously transmit.

900MHz Band Antenna = 5.25dBi gain

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.

High Channel


Page 38 of 58 Report No.: 94367-6



Ext Attn: 0 dB

Measu	rement Data:	Re	eading lis	ted by ma	argin.		Те	est Distance	e: 3 Meters		
#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5								
	MHz	dΒμV	dB	dB	dB	dB	Table	$dB\mu V/m$	dBμV/m	dB	Ant
1	130.062M	45.4	-27.0	+11.3	+1.1	+0.5	+0.0	31.6	43.5	-11.9	Vert
			+0.3								
2	133.186M	45.0	-27.0	+11.4	+1.1	+0.5	+0.0	31.3	43.5	-12.2	Vert
			+0.3								
3	120.213M	37.6	-27.0	+11.3	+1.1	+0.3	+0.0	23.6	43.5	-19.9	Vert
			+0.3								
4	613.185M	28.8	-26.9	+19.6	+2.7	+1.0	+0.0	25.9	46.0	-20.1	Horiz
			+0.7								
5	610.062M	28.7	-26.9	+19.3	+2.7	+1.0	+0.0	25.5	46.0	-20.5	Horiz
			+0.7								
6	982.782M	29.0	-27.2	+24.3	+3.6	+1.3	+0.0	31.9	54.0	-22.1	Horiz
			+0.9								

CKC Laboratories, Inc. Date: 4/2/2014 Time: 10:58:36 AquaCheck (Pty) LTD WO#: 94367 Test Distance: 3 Meters Sequence#: 14





Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: 15.247(d) / 15.209 Radiated Spurious Emissions

Work Order #: 94367 Date: 4/3/2014
Test Type: Radiated Scan Time: 11:56:05

Equipment: Basic II Wireless Probe Sequence#: 42

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE_xM

S/N: 21648

Test Equipment:

1 csi Lyuq	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN03114	Preamp	AMF-7D-	4/11/2013	4/11/2015
			00101800-30-10P		
T2	AN02157	Horn Antenna-ANSI	3115	1/23/2013	1/23/2015
		C63.5			
Т3	AN03302	Cable	32026-29094K-	3/24/2014	3/24/2016
			29094K-72TC		
T4	ANP01210	Cable	FSJ1P-50A-4A	2/19/2013	2/19/2015
T5	ANP06125	Cable	32022-29094K-	5/6/2013	5/6/2015
			29094K-72TC		
	AN02668	Spectrum Analyzer	E4446A	2/22/2013	2/22/2015
T6	AN03172	High Pass Filter	HM1155-11SS	1/15/2014	1/15/2016
T7	ANDuty Cycle	<-Select Sub Type->	·	5/29/2013	5/29/2015
	Correct Factor				

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None
900MHz Band Antenna	SkyWave Antennas	16-1003-A	None

Support Devices:

Tr (NA C	3.6 1.1//	CAT	
Function	Manufacturer	Model #	S/N	
Tunction	Manufacturei	100001π	D/1 V	

Test Conditions / Notes:

Radiated Emission

Frequency Range: 1000MHz to 10000MHz

RF output power =10mW and attenuator "1"

Resolution bandwidth for restricted band

9 kHz -150 kHz;RBW=200 Hz,VBW=200 Hz; 150 kHz-30 MHz;RBW=9 kHz,VBW=9 kHz; 30 MHz-1000 MHz;RBW=120 kHz,VBW=120 kHz, 1000 MHz-10,000 MHz;RBW=1 MHz,VBW=1 MHz.

Resolution bandwidth for non-restricted band

RBW=100kHz, VBW=300kHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Page 40 of 58 Report No.: 94367-6



Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is placed on 80cm Styrofoam table. It is powered by 3.6VDC internal Batteries Lithium Package and set

continuously transmit.

900MHz Band Antenna = 5.25dBi gain

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.


High Channel

Ext Attn: 0 dB

Measu	rement Data:	Re	eading lis	ted by ma	argin.		Тє	est Distance	e: 3 Meters		
#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7						
	MHz	$dB\mu V$	dB	dB	dB	dB	Table	$dB\mu V/m$	$dB\mu V/m$	dB	Ant
1	7744.738M	58.3	-58.9	+36.6	+2.1	+5.5	+0.0	45.8	54.0	-8.2	Horiz
			+2.1	+0.1	+0.0						
2	4592.589M	81.9	-58.9	+32.6	+1.6	+3.7	+0.0	43.0	54.0	-11.0	Vert
			+1.6	+0.2	-19.7						
3	3674.672M	77.6	-59.3	+31.8	+1.4	+3.2	+0.0	36.5	54.0	-17.5	Vert
			+1.4	+0.1	-19.7						
4	7348.342M	69.0	-59.4	+36.7	+2.1	+5.4	+0.0	36.2	54.0	-17.8	Horiz
			+2.0	+0.1	-19.7						
5	9188.544M	63.1	-57.0	+38.2	+2.3	+6.0	+0.0	35.2	54.0	-18.8	Vert
			+2.2	+0.1	-19.7						
6	2756.755M	69.1	-58.9	+29.2	+1.3	+2.8	+0.0	25.4	54.0	-28.6	Horiz
			+1.4	+0.2	-19.7						



CKC Laboratories, Inc. Date: 4/3/2014 Time: 11:56:05 AquaCheck (Pty) LTD WO#: 94367 Test Distance: 3 Meters. Sequence#: 42





Band Edge

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: Band Edge

Work Order #: 94367 Date: 3/28/2014
Test Type: Conducted Power Measurement Time: 08:25:41
Equipment: Basic II Wireless Probe Sequence#: 1

Manufacturer: AquaCheck (Pty) LTD Sequencer: 1

Tested By: Hieu Song Nguyenpham

Model: ACBPROBE xM

S/N: 21648

Test Equipment:

1 cst Lyu	прист.				
ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP01211	Attenuator	PE7002-10	4/2/2013	4/2/2015
T2	ANP06138	Cable	32022-29094K- 29094K-72TC	8/2/2013	8/2/2015
	AN03471	RF Characteristics Analyzer	E4440A	12/19/2013	12/19/2015

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None

Support Devices:

Support Devices.				
Function	Manufacturer	Model #	S/N	

Test Conditions / Notes:

Band Edge Set up

RF output power =10mW and attenuator "1"

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz


The EUT is set continuously transmit

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power.


Page 43 of 58 Report No.: 94367-6



Test Plots - Bandedge




Low Channel



High Channel



Duty Cycle Factor



REAL TIME ANALYSIS, REFER TO ATTACHED SPECTRUM ANALYER PRINT OUTS.

Description Total Time On Time

Total Transmission 100mSec. 10.4 mSec. in any 100 mSec.. Window.

FCC Rules 15.35(c) 10.54 E-3 (on time) = 20 Log (0.104) = -19.659 dB (per FCC rules)

NOTE: The total on time per RF burst above is presented for the worst case


100 E-3 (window)



Test Setup Photo(s)




9kHz - 30MHz, 900MHz Band Antenna



9kHz - 30MHz, 900MHz Band Antenna






30MHz - 1GHz, 900MHz Band Antenna



30MHz - 1GHz, 900MHz Band Antenna





1GHz - 10GHz, 900MHz Band Antenna




1GHz - 10GHz, 900MHz Band Antenna






9kHz - 30MHz, GSM Wide Band Antenna




9kHz - 30MHz, GSM Wide Band Antenna





30MHz - 1GHz, GSM Wide Band Antenna




30MHz - 1GHz, GSM Wide Band Antenna





1GHz - 10GHz, GSM Wide Band Antenna



1GHz - 10GHz, GSM Wide Band Antenna





Test Setup, Band Edge



Test Setup – Close View



15. 247(e) Power Spectral Density

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: AquaCheck (Pty) LTD

Specification: 15.247(e) Peak Power Spectral Density (902-928 MHz DTS)

Work Order #: 94367 Date: 3/28/2014
Test Type: Conducted Power Measurement Time: 10:38:43

Equipment: Basic II Wireless Probe Sequence#: 2

Manufacturer: AquaCheck (Pty) LTD Tested By: Hieu Song Nguyenpham

Model: ACBPROBE xM

S/N: 21648

Test Equipment:

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP01211	Attenuator	PE7002-10	4/2/2013	4/2/2015
T2	ANP06138	Cable	32022-29094K-	8/2/2013	8/2/2015
			29094K-72TC		
	AN03471	RF Characteristics	E4440A	12/19/2013	12/19/2015
		Analyzer			

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Basic II Wireless Probe*	AquaCheck (Pty) LTD	ACBPROBE_xM	21648
Batteries Lithium Pack	QC	SB6044	None

Support Devices:

Function	Manufacturer	Model #	S/N
1 diletion	111411414014101	1110401 //	5/11

Test Conditions / Notes:

Power Spectral Density

RF output power =10mW and attenuator "1"

RBW = 100kHzVBW = 300kHz

Software Used: AC Utility Program

Firmware: AC Probe Basic-II-W, FirmwareV24, Boot V10

Transmit Frequency Range =902 to 928MHz

Low channel: 902.5MHz Middle channel: 910.5MHz High Channel: 919MHz

The EUT is set continuously transmit

Note: Attenuator is from 0 to 27. For each step of the attenuator reduces 0.3dB for RF output power

Page 53 of 58 Report No.: 94367-6




Ext Attn: 0 dB

Measurement Data:		Re	eading lis	ted by ma	argin.		Te	st Distano	e: None		
#	Freq	Rdng	T1	T2			Dist	Corr	Spec	Margin	Polar
	MHz	$dB\mu V$	dB	dB	dB	dB	Table	dΒμV	dΒμV	dB	Ant
1	918.993M	84.2	+9.9	+0.7			+0.0	94.8	115.0	-20.2	None
									High chan	nel	
2	910.798M	82.9	+9.9	+0.7			+0.0	93.5	115.0	-21.5	None
									Middle Ch	annel	
3	902.806M	81.5	+9.9	+0.7			+0.0	92.1	115.0	-22.9	None
									Low Chan	nel	

Convert equivalent electric field strength to the resultant power level


	Frequency (MHz)	Measured Power in dBm	Power Limit in dBm	Pass/Fail
Ī	Low Channel	-14.9	8.00	Pass
Ī	Middle Channel	-13.5	8.00	Pass
Ī	High Channel	-12.2	8.00	Pass

Test Data




Low Channel





Middle Channel



High Channel



Test Setup Photo(s)



Test Setup



Test Setup - Close View



SUPPLEMENTAL INFORMATION

Measurement Uncertainty

Uncertainty Value	Parameter
4.73 dB	Radiated Emissions
3.34 dB	Mains Conducted Emissions
3.30 dB	Disturbance Power

The reported measurement uncertainties are calculated based on the worst case of all laboratory environments from CKC Laboratories, Inc. test sites. Only those parameters which require estimation of measurement uncertainty are reported. The reported worst case measurement uncertainty is less than the maximum values derived in CISPR 16-4-2. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k=2. Compliance is deemed to occur provided measurements are below the specified limits.

Emissions Test Details

TESTING PARAMETERS

Unless otherwise indicated, the following configuration parameters are used for equipment setup: The cables were routed consistent with the typical application by varying the configuration of the test sample. Interface cables were connected to the available ports of the test unit. The effect of varying the position of the cables was investigated to find the configuration that produced maximum emissions. Cables were of the type and length specified in the individual requirements. The length of cable that produced maximum emissions was selected.

The equipment under test (EUT) was set up in a manner that represented its normal use, as shown in the setup photographs. Any special conditions required for the EUT to operate normally are identified in the comments that accompany the emissions tables.

The emissions data was taken with a spectrum analyzer or receiver. Incorporating the applicable correction factors for distance, antenna, cable loss and amplifier gain, the data was reduced as shown in the table below. The corrected data was then compared to the applicable emission limits. Preliminary and final measurements were taken in order to ensure that all emissions from the EUT were found and maximized.

CORRECTION FACTORS

The basic spectrum analyzer reading was converted using correction factors as shown in the highest emissions readings in the tables. For radiated emissions in $dB\mu V/m$, the spectrum analyzer reading in $dB\mu V$ was corrected by using the following formula. This reading was then compared to the applicable specification limit.

Page 57 of 58 Report No.: 94367-6



SAMPLE CALCULATIONS					
	Meter reading	(dBμV)			
+	Antenna Factor	(dB)			
+	Cable Loss	(dB)			
-	Distance Correction	(dB)			
-	Preamplifier Gain	(dB)			
=	Corrected Reading	(dBμV/m)			

TEST INSTRUMENTATION AND ANALYZER SETTINGS

The test instrumentation and equipment listed were used to collect the emissions data. A spectrum analyzer or receiver was used for all measurements. Unless otherwise specified, the following table shows the measuring equipment bandwidth settings that were used in designated frequency bands. For testing emissions, an appropriate reference level and a vertical scale size of 10 dB per division were used.

MEASURING EQUIPMENT BANDWIDTH SETTINGS PER FREQUENCY RANGE						
TEST	BEGINNING FREQUENCY	ENDING FREQUENCY	BANDWIDTH SETTING			
CONDUCTED EMISSIONS	150 kHz	30 MHz	9 kHz			
RADIATED EMISSIONS	9 kHz	150 kHz	200 Hz			
RADIATED EMISSIONS	150 kHz	30 MHz	9 kHz			
RADIATED EMISSIONS	30 MHz	1000 MHz	120 kHz			
RADIATED EMISSIONS	1000 MHz	>1 GHz	1 MHz			

SPECTRUM ANALYZER/RECEIVER DETECTOR FUNCTIONS

The notes that accompany the measurements contained in the emissions tables indicate the type of detector function used to obtain the given readings. Unless otherwise noted, all readings were made in the "positive peak" detector mode. Whenever a "quasi-peak" or "average" reading was recorded, the measurement was annotated with a "QP" or an "Ave" on the appropriate rows of the data sheets. In cases where quasi-peak or average limits were employed and data exists for multiple measurement types for the same frequency then the peak measurement was retained in the report for reference, however the numbering for the affected row was removed and an arrow or carrot ("A") was placed in the far left-hand column indicating that the row above takes precedence for comparison to the limit. The following paragraphs describe in more detail the detector functions and when they were used to obtain the emissions data.

Peak

In this mode, the spectrum analyzer or receiver recorded all emissions at their peak value as the frequency band selected was scanned. By combining this function with another feature called "peak hold," the measurement device had the ability to measure intermittent or low duty cycle transient emission peak levels. In this mode the measuring device made a slow scan across the frequency band selected and measured the peak emission value found at each frequency across the band.

Quasi-Peak

Quasi-peak measurements were taken using the quasi-peak detector when the true peak values exceeded or were within 2 dB of a quasi-peak specification limit. Additional QP measurements may have been taken at the discretion of the operator.

Average

Average measurements were taken using the average detector when the true peak values exceeded or were within 2 dB of an average specification limit. Additional average measurements may have been taken at the discretion of the operator. If the specification or test procedure requires trace averaging, then the averaging was performed using 100 samples or as required by the specification. All other average measurements are performed using video bandwidth averaging. To make these measurements, the test engineer reduces the video bandwidth on the measuring device until the modulation of the signal is filtered out. At this point the measuring device is set into the linear mode and the scan time is reduced.

Page 58 of 58 Report No.: 94367-6