

FCC PART 15.247 TEST REPORT

For

Shenzhen CE and IT Limited

113 Zhenxing Road, Xinxin Building, Tower B, Suite 501, Futian District, Shenzhen, China

FCC ID: YG5SMART2

Report Type: **Product Type:** Original Report Mobile Phone Mile Un **Test Engineer:** Mike Hu **Report Number:** RSZ131104005-00C **Report Date:** 2013-12-03 Strand Alvin Huang RF Leader **Reviewed By:** Bay Area Compliance Laboratories Corp. (Shenzhen) Prepared By: 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	4
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT Exercise Software	
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
EXTERNAL I/O CABLEBLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE	7
APPLICABLE STANDARD	
RESULT	7
FCC §15.203 - ANTENNA REQUIREMENT	8
APPLICABLE STANDARD	
Antenna Connector Construction	8
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUP.	
EMI TEST RECEIVER SETUP	10
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
CORRECTED FACTOR & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
Applicable Standard	
EUT SETUP	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
TEST EQUIPMENT LIST AND DETAILS.	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST DATA	
TEST DATA	

Report No.: RSZ131104005-00C

Report No.: RSZ131104005-00C

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Shenzhen CE and IT Limited's product, model number: JT Smart 2 (FCC ID: YG5SMART2) or the "EUT" in this report was a Mobile Phone, which was measured approximately: 115.3 mm (L) x 62.3 mm (W) x 10.5 mm (H), rated with input voltage: DC 3.7V Li-ion battery or DC 5.0V charging from adapter.

Report No.: RSZ131104005-00C

*All measurement and test data in this report was gathered from production sample serial number: 1311007 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2013-11-04.

Objective

This report is prepared on behalf of *Shenzhen CE and IT Limited* in accordance with Part 2-Subpart J, Part 15- Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS, Part 22H/24E PCE and Part 15B JBP submission with FCC ID: YG5SMART2.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.247 Page 4 of 32

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineer mode.

EUT Exercise Software

N/A

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.


External I/O Cable

Cable Description	Length (m)	From Port	То
Unshielded detachable USB Cable	0.8	EUT	Adapter
B mobile	Adapter	QW130	

Report No.: RSZ131104005-00C

Block Diagram of Test Setup

For conducted emission



FCC Part 15.247 Page 5 of 32

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a),	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
\$15.205, \$15.209, \$15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Report No.: RSZ131104005-00C

FCC Part 15.247 Page 6 of 32

FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RSZ131104005-00C

According to KDB 447498 D01 General RF Exposure Guidance v05

Result

According to FCC KDB 447498 D01 General RF Exposure Guidance v05 generic portable criteria

The distance between antenna and test point is 5 mm The maximum peak conducted output power: -2.76 dBm (0.53 mW)

According to the Appendix A of KDB 447498, the exclusion thresholds for 2450 MHz is 10 mW

Conclusion:

The time-averaged output power is $0.53 \text{ mW} \le$ the exclusion thresholds 10 mW, so stand-alone SAR evaluation is not required.

The other SAR data please refer to the SAR report, report No.: RSZ131104005-20.

FCC Part 15.247 Page 7 of 32

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: RSZ131104005-00C

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one integral antenna arrangement for bluetooth, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliant.

FCC Part 15.247 Page 8 of 32

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty


Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between AMN/ISN and receiver, AMN/ISN voltage division factor, AMN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Report No.: RSZ131104005-00C

Port	Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2009. The related limit was specified in FCC Part 15.207.

The adapter was connected to a 120 VAC/60 Hz power source.

FCC Part 15.247 Page 9 of 32

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Report No.: RSZ131104005-00C

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2013-06-17	2014-06-17
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2013-05-07	2014-05-07
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2013-10-15	2014-10-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53	-	-

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Pulse Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Pulse Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 10 of 32

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

Report No.: RSZ131104005-00C

17.7 dB at 0.610000 MHz in the Line conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{\rm (Lm)} \leq L_{\rm lim} + U_{\rm cispr}$$

in BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

The testing was performed by Mike Hu on 2013-11-25.


FCC Part 15.247 Page 11 of 32

EUT operation mode: Charging & Transmitting

AC 120 V, 60 Hz, Line:

EMI Auto Test L

Report No.: RSZ131104005-00C




Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.610000	38.3	19.5	56.0	17.7	QP
0.610000	19.8	19.5	46.0	26.2	Ave.
0.810000	34.8	19.5	56.0	21.2	QP
0.810000	21.3	19.5	46.0	24.7	Ave.
0.914000	33.0	19.5	56.0	23.0	QP
0.914000	21.5	19.5	46.0	24.5	Ave.
1.014000	33.1	19.5	56.0	22.9	QP
1.014000	21.8	19.5	46.0	24.2	Ave.
1.218000	32.4	19.5	56.0	23.6	QP
1.218000	20.6	19.5	46.0	25.4	Ave.
1.318000	28.1	19.5	56.0	27.9	QP
1.318000	18.9	19.5	46.0	27.1	Ave.

FCC Part 15.247 Page 12 of 32

AC 120V, 60 Hz, Neutral:

EMI Auto Test N

Report No.: RSZ131104005-00C



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.386000	28.5	19.5	58.1	29.6	QP
0.386000	21.4	19.5	48.1	26.7	Ave.
0.802000	24.4	19.5	56.0	31.6	QP
0.802000	19.1	19.5	46.0	26.9	Ave.
0.818000	28.2	19.5	56.0	27.8	QP
0.818000	17.0	19.5	46.0	29.0	Ave.
0.990000	26.4	19.5	56.0	29.6	QP
0.990000	16.4	19.5	46.0	29.6	Ave.
1.042000	25.6	19.5	56.0	30.4	QP
1.042000	15.0	19.5	46.0	31.0	Ave.
21.026000	27.3	20.2	60.0	32.7	QP
21.026000	18.8	20.2	50.0	31.2	Ave.

Note:

FCC Part 15.247 Page 13 of 32

¹⁾ Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation The corrected factor has been input into the transducer of the test software.

²⁾ Corrected Amplitude = Reading + Correction Factor
3) Margin = Limit - Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Report No.: RSZ131104005-00C

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz. And this uncertainty will not be taken into consideration for the test data recorded in the report.

EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

FCC Part 15.247 Page 14 of 32

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 CHa	1 MHz	3 MHz	/	PK
Above 1 GHz	1 MHz	10 Hz	/	Ave.

Report No.: RSZ131104005-00C

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2013-09-30	2014-09-30
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
Mini	Amplifier	ZVA-183-S+	5969001149	2013-04-03	2014-04-03
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2015-02-10
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12
the electro- Mechanics Co.	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13
Rohde & Schwarz	CE Test software	EMC 32	V8.53	-	-

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

FCC Part 15.247 Page 15 of 32

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247</u>, with the worst margin reading of:

11.36 dB at 149.7 MHz in the Horizontal polarization

Report No.: RSZ131104005-00C

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{\rm (Lm)} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_{m} is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

The testing was performed by Mike Hu on 2013-11-18.

EUT operation mode: Transmitting

FCC Part 15.247 Page 16 of 32

30 MHz-25 GHz

Frequency	Re	Receiver		Rx Ar	itenna	Corrected	Corrected		
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	table Degree	Height (m)	Polar (H/V)	Factor (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			Low C	hannel(2	2402 MI	Hz)			
149.7	45.10	QP	91	1.1	Н	-14.9	30.20	43.5	13.30
2402.0	80.07	PK	253	1.3	Н	6.13	86.20	/	/
2402.0	75.07	Ave.	253	1.3	Н	6.13	81.20	/	/
2402.0	81.14	PK	125	1.2	V	6.13	87.27	/	/
2402.0	75.06	Ave.	125	1.2	V	6.13	81.19	/	/
2356.8	33.85	PK	278	1.2	Н	5.48	39.33	74	34.67
2356.8	21.24	Ave.	278	1.2	Н	5.48	26.72	54	27.28
2389.7	35.64	PK	329	1.4	V	6.13	41.77	74	32.23
2389.7	22.26	Ave.	329	1.4	V	6.13	28.39	54	25.61
2490.5	35.72	PK	255	1.3	Н	7.21	42.93	74	31.07
2490.5	21.98	Ave.	255	1.3	Н	7.21	29.19	54	24.81
4804.0	32.96	PK	354	1.4	Н	12.40	45.36	74	28.64
4804.0	21.20	Ave.	354	1.4	Н	12.40	33.60	54	20.40
7206.0	32.05	PK	21	1.4	V	17.06	49.11	74	24.89
7206.0	22.61	Ave.	21	1.4	V	17.06	39.67	54	14.33
9608.0	33.24	PK	259	1.4	V	19.28	52.52	74	21.48
9608.0	21.27	Ave.	259	1.4	V	19.28	40.55	54	13.45
	•		Middle	Channel	(2440 M	(Hz)			
149.7	46.26	QP	240	1.1	Н	-14.9	31.36	43.5	12.14
2440.0	78.07	PK	319	1.2	Н	7.21	85.28	/	/
2440.0	72.90	Ave.	319	1.2	Н	7.21	80.11	/	/
2440.0	80.34	PK	187	1.4	V	7.21	87.55	/	/
2440.0	74.47	Ave.	187	1.4	V	7.21	81.68	/	/
2386.4	35.34	PK	195	1.5	V	6.13	41.47	74	32.53
2386.4	22.10	Ave.	195	1.5	V	6.13	28.23	54	25.77
2485.0	35.21	PK	246	1.3	Н	7.21	42.42	74	31.58
2485.0	21.58	Ave.	246	1.3	Н	7.21	28.79	54	25.21
2493.4	34.46	PK	168	1.3	Н	7.21	41.67	74	32.33
2493.4	21.36	Ave.	168	1.3	Н	7.21	28.57	54	25.43
4880.0	34.14	PK	165	1.4	V	12.46	46.60	74	27.40
4880.0	21.01	Ave.	165	1.4	V	12.46	33.47	54	20.53
7320.0	34.62	PK	313	1.2	V	16.49	51.11	74	22.89
7320.0	22.07	Ave.	313	1.2	V	16.49	38.56	54	15.44
9760.0	33.66	PK	74	1.4	Н	19.40	53.06	74	20.94
9760.0	21.40	Ave.	74	1.4	Н	19.40	40.80	54	13.20

Report No.: RSZ131104005-00C

FCC Part 15.247 Page 17 of 32

Frequency	Re	Receiver		Rx An	tenna		Corrected	15.247	C Part 7/205/209
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	table Degree	Height (m)	Polar (H/V)	Factor (dB)	Amplitude (dBµV/m)		Margin (dB)
High Channel(2480 MHz)									
149.7	47.04	QP	102	1.4	Н	-14.9	32.14	43.5	11.36
2480.0	77.98	PK	251	1.6	Н	7.21	85.19	/	/
2480.0	72.86	Ave.	251	1.6	Н	7.21	80.07	/	/
2480.0	81.32	PK	243	1.3	V	7.21	88.53	/	/
2480.0	75.66	Ave.	243	1.3	V	7.21	82.87	/	/
2388.1	35.92	PK	30	1.3	Н	6.13	42.05	74	31.95
2388.1	22.36	Ave.	30	1.3	Н	6.13	28.49	54	25.51
2483.2	35.29	PK	104	1.3	V	7.21	42.50	74	31.50
2483.2	21.52	Ave.	104	1.3	V	7.21	28.73	54	25.27
2491.2	34.41	PK	152	1.3	V	7.21	41.62	74	32.38
2491.2	21.26	Ave.	152	1.3	V	7.21	28.47	54	25.53
4960.0	33.55	PK	103	1.4	V	12.50	46.05	74	27.95
4960.0	20.57	Ave.	103	1.4	V	12.50	33.07	54	20.93
7440.0	33.82	PK	128	1.5	Н	15.90	49.72	74	24.28
7440.0	21.02	Ave.	128	1.5	Н	15.90	36.92	54	17.08
9920.0	34.15	PK	68	1.4	V	19.38	53.53	74	20.47
9920.0	20.51	Ave.	68	1.4	V	19.38	39.89	54	14.11

Report No.: RSZ131104005-00C


FCC Part 15.247 Page 18 of 32

Conducted Spurious Emissions at Antenna Port:

Channel	Delta Peak to band emission (dBc)	Limit (dBc)
Low	42.68	20
Middle	43.86	20
High	35.59	20

Report No.: RSZ131104005-00C


Low Channel




FCC Part 15.247 Page 19 of 32

Middle Channel

Report No.: RSZ131104005-00C



High Channel



FCC Part 15.247 Page 20 of 32

FCC $\S15.247(a)$ (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard


Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: RSZ131104005-00C

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	54 %
ATM Pressure:	100.1 kPa

The testing was performed by Mike Hu on 2013-11-16.

EUT operation mode: Transmitting

Test Result: Compliance


FCC Part 15.247 Page 21 of 32

Please refer to the following tables and plots.

Channel	Channel Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
Low	2402	733.5	≥500
Middle	2440	733.5	≥500
High	2480	729.5	≥500

Report No.: RSZ131104005-00C


Low Channel




FCC Part 15.247 Page 22 of 32

Middle Channel

Report No.: RSZ131104005-00C



High Channel



FCC Part 15.247 Page 23 of 32

FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER

Applicable Standard


According to §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Report No.: RSZ131104005-00C

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

- 1. Place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to a test equipment.
- 3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	100.1 kPa

The testing was performed by Mike Hu on 2013-11-30.


EUT operation mode: Transmitting

FCC Part 15.247 Page 24 of 32

Channel	Frequency (MHz)	Conducted Output Power (dBm)	Limit (dBm)	Result
Low	2402	-3.34	30	Pass
Middle	2440	-2.95	30	Pass
High	2480	-2.76	30	Pass

Report No.: RSZ131104005-00C


RF Output Power, Low Channel




FCC Part 15.247 Page 25 of 32

RF Output Power, Middle Channel

Report No.: RSZ131104005-00C



RF Output Power, High Channel



FCC Part 15.247 Page 26 of 32

FCC §15.247(d) - 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Report No.: RSZ131104005-00C


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

FCC Part 15.247 Page 27 of 32

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	54 %
ATM Pressure:	100.1 kPa

The testing was performed by Mike Hu on 2013-11-16.

EUT operation mode: Transmitting

Test Result: Compliance.

Please refer to following table and plots.


Frequency Band	Frequency Band Delta Peak to band emission (dBc)		Result
Left-band	45.92	20	Pass
Right-band	47.05	20	Pass

Report No.: RSZ131104005-00C


FCC Part 15.247 Page 28 of 32

Band Edge, Left Side

Report No.: RSZ131104005-00C



Band Edge, Right Side



FCC Part 15.247 Page 29 of 32

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Report No.: RSZ131104005-00C

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

- 1. Set analy center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS channel bandwidth.
- 3. Set the RBW \geq 3 kHz.
- 4. Set the VBW \geq 3 x RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum power level.
- 10. If measurement value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24 ℃	
Relative Humidity:	54 %	
ATM Pressure:	100.1 kPa	

The testing was performed by Mike Hu on 2013-11-16.

FCC Part 15.247 Page 30 of 32


EUT operation mode: Transmitting

Test Result: Pass

Channel	Frequency (MHz)	Power spectral density (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-17.98	€8
Middle	2440	-17.75	€8
High	2480	-17.67	€8

Report No.: RSZ131104005-00C


Low Channel




FCC Part 15.247 Page 31 of 32

Middle Channel

Report No.: RSZ131104005-00C



High Channel



FCC Part 15.247 Page 32 of 32