

SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Application
For
Certification
FCC ID: YGB-DV111

DIGITAL VIDEO CAMERA**Model: DV111****Computer Peripheral****Report No.: SZ12060482-1**

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-11]

Prepared and Checked by:

Approved by:

Sign on file

Andy Yan
Engineer

Billy Li
Supervisor
Date: 21 August, 2012

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_PC_b**Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch**

6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: www.china.intertek-etylsemko.com

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labeling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Test Equipment List

INTERTEK TESTING SERVICES

MEASUREMENT / TECHNICAL REPORT

SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.
MODEL: DV111
FCC ID: YGB-DV111

21 August, 2012

This report concerns (check one): Original Grant Class II Change

Equipment Type: JBP-Class B Computing Device Peripheral

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date
of the intended date of announcement of the product so that the grant can be issued on
that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-01-11
Edition] provision.

Report prepared by:

Billy Li
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6F, D Block, Huahan Building, Langshan Road
Nanshan District, Shenzhen, P. R. China
Phone: (86 755) 8601 6288
Fax: (86 755) 8601 6751

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

Table of Contents

1.0 General Description	2
1.1 Product Description.....	2
1.2 Related Submittal(s) Grants.....	2
1.3 Test Methodology.....	3
1.4 Test Facility.....	3
2.0 System Test Configuration	5
2.1 Justification	5
2.2 EUT Exercising Software	5
2.3 Special Accessories	5
2.4 Equipment Modification.....	5
2.5 Measurement Uncertainty	6
2.6 Support Equipment List and Description	6
3.0 Emission Results	8
3.1 Field Strength Calculation	9
3.2 Radiated Emission Configuration Photograph	11
3.3 Radiated Emission Data	12
3.4 Conducted Emission Configuration Photograph	18
3.5 Conducted Emission Data.....	19
4.0 Equipment Photographs	25
5.0 Product Labelling	27
6.0 Technical Specifications	29
7.0 Instruction Manual	31
8.0 Miscellaneous Information	33
8.1 Emissions Test Procedures	34
9.0 Test Equipment List	37

INTERTEK TESTING SERVICES

List of attached file

Exhibit Type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated photos	radiated photos.pdf
Test Setup Photo	Conducted photos	conducted photos.pdf
External Photo	External Photos	external photos.pdf
Internal Photo	Internal Photos	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
ID Label / Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Letter of Agency	agency.pdf

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

EXHIBIT 1

GENERAL DESCRIPTION

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is a DIGITAL VIDEO CAMERA. The device can be used to transfer data connecting PC by USB port. The EUT is powered by DC 4.5V (3 x 1.5V " AAA") batteries or PC USB port with PC download and PC camera mode.

1.2 Related Submittal(s) Grants

This is an application for certification of a computer peripheral.

INTERTEK TESTING SERVICES

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

INTERTEK TESTING SERVICES

EXHIBIT 2

SYSTEM TEST CONFIGURATION

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device is powered by DC 4.5V (3 x 1.5V " AAA") new batteries or PC USB port with PC download mode and PC camera mode during the test. The worst case data was reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. The step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

The frequency range from 30MHz to 1GHz was searched for spurious emissions from the device. Only those emissions reported were detected. All other emissions were at least 20 dB below the applicable limits.

2.2 EUT Exercising Software

There is a CD attached to exercise the device.

2.3 Special Accessories

Shielded USB cable with one ferrite ring. Un-shielded AV cable with one ferrite ring.

2.4 Equipment Modification

Any modifications installed previous to testing by SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

INTERTEK TESTING SERVICES

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
Laptop	Lenovo	T61
SD Card	SanDisk	33806
Hard Disk	Smart.drive	HD-003
USB Cable	Smart.drive	shielded, Length 100cm
1394 Cable	Smart.drive	shielded, Length 180cm
USB Cable	Shuoying	Shielded with one ferrite ring, Length 80cm
AV out Cable	Shuoying	Unshielded with one ferrite ring, Length 122cm
Dummy Load	MTC	DL-002

INTERTEK TESTING SERVICES

EXHIBIT 3

EMISSION RESULTS

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

INTERTEK TESTING SERVICES

3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in $dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in $dB\mu V$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

INTERTEK TESTING SERVICES

3.1 Field Strength Calculation (cont'd)

Example

Assume a receiver reading of 62.0dB μ V is obtained. The antenna factor of 7.4dB and cable factor of 1.6dB is added. The amplifier gain of 29dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0dB, and the resultant average factor was -10dB. The net field strength for comparison to the appropriate emission limit is 32dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{dB}\mu\text{V}$$

$$AF = 7.4 \text{dB}$$

$$CF = 1.6 \text{dB}$$

$$AG = 29.0 \text{dB}$$

$$PD = 0 \text{dB}$$

$$AV = -10 \text{dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32 \text{dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

**Worst Case Radiated Emission
At
288.008MHz (PC Camera Mode)**

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.pdf.

INTERTEK TESTING SERVICES

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 0.5dB margin (PC Camera Mode)

TEST PERSONNEL:

Sign on file

Andy Yan, Engineer
Typed/Printed Name

21 August, 2012
Date

INTERTEK TESTING SERVICES

Company: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Date of Test: 21 August, 2012

Model: DV111

Worst Operating Mode: PC Camera

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	163.860	45.2	20.0	10.1	35.3	43.5	-8.2
Horizontal	288.008	51.2	20.0	14.3	45.5	46.0	-0.5
Horizontal	946.165	37.9	20.0	25.9	43.8	46.0	-2.2
Vertical	35.992	43.1	20.0	14.4	37.5	40.0	-2.5
Vertical	43.580	46.3	20.0	11.2	37.5	40.0	-2.5
Vertical	945.208	37.0	20.0	25.9	42.9	46.0	-3.1

NOTES:

1. Quasi-Peak detector is used for frequency up to 1GHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3 meter distances were measured at 0.3- meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions up to 1GHz are below the QP limit.

Test Engineer: Andy Yan

TRF No.: FCC 15C_PC_b

FCC ID: YGB-DV111

Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

Company: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Date of Test: 21 August, 2012

Model: DV111

Operating Mode: PC Download

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	115.994	49.2	20.0	7.2	36.4	43.5	-7.1
Horizontal	132.005	51.2	20.0	7.7	38.9	43.5	-4.6
Horizontal	288.013	47.9	20.0	14.3	42.2	46.0	-3.8
Vertical	43.560	40.7	20.0	11.2	31.9	40.0	-8.1
Vertical	240.005	44.2	20.0	12.0	36.2	46.0	-9.8
Vertical	480.080	41.6	20.0	18.5	40.1	46.0	-5.9

NOTES:

1. Quasi-Peak detector is used for frequency up to 1GHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3 meter distances were measured at 0.3- meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions up to 1GHz are below the QP limit.

Test Engineer: Andy Yan

TRF No.: FCC 15C_PC_b

FCC ID: YGB-DV111

Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

Company: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Date of Test: 21 August, 2012

Model: DV111

Operating Mode: AV Out

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	192.023	50.0	20.0	8.3	38.3	43.5	-5.2
Horizontal	324.059	46.8	20.0	15.4	42.2	46.0	-3.8
Horizontal	576.024	44.7	20.0	20.2	44.9	46.0	-1.1
Vertical	30.960	31.5	20.0	18.3	29.8	40.0	-10.2
Vertical	76.560	49.3	20.0	5.7	35.0	40.0	-5.0
Vertical	480.000	42.2	20.0	18.5	40.7	46.0	-5.3

NOTES:

1. Quasi-Peak detector is used for frequency up to 1GHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3 meter distances were measured at 0.3- meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions up to 1GHz are below the QP limit.

Test Engineer: Andy Yan

TRF No.: FCC 15C_PC_b

FCC ID: YGB-DV111

Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

Company: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Date of Test: 21 August, 2012

Model: DV111

Operating Mode: Video Record

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	672.140	40.1	20.0	22.0	42.1	46.0	-3.9
Horizontal	768.170	37.6	20.0	23.2	40.8	46.0	-5.2
Horizontal	959.992	39.0	20.0	26.4	45.4	46.0	-0.6
Vertical	480.030	36.1	20.0	18.5	34.6	46.0	-11.4
Vertical	576.110	32.9	20.0	20.2	33.1	46.0	-12.9
Vertical	960.240	30.9	20.0	26.4	37.3	54.0	-16.7

NOTES:

1. Quasi-Peak detector is used for frequency up to 1GHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3 meter distances were measured at 0.3- meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions up to 1GHz are below the QP limit.

Test Engineer: Andy Yan

TRF No.: FCC 15C_PC_b

FCC ID: YGB-DV111

Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

Company: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Date of Test: 21 August, 2012

Model: DV111

Operating Mode: Play back

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	480.100	34.0	20.0	18.5	32.5	46.0	-13.5
Horizontal	768.250	38.0	20.0	23.2	41.2	46.0	-4.8
Horizontal	959.673	37.3	20.0	26.3	43.6	46.0	-2.4
Vertical	672.140	24.4	20.0	22.0	26.4	46.0	-19.6
Vertical	768.170	28.7	20.0	23.2	31.9	46.0	-14.1
Vertical	960.260	25.7	20.0	26.4	32.1	54.0	-21.9

NOTES:

1. Quasi-Peak detector is used for frequency up to 1GHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3 meter distances were measured at 0.3- meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions up to 1GHz are below the QP limit.

Test Engineer: Andy Yan

TRF No.: FCC 15C_PC_b

FCC ID: YGB-DV111

Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

3.4 Conducted Emission Configuration Photograph

**Worst Case Neutral-Conducted Configuration
at
0.190 MHz (PC Camera Mode)**

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

INTERTEK TESTING SERVICES

3.5 Conducted Emission Data

Judgement: Passed by 6.5 dB margin (PC Camera Mode)

TEST PERSONNEL:

Sign on file

Andy Yan, Engineer
Typed/Printed Name

21 August, 2012

Date

INTERTEK TESTING SERVICES


Company: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Date of Test: 21 August, 2012

Model: DV111

Worst Operating Mode: PC Camera

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.197	55.1	L1	9.6	8.6	63.7
0.270	49.5	L1	9.6	11.6	61.1
0.505	31.2	L1	9.6	24.8	56.0
3.330	32.5	L1	9.7	23.5	56.0
8.306	29.2	L1	9.9	30.8	60.0
28.418	24.1	L1	10.7	35.9	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.197	44.3	L1	9.6	9.4	53.7
0.270	38.9	L1	9.6	12.2	51.1
0.505	17.9	L1	9.6	28.1	46.0
3.330	20.2	L1	9.7	25.8	46.0
8.306	20.4	L1	9.9	29.6	50.0
28.418	19.1	L1	10.7	30.9	50.0

Test Engineer: Andy Yan

TRF No.: FCC 15C_PC_b

FCC ID: YGB-DV111

Report No.: SZ12060482-1

INTERTEK TESTING SERVICES


Company: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Date of Test: 21 August, 2012

Model: DV111

Worst Operating Mode: PC Camera

Conducted Emission Test – FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.190	57.5	N	9.6	6.5	64.0
0.250	50.9	N	9.6	10.9	61.8
0.498	32.4	N	9.6	23.6	56.0
3.546	34.0	N	9.8	22.0	56.0
8.574	28.1	N	10.0	31.9	60.0
28.002	33.2	N	10.3	26.8	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.190	44.4	N	9.6	9.6	54.0
0.250	35.2	N	9.6	16.6	51.8
0.498	17.3	N	9.6	28.7	46.0
3.546	22.1	N	9.8	23.9	46.0
8.574	20.2	N	10.0	29.8	50.0
28.002	26.9	N	10.3	23.1	50.0

Test Engineer: Andy Yan

TRF No.: FCC 15C_PC_b

FCC ID: YGB-DV111

Report No.: SZ12060482-1

INTERTEK TESTING SERVICES


Company: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Date of Test: 21 August, 2012

Model: DV111

Operating Mode: PC Download

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.194	54.3	L1	9.6	9.6	63.9
0.262	45.1	L1	9.6	16.3	61.4
1.524	31.6	L1	9.7	24.4	56.0
3.402	32.1	L1	9.7	23.9	56.0
6.034	31.2	L1	9.9	28.8	60.0
8.411	31.3	L1	9.9	28.7	60.0

Result Table AV

Frequency (MHz)	CAverage (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.194	43.2	L1	9.6	10.7	53.9
0.262	36.5	L1	9.6	14.9	51.4
1.524	19.0	L1	9.7	27.0	46.0
3.402	21.1	L1	9.7	24.9	46.0
6.034	20.8	L1	9.9	29.2	50.0
8.411	21.8	L1	9.9	28.2	50.0

Test Engineer: Andy Yan

TRF No.: FCC 15C_PC_b

FCC ID: YGB-DV111

Report No.: SZ12060482-1

INTERTEK TESTING SERVICES


Company: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA) Co., Ltd.

Date of Test: 21 August, 2012

Model: DV111

Operating Mode: PC Download

Conducted Emission Test – FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.198	51.2	N	9.7	12.5	63.7
0.258	47.3	N	9.6	14.2	61.5
0.314	42.1	N	9.6	17.8	59.9
2.782	28.1	N	9.7	27.9	56.0
4.886	30.1	N	9.8	25.9	56.0
7.210	28.9	N	9.9	31.1	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.198	39.2	N	9.7	14.5	53.7
0.258	33.9	N	9.6	17.6	51.5
0.314	30.2	N	9.6	19.7	49.9
2.782	15.6	N	9.7	30.4	46.0
4.886	17.1	N	9.8	28.9	46.0
7.210	16.8	N	9.9	33.2	50.0

Test Engineer: Andy Yan

TRF No.: FCC 15C_PC_b

FCC ID: YGB-DV111

Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

EXHIBIT 4

EQUIPMENT PHOTOGRAPHS

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, photographs of the tested EUT are saved with filename: external photos.pdf and internal photos.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 5

PRODUCT LABELLING

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

5.0 Product Labelling

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 6

TECHNICAL SPECIFICATIONS

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

6.0 Technical Specifications

For electronic filing, the block diagram of the tested EUT is saved with filename: block.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 7

INSTRUCTION MANUAL

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold / leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 8

MISCELLANEOUS INFORMATION

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

8.0 **Miscellaneous Information**

This miscellaneous information includes emission measuring procedure.

INTERTEK TESTING SERVICES

8.1 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of computer peripheral operating under Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 – 2009.

The computer peripheral equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The antenna height and polarization are varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions are in QP mode from the frequency band 30MHz to 1GHz with RBW setting 120kHz. Detector function for conducted emissions are in QP & AV mode and IFBW setting is 9kHz from the frequency band 150kHz to 30MHz.

For radiated emission, the frequency range scanned is 30MHz to 1GHz. For line-conducted emissions, the range scanned is 150kHz to 30MHz.

INTERTEK TESTING SERVICES

8.1 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

Conducted measurements are made as described in ANSI C63.4 – 2009.

INTERTEK TESTING SERVICES

EXHIBIT 9

TEST EQUIPMENT LIST

TRF No.: FCC 15C_PC_b
FCC ID: YGB-DV111
Report No.: SZ12060482-1

INTERTEK TESTING SERVICES

9.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	30-Jun-12	30-Jun-13
SZ185-01	EMI Receiver	R&S	ESCI	100547	11-Mar-12	11-Mar-13
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	03-Mar-12	03-Mar-13
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	12-Nov-11	12-Nov-12
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	12-Nov-11	12-Nov-12
SZ188-03	Shielding Room	ETS	RFD-100	4100	16-Sep-11	16-Sep-12