

SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Application
For
Certification

FCC ID: YGB-PDV3600S

PANOVIEW 360°Camera

Model: 1002929

Brand name: N/A

2.4GHz WiFi Transceiver

Report No.: 170502012GZU-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-15]

Prepared and Checked by:

Sign on file

Sunny Zhou
Project Engineer

Approved by:

Kidd Yang
Senior Project Engineer
Date: June 26, 2017

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C_Tx_c

INTERTEK TESTING SERVICE

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labeling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Confidentiality Request
<i>EXHIBIT 10:</i>	Miscellaneous Information
<i>EXHIBIT 11:</i>	Test Equipment List

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

PANOVIEW 360°Camera

Model: 1002929

FCC ID: YGB-PDV3600S

This report concerns (check one) Original Grant Class II Change

Equipment Type: DTS - Part 15 Digital Transmission Systems (WiFi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-15] Edition] provision.

Report prepared by:

Sunny Zhou
Intertek Testing Services Shenzhen Ltd. Guangzhou Branch
Block E, No.7-2 Guang Dong Software Science Park,
Caipin Road, Guangzhou Science City, GETDD
Guangzhou, China
Tel / Fax: 86-20-8213 9688/86-20-3205 7538

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>Summary of Test results</u>	6
2.0	<u>General Description</u>	8
2.1	Product Description	8
2.2	Related Submittal(s) Grants	8
2.3	Test Methodology	9
2.4	Test Facility	9
3.0	<u>System Test Configuration</u>	11
3.1	Justification	11
3.2	EUT Exercising Software	11
3.3	Special Accessories	12
3.4	Measurement Uncertainty	12
3.5	Equipment Modification	12
3.6	Support Equipment List and Description	12
4.0	<u>Measurement Results</u>	14
4.1	Maximum Conducted Output Power at Antenna Terminals	14
4.2	Minimum 6 dB RF Bandwidth	16
4.3	Maximum Power Density Reading	24
4.4	Out of Band Conducted Emissions	31
4.5	Out of Band Radiated Emissions	49
4.6	Transmitter Radiated Emissions in Restricted Bands	50
4.7	Field Strength Calculation	51
4.8	Radiated Spurious Emission	52
4.10	Radiated Emissions from Digital Section of Transceiver	66
4.11	Transmitter Duty Cycle Calculation and Measurements	67
5.0	<u>Equipment Photographs</u>	69
6.0	<u>Product Labelling</u>	71
7.0	<u>Technical Specifications</u>	73
8.0	<u>Instruction Manual</u>	75
9.0	<u>Confidentiality Request</u>	77
10.0	<u>Discussion of Pulse Desensitization</u>	79
11.0	<u>Test Equipment List</u>	81

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1

SUMMARY OF TEST RESULTS

INTERTEK TESTING SERVICES

1.0 Summary of Test results

PANOVIEW 360°Camera

Model: 1002929

FCC ID: YGB-PDV3600S

TEST	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	N/A
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

INTERTEK TESTING SERVICES

EXHIBIT 2

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a PANOVIEW 360°Camera with WiFi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 7 channels with 5MHz channel spacing. The EUT was powered by DC 3.8V internal rechargeable battery which was charged by USB port (DC 5V). For more detailed features description, please refer to the user's manual.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK.

Antenna Type: Integral Antenna.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of:

DTS- Part 15 Digital Transmission Systems (2.4GHz WiFi transmitter portion).

Remaining portions are subject the following procedure

1. PC download (Class B personal computer and peripherals):170502012GZU-002
2. Other digital functions were reported in the verification report: 170502016GZU-001.

INTERTEK TESTING SERVICES

2.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10: 2013 and KDB 558074 D01 v04. Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **“Justification Section”** of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The Semi-Anechoic chamber used to collect the radiated data is **Intertek Testing Services Shenzhen Ltd. Guangzhou Branch** and located at Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD Guangzhou, China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 549654).

INTERTEK TESTING SERVICES

EXHIBIT 3

SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by DC 3.8V internal rechargeable battery which was charged by USB port (DC 5V). The EUT can't operate during the charging. Only the worst case data was reported.

On 802.11b, g, n (20MHz, 40MHz) mode, only one antenna is used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

The EUT placed in the centre of turntable for Radiated Emission test.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

INTERTEK TESTING SERVICES

3.3 Special Accessories

USB cable with two ferrites.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

3.5 Equipment Modification

Any modifications installed previous to testing by SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

3.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Detail
Micro SD Card	SanDisk	1GB
iPhone	Apple	Model: A1303

INTERTEK TESTING SERVICES

EXHIBIT 4

MEASUREMENT RESULTS

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter has a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 0dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	7.1	5.1
Middle Channel: 2437	8.4	6.9
High Channel: 2462	7.8	6.0

IEEE 802.11g (Antenna Gain = 0dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	8.3	6.8
Middle Channel: 2437	8.3	6.8
High Channel: 2462	8.1	6.5

IEEE 802.11n-HT20 (Antenna Gain = 0dBi) (16QAM, 6.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	7.8	6.0
Middle Channel: 2437	7.8	6.0
High Channel: 2462	7.7	5.9

INTERTEK TESTING SERVICES

IEEE 802.11n-HT40 (Antenna Gain = 0dBi) (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2422	8.8	7.6
Middle Channel: 2437	8.8	7.6
High Channel: 2452	9.1	8.1

Cable loss: 1.0 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 9.1dBm

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v04. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	10.029
2437	10.072
2462	10.029

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.585
2437	16.541
2462	16.498


IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	17.757
2437	17.800
2462	17.887

INTERTEK TESTING SERVICES



IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2422	36.035
2437	36.035
2452	36.035

The test plots are attached as below.

802.11b





INTERTEK TESTING SERVICES




802.11g

TRF no.: FCC 15C_TX_c
 FCC ID: YGB-PDV3600S


INTERTEK TESTING SERVICES





INTERTEK TESTING SERVICES



802.11n-HT20





INTERTEK TESTING SERVICES




INTERTEK TESTING SERVICES

802.11n-HT40



INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v04.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density (dBm)
2412	-5.52
2437	-2.40
2462	-6.05

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz (dBm)
2412	-13.37
2437	-10.66
2462	-7.63

IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz (dBm)
2412	-13.46
2437	-10.95
2462	-8.16

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz (dBm)
2422	-15.27
2437	-13.83
2452	-11.96



The test plots are attached as below.

TRF no.: FCC 15C_TX_c


FCC ID: YGB-PDV3600S

INTERTEK TESTING SERVICES


802.11b





INTERTEK TESTING SERVICES



802.11g





INTERTEK TESTING SERVICES




INTERTEK TESTING SERVICES


802.11n-HT20





INTERTEK TESTING SERVICES



802.11n-HT40



INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v04.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b, 6Mbps for 802.11g and 6.5Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.



The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.


INTERTEK TESTING SERVICES

802.11b


Channel 01 (2412MHz) Reference Level: -5.52dBm




INTERTEK TESTING SERVICES




Channel 06 (2437MHz) Reference Level: -2.40dBm





INTERTEK TESTING SERVICES



Channel 11 (2462MHz) Reference Level: -6.05dBm





INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES


802.11g

Channel 01 (2412MHz) Reference Level: -13.37dBm




TRF no.: FCC 15C_TX_c
 FCC ID: YGB-PDV3600S


INTERTEK TESTING SERVICES




Channel 06 (2437MHz) Reference Level: -10.66dBm





INTERTEK TESTING SERVICES



Channel 11 (2462MHz) Reference Level: -7.63dBm




INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES


802.11n-HT20

Channel 01 (2412MHz) Reference Level: -13.46dBm





TRF no.: FCC 15C_TX_c
 FCC ID: YGB-PDV3600S

INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES


Channel 06 (2437MHz) Reference Level: -10.95dBm



TRF no.: FCC 15C_TX_c
 FCC ID: YGB-PDV3600S


INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: -8.16dBm




TRF no.: FCC 15C_TX_c
 FCC ID: YGB-PDV3600S

INTERTEK TESTING SERVICES





802.11n-HT40

Channel 01 (2422MHz) Reference Level: -15.27dBm





TRF no.: FCC 15C_TX_c
 FCC ID: YGB-PDV3600S

INTERTEK TESTING SERVICES





INTERTEK TESTING SERVICES

Channel 06 (2437MHz) Reference Level: -13.83dBm




INTERTEK TESTING SERVICES

Channel 9 (2452MHz) Reference Level: -11.96dBm



INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- Not required, since all emissions are more than 20dB below fundamental
- See attached data sheet

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified. Simultaneous transmitting was considered during the testing.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission 802.11g (TX-Channel 11) at 7386.0MHz is passed by 10.9dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	31.455	29.4	20.0	11.7	21.1	40.0	-18.9
Horizontal	99.840	25.3	20.0	11.3	16.6	43.5	-26.9
Horizontal	360.036	31.9	20.0	14.5	26.4	46.0	-19.6
Vertical	46.005	26.8	20.0	13.4	20.2	40.0	-19.8
Vertical	99.355	26.3	20.0	11.3	17.6	43.5	-25.9
Vertical	468.895	35.8	20.0	16.3	32.1	46.0	-13.9

NOTES: 1. Quasi-Peak detector is used for frequency below 1GHz.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11b (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	58.6	41.2	33.8	51.2	74.0	-22.8
Horizontal	*2385.030	64.4	41.4	29.3	52.3	74.0	-21.7

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	43.4	41.2	33.8	36.0	54.0	-18.0
Horizontal	*2385.030	49.6	41.4	29.3	37.5	54.0	-16.5

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11b (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Peak Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4874.000	57.5	41.2	33.8	50.1	74.0	-23.9
Horizontal	*7311.000	61.4	41.3	36.1	56.2	74.0	-17.8

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Average Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4874.000	44.0	41.2	33.8	36.6	54.0	-17.4
Horizontal	*7311.000	45.7	41.3	36.1	40.5	54.0	-13.5

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11b (TX-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Peak Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4924.000	58.6	41.2	33.8	51.2	74.0	-22.8
Horizontal	*7386.000	59.7	41.3	36.1	54.5	74.0	-19.5
Horizontal	*2484.460	64.9	41.4	29.3	52.8	74.0	-21.2

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Average Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4924.000	43.5	41.2	33.8	36.1	54.0	-17.9
Horizontal	*7386.000	45.4	41.3	36.1	40.2	54.0	-13.8
Horizontal	*2484.450	52.0	41.4	29.3	39.9	54.0	-14.1

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
 - * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11g (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Peak Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4824.000	57.7	41.2	33.8	50.3	74.0	-23.7
Horizontal	*2380.000	52.0	41.4	29.3	39.9	74.0	-34.1

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Average Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4824.000	44.7	41.2	33.8	37.3	54.0	-16.7
Horizontal	*2380.000	50.7	41.4	29.3	38.6	54.0	-15.4

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11g (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor	Net at 3m (dB _礦 /m)	Peak Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4874.000	57.8	41.2	33.8	50.4	74.0	-23.6
Horizontal	*7311.000	62.3	41.3	36.1	57.1	74.0	-16.9

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor	Net at 3m (dB _礦 /m)	Average Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4874.000	44.2	41.2	33.8	36.8	54.0	-17.2
Horizontal	*7311.000	47.8	41.3	36.1	42.6	54.0	-11.4

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11g (TX-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _{FS})	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _{FS} /m)	Peak Limit at 3m (dB _{FS} /m)	Margin (dB)
Horizontal	*4924.000	57.8	41.2	33.8	50.4	74.0	-23.6
Horizontal	*7386.000	61.6	41.3	36.1	56.4	74.0	-17.6
Horizontal	*2484.460	64.4	41.4	29.3	52.3	74.0	-21.7

Polarization	Frequency (MHz)	Reading (dB _{FS})	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _{FS} /m)	Average Limit at 3m (dB _{FS} /m)	Margin (dB)
Horizontal	*4924.000	44.3	41.2	33.8	36.9	54.0	-17.1
Horizontal	*7386.000	48.3	41.3	36.1	43.1	54.0	-10.9
Horizontal	*2484.460	53.8	41.4	29.3	41.7	54.0	-12.3

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _{FS})	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _{FS} /m)	Peak Limit at 3m (dB _{FS} /m)	Margin (dB)
Horizontal	*4824.000	57.9	41.2	33.8	50.5	74.0	-23.5
Horizontal	*2389.850	62.3	41.4	29.3	50.2	74.0	-23.8

Polarization	Frequency (MHz)	Reading (dB _{FS})	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _{FS} /m)	Average Limit at 3m (dB _{FS} /m)	Margin (dB)
Horizontal	*4824.000	44.5	41.2	33.8	37.1	54.0	-16.9
Horizontal	*2389.850	51.9	41.4	29.3	39.8	54.0	-14.2

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Peak Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4874.000	62.2	41.2	29.3	50.3	74.0	-23.7
Horizontal	*7311.000	61.6	41.3	36.1	56.4	74.0	-17.6

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Average Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4874.000	49.1	41.2	29.3	37.2	54.0	-16.8
Horizontal	*7311.000	48.2	41.3	36.1	43.0	54.0	-11.0

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Peak Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4924.000	57.8	41.2	33.8	50.4	74.0	-23.6
Horizontal	*7386.000	62.2	41.3	36.1	57.0	74.0	-17.0
Horizontal	*2487.489	63.9	41.4	29.3	51.8	74.0	-22.2

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Average Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4924.000	44.6	41.2	33.8	37.2	54.0	-16.8
Horizontal	*7386.000	48.2	41.3	36.1	43.0	54.0	-11.0
Horizontal	*2487.489	53.0	41.4	29.3	40.9	54.0	-13.1

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11n-HT40 (TX-Channel 03)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Peak Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4844.000	57.2	41.2	34.2	50.2	74.0	-23.8
Horizontal	*2389.570	64.6	41.4	29.3	52.5	74.0	-21.5

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Average Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4844.000	43.7	41.2	34.2	36.7	54.0	-17.3
Horizontal	*2389.570	48.3	41.4	29.3	36.2	54.0	-17.8

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11n-HT40 (TX-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Peak Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4874.000	57.7	41.2	33.8	50.3	74.0	-23.7
Horizontal	*7311.000	61.1	41.3	36.1	55.9	74.0	-18.1

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Average Limit at 3m (dB _礦 /m)	Margin (dB)
Horizontal	*4874.000	44.6	41.2	33.8	37.2	54.0	-16.8
Horizontal	*7311.000	47.7	41.3	36.1	42.5	54.0	-11.5

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

Worst Case Operating Mode: 802.11n-HT40 (TX-Channel 09)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Peak Limit at 3m (dB _礦 /m)	Margin (dB)
Vertical	*4904.000	57.7	41.2	33.8	50.3	74.0	-23.7
Vertical	*2483.200	64.4	41.4	29.3	52.3	74.0	-21.7

Polarization	Frequency (MHz)	Reading (dB _礦)	Pre- Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB _礦 /m)	Average Limit at 3m (dB _礦 /m)	Margin (dB)
Vertical	*4904.000	43.6	41.2	33.8	36.2	54.0	-17.8
Vertical	*2483.200	45.8	41.4	29.3	33.7	54.0	-20.3

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.9 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

- [] Not required - No digital part
- [] Test results are attached
- [x] Included in the separated report.

INTERTEK TESTING SERVICES

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)Co.,Ltd

Date of Test: 12 May 2017

Model: 1002929

4.10 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

INTERTEK TESTING SERVICES

EXHIBIT 5

EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 6

PRODUCT LABELLING

INTERTEK TESTING SERVICES

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

EXHIBIT 7

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

INTERTEK TESTING SERVICES

EXHIBIT 8

INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 9

CONFIDENTIALITY REQUEST

INTERTEK TESTING SERVICES

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 10

MISCELLANEOUS INFORMATION

INTERTEK TESTING SERVICES

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

INTERTEK TESTING SERVICES

EXHIBIT 11

TEST EQUIPMENT LIST

INTERTEK TESTING SERVICES

11.0 Test Equipment List

RF conducted test

Equipment No.	Equipment	Model	Manufacturer	Cal. Due date (YYYY-MM-DD)	Calibration Interval
EM031-03	Signal and Spectrum Analyzer (10 Hz~40 GHz)	R&S FSV40	R&S	6/3/2017	1Y
EM086-11	Power Meter	NRP2	R&S	1/5/2018	1Y
EM086-11-01	Power Sensor	NRP-Z91	R&S	1/5/2018	1Y
EM006-06-10	Coaxial cable	/	R&S	4/11/2018	1Y

Radiated Emission

Equipment No.	Equipment	Model	Manufacturer	Cal. Due date (YYYY-MM-DD)	Calibration Interval
EM030-04	3m Semi-Anechoic Chamber	9×6×6 m ³	ETS•LINDGREN	5/9/2018	1Y
EM031-02	EMI Test Receiver (9 kHz~7 GHz)	R&S ESR7	R&S	6/7/2017	1Y
EM031-03	Signal and Spectrum Analyzer (10 Hz~40 GHz)	R&S FSV40	R&S	6/3/2017	1Y
EM011-04	Loop antenna (9 kHz-30 MHz)	HFH2-Z2	R&S	6/6/2017	1Y
EM061-03	TRILOG Super Broadband test Antenna (30 MHz-1.5 GHz) (TX)	VULB 9161	SCHWARZBECK	6/6/2017	1Y
EM033-01	TRILOG Super Broadband test Antenna(30 MHz-3 GHz) (RX)	VULB 9163	SCHWARZBECK	9/8/2017	1Y
EM033-02	Bouble-Ridged Waveguide Horn Antenna (800 MHz-18 GHz)(RX)	R&S HF907	R&S	6/6/2017	1Y
EM033-03	High Frequency Antenna & preamplifier(18 GHz~26.5 GHz) (RX)	R&S SCU-26	R&S	4/1/2018	1Y
EM033-04	High Frequency Antenna & preamplifier (26 GHz-40 GHz)	R&S SCU-40	R&S	4/1/2018	1Y
EM031-02-01	Coaxial cable(9 kHz-1 GHz)	N/A	R&S	5/30/2017	1Y
EM033-02-02	Coaxial cable(1 GHz-18 GHz)	N/A	R&S	5/30/2017	1Y
EM033-04-02	Coaxial cable(18 GHz~40 GHz)	N/A	R&S	4/1/2018	1Y
EM022-03	2.45 GHz Filter	BRM50702	Micro-Tronics	5/9/2018	1Y