

SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Application For Certification

FCC ID: YGB-WDV6000

Wifi Camera

Model: WDV6000

WiFi Transceiver

Report No.: 150109018SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-01-13]

Prepared and Checked by:	Approved by:
Sign on file	
Sunny Zhou Engineer	Andy Yan Senior Project Engineer Date: March 23, 2015

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C_Tx_b

LIST OF EXHIBITS

INTRODUCTION

EXHIBIT 1: Summary of Tests

EXHIBIT 2: General Description

EXHIBIT 3: System Test Configuration

EXHIBIT 4: Measurement Results

EXHIBIT 5: Equipment Photographs

EXHIBIT 6: Product Labeling

EXHIBIT 7: Technical Specifications

EXHIBIT 8: Instruction Manual

EXHIBIT 9: Confidentiality Request

EXHIBIT 10: Miscellaneous Information

EXHIBIT 11: Test Equipment List

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

MEASUREMENT/TECHNICAL REPORT

SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD MODEL: WDV6000

FCC ID: YGB-WDV6000

This report concerns (check one) Original	Grant X Class II Change	
Equipment Type: <u>DTS - Part 15 Digital Transmission Systems (WiFi transmitter</u>		
portion)		
Deferred grant requested per 47 CFR 0.457	d)(1)(ii)? Yes NoX	
	If yes, defer until:	
Company Name agrees to notify the Commis		
	date	
of the intended date of announcement of issued on that date.	the product so that the grant can be	
Transition Rules Request per 15.37?	Yes NoX	
If no, assumed Part 15, Subpart C for in [10-01-13 Edition] provision.	tentional radiator - the new 47 CFR	
Report prepared by:		
Sunny Zhou Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch 6F, Block D, Huahan Building, Langshan Road Nanshan District, Shenzhen, P. R. China Phone: (86 755) 8614 0695 Fax: (86 755) 8614 6751		

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Table of Contents

1.0 <u>Su</u>	mmary of test results	2
0.00	and December the	
	peral Description	
2.1		
2.2	(-)	
2.3	Test Methodology	5
2.4	Test Facility	5
3.0 Sys	tem Test Configuration	7
3.1	Justification	
3.2	EUT Exercising Software	
3.3	Details of EUT and Description of Peripherals	
3.4	Measurement Uncertainty	
3.5	Equipment Modification	
3.6	Support Equipment List and Description	δ
4.0 Me	asurement Results	10
4.1	Maximum Conducted Output Power at Antenna Terminals	10
4.2	Minimum 6dB RF Bandwidth	12
4.3	Maximum Power Density	22
4.4	Out of Band Conducted Emissions	
4.5	Out of Band Radiated Emissions	
4.6	Transmitter Radiated Emissions in Restricted Bands	
4.7	Field Strength Calculation	
4.8	Radiated Spurious Emission	
4.9	Conducted Emission	
_		
	Radiated Emission from Digital Section of Transceiver	
4.11	Transmitter Duty Cycle Calculation and Measurements	73
5.0 Eq	iipment Photographs	
6 0 Pro	duct Labelling	77
		
7.0 <u>Tec</u>	hnical Specifications	79
8.0 <u>Ins</u> t	ruction Manual	81
0.0.0	ofidentiality Request	00
ಶ.∪ <u>COI</u>	nfidentiality Request	03
10.0 <u>Mi</u>	scellaneous Information	85
11.0 <u>Te</u>	st Equipment List	87

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 1 SUMMARY OF TEST RESULTS

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

1.0 Summary of Test results

SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD MODEL: WDV6000

FCC ID: YGB-WDV6000

TEST	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Note: The EUT uses an integral antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 2 GENERAL DESCRIPTION

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

2.0 **General Description**

2.1 Product Description

The Equipment Under Test (EUT) is a Wifi Camera with WiFi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 9 channels with 5MHz channel spacing. The EUT can be powered by 3.8Vdc rechargeable battery which can be charged by 5Vdc USB port. For more detailed features description, please refer to the user's manual.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK. Antenna Type: Integral Antenna.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

2.2 Related Submittal(s) Grants

This is an application for certification of:
DTS- Part 15 Digital Transmission Systems (WiFi transmitter portion)

Remaining portions are subject to the following procedures:

- 1. Receiver portion of WiFi: exempt from technical requirement of this Part.
- 2. Other Digital Function: Refer to report 150109018SZN-002

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009) and KDB 558074. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, Block D, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 3 SYSTEM TEST CONFIGURATION

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

3.0 **System Test Configuration**

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by the fully charged 3.8Vdc rechargeable battery and charged by PC USB Port (The PC was powered by AC 120V/60Hz) during the testing. All data rate were tested and only the worst case data is showed in the report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

3.3 Special Accessories

One shielded USB cable attached with the EUT was used.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

3.5 Equipment Modification

Any modifications installed previous to testing by SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

3.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
Laptop	Lenovo	T420
Hard Disk	Smart.drive	HD-003
1394 Cable	Smart.drive	Unshielded, Length 180cm
USB Cable	Smart.drive	Unshielded, Length 120cm
Mini SD Card	SanDisk	4G
HDMI cable	N/A	Unshielded, Length 150cm
USB Cable	N/A	Shielded, Length 100cm
Dummy Load	N/A	E214887 RM-01

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 4

MEASUREMENT RESULTS

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 2dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	8.20	6.61
Middle Channel: 2437	7.28	5.35
High Channel: 2462	7.59	5.74

IEEE 802.11g (Antenna Gain = 2dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	5.00	3.16
Middle Channel: 2437	5.42	3.48
High Channel: 2462	5.92	3.91

IEEE 802.11n-HT20 (Antenna Gain = 2dBi) (16QAM, 6.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	5.86	3.85
Middle Channel: 2437	6.70	4.68
High Channel: 2462	7.40	5.50

IEEE 802.11n-HT40 (Antenna Gain = 2.0dBi) (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Low Channel: 2422	7.13	5.16
Middle Channel: 2437	7.42	5.52
High Channel: 2452	7.70	5.89

Cable loss: <u>0.5</u> dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 8.20dBm

For RF Exposure, the information is saved with filename: RF exposure.pdf.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

IEEE 802.11b (CCK, 1Mbps)		
Frequency (MHz)	6 dB Bandwidth (MHz)	
2412	9.57	
2437	10.07	
2462	10.07	

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.28
2437	16.28
2462	15.33

IEEE 802.11n-HT20 (16QAM, 6.5Mbps)		
Frequency (MHz)	6 dB Bandwidth (MHz)	
2412	17.56	
2437	17.58	
2462	17.11	


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2422	35.53
2437	35.53
2452	35.50


The test plots are attached as below.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11b




Date: 29.JAN.2015 09:53:51



Date: 29.JAN.2015 10:14:46


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 10:27:14

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000


802.11g





Date: 29.JAN.2015 10:43:35


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 10:36:35

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11 n-HT20




Date: 29.JAN.2015 11:04:21



Date: 29.JAN.2015 11:08:23


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 11:13:47

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11 n-HT40




Date: 29.JAN.2015 13:13:49



Date: 29.JAN.2015 11:36:41

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000



Date: 29.JAN.2015 11:32:10

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/ 3 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	0.09
2437	1.23
2462	2.47

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-7.68
2437	-6.65
2462	-6.63


IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-8.41
2437	-6.72
2462	-6.07

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2422	-9.79
2437	-9.29
2452	-8.57


The test plots are attached as below.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11b




Date: 29.JAN.2015 10:00:34



Date: 29.JAN.2015 10:17:18


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 10:28:13

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11g




Date: 29.JAN.2015 10:49:31



Date: 29.JAN.2015 10:45:48

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 10:37:32

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000


Report No.: 150109018SZN-001

26

802.11 n-HT20




Date: 29.JAN.2015 11:05:13



Date: 29.JAN.2015 11:09:08


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 11:16:05

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11 n-HT40




Date: 29.JAN.2015 13:14:38



Date: 29.JAN.2015 11:38:08

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000



Date: 29.JAN.2015 11:32:56

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074.


Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.

The test plots showed all spurious emission up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.


The test plots are attached as below.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11b Channel 01 (2412MHz) Reference Level: 0.09 dBm



Date: 29.JAN.2015 10:05:53



Date: 29.JAN.2015 10:06:34


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000



Date: 29.JAN.2015 10:07:20

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Channel 06 (2437MHz) Reference Level: 1.23dBm



691 pts

Measuring...

Date: 29.JAN.2015 10:25:11


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

-80 dBm Start 2.4835 GHz


Report No.: 150109018SZN-001

Stop 25.0 GHz

Channel 11 (2462MHz) Reference Level: 2.47dBm




Date: 29.JAN.2015 10:29:32



Date: 29.JAN.2015 10:29:04


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 10:30:40

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11g Channel 01 (2412MHz) Reference Level: -7.68dBm




Date: 29.JAN.2015 10:50:10



Date: 29.JAN.2015 10:51:21


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 10:52:02

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Channel 06 (2437MHz) Reference Level: -6.65dBm




Date: 29.JAN.2015 10:46:18




Date: 29.JAN.2015 10:46:57

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Channel 11 (2462MHz) Reference Level: -6.63dBm




Date: 29.JAN.2015 10:41:32



Date: 29.JAN.2015 10:39:24


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 10:34:48

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11 n-HT20 Channel 01 (2412MHz) Reference Level: -8.41dBm



Date: 29.JAN.2015 11:05:54




Date: 29.JAN.2015 11:06:30

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000



Date: 29.JAN.2015 11:02:50

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000



691 pts

Measuring...

Date: 29.JAN.2015 11:10:23


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

-70 dBm


Start 2.4835 GHz

Report No.: 150109018SZN-001

Stop 25.0 GHz








Date: 29.JAN.2015 11:17:26


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000




Date: 29.JAN.2015 11:18:57

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

802.11 n-HT40 Channel 03 (2422MHz) Reference Level: -9.79dBm



Date: 29.JAN.2015 13:15:23




Date: 29.JAN.2015 13:15:59

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000



Date: 29.JAN.2015 13:16:34

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000



691 pts

Measuring...

Date: 29.JAN.2015 11:39:05


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

-70 dBm

Start 2.4835 GHz

Report No.: 150109018SZN-001

Stop 25.0 GHz



691 pts

Measuring...

Date: 29.JAN.2015 11:33:46


TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

-70 dBm

Start 2.4835 GHz

Report No.: 150109018SZN-001

Stop 25.0 GHz



Date: 29.JAN.2015 11:31:09

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

[×] Not required, since all emissions are more than 20dB below fundamental [] See attached data sheet

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

FS = RA + AF + CF - AG + PD

Where FS = Field Strength in $dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in $dB\mu V$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

 $RA = 62.0 dB\mu V$

AF = 7.4 dB

CF = 1.6 dB

AG = 29.0 dB

PD = 0 dB

 $FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \, dB\mu V/m$

Level in mV/m = Common Antilogarithm [(42 dB μ V/m)/20] = 125.9 μ V/m

54

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission (802.11 g) at 242.920MHz is passed by 3.7 dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Worst Case Operating Mode: 802.11 g (TX-Channel 01)

Radiated Emissions

	_		_				
Polarization	Frequency	Reading	Pre-	Antenna	Net	Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,	, , ,	Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)				
Horizontal	221.330	42.9	20.0	6.1	29.0	46.0	-17.0
Horizontal	242.920	52.0	20.0	10.3	42.3	46.0	-3.7
Horizontal	351.040	39.3	20.0	13.9	33.2	46.0	-12.8
Vertical	60.640	38.4	20.0	9.8	28.2	40.0	-11.8
Vertical	143.002	44.4	20.0	6.8	31.2	43.5	-12.3
Vertical	255.300	44.2	20.0	16.3	40.5	46.0	-5.5

NOTES: 1. Quasi-Peak detector is used except for others stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. All emissions are below the QP limit.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11b (TX-Channel 01)

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4824.000	48.2	36.1	34.1	46.2	74.0	-27.8
Horizontal	*2389.000	69.5	36.8	26.5	59.2	74.0	-14.8

	Polarization	Frequency (MHz)	Reading (dBµV)	Pre- Amp Gain	Antenna Factor (dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
				(dB)	(GD)	(αΒμ ν/ιτι)	(dDµ v/111)	
	Horizontal	*4824.000	40.4	36.1	34.1	38.4	54.0	-15.6
Ī	Horizontal	*2389.000	52.4	36.8	26.5	42.1	54.0	-11.9

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11b (TX-Channel 06)

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,	, , ,	Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)	, ,			
Horizontal	*4874.000	51.7	36.1	34.5	50.1	74.0	-23.9
Horizontal	*7311.000	48.7	35.6	37.1	50.2	74.0	-23.8

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,	,	Gain	(dB)	(dBµV/m)	(dBµV/m)	` ,
			(dB)				
Horizontal	*4874.000	36.7	36.1	34.5	35.1	54.0	-18.9
Horizontal	*7311.000	36.7	35.6	37.1	38.2	54.0	-15.8

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11b (TX-Channel 11)

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,		Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)				
Horizontal	*4924.000	48.9	36.1	34.7	47.5	74.0	-26.5
Horizontal	*2484.550	55.0	35.6	39.5	58.9	74.0	-15.1

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	$(dB\mu V/m)$	(dBµV/m)	
			(dB)				
Horizontal	*4924.000	34.6	36.1	34.7	33.2	54.0	-20.8
Horizontal	*2483.550	37.1	35.6	39.5	41.0	54.0	-13.0

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11g (TX-Channel 01)

Radiated Emissions

-								
	Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
		(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
				Gain	(dB)	(dBµV/m)	(dBµV/m)	
				(dB)				
	Horizontal	*4824.000	52.2	36.1	34.1	50.2	74.0	-23.8
	Horizontal	*2385.466	73.5	36.8	26.5	63.2	74.0	-10.8

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,		Gain	(dB)	(dBµV/m)	(dBµV/m)	` ′
			(dB)	, ,	, ,	, , ,	
Horizontal	*4824.000	42.5	36.1	34.1	40.5	54.0	-13.5
Horizontal	*2385.466	55.8	36.8	26.5	45.5	54.0	-8.5

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11g (TX-Channel 06)

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,		Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)				
Horizontal	*4874.000	51.9	36.1	34.5	50.3	74.0	-23.7
Horizontal	*7311.000	51.7	35.6	37.1	53.2	74.0	-20.8

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4874.000	40.1	36.1	34.5	38.5	54.0	-15.5
Horizontal	*7311.000	35.0	35.6	37.1	36.5	54.0	-17.5

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11g (TX-Channel 11)

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	. ,
			(dB)				
Horizontal	*4924.000	50.6	36.1	34.7	49.2	74.0	-24.8
Horizontal	*2484.610	58.6	35.6	39.5	62.5	74.0	-11.5

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4924.000	37.3	36.1	34.7	35.9	54.0	-18.1
Horizontal	*2484.610	38.1	35.6	39.5	42.0	54.0	-12.0

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11 n-HT20 (TX-Channel 01)

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4824.000	51.5	36.1	34.1	49.5	74.0	-24.5
Horizontal	*2388.422	70.5	36.8	26.5	60.2	74.0	-13.8

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4824.000	37.9	36.1	34.1	35.9	54.0	-18.1
Horizontal	*2388.422	54.6	36.8	26.5	44.3	54.0	-9.7

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11 n-HT20 (TX-Channel 06)

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,		Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)	, ,			
Horizontal	*4874.000	50.1	36.1	34.5	48.5	74.0	-25.5
Horizontal	*7311.000	49.8	35.6	37.1	51.3	74.0	-22.7

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4874.000	37.8	36.1	34.5	36.2	54.0	-17.8
Horizontal	*7311.000	36.0	35.6	37.1	37.5	54.0	-16.5

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11 n-HT20 (TX-Channel 11)

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,		Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4924.000	49.9	36.1	34.7	48.5	74.0	-25.5
Horizontal	*2485.521	59.8	35.6	39.5	63.7	74.0	-10.3

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4924.000	35.7	36.1	34.7	34.3	54.0	-19.7
Horizontal	*2485.521	36.1	35.6	39.5	40.0	54.0	-14.0

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11 n-HT40 (TX-Channel 03)

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	. ,
			(dB)				
Horizontal	*4844.000	51.5	36.1	34.1	49.5	74.0	-24.5
Horizontal	*2388.720	72.7	36.8	26.5	62.4	74.0	-11.6

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4844.000	39.6	36.1	34.1	37.6	54.0	-16.4
Horizontal	*2388.720	55.5	36.8	26.5	45.2	54.0	-8.8

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11 n-HT40 (TX-Channel 06)

Radiated Emissions

Polarizatio	n Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)		, , ,		
Horizonta	*4874.000	51.8	36.1	34.5	50.2	74.0	-23.8
Horizonta	*7311.000	49.8	35.6	37.1	51.3	74.0	-22.7

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	*4874.000	39.9	36.1	34.5	38.3	54.0	-15.7
Horizontal	*7311.000	34.4	35.6	37.1	35.9	54.0	-18.1

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

Mode: 802.11 n-HT40 (TX-Channel 9)

Radiated Emissions

Ρ	olarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
		(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
		, ,		Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
				(dB)				
H	Iorizontal	*4904.000	51.9	36.1	34.7	50.5	74.0	-23.5
H	Horizontal	*2484.522	59.3	35.6	39.5	63.2	74.0	-10.8

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)				
Horizontal	*4904.000	36.6	36.1	34.7	35.2	54.0	-18.8
Horizontal	*2484.522	39.3	35.6	39.5	43.2	54.0	-10.8

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

4.9 Conducted Emission

Worst Case Conducted emission at 0.232MHz is Passed by 8.6 dB margin

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD


Date of Test: January 29, 2015

Model: WDV6000

Worst Case Operating Mode: 802.11g (TX-Channel 01)

Line: Live

Conducted Emission Test - FCC



Result Table QP

Frequency	QuasiPeak	Line	Corr.	Margin	Limit
(MHz)	(dB µ V)		(dB)	(dB)	(dB µ V)
0.168	55.0	L1	9.8	10.1	65.1
0.186	55.2	L1	9.8	9.0	64.2
0.206	52.7	L1	9.8	10.7	63.4
0.232	53.8	L1	9.8	8.6	62.4
0.334	46.6	L1	9.8	12.8	59.4
0.418	44.7	L1	9.8	12.8	57.5

Result Table AV

Frequency	Average	Line	Corr.	Margin	Limit
(MHz)	(dB µ V)		(dB)	(dB)	(dB µ V)
0.168	38.7	L1	9.8	16.4	55.1
0.186	37.6	L1	9.8	16.6	54.2
0.206	38.5	L1	9.8	14.9	53.4
0.232	37.0	L1	9.8	15.4	52.4
0.334	38.0	L1	9.8	11.4	49.4
0.418	36.8	L1	9.8	10.7	47.5

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Report No.: 150109018SZN-001

70

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD


Date of Test: January 29, 2015

Model: WDV6000

Worst Case Operating Mode: 802.11g (TX-Channel 01)

Line: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency	QuasiPeak	Line	Corr.	Margin	Limit
(MHz)	(dB µ V)		(dB)	(dB)	(dB µ V)
0.167	54.0	N	10.0	11.1	65.1
0.192	54.2	N	10.0	9.8	64.0
0.205	53.2	N	10.1	10.2	63.4
0.231	51.9	N	10.1	10.5	62.4
0.335	45.9	N	10.1	13.5	59.4
0.416	47.2	N	10.1	10.4	57.6

Result Table AV

Frequency (MHz)	Average (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.167	35.5	N	10.0	19.6	55.1
0.192	32.8	N	10.0	21.2	54.0
0.205	33.6	N	10.1	19.8	53.4
0.231	34.6	N	10.1	17.8	52.4
0.335	36.4	N	10.1	13.0	49.4
0.416	35.6	N	10.1	12.0	47.6

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTI Date of Test: January 29, 2015 Model: WDV6000)
4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109	
[] Not required - No digital part	
[] Test results are attached	
[x] Included in the separated report.	

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Applicant: SHUOYING DIGITAL SCIENCE&TECHNOLOGY (CHINA)CO., LTD

Date of Test: January 29, 2015

Model: WDV6000

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
Х	Not applicable, duty cycle was not used.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 5

EQUIPMENT PHOTOGRAPHS

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

5.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.pdf.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 6

PRODUCT LABELLING

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

6.0 **Product Labeling**

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 7

TECHNICAL SPECIFICATIONS

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

7.0 <u>Technical Specifications</u>

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Report No.: 150109018SZN-001

79

EXHIBIT 8

INSTRUCTION MANUAL

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

8.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 9

CONFIDENTIALITY REQUEST

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

9.0 **Confidentiality Request**

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 10

MISCELLANEOUS INFORMATION

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

Report No.: 150109018SZN-001

84

10.0 <u>Discussion of Pulse Desensitization</u>

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF.*

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

EXHIBIT 11

TEST EQUIPMENT LIST

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000

11.0 **Test Equipment List**

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	21-May-2014	21-May-2015
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	21-May-2014	21-May-2015
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	28-Jun-2014	28-Jun-2015
SZ185-01	EMI Receiver	R&S	ESCI	100547	10-Mar-2014	10-Mar-2015
SZ061-09	Horn Antenna	ETS	3115	00092346	01-Nov-2014	01-Nov-2015
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	03-Sep-2014	03-Sep-2015
SZ061-06	Active Loop Antenna	Electro- Metrics	EM-6876	217	29-Apr-2014	29-Apr-2015
EM031-03	EXA Spectrum Analyzer	R&S	FSV40	101506	09-Jun-2014	09-Jun-2015
SZ181-04	Preamplifier	Agilent	8449B	3008A024 74	10-Mar-2014	10-Mar-2015
SZ188-01	Anechoic Chamber	ETS	RFD-F/A- 100	4102	19-Apr-2014	19-Apr-2015
SZ062-02	RF Cable	RADIALL	RG 213U		03-Jan-2015	03-Jan-2016
SZ062-05	RF Cable	RADIALL	0.04- 26.5GHz	1	09-Oct-2014	09-Apr-2015
SZ062-12	RF Cable	RADIALL	0.04- 26.5GHz		09-Oct-2014	09-Apr-2015
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	-	21-May-2014	21-May-2015
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	01-Nov-2014	01-Nov-2015
SZ187-01	Two-Line V- Network	R&S	ENV216	100072	01-Nov-2014	01-Nov-2015
SZ187-02	Two-Line V- Network	R&S	ENV216	100073	16-Jun-2014	16-Jun-2015
SZ188-03	Shielding Room	ETS	RFD-100	4100	23-Aug-2014	23-Aug-2015

TRF no.: FCC 15C_TX_b FCC ID: YGB-WDV6000