

# TEST RESULT SUMMARY

## FCC Part 15 Subpart C Section 15.247

MANUFACTURER'S NAME	ClimateMinder Incorporated
MANUFACTURER'S ADDRESS	9444 Haines Canyon Avenue Tujunga CA 91042
NAME OF EQUIPMENT	NodeRF V2.1.90 – Wireless Sensor Network RF Node
MODEL NUMBER(S) TESTED	V2.1.90
TEST REPORT NUMBER	WC909614 Rev C
TEST DATE(S)	30 March – 08 July 2010

TÜV SÜD America Inc, as an independent testing laboratory, declares that the equipment tested as specified above conforms to the applicable EMC requirements of FCC Part 15 Subpart C Section 15.247 *“Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz; General requirements.”*


It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics. Any modifications necessary for compliance made during testing on the above mentioned date(s) must be implemented in all production units for compliance to be maintained.


Date: 09 July 2010

Tested by:

Approved by:

Location: Taylors Falls MN  
USA

  
Greg Jakubowski  
Senior EMC Technician

  
Joel T Schneider  
Senior EMC Engineer

Not Transferable

# EMC TEST REPORT

Test Report No. WC909614 Rev C Date of issue: 09 July 2010

Model / Serial No(s) Tested V2.1.90 / N/A

Product Type NodeRF V2.1.90 – Wireless Sensor Network RF Node

Manufacturer ClimateMinder Incorporated

Address 9444 Haines Canyon Avenue  
Tujunga CA 91042

Test Result ☒ **Positive** ☐ **Negative**

*TÜV SÜD America Inc reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. TÜV SÜD America Inc shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD America Inc issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval. This report shall not be used by the client to claim product endorsement by NVLAP, NIST, or any agency of the US government.*

*TÜV SÜD America Inc and its professional staff hold government and Professional organization certifications and are members of AAMI, ACIL, AEA, ANSI, IEEE, NARTE, and VCCI.*

## REVISION RECORD

REVISION	TOTAL NUMBER OF PAGES	DATE	DESCRIPTION
	48	27 May 2010	Initial Release
A	50	28 June 2010	▪ Revisions include additional test data.
B	57	09 July 2010	▪ Revisions include additional conducted AC power line test data.
C	50	09 July 2010	▪ Revisions include removal of external antenna data



## TEST REPORT CONTENTS

	Page(s)
Revision Record	2
Directory	3
Test Regulations, Environmental conditions, Power supply	4
Test Information:	
6 dB Bandwidth, 15.247(1)(2)	5 - 8
Maximum peak output power, 15.247(b)(3)	9 - 12
Spurious Emissions, 15.247(d)	13 - 24
Power Spectral Density, 15.247(e)	25 - 28
AC power line conducted emissions, 15.207	29 - 34
Test-setups (Photos)	35 - 38
Equipment Under Test Information	39
General Remarks and Summary	40
<b>Appendix A</b>	
Constructional Data Form	41 - 48
<b>Appendix B</b>	
Measurement Protocol	49 - 50

## STATEMENT OF MEASUREMENT UNCERTAINTY

The data and results referenced in this document are accurate. The reader is cautioned that there is some measurement variability due to the tolerances of the test equipment that can contribute to a nominal product measurement uncertainty. Furthermore, component differences and manufacturing process variability of production units similar to that tested may result in additional product uncertainty. If necessary, refer to the test lab for the actual measurement uncertainty for specific tests.

## TEST EQUIPMENT

All measurement instrumentation is traceable to the National Institute of Standards and Technology and is calibrated according to internal procedure.

**EMC TEST REGULATIONS:**

The tests were performed according to the following regulations:

- - FCC Part 15 Subpart C Section 15.247

**ENVIRONMENTAL CONDITIONS IN THE LAB**


	<u>Actual</u>
Temperature:	: 20 – 23°C
Atmospheric pressure	: 98 – 99.5kPa
Relative Humidity	: 26 – 69%

**POWER SUPPLY UTILIZED**

Power supply system	: 3.6VDC Battery Powered 110 VAC, 60 Hz from bench power supply
---------------------	--

**SIGN EXPLANATIONS**

- ☐ - not applicable
- - applicable



## 6 dB Bandwidth FCC 15.247(a)(2)

### Test summary

The requirements are: ☒ - MET ☐ - NOT MET

Test was performed in accordance with the test procedure of FCC KDB Publication 558074

The minimum 6 dB bandwidth = 1.56 MHz

### Test location

- ☐ - Wild River Lab Large Test Site (Open Area Test Site)
- ☐ - Wild River Lab Small Test Site (Open Area Test Site)
- ☒ - Wild River Lab Tech Area, conducted measurement

### Test equipment

TUV ID	Model Number	Manufacturer	Description	Serial Number	Cal Due
WRLE03371	E4440A	Agilent	Spectrum Analyzer	MY43362222	11-Aug-10

### Test limit

500 kHz minimum

### Test data

See following pages

### 6 dB Bandwidth Low Channel

Agilent 11:15:42 Mar 30, 2010

▲ Mkr2 1.60 MHz  
-0.20 dB

Ref 15 dBm

#Atten 30 dB

#Peak

Log

10

dB/

Offst

0.5

dB

DI

-1.1

dBm

LgAv

V1 S2

Center 2.450 00 GHz

Span 10 MHz

#Res BW 100 kHz

VBW 300 kHz

Sweep 1 ms (1001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.449 50 GHz	4.86 dBm
2R	(1)	Freq	2.449 22 GHz	-1.82 dBm
2Δ	(1)	Freq	1.60 MHz	-0.20 dB

# 6 dB Bandwidth Mid Channel

Agilent 10:19:46 Mar 30, 2010

▲ Mkr2 1.58 MHz  
-0.59 dB

Ref 15 dBm

#Atten 30 dB

#Peak

Log

10

dB/

Offst

0.5

dB

DI

-2.2

dBm

LgAv

V1 S2

Center 2.465 00 GHz

Span 10 MHz

#Res BW 100 kHz

VBW 300 kHz

Sweep 1 ms (1001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.464 89 GHz	3.81 dBm
2R	(1)	Freq	2.464 26 GHz	-2.65 dBm
2▲	(1)	Freq	1.58 MHz	-0.59 dB

# 6 dB Bandwidth High Channel

Agilent 11:25:54 Mar 30, 2010

▲ Mkr2 1.56 MHz  
-0.24 dB

Ref 15 dBm

#Atten 30 dB

#Peak

Log

10

dB/

Offst

0.5

dB

DI

-1.8

dBm

LgAv

V1 S2

Center 2.480 00 GHz

Span 10 MHz

#Res BW 100 kHz

VBW 300 kHz

Sweep 1 ms (1001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.479 51 6Hz	4.21 dBm
2R	(1)	Freq	2.479 24 6Hz	-1.96 dBm
2▲	(1)	Freq	1.56 MHz	-0.24 dB

**Maximum peak output power**  
**FCC 15.247(b)(3), IC RSS-210 A8.4(4)**

**Test summary**

The requirements are: ☒ - MET ☐ - NOT MET

Test was performed in accordance with the test procedure of FCC KDB Publication 558074

Maximum peak output power is 9.26 dBm or 8.45 mW

**Test location**

☐ - Wild River Lab Large Test Site (Open Area Test Site)

☐ - Wild River Lab Small Test Site (Open Area Test Site)

☒ - Wild River Lab Tech Area, conducted measurement

**Test equipment**

TUV ID	Model Number	Manufacturer	Description	Serial Number	Cal Due
WRLE03371	E4440A	Agilent	Spectrum Analyzer	MY43362222	11-Aug-10

**Test limit**


1 watt

**Test data**

See following pages

# **Peak output power Low Channel**


\* Agilent 11:17:50 Mar 30, 2010



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.449 55 GHz	9.26 dBm

### Peak output power Mid Channel


✱ Agilent 10:14:38 Mar 30, 2010



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.465 40 GHz	8.42 dBm

### Peak output power High Channel

\* Agilent 11:27:17 Mar 30, 2010



## Spurious emissions

FCC 15.247(d), IC RSS-210 A8.5

### Test summary

The requirements are: ☐ - MET ☒ - NOT MET

Test was performed in accordance with ANSI C63.4 2003, clause 8.3 and FCC KDB Publication 558074

Maximum conducted spurious emission is -54.10dBc (-54.10dBm) at 2.632 GHz

Maximum radiated spurious emissions in the restricted bands below 1 GHz >10dBm since no significant emissions detected from 30 – 1000 MHz on all 3 channels in the Vertical and Horizontal polarization.

Maximum radiated spurious emissions in the restricted bands below 1 GHz >10dBm since no significant emissions detected from 1000 – 26000 MHz on all 3 channels in the Vertical and Horizontal polarization.

### Test location

- ☒ - Wild River Lab Large Test Site (Open Area Test Site)
- ☐ - Wild River Lab Small Test Site (Open Area Test Site)
- ☒ - Wild River Lab Tech Area, conducted measurement

### Test equipment

TUV ID	Model Number	Manufacturer	Description	Serial Number	Cal Due
WRLE03371	E4440A	Agilent	Spectrum Analyzer	MY43362222	11-Aug-10
WRLE02681	85650A	Hewlett-Packard	Quasi-Peak Adapter	2430A00562	12-May-11
WRLE02690	8566B	Hewlett-Packard	Spectrum Analyzer	2430A00930	28-Oct-10
WRLE02674	85662A	Hewlett-Packard	Analyzer Display	2050A02007	28-Oct-10
WRLE03995	EM-6917B	Electro-Metrics	Biconicalog Periodic	151	07-May-11
WRLE10617	ZHL-1042J	Mini-Circuits	Preamplifier 30 MHz-5 GHz	QA0746004	Code B 25-Sep-10
WRLE02075	3115	EMCO	Ridge Guide Ant. 1-18 GHz	9001-3275	18-Jan-11
WRLE10527	SL18B4020	Phase One Microwave	Preamplifier 1 – 18 GHz	0001	Code B 28-Sep-10
WRLE06717	3116	EMCO	Ridge Guide Ant 18-40 GHz	2005	03-Jun-10
WRLE03978	SL26-3010	Phase One Microwave	Amplifier 18-26.5 GHz	0005	Code B 14-Jun-10
WRLE03997	EWT-14-0066	EWT	2.4 GHz Notch filter	E2	Code B 26-Feb-11

Code B = Calibration verification performed internally. Code Y = Calibration not required when used with other calibrated equipment.

### Test limit - conducted

-20 dBc

### Test limit within restricted bands per 15.205 - radiated

Frequency (MHz)	Field strength (μV/meter)	Field strength (dBμV/meter)
30 - 88	100, QP	40.0
88 - 216	150, QP	43.5
216 - 960	200, QP	46.0
Above 960	500, QP	54.0
> 1000	500, AV	54.0
	5000, PK	74.0

### Test data

See following pages

# Radiated Spurious emissions

## List of measurements for run #: 4

FREQ	LEVEL (dBuV)	CABLE / ANT / PREAMP / ATTEN (dB)	FINAL (dBuV / m)	POL / HGT / AZ (m)(DEG)	DELTA1 FCC 15.247 restricted bands >1GHz 3m av	DELTA2 FCC 15.247 restricted bands >1GHz 3m pk
Begin scan 1 - 18 GHz						
Low channel, internal antenna, board upright, standing on narrow edge, antenna at top						
Device rotated 360 degrees, measurement antenna 1 - 4 meters high, vertical and horizontal						
No significant emissions detected						
measured both mid and high channel versions, internal antenna						
No significant emissions detected						
End scan 1 - 18 GHz						
2.485 GHz	59.8 Pk	4.25 / 28.4 / 29.25 / 0.0	63.2	V / 1.00 / 0		-10.8
2.486 GHz	53.5 Pk	4.25 / 28.41 / 29.25 / 0.0	56.9	V / 1.00 / 0		-17.1
2.487 GHz	49.0 Pk	4.25 / 28.41 / 29.25 / 0.0	52.4	V / 1.00 / 0		-21.6
2.489 GHz	43.3 Pk	4.25 / 28.42 / 29.26 / 0.0	46.71	V / 1.00 / 0		-27.29
2.49 GHz	44.6 Pk	4.25 / 28.42 / 29.26 / 0.0	48.01	V / 1.00 / 0		-25.99
2.5 GHz	43.0 Pk	4.26 / 28.45 / 29.27 / 0.0	46.44	V / 1.00 / 0		-27.56


The duty cycle correction factor for average reading is -41.4 dB, so average levels are >20 dB below the average limit.

Begin spurious scan 30 - 1000 MHz						
High channel internal antenna						
Device rotated 360 degrees, measurement antenna 1 - 4 meters high, vertical and horizontal						
No significant emissions detected						
measured both low and mid channel versions, internal antenna						
No significant emissions detected						
end scan 30 - 1000 MHz						


Begin scan 18 - 26 GHz						
Low channel						
No significant emissions detected						
with internal antenna version						
No significant emissions detected						
Repeat all previous testing with both mid and high channel versions, internal antenna						
No significant emissions detected						
End scan 18 - 26 GHz						

### Conducted spurious emissions Low Channel


Agilent 11:05:57 Mar 30, 2010



Agilent 11:08:59 Mar 30, 2010




Agilent 11:10:24 Mar 30, 2010




### Conducted spurious emissions Mid Channel


Agilent 10:24:44 Mar 30, 2010



Agilent 10:27:02 Mar 30, 2010




Agilent 10:28:38 Mar 30, 2010




### Conducted spurious emissions High Channel


Agilent 11:33:47 Mar 30, 2010



Agilent 11:38:14 Mar 30, 2010




✱ Agilent 11:40:16 Mar 30, 2010



### Conducted band edge Low Channel

Agilent 11:00:31 Mar 30, 2010



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.450 12 GHz	3.87 dBm
2	(1)	Freq	2.390 00 GHz	-63.35 dBm
3	(1)	Freq	2.400 00 GHz	-62.91 dBm

# **Conducted band edge High Channel**

✱ Agilent 11:45:36 Mar 30, 2010

Mkr2 2.483 50 GHz  
-29.84 dBm

Ref 15 dBm

#Atten 30 dB

#Peak

Log

10

dB/

Offst

0.5

dB

DI

-16.7

dBm

LgAv

V1 S2

Start 2.479 00 GHz

Stop 2.500 00 GHz


#Res BW 100 kHz

VBW 300 kHz

Sweep 2.067 ms (1001 pts)


Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.480 39 GHz	3.29 dBm
2	(1)	Freq	2.483 50 GHz	-29.84 dBm

Agilent 14:45:29 Jun 14, 2010



**Duty cycle correction =  $20 \log (846 \text{ us}/100 \text{ ms}) = -41.4 \text{ dB}$**


Agilent 14:47:51 Jun 14, 2010



## Radiated band edge Low Channel

### Peak Internal Antenna

Agilent 12:25:29 Mar 30, 2010




### Average Internal Antenna

The duty cycle correction factor for average reading is -41.4 dB, so band edge compliance is maintained.

## Radiated band edge High Channel

### Peak Internal Antenna

Agilent 14:52:59 Apr 12, 2010



### Average Internal Antenna

The duty cycle correction factor for average reading is -41.4 dB, so band edge compliance is maintained.

## Power spectral density

FCC 15.247(e), IC RSS-210 A8.2(b)

### Test summary

The requirements are: ☒ - MET ☐ - NOT MET

Test was performed in accordance with the test procedure of FCC KDB Publication 558074

Maximum power spectral density is -5.17dBm / 3 kHz

### Test location

☐ - Wild River Lab Large Test Site (Open Area Test Site)

☐ - Wild River Lab Small Test Site (Open Area Test Site)

☒ - Wild River Lab Tech Area, conducted measurement

### Test equipment

TUV ID	Model Number	Manufacturer	Description	Serial Number	Cal Due
WRLE03371	E4440A	Agilent	Spectrum Analyzer	MY43362222	11-Aug-10

### Test limit

No greater than 8 dBm in any 3 kHz band

### Test data

See following pages.

# **Power spectral density Low Channel**

\* Agilent 10:58:01 Mar 30, 2010

Mkr1 2.450 436 GHz  
-5.17 dBm

Ref 15 dBm

#Atten 30 dB

#Peak

Log

10

dB/

Offst

0.5

dB

DI

8.0

dBm

LgAv

V1 S2


S3 FS

AA

$\mathcal{E}(f)$ :

f>50k

#Swp



Center 2.450 000 GHz

Span 2 MHz

#Res BW 3 kHz

VBW 9.1 kHz

#Sweep 666.7 s (1001 pts)

# **Power spectral density Mid Channel**

Agilent 10:41:54 Mar 30, 2010

Mkr1 2.465 120 GHz

-6.88 dBm

Ref 15 dBm

#Atten 30 dB

#Peak

Log

10

dB/

Offst

0.5

dB

DI

8.0

dBm

LgAv

V1 S2


S3 FS

AA

$\mathcal{E}(f)$ :

f>50k

#Swp



Center 2.465 000 GHz

Span 2 MHz

#Res BW 3 kHz

VBW 9.1 kHz

#Sweep 666.7 s (1001 pts)

# **Power spectral density High Channel**

Agilent 11:58:59 Mar 30, 2010

Mkr1 2.480 440 GHz

-7.24 dBm

Ref 15 dBm

#Atten 30 dB

#Peak

Log

10

dB/

Offst

0.5

dB

DI

8.0

dBm

LgAv

V1 S2


S3 FC

AA

$\mathcal{E}(f)$ :

f>50k

#Swp



Center 2.480 000 GHz

Span 2 MHz

#Res BW 3 kHz

VBW 9.1 kHz

#Sweep 666.7 s (1001 pts)

## CONDUCTED EMISSIONS (Interference Voltage) AC Power Lines

The measurements were performed at the following TÜV SÜD America test location:

☐ - Test not applicable

- - Wild River Shield Room 2 - Shielded room (3.7m x 3.5m x 2.4m) or (12' x 11.5' x 8')
- - Tabletop equipment is placed on a non-conducting table 80 centimeters above the floor, 40 centimeters from a vertical ground plane.

### Test equipment used:

TUV ID	Model	Manufacturer	Description	Serial	Cal Due
WRLE02417	3825/2	Electro-Mechanics (EMCO)	50 $\Omega$ LISN	8812-1439	Code B 23-Mar-11
WRLE	ESCS-30	Rohde & Schwarz	EMI Receiver		

Cal Code B = Calibration verification performed internally. Cal Code Y = Calibration not required when used with other calibrated equipment.

All measurement instrumentation is traceable to the National Institute of Standards and Technology and is calibrated according to internal procedure. The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasi-peak/average detection, and a Line Impedance Stabilization Network (LISN), with 50  $\Omega$ /50  $\mu$ H (CISPR 16-1-1) characteristics.

### Test specification:

Frequency - range: ■ - 150 kHz to 30 MHz

EUT Power: ■ - 60 Hz ■ - 110 VAC

### Test Results - Conducted emissions 150 kHz - 30 MHz

The requirements are ☐ - N/A ☒ - MET ☐ - NOT MET

Minimum margin of compliance (Average) 35 dB at 24.35 MHz

Minimum margin of compliance (Quasi-peak) 40 dB at 19.55 MHz

Remarks: A BK Precision 1646 Bench Power Supply was used to provide 3.6 VDC to the units under test. It does not contain any special line filtering, so representative source to demonstrate compliance of EUT.

See the following pages for test set-up photos and data.

# CONDUCTED EMISSIONS



Test Report #: WC909614 Run 11 Test Area: SCREENROOM

EUT Model #: V2.1.90 Date: 7/8/2010

EUT Serial #: N/A EUT Power: 60 Hz 110 VAC Temperature: 21.0 °C

Test Method: FCC 15.247 Air Pressure: 98.0 kPa

Customer: Climate Minder Rel. Humidity: 69.0 %

EUT Description: Wireless Sensor Network RF Node.

Notes:

Data File Name: 9614.dat

Page: 1 of 5

## List of measurements for run #: 11

FREQ	LEVEL (dBuV)	CABLE / ANT / PREAMP / ATTEN (dB)	FINAL (dBuV)	EUT Lead	DELTA1 FCC B Qp	DELTA2 FCC B Avg
150.0 kHz	1.8 Qp	0.12 / 0.2 / 0.0 / 0.0	2.12	N	-63.88	n/a
225.0 kHz	-1.81 Qp	0.14 / 0.1 / 0.0 / 0.0	-1.57	N	-64.21	n/a
300.0 kHz	-2.17 Qp	0.15 / 0.1 / 0.0 / 0.0	-1.92	N	-62.16	n/a
450.0 kHz	-2.71 Qp	0.17 / 0.1 / 0.0 / 0.0	-2.44	N	-59.31	n/a
750.0 kHz	-2.77 Qp	0.21 / 0.2 / 0.0 / 0.0	-2.36	N	-58.36	n/a
1.0 MHz	-2.36 Qp	0.22 / 0.2 / 0.0 / 0.0	-1.94	N	-57.94	n/a
1.5 MHz	-2.68 Qp	0.26 / 0.1 / 0.0 / 0.0	-2.32	N	-58.32	n/a
2.0 MHz	-2.19 Qp	0.29 / 0.1 / 0.0 / 0.0	-1.8	N	-57.8	n/a
3.0 MHz	-1.05 Qp	0.33 / 0.1 / 0.0 / 0.0	-0.62	N	-56.62	n/a
4.0 MHz	-1.79 Qp	0.37 / 0.1 / 0.0 / 0.0	-1.32	N	-57.32	n/a
5.6 MHz	16.97 Qp	0.42 / 0.1 / 0.0 / 0.0	17.49	N	-42.51	n/a
8.0 MHz	3.87 Qp	0.48 / 0.2 / 0.0 / 0.0	4.55	N	-55.45	n/a
12.0 MHz	8.92 Qp	0.63 / 0.4 / 0.0 / 0.0	9.95	N	-50.05	n/a
13.3 MHz	15.42 Qp	0.66 / 0.47 / 0.0 / 0.0	16.54	N	-43.46	n/a
19.55 MHz	17.45 Qp	0.78 / 0.78 / 0.0 / 0.0	19.01	N	-40.99	n/a
24.35 MHz	14.71 Qp	0.86 / 0.99 / 0.0 / 0.0	16.56	N	-43.44	n/a
150.0 kHz	-2.12 Av	0.12 / 0.2 / 0.0 / 0.0	-1.8	N	n/a	-57.8
225.0 kHz	-5.44 Av	0.14 / 0.1 / 0.0 / 0.0	-5.2	N	n/a	-57.84
300.0 kHz	-5.93 Av	0.15 / 0.1 / 0.0 / 0.0	-5.68	N	n/a	-55.92
450.0 kHz	-6.17 Av	0.17 / 0.1 / 0.0 / 0.0	-5.9	N	n/a	-52.77
750.0 kHz	-6.38 Av	0.21 / 0.2 / 0.0 / 0.0	-5.97	N	n/a	-51.97
1.0 MHz	-6.31 Av	0.22 / 0.2 / 0.0 / 0.0	-5.89	N	n/a	-51.89
1.5 MHz	-6.28 Av	0.26 / 0.1 / 0.0 / 0.0	-5.92	N	n/a	-51.92
2.0 MHz	-6.28 Av	0.29 / 0.1 / 0.0 / 0.0	-5.89	N	n/a	-51.89
3.0 MHz	-4.95 Av	0.33 / 0.1 / 0.0 / 0.0	-4.52	N	n/a	-50.52
4.0 MHz	-5.66 Av	0.37 / 0.1 / 0.0 / 0.0	-5.19	N	n/a	-51.19
5.6 MHz	8.82 Av	0.42 / 0.1 / 0.0 / 0.0	9.34	N	n/a	-40.66
8.0 MHz	-1.64 Av	0.48 / 0.2 / 0.0 / 0.0	-0.96	N	n/a	-50.96
12.0 MHz	3.02 Av	0.63 / 0.4 / 0.0 / 0.0	4.05	N	n/a	-45.95
13.3 MHz	5.1 Av	0.66 / 0.47 / 0.0 / 0.0	6.22	N	n/a	-43.78

Tested by: J. T. Schneider

Printed

*Joel T. Schneider*

Signature

Reviewed by: Robert J Behringer

Printed

*Robert J Behringer*

Signature

# CONDUCTED EMISSIONS



Test Report #: WC909614 Run 11 Test Area: SCREENROOM

EUT Model #: V2.1.90 Date: 7/8/2010

EUT Serial #: N/A EUT Power: 60 Hz 110 VAC Temperature: 21.0 °C

Test Method: FCC 15.247 Air Pressure: 98.0 kPa

Customer: Climate Minder Rel. Humidity: 69.0 %

EUT Description: Wireless Sensor Network RF Node.

Notes: \_\_\_\_\_

Data File Name: 9614.dat

Page: 2 of 5

## List of measurements for run #: 11

FREQ	LEVEL (dBuV)	CABLE / ANT / PREAMP / ATTEN (dB)	FINAL (dBuV)	EUT Lead	DELTA1 FCC B Qp	DELTA2 FCC B Avg
19.55 MHz	7.77 Av	0.78 / 0.78 / 0.0 / 0.0	9.33	N	n/a	-40.67
24.35 MHz	12.26 Av	0.86 / 0.99 / 0.0 / 0.0	14.11	N	n/a	-35.89
150.0 kHz	9.56 Qp	0.12 / 0.2 / 0.0 / 0.0	9.88	L1	-56.12	n/a
150.0 kHz	-2.53 Av	0.12 / 0.2 / 0.0 / 0.0	-2.21	L1	n/a	-58.21

Tested by: J. T. Schneider  
Printed

Signature

Reviewed by: Robert J Behringer  
Printed

Signature

# CONDUCTED EMISSIONS

Test Report #: WC909614 Run 11 Test Area: SCREENROOM

EUT Model #: V2.1.90 Date: 7/8/2010

EUT Serial #: N/A EUT Power: 60 Hz 110 VAC Temperature: 21.0 °C

Test Method: FCC 15.247 Air Pressure: 98.0 kPa

Customer: Climate Minder Rel. Humidity: 69.0 %

EUT Description: Wireless Sensor Network RF Node.

Notes:

Data File Name: 9614.dat

Page: 3 of 5

## Measurement summary for limit1: FCC B Qp (Qp)

FREQ	LEVEL (dBuV)	CABLE / ANT / PREAMP / ATTEN (dB)	FINAL (dBuV)	EUT Lead	DELTA1 EN55022 B Qp
19.55 MHz	17.45 Qp	0.78 / 0.78 / 0.0 / 0.0	19.01	N	-40.99
5.6 MHz	16.97 Qp	0.42 / 0.1 / 0.0 / 0.0	17.49	N	-42.51
24.35 MHz	14.71 Qp	0.86 / 0.99 / 0.0 / 0.0	16.56	N	-43.44
13.3 MHz	15.42 Qp	0.66 / 0.47 / 0.0 / 0.0	16.54	N	-43.46
12.0 MHz	8.92 Qp	0.63 / 0.4 / 0.0 / 0.0	9.95	N	-50.05
8.0 MHz	3.87 Qp	0.48 / 0.2 / 0.0 / 0.0	4.55	N	-55.45
150.0 kHz	9.56 Qp	0.12 / 0.2 / 0.0 / 0.0	9.88	L1	-56.12
3.0 MHz	-1.05 Qp	0.33 / 0.1 / 0.0 / 0.0	-0.62	N	-56.62
4.0 MHz	-1.79 Qp	0.37 / 0.1 / 0.0 / 0.0	-1.32	N	-57.32
2.0 MHz	-2.19 Qp	0.29 / 0.1 / 0.0 / 0.0	-1.8	N	-57.8
1.0 MHz	-2.36 Qp	0.22 / 0.2 / 0.0 / 0.0	-1.94	N	-57.94
1.5 MHz	-2.68 Qp	0.26 / 0.1 / 0.0 / 0.0	-2.32	N	-58.32
750.0 kHz	-2.77 Qp	0.21 / 0.2 / 0.0 / 0.0	-2.36	N	-58.36
450.0 kHz	-2.71 Qp	0.17 / 0.1 / 0.0 / 0.0	-2.44	N	-59.31
300.0 kHz	-2.17 Qp	0.15 / 0.1 / 0.0 / 0.0	-1.92	N	-62.16
225.0 kHz	-1.81 Qp	0.14 / 0.1 / 0.0 / 0.0	-1.57	N	-64.21

Tested by: J. T. Schneider  
Printed

*Joel T. Schneider*

Signature

Reviewed by: Robert J Behringer  
Printed

*Robert J Behringer*

Signature

# CONDUCTED EMISSIONS



Test Report #: WC909614 Run 11 Test Area: SCREENROOM

EUT Model #: V2.1.90 Date: 7/8/2010

EUT Serial #: N/A EUT Power: 60 Hz 110 VAC Temperature: 21.0 °C

Test Method: FCC 15.247 Air Pressure: 98.0 kPa

Customer: Climate Minder Rel. Humidity: 69.0 %

EUT Description: Wireless Sensor Network RF Node.

Notes:

Data File Name: 9614.dat

Page: 4 of 5

## Measurement summary for limit2: FCC B Avg (Av)

FREQ	LEVEL (dBuV)	CABLE / ANT / PREAMP / ATTEN (dB)	FINAL (dBuV)	EUT Lead	DELTA2 EN55022 B Avg
24.35 MHz	12.26 Av	0.86 / 0.99 / 0.0 / 0.0	14.11	N	-35.89
5.6 MHz	8.82 Av	0.42 / 0.1 / 0.0 / 0.0	9.34	N	-40.66
19.55 MHz	7.77 Av	0.78 / 0.78 / 0.0 / 0.0	9.33	N	-40.67
13.3 MHz	5.1 Av	0.66 / 0.47 / 0.0 / 0.0	6.22	N	-43.78
12.0 MHz	3.02 Av	0.63 / 0.4 / 0.0 / 0.0	4.05	N	-45.95
3.0 MHz	-4.95 Av	0.33 / 0.1 / 0.0 / 0.0	-4.52	N	-50.52
8.0 MHz	-1.64 Av	0.48 / 0.2 / 0.0 / 0.0	-0.96	N	-50.96
4.0 MHz	-5.66 Av	0.37 / 0.1 / 0.0 / 0.0	-5.19	N	-51.19
1.0 MHz	-6.31 Av	0.22 / 0.2 / 0.0 / 0.0	-5.89	N	-51.89
2.0 MHz	-6.28 Av	0.29 / 0.1 / 0.0 / 0.0	-5.89	N	-51.89
1.5 MHz	-6.28 Av	0.26 / 0.1 / 0.0 / 0.0	-5.92	N	-51.92
750.0 kHz	-6.38 Av	0.21 / 0.2 / 0.0 / 0.0	-5.97	N	-51.97
450.0 kHz	-6.17 Av	0.17 / 0.1 / 0.0 / 0.0	-5.9	N	-52.77
300.0 kHz	-5.93 Av	0.15 / 0.1 / 0.0 / 0.0	-5.68	N	-55.92
150.0 kHz	-2.12 Av	0.12 / 0.2 / 0.0 / 0.0	-1.8	N	-57.8
225.0 kHz	-5.44 Av	0.14 / 0.1 / 0.0 / 0.0	-5.2	N	-57.84

Tested by: J. T. Schneider  
Printed

*Joel T. Schneider*

Signature

Reviewed by: Robert J Behringer  
Printed

*Robert J Behringer*

Signature

# CONDUCTED EMISSIONS

Test Report #: WC909614 Run 11 Test Area: SCREENROOM

EUT Model #: V2.1.90 Date: 7/8/2010

EUT Serial #: N/A EUT Power: 60 Hz 110 VAC Temperature: 21.0 °C

Test Method: FCC 15.247 Air Pressure: 98.0 kPa

Customer: Climate Minder Rel. Humidity: 69.0 %


EUT Description: Wireless Sensor Network RF Node.

Notes:

Data File Name: 9614.dat

Page: 5 of 5

## Graph:



Tested by: J. T. Schneider  
Printed

*Joel T. Schneider*

Signature

Reviewed by: Robert J Behringer  
Printed

*Robert J Behringer*


Signature

## TEST SETUP FOR EMISSIONS TESTING


### WILD RIVER LAB Large Test Site

#### Notes:

1. Items shown in dotted lines are located on the floor below the test area. It is 5 meters vertically from the ground floor to the test area.
2. 50 Hz, 60 Hz, and 400 Hz are power panels for alternating current.
3. The antenna may be positioned horizontally 3, 10 or 30 meters from the center of the turntable.
4. The circle is a 6.7 meter diameter turntable.
5. A ground plane is in the plane of this sheet.
6. The test sample is shown in the azimuthal position representing zero degrees.



**Test-setup photo(s):**  
**Conducted measurements**



**Test-setup photo(s):**  
**Conducted AC power line measurements**



**Test-setup photo(s):**  
**Radiated measurements**



## Equipment Under Test (EUT) Test Operation Mode:

The device under test was operated under the following conditions during immunity testing :

- ☐ - Standby
- ☐ - Test program (H - Pattern)
- ☐ - Test program (color bar)
- ☐ - Test program (customer specific)
- ☐ - Practice operation
- ☒ - Normal operating mode

☒ - \_\_\_\_\_

## Configuration of the device under test:

- ☒ - See Constructional Data Form in Appendix B
- ☐ - See Product Information Form(s) in Appendix B

The following peripheral devices and interface cables were connected during the measurement:

- |                                  |              |
|----------------------------------|--------------|
| <input type="checkbox"/> - _____ | Type : _____ |
| <input type="checkbox"/> - _____ | Type : _____ |
| <input type="checkbox"/> - _____ | Type : _____ |
| <input type="checkbox"/> - _____ | Type : _____ |
| <input type="checkbox"/> - _____ | Type : _____ |
| <input type="checkbox"/> - _____ | Type : _____ |
| <input type="checkbox"/> - _____ | Type : _____ |
| <input type="checkbox"/> - _____ | Type : _____ |

☐ - unshielded power cable

☐ - unshielded cables

☐ - shielded cables

MPS.No.: \_\_\_\_\_

☐ - customer specific cables

☐ - \_\_\_\_\_

☐ - \_\_\_\_\_

## GENERAL REMARKS:

### Modifications required to pass:

- ☐ None
- ☒ As indicated on the data sheet(s)

### Test Specification Deviations: Additions to or Exclusions from:

- ☒ None
- ☐ As indicated in the Test Plan
- ☐

## SUMMARY:

The requirements according to the technical regulations are

- ☒ - **met** and the equipment under test does fulfill the general approval requirements.
- ☐ - not met and the equipment under test does not fulfill the general approval requirements.

EUT Received Date: 26 March 2010

Condition of EUT: Normal

Testing Start Date: 30 March 2010

Testing End Date: 08 July 2010


## TÜV SÜD AMERICA INC

Tested by:



Greg Jakubowski  
Senior EMC Technician

Approved by:



Joel T Schneider  
Senior EMC Engineer

## Appendix A

### Constructional Data Form





## EMC Test Plan and Constructional Data Form

PLEASE COMPLETE THIS DOCUMENT IN FULL, ENTERING N/A IF THE FIELD IS NOT APPLICABLE. IF TESTING RESULTS IN MODIFICATIONS TO THE EQUIPMENT, PLEASE SUBMIT A REVISED TP/CDF INDICATING THOSE MODIFICATIONS.

**NOTE: This information will be input into your test report as shown below. Press the F1 key at any time to get HELP for the current field selected.**

Company: ClimateMinder, Inc.  
 Address: 9444 Haines Canyon Ave.  
Tujunga, CA, 91042  
FORMTEXT  
 Contact: Bulut F. Ersavas Position: CEO  
 Phone: 1-818-482-3711 Fax: \_\_\_\_\_  
 E-mail Address: bulut@climateminder.com

### General Equipment Description -- NOTE: This information will be input into your test report as shown below.

EUT Description Wireless Sensor Network RF Node  
 EUT Name NodeRF V2.1.90  
 Model No.: V2.1.90 Serial No.: \_\_\_\_\_  
 Product Options: Modulated Communication  
 Configurations to be tested: Modulated Radiation

### Equipment Modification (If applicable, indicate modifications since EUT was last tested. If modifications are made during this testing, submit revised TP/CDF after testing is complete.)

Modifications since last test: N/A  
 Modifications made during test: N/A

### Test Objective(s): Please indicate the tests to be performed, entering the applicable standard(s) where noted.

- |   |   |
|---|---|
| <input type="checkbox"/> EMC Directive 2004/108/EC (EMC)  | <input checked="" type="checkbox"/> FCC: Class <input type="checkbox"/> A <input type="checkbox"/> B Part <u>15</u> |
| Std: _____  | <input type="checkbox"/> VCCI: Class <input type="checkbox"/> A <input type="checkbox"/> B                          |
| <input type="checkbox"/> Machinery Directive 89/392/EEC (EMC)   | <input type="checkbox"/> BSMI: Class <input type="checkbox"/> A <input type="checkbox"/> B (Separate Report)        |
| Std: _____  | <input type="checkbox"/> Canada: Class <input type="checkbox"/> A <input type="checkbox"/> B                        |
| <input type="checkbox"/> Medical Device Directive 93/42/EEC (EMC)   | <input type="checkbox"/> Australia: Class <input type="checkbox"/> A <input type="checkbox"/> B                     |
| Std: _____  | <input type="checkbox"/> Other: _____   |
| <input type="checkbox"/> Vehicle Directive: <input type="checkbox"/> 2001/3/EC (EMC) <input type="checkbox"/> 2004/104/EC (EMC) |   |
| <input type="checkbox"/> Other Vehicle Std: _____   |   |
| <input type="checkbox"/> FDA Reviewers Guidance for Premarket Notification Submissions (EMC)                                    |   |

### Third Party Certification, if applicable (\*Signature on Page 6 Required)

- |   |   |
|---|---|
| <input type="checkbox"/> Attestation of Conformity (AoC)*                             | <input type="checkbox"/> EMC Certification (used with Octagon Mark)*                                  |
| <input type="checkbox"/> Certificate of Conformity (CoC)*                             | <input type="checkbox"/> Compliance Document*   |
| Protection Class (N/A for vehicles)   | <input type="checkbox"/> Class I <input type="checkbox"/> Class II <input type="checkbox"/> Class III |
| (Press F1 when field is selected to show additional information on Protection Class.) |   |
| <input checked="" type="checkbox"/> FCC / TCB Certification                           | <input type="checkbox"/> Industry Canada / FCB Certification  |
| <input type="checkbox"/> E-Mark Certification   | <input type="checkbox"/> Taiwan Certification   |



## EMC Test Plan and Constructional Data Form

### Attendance

Test will be: ☐ Attended by the customer ☒ Unattended by the customer

### Failure - Complete this section if testing will not be attended by the customer.

If a failure occurs, TÜV SÜD America should:

- ☒ Call contact listed above, if not available then stop testing. (After hrs phone): 818-482-3711
- ☐ Continue testing to complete test series.
- ☐ Continue testing to define corrective action.
- ☐ Stop testing.

### EUT Specifications and Requirements

Length: 52mm Width: 29mm Height: 9mm Weight: 12gr

### Power Requirements

*Regulations require testing to be performed at typical power ratings in the countries of intended use. (i.e., European power is typically 230 VAC 50 Hz or 400 VAC 50 Hz, single and three phase, respectively)*

Voltage: 3.6V (If battery powered, make sure battery life is sufficient to complete testing.)

# of Phases: N/A

Current (Amps/phase(max)): 80mA Current (Amps/phase(nominal)): 30 mA

Other \_\_\_\_\_

### Other Special Requirements

1 x D Size Battery Holder with Proper Connector Provided for testing.

### Typical Installation and/or Operating Environment

(ie. Hospital, Small Business, Industrial/Factory, etc.)  
Agriculture (Open Field, Greenhouses) and Industrial

### EUT Power Cable

☐ Permanent OR ☒ Removable Length (in meters): 0.3 ( Battery DC battery cable)

☐ Shielded OR ☒ Unshielded

☐ Not Applicable

# EMC Test Plan and Constructional Data Form

EUT Interface Ports and Cables														
Type	Analog	Digital	During Test		Qty	Shielding		Termination	Connector Type	Port Termination	Length tested (in meters)	Removable	Permanent	
			Active	Passive		Yes	No							Type
<b>EXAMPLE:</b> RS232	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Foil over braid	Coaxial	Metallized 9-pin D-Sub	Characteristic Impedance	6	<input checked="" type="checkbox"/>	<input type="checkbox"/>
SMA Connector for conducted emissions measurements	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1	<input type="checkbox"/>	<input checked="" type="checkbox"/>		Coaxial	SMA	50 ohm		<input checked="" type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>

**EUT Software.**

Description: uC(MSP430F1611) software loaded and ready in order to control data transmission through RF Module

**Equipment Under Test (EUT) Operating Modes to be Tested** -- list the operating modes to be used during test. It is recommended the equipment be tested while operating in a typical operation mode. FCC testing of personal computers and/or peripherals requires that a simple program generate a complete line of upper case H's. Provide a general description of all software, firmware, and PLD algorithms used in the equipment. List all code modules as described above, with the revision level used during testing. Consult with your TÜV Product Service Representative if additional assistance is required.

1. - High Power Data Transmission Mode at low channel (2450 MHz).  
Max duty cycle is 30%, which means in the worst condition transmission is no more than 30 milliseconds for a 100 milliseconds period.
2. High Power Data Transmission Mode at high channel (2485 MHz)  
Max duty cycle is 30%, which means in the worst condition transmission is no more than 30 milliseconds for a 100 milliseconds period.
3. High Power Data Transmission Mode at mid channel (2445 MHz)  
Max duty cycle is 30%, which means in the worst condition transmission is no more than 30 milliseconds for a 100 milliseconds period.

Please note that our RF chip can operate in one of the 16 channels available between 2405 to 2485. However, since the end users can not change the channels we want to certificate our product only on 2450 – 2485 band.

**Equipment Under Test (EUT) System Components** -- List and describe all components which are part of the EUT. For FCC & Taiwan testing a minimum configuration is required. (ie. Mouse, Printer, Monitor, External Disk Drive, Motherboard, etc)

Description	Model #	Serial #	FCC ID #
Wireless Sensor Node	NodeRF V2.1.90		



## EMC Test Plan and Constructional Data Form

**Support Equipment** -- List and describe all support equipment which is not part of the EUT. (i.e. peripherals, simulators, etc)  
This information is required for FCC & Taiwan testing.

<i>Description</i>	<i>Model #</i>	<i>Serial #</i>	<i>FCC ID #</i>

### Oscillator Frequencies

<i>Manufacturer</i>	<i>Frequency</i>	<i>Derived Frequency</i>	<i>Component # / Location</i>	<i>Description of Use</i>
Abracomm	16MHz	2.4-2.485 GHz	X3/26-9.8mm	RF Modem Clock
Abracomm	8MHz	4 MHz	X1/1.53-18.7 mm	uC Module Clock-1
Abracomm	32.768 KHz	32.768 KHz	X2/18.4-25mm	uC Module Clock-2

### Power Supply

<i>Manufacturer</i>	<i>Model #</i>	<i>Serial #</i>	<i>Type</i>
Standard Type	D size Tadiran		<input type="checkbox"/> Switched-mode: (Frequency) _____ <input type="checkbox"/> Linear <input checked="" type="checkbox"/> Other: <u>Battery</u>
			<input type="checkbox"/> Switched-mode: (Frequency) _____ <input type="checkbox"/> Linear <input type="checkbox"/> Other: _____

### Power Line Filters

<i>Manufacturer</i>	<i>Model #</i>	<i>Location in EUT</i>



## EMC Test Plan and Constructional Data Form

### Critical EMI Components (Capacitors, ferrites, etc.)

<i>Description</i>	<i>Manufacturer</i>	<i>Part # or Value</i>	<i>Qty</i>	<i>Component # / Location</i>
On Board PCB Antenna	Genetlab	2dBi- Inverted F	1	62.9-17.8mm
RF Modem	TI	CC2420-cc2590	1	U2/37.8-18.6mm
SMA OPTIONAL	ANTENNOVA	TITANIS	1	62.9-17.8mm

### EMC Critical Detail -- Describe other EMC Design details used to reduce high frequency noise.

4-Layer PCB Design with adequate vias  
 Separate DC and RF Grounds  
 By-Pass Capacitors near DC Power pins on each IC

PLEASE ENTER NAMES BELOW (INSERT ELECTRONIC SIGNATURE IF POSSIBLE)

### Authorization (Signature Required if a Third Party Certification is checked on pg 1)

\_\_\_\_\_  
 Customer authorization to perform tests  
 according to this test plan.


\_\_\_\_\_  
 Date

\_\_\_\_\_  
 Test Plan/CDF Prepared By (please print)

\_\_\_\_\_  
 Date

## EMC Block Diagram Form

**System Configuration Block Diagram** -- Provide a line drawing identifying the EUT, simulators, support equipment, I/O cables, power cables, and any other pertinent components to be used during testing. Use a dashed line to separate the equipment in the testing field versus equipment outside testing field.



uC Module:	Texas Instruments MSP430F1611 ultra-low power MCU
RF Communication:	2400-2485 MHz
RF Module:	Texas Instruments CC2420 RF IC and CC2590 front end amp. +8dBm maximum output power.
Battery:	2 Units of standard AA type non-rechargeable with proper connector and housing Provided. Alternatively, 1 D-size 3.6V lithium primary battery can be used as well.
Oscillators:	16Mhz Crystall Oscillator(RF) ; 8MHZ Crystall Oscillator (MCU); 32KHz(MCU)

### Authorization Signatures

Customer authorization to perform tests  
according to this test plan.

Date

Test Plan/CDF Prepared By (please print)

Date

## Appendix B

### Measurement Protocol



# MEASUREMENT PROTOCOL

## GENERAL INFORMATION

### Test Methodology

Emissions testing is performed according to the procedures in ANSI C63.4-2003.

### Measurement Uncertainty

The test system for conducted emissions is defined as the LISN, tuned receiver or spectrum analyzer, and coaxial cable. The test system has a measurement uncertainty of  $\pm 1.8$  dB. The test system for radiated emissions is defined as the antenna, the pre-amplifier, the spectrum analyzer and the coaxial cable. The test system has a measurement uncertainty of  $\pm 4.8$  dB. The equipment comprising the test systems is calibrated on an annual basis.

### Justification

The Equipment Under Test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral into its characteristic impedance or left unterminated. When appropriate, the cables are manually manipulated with respect to each other to obtain maximum emissions from the unit.

### Conducted Emissions

The final level, in dB $\mu$ V, equals the EMI receiver level plus the cable loss and LISN factor.

### Radiated Emissions

The final level, in dB $\mu$ V/m, equals the reading from the spectrum analyzer (Level dB $\mu$ V), adding the antenna correction factor and cable loss factor (Factor dB) to it, and subtracting the preamp gain (and duty cycle correction factor, if applicable). This result then has the limit subtracted from it to provide the Delta, which gives the tabular data as shown in the data sheets in Attachment A. Intentional radiators are rotated through 3 orthogonal axes to determine the test position yielding the maximum emission levels.

Example:

FREQ (MHz)	LEVEL (dB $\mu$ V)	CABLE/ANT/PREAMP			FINAL (dB $\mu$ V/m)	POL/HGT/AZ			DELTA1
		(dB)	(dB/m)	(dB)		(m)	(deg)		
60.80	42.5Qp +	1.2	+ 10.9	- 25.5 =	29.1	V	1.0	0.0	-10.9

### Test Equipment

All measurement instrumentation is traceable to the National Institute of Standards and Technology and is calibrated according to internal procedure.