FCC Radio TEST Report

FCC ID: YGWLH-918C

This report concerns (check one): Original Grant Class II Change

Issued Date : Sep. 15, 2010
Project No. : 1008C297

Equipment : Triple Technology Detector

Model Name : LH-918C

Applicant : Longhorn Security Technology Co.,Ltd : New and High Technology Industrial Park,

Guangming Shenzhen

Manufacturer: Longhorn Security Technology Co., Ltd

Address : The 4th Building, 1st floor of the 5th Building, New

and High Technology Industrial Park, Guangming, Wan Dai HengGuangming, shenzhen, China

Tested by:

Neutron Engineering Inc. EMC Laboratory

Date of Receipt: Aug. 24, 2010

Date of Test:

Aug. 24, 2010 ~ Sep. 14, 2010

Testing Engineer

(Jeff Yang)

Technical Manager

(Vic Chiu)

Authorized Signatory

(Steven Lu)

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL: (0769) 8318-3000 FAX: (0769) 8319-6000



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**), or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Report No.: NEI-FCCP-1-1008C297 Page 2 of 32

Table of Contents	Page
1 . CERTIFICATION	5
2 . SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3 . GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTER) 10
3.4 DESCRIPTION OF SUPPORT UNITS	11
4 . EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS 4.1.2 MEASUREMENT INSTRUMENTS LIST	12 12
4.1.3 TEST PROCEDURE	13
4.1.4 DEVIATION FROM TEST STANDARD 4.1.5 TEST SETUP	13 13
4.1.6 EUT OPERATING CONDITIONS	13
4.1.7 TEST RESULTS	14
4.2 RADIATED EMISSION MEASUREMENT	15 45
4.2.1 RADIATED EMISSION LIMITS 4.2.2 MEASUREMENT INSTRUMENTS LIST	15 16
4.2.3 TEST PROCEDURE	18
4.2.4 DEVIATION FROM TEST STANDARD 4.2.5 TEST SETUP	18 19
4.2.6 EUT OPERATING CONDITIONS	19
4.2.7 TEST RESULTS (BETWEEN 30 – 1000 MHz)	20
4.2.8 TEST RESULTS (ABOVE 1000 MHz)	22
5 . BANDWIDTH TEST 5.1 MEASUREMENT INSTRUMENTS LIST	26 26
5.2 TEST PROCEDURE	26
5.3 DEVIATION FROM STANDARD	26
5.4 TEST SETUP 5.5 EUT OPERATION CONDITIONS	26 26
5.6 TEST RESULTS	27
6 . ANTENNA CONDUCTED SPURIOUS EMISSION	28

Report No.: NEI-FCCP-1-1008C297 Page 3 of 32



Table of Contents	Page
6.1 APPLIED PROCEDURES / LIMIT	28
6.1.1 MEASUREMENT INSTRUMENTS LIST	28
6.1.2 TEST PROCEDURE	28
6.1.3 DEVIATION FROM STANDARD	28
6.1.4 TEST SETUP	28
6.1.5 EUT OPERATION CONDITIONS	28
6.1.6 TEST RESULTS	29
7 . EUT TEST PHOTO	32

Report No.: NEI-FCCP-1-1008C297 Page 4 of 32

1. CERTIFICATION

Equipment: Triple Technology Detector

Brand Name : (S) Longhorn

Model Name.: LH-918C

Applicant: Longhorn Security Technology Co.,Ltd Factory: Longhorn Security Technology Co.,Ltd

A d d r e s s: The 4th Building, 1st floor of the 5th Building, New and High Technology Industrial Park, Guangming, Wan Dai HengGuangming, shenzhen, China

Date of Test: Aug. 24, 2010 ~ Sep. 14, 2010 Test Item: ENGINEERING SAMPLE

Standards: FCC Part15, Subpart C(15.245)/ ANSI C63.4: 2003

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-1008C297) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Report No.: NEI-FCCP-1-1008C297 Page 5 of 32

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.245)				
Standard Section	Test Item	Judgment	Remark	
15.207	Conducted Emission	N/A	Note(1)	
15.209 Radiated Emission		PASS		
FCC Part 15 Subpart C Paragraph 15.245 Limit	Field Strength of Fundamental/emissions	PASS		
15.245(b)(3)	Band Edge Test	PASS	Note(2)	

NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2) Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the Radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Report No.: NEI-FCCP-1-1008C297 Page 6 of 32

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C03/CB03**at the location of No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792 Neutron's test firm number is 319330

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % $^{\circ}$

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
DG-C03	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
CB03 CISPR		30MHz ~ 200MHz	V	2.48	
	CIEDD	30MHz ~ 200MHz	Н	2.16	
	,bus CISPR	200MHz ~ 1,000MHz	V	2.50	
		200MHz ~ 1,000MHz	Н	2.66	

Report No.: NEI-FCCP-1-1008C297 Page 7 of 32

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Triple Technology Detector		
Brand Name	Longhorn		
Model Name.	LH-918C		
OEM Brand/Model Name	N/A		
Model Difference	N/A		
Product Description	Product Type Stand-alone Operation Frequency: 10525.00MHz Number Of Channel 1CH .Please see Note 2. Antenna Designation: Integral antenna Antenna Gain(Peak) 1.0 dBi Output Power: 80.59 dBuv/m (AV MAX) More details of EUT technical specification. Please refer the User's Manual.		
Channel List	Please refer to the Note	e 2.	
Power Source	DC Voltage supplied		
Power Rating	DC 12V 38mA MAX		
Connecting I/O Port(s)	Please refer to the User's Manual		
Products Covered	N/A		

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel	Frequency (MHz)
01	10525

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Microwave Antenna Note(4)	N/A	1.0dBi

4. Plane antenna with high frequency oscillator GaAs:FET

Report No.: NEI-FCCP-1-1008C297 Page 8 of 32

3.2 DESCRIPTION OF TEST MODES


To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX

For Conducted Test			
Final Test Mode	Description		
	" N/A" denotes test is not applicable in this Test Report		

For Radiated Test		
Final Test Mode	Description	
Mode 1	TX	

Report No.: NEI-FCCP-1-1008C297 Page 9 of 32



Report No.: NEI-FCCP-1-1008C297 Page 10 of 32

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	Triple Technology Detector	(3) Longhorn	LH-918C	YGWLH-918C	N/A	EUT
E-2	burglar-alarm control units	Longhorn	LHD7000	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	ОИ	10M	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in m in <code>[Length_]</code> column.

Report No.: NEI-FCCP-1-1008C297 Page 11 of 32

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
TREQUENCT (MHZ)	Quasi-peak	Average	Quasi-peak	Average	Stanuaru
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	May.26.2011
2	LISN	Rolf Heine	NNB-2-16Z	99044	May.26.2011
3	50Ω Terminator	SHX	TF2-3G-A	08122901	May.26.2011
4	Transient Limiter	Agilent	11947A	3107A03668	May.26.2011
5	Test Cable	N/A	C-06_C03	N/A	Nov.16.2010
6	EMI TEST RECEIVER	R&S	ESCS30	8333641017	May.26.2011

Remark: "N/A" denotes No Model Name., Serial No. or No Calibration specified.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

Report No.: NEI-FCCP-1-1008C297 Page 12 of 32


4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT was programmed to be in continuously transmitting

Report No.: NEI-FCCP-1-1008C297 Page 13 of 32

4.1.7 TEST RESULTS

EUT:	Triple Technology Detector	Model Name :	LH-918C
Temperature :		Relative Humidity:	
Pressure:		Test Power :	
Test Mode :	" N/A" denotes test is not applicable in this Test Report.		

Remark

- (1) All readings are QP Mode value unless otherwise stated AVG in column of Note. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform In this case, a " * " marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.
- (3) " N/A" denotes test is not applicable in this Test Report.

Report No.: NEI-FCCP-1-1008C297 Page 14 of 32

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (FCC 15.209)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

FCC Part15 (15.245), Subpart C			
Fundamental Frequency (MHz)	Field Strength of Fundamental (3m)		
	2500 mV/m (128dBuV)		
	Field Strength of Harmonics (3m)		
10500-10550	Harmonic emissions in the restricted bands at and above 17.7 GHz: 7.5mV/m		
	Harmonic emissions in the non-restricted bands: 25mV/m (88dBuV)		

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

Report No.: NEI-FCCP-1-1008C297 Page 15 of 32

4.2.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Triple Loop Antenna	R&S	HFH2-Z2	830749/020	May.27.2011
2	Bi-log Antenna	Schwarbeck	VULB9160	9160-3232	May.26.2011
3	Amplifier	HP	8447D	2944A09673	May.26.2011
4	Test Receiver	R&S	ESCI	100895	May.26.2011
5	Test Cable	N/A	C-01_CB03	N/A	Jul.05.2011
6	Controller	СТ	SC100	N/A	N/A
7	Horn Antenna	ETS	3115	00075789	May.12.2011
8	Amplifier	Agilent	8449B	3008A02274	May.26.2011
9	Spectrum	Agilent	E4408B	US39240143	Nov.16.2010
10	Test Cable	HUBER+SUHNER	CB03 High Fre	N/A	May.03.2011
11	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170340	Dec.16.2010
12	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	May.27.2011
14	Amplifier	EMC	EMC2654045	980039	Aug.12.2011

Remark: "N/A" denotes No Model Name. / Serial No. and No Calibration specified.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, Average=PK-dycty cycle

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

Report No.: NEI-FCCP-1-1008C297 Page 16 of 32

DUTY CYCLE: TX 10525MHz

Dwell time=ON/ON+OFF


ON: 0.028msec

ON+OFF: (total time):0.808msec

Dwell time: 3.47%

AV=PK+20 log(Dwell time)

AV=PK-29.205



Report No.: NEI-FCCP-1-1008C297 Page 17 of 32



4.2.3 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


4.2.4 DEVIATION FROM TEST STANDARI	C
No deviation	

Report No.: NEI-FCCP-1-1008C297 Page 18 of 32




4.2.5 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



4.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-1008C297 Page 19 of 32


4.2.7 TEST RESULTS (BETWEEN 30 – 1000 MHz)

EUT:	Triple Technology Detector	Model Name. :	LH-918C
Temperature :	23 ℃	Relative Humidity:	58 %
Pressure :	1001 hPa	Test Power :	DC 12V
Test Mode :	TX Mode10525MHz		

Freq.	Ant.	Reading(RA)	Corr.Factor(CF)	Measured(FS)	Limits(QP)	Margin	Note
(MHz)	H/V	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	NOLE
47.00	V	32.24	-17.09	15.15	40.00	- 24.85	
76.10	V	44.81	-18.87	25.94	40.00	- 14.06	
141.60	V	40.44	-17.70	22.74	43.50	- 20.76	
185.20	V	32.67	-16.81	15.86	43.50	- 27.64	
233.70	V	32.21	-15.45	16.76	46.00	- 29.24	
291.90	V	32.65	-12.06	20.59	46.00	- 25.41	

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode or QP detector mode of the emission
- (4) Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Report No.: NEI-FCCP-1-1008C297 Page 20 of 32




EUT:	Triple Technology Detector	Model Name. :	LH-918C
Temperature :	23 ℃	Relative Humidity:	58 %
Pressure:	1001 hPa	Test Power :	DC 12V
Test Mode :	TX Mode10525MHz		

Freq.	Ant.	Reading(RA)	Corr.Factor(CF)	Measured(FS)	Limits(QP)	Margin	Note
(MHz)	H/V	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	NOLE
39.70	Ι	38.63	-16.83	21.80	40.00	- 18.20	
117.30	Ι	31.19	-18.30	12.89	43.50	- 30.61	
124.60	Η	31.91	-18.20	13.71	43.50	- 29.79	
165.80	Н	30.77	-17.45	13.32	43.50	- 30.18	
267.70	Η	31.93	-13.41	18.52	46.00	- 27.48	
316.20	Η	31.91	-11.68	20.23	46.00	- 25.77	

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode or QP detector mode of the emission
- (4) Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Report No.: NEI-FCCP-1-1008C297 Page 21 of 32

4.2.8 TEST RESULTS (ABOVE 1000 MHz)

EUT:	Triple Technology Detector	Model Name. :	LH-918C
Temperature:	22 ℃	Relative Humidity:	56 %
Pressure :	1001 hPa	Test Power :	DC 12V
Test Mode :	TX Mode10525MHz		

Freq.	Ant.Pol.	Rea	ding	Ant./CF	A	ct.	Lir	nit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
10500.00	V	47.84	18.64	13.17	61.01	31.81	74.00	54.00	X/E
10523.60	٧	84.48	55.27	13.20	97.68	68.47	148.00	128.00	X/F
10550.00	٧	47.20	18.00	13.23	60.43	31.23	74.00	54.00	X/E
21054.81	V	66.26	37.05	-19.64	46.62	17.41	108.00	88.00	X/H


Remark:


- Emission level (dBuV/m) = 20 log Emission level (uV/m).
 Distance extrapolation factor = 20 log (specific distance / test distance) (dB);
 Limit line = specific limits (dBuV) + distance extrapolation factor.
 Frequency Range above 15GHz> Test distance is 1.5meter.
- (2) Measuring frequency range is 40GHz \circ "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The amplitude of spurious emissions (3th harmonic of fundamental frequency to 40GHz) which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (8) The average value of fundamental frequency is:

 Average = Peak value + 20log(Duty cycle) , Final AV=PK-29.205

Report No.: NEI-FCCP-1-1008C297 Page 22 of 32

Neutron Engineering Inc. Orthogonal Axis: X TX 10525MHz (Above 1000 MHz, Vertical)





Report No.: NEI-FCCP-1-1008C297 Page 23 of 32

EUT:	Triple Technology Detector	Model Name. :	LH-918C
Temperature :	22 ℃	Relative Humidity:	56 %
Pressure:	1001 hPa	Test Power :	DC 12V
Test Mode :	TX Mode10525MHz		


Freq.	Ant.Pol.	Rea	ding	Ant./CF	A	ct.	Lir	mit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
10500.00	Н	50.75	21.54	13.16	63.91	34.70	74.00	54.00	X/E
10523.60	Н	96.60	67.39	13.20	109.80	80.59	148.00	128.00	X/F
10550.00	Н	50.71	21.50	13.23	63.94	34.73	74.00	54.00	X/E
21054.81	Н	71.07	41.87	-19.64	51.43	22.23	108.00	88.00	X/H

Remark:

- Emission level (dBuV/m) = 20 log Emission level (uV/m).
 Distance extrapolation factor = 20 log (specific distance / test distance) (dB);
 Limit line = specific limits (dBuV) + distance extrapolation factor.
 Frequency Range above 15GHz> Test distance is 1.5meter.
- (2) Measuring frequency range is 40GHz "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The amplitude of spurious emissions (3th harmonic of fundamental frequency to 40GHz) which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (8) The average value of fundamental frequency is:

 Average = Peak value + 20log(Duty cycle) , Final AV=PK-29.205

Report No.: NEI-FCCP-1-1008C297 Page 24 of 32



5. BANDWIDTH TEST

5.1 MEASUREMENT INSTRUMENTS LIST

Iten	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.27.2010

Remark: "N/A" denotes No Model Name., Serial No. or No Calibration specified.

5.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = 20 ms.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

5.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-1008C297 Page 26 of 32

5.6 TEST RESULTS

EUT:	Triple Technology Detector	Model Name. :	LH-918C
Temperature:	20 ℃	Relative Humidity:	51 %
Pressure:	1001 hPa	Test Power :	DC 12V
Test Mode :	TX CH 01		

Test Channel	Frequency	20 dBc Bandwidth	99% occupied
	(MHz)	(MHz)	Bandwidth(MHz)
CH01	10525	0.944	0.508



Report No.: NEI-FCCP-1-1008C297 Page 27 of 32

6. ANTENNA CONDUCTED SPURIOUS EMISSION

6.1 APPLIED PROCEDURES / LIMIT

This test was performed to verify the EUT band edge emsiion including all associated side bands was attenuated at least 50dB below the unmodulated carrier level or below the general spurious emissions limit. Specification test limits in the table below has to be followed.

Frequency band (MHz)	Field Strength limit at 3m (dBuV/m)		Attenuation below carrier
(IVITIZ)	Peak	Average	(dBc)
10500~10550	74.0	54.0	50

6.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.27.2010

Remark: "N/A" denotes No Model Name., Serial No. or No Calibration specified.

6.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.

6.1.3 DEVIATION FROM STANDARD

No deviation.

6.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

6.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-1008C297 Page 28 of 32

6.1.6 TEST RESULTS

EUT:	Triple Technology Detector	Model Name. :	LH-918C
Temperature:	20 ℃	Relative Humidity:	51 %
Pressure :	1001 hPa	Test Power :	DC 12V
Test Mode :	TX CH01		


Channel of Worst Data: CH01				
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.		
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)	
10461.21	-46.84	10577.91	-47.26	
Docult				


Result

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 50dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.


Report No.: NEI-FCCP-1-1008C297 Page 29 of 32


Neutron Engineering Inc.





Neutron Engineering Inc.








7. EUT TEST PHOTO

Radiated Measurement Photos





Report No.: NEI-FCCP-1-1008C297 Page 32 of 32