

NXSMP3-LMI

NX Low Mount Indoor Sensor Module

Class 2, 12-24VDC, 24mA

Manufactured for: HLI Solutions, Inc
www.currentlighting.com

ST: VTBD

BP: VTBD

HW01

DATE: WWYY

FCC ID: YH9NXSMP3

IC: 9044A-NXSMP3

CAN ICES (B) / NMB (B)



LISTED

Energy Mgmt

Equipment

11AA - KL

China

Current

NXSMP3-LMO

NX Low Mount
Outdoor
Sensor Module

NX Module
de Capteur
Extérieur
à Montage
Bas

ST: VTBD
BP: VTBD
HW01
DATE: WWYY



Energy Mgmt
Equipment |
Équipement de
Gestion de L'énergie
11AA - KL

Class 2 | Classe 2
12-24VDC 24mA

FCC ID: YH9NXSMP3
IC: 9044A-NXSMP3
CAN ICES (B) / NMB (B)

Operating Temperature: -40°C to 65°C | Température de Fonctionnement: -40°C to 65°C

Assembled in China from local and foreign components |
Assemblé en Chine à partir de composants locaux et étrangers



Manufactured for | Fabriqué pour:
HLI Solutions, Inc
www.currentlighting.com

Current

NXSMP3-HMO

NX High Mount
Outdoor
Sensor Module

NX Module
de Capteur
Extérieur
à Montage
Élevé

ST: VTBD
BP: VTBD
HW01
DATE: WWYY



Energy Mgmt
Equipment |
Équipement de
Gestion de L'énergie
11AA - KL

Class 2 | Classe 2
12-24VDC 24mA

FCC ID: YH9NXSMP3
IC: 9044A-NXSMP3
CAN ICES (B) / NMB (B)

Operating Temperature: -40°C to 65°C | Température de Fonctionnement: -40°C to 65°C

Assembled in China from local and foreign components |
Assemblé en Chine à partir de composants locaux et étrangers



Manufactured for | Fabriqué pour:
HLI Solutions, Inc
www.currentlighting.com

Current 

NX OMNI Indoor/Outdoor Sensor |
Class 2, 12-24 VDC 24mA

Manufactured for: HLI Solutions, Inc
www.currentlighting.com
China



Energy Mgmt Equipment
11AA-KL

NXSMP3-OMNI

ST: VTBD | BP: VTBD | HW01 | DATE WWWW

IC: FCC ID: YH6NXSMP3
CANICES (B) / NMB (B)
9044A

NXSMP3-RM

NX Radio Module

Class 2, 12-24VDC 24mA

Manufactured for: HLI Solutions, Inc
www.currentlighting.com

ST: VTBD

BP: VTBD

HW01

DATE: WWYY

FCC ID: YH9NXSMP3

IC: 9044A-NXSMP3

CAN ICES (B) / NMB (B)



LISTED

Energy Mgmt

Equipment

11AA - KL

China