

BTXSMP-LMI

BTX Low Mount Indoor Sensor Module

Class 2, 12-24VDC, 24mA

Manufactured for: HLI Solutions, Inc
www.currentlighting.com

FCC ID: YH9NXSMP3
IC: 9044A-NXSMP3
CAN ICES (B) / NMB (B)

BP: VTBD
HW01
DATE: WWYY



Current

BTXSMP-LMO

BTX Low Mount
Outdoor
Sensor Module

BTX Module
de Capteur
Extérieur
à Montage
Bas

BP: VTBD
HW01
DATE: WWYY



LISTED

Energy Mgmt
Equipment |
Équipement de
Gestion de L'énergie
11AA - KL

Class 2 | Classe 2
12-24VDC 24mA

FCC ID: YH9NXSMP3
IC: 9044A-NXSMP3
CAN ICES (B) / NMB (B)

Operating Temperature: -40°C to 65°C | Température de Fonctionnement: -40°C to 65°C

Assembled in China from local and foreign components |
Assemblé en Chine à partir de composants locaux et étrangers

Manufactured for | Fabriqué pour:
HLI Solutions, Inc
www.currentlighting.com

Current

BTXSMP-HMO

BTX High Mount
Outdoor
Sensor Module

BTX Module
de Capteur
Extérieur
à Montage
Élevé

BP: VTBD
HW01
DATE: WWYY



LISTED

Energy Mgmt
Equipment |
Équipement de
Gestion de L'énergie
11AA - KL

Class 2 | Classe 2
12-24VDC 24mA

FCC ID: YH9NXSMP3
IC: 9044A-NXSMP3
CAN ICES (B) / NMB (B)

Operating Temperature: -40°C to 65°C | Température de Fonctionnement: -40°C to 65°C

Assembled in China from local and foreign components |
Assemblé en Chine à partir de composants locaux et étrangers

Manufactured for | Fabriqué pour:
HLI Solutions, Inc
www.currentlighting.com

Current 

BTX OMNI Indoor/Outdoor Sensor |
Class 2, 12-24 VDC 24mA

Manufactured for: HLI Solutions, Inc
www.currentinc.com
China



Energy Mgmt Equipment
11AA-KL

BTXSMP-OMNI

BP: VTBD | HW01 | DATE: WWYY

IC: 9044A- - / NMB (B)
CANICES (B) |
FCC ID: YH6NXXSMP3
X S M P 3