



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / [www.sporton.com.tw](http://www.sporton.com.tw)

## FCC RADIO TEST REPORT

Applicant's company	<b>NEXCOM International Co., LTD</b>
Applicant Address	15F, No. 920, Chung-Cheng Rd., Zhonghe Dist., New Taipei City 235,, 235 Taiwan
FCC ID	<b>YHI-IWF2220</b>
Manufacturer's company	<b>NEXCOM International Co., LTD</b>
Manufacturer Address	15F, No. 920, Chung-Cheng Rd., Zhonghe Dist., New Taipei City 235,, 235 Taiwan

Product Name	Light Duty Industrial Access Point
Brand Name	NEXCOM
Model No.	IWF2220****, * = A~Z, a~z, and "-"
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Mar. 12, 2013
Final Test Date	May 27, 2013
Submission Type	Original Equipment



### Statement

**Test result included is only for the IEEE 802.11n, IEEE 802.11b/g part and IEEE 802.11a (5725 ~ 5850MHz) of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r01 and KDB 662911 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies .....	7
3.5. Table for Test Modes.....	8
3.6. Table for Testing Locations.....	10
3.7. Table for Supporting Units .....	10
3.8. Table for Parameters of Test Software Setting .....	11
3.9. EUT Operation during Test .....	11
3.10. Duty Cycle.....	12
3.11. Test Configurations .....	16
<b>4. TEST RESULT .....</b>	<b>18</b>
4.1. AC Power Line Conducted Emissions Measurement.....	18
4.2. Maximum Conducted Output Power Measurement .....	22
4.3. Power Spectral Density Measurement .....	25
4.4. 6dB Spectrum Bandwidth Measurement .....	33
4.5. Radiated Emissions Measurement .....	40
4.6. Emissions Measurement .....	66
4.7. Antenna Requirements .....	90
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>91</b>
<b>6. TEST LOCATION.....</b>	<b>93</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A5</b>
<b>APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>B1 ~ B3</b>
<b>APPENDIX C. CO-LOCATION REPORT.....</b>	<b>C1 ~ C3</b>



## History of This Test Report



## 1. CERTIFICATE OF COMPLIANCE

Product Name : Light Duty Industrial Access Point  
Brand Name : NEXCOM  
Model No. : IWF2220\*\*\*\*, \* = A~Z, a~z, and "-"  
Applicant : NEXCOM International Co., LTD  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sportun International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 12, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that appears to read "Sam Chen". The signature is written in a cursive, flowing style.

Sam Chen

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	10.07 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	0.01 dB
4.3	15.247(e)	Power Spectral Density	Complies	3.06 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.15 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.12 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adaptor / POE
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	For 2.4GHz Band: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth For 5GHz Band: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	For 2.4GHz Band: MCS0 (20MHz): 16.96 MHz ; MCS0 (40MHz): 36.16 MHz For 5GHz Band: MCS0 (20MHz): 17.76 MHz ; MCS0 (40MHz): 36.32 MHz
Maximum Conducted Output Power	For 2.4GHz Band: MCS0 (20MHz): 29.71 dBm ; MCS0 (40MHz): 21.83 dBm For 5GHz Band: MCS0 (20MHz): 29.90 dBm ; MCS0 (40MHz): 29.96dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

**802.11a/b/g**

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adaptor / POE
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1 / 2 / 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 13.12 MHz ; 11g: 16.00 MHz ; 11a: 16.48 MHz
Maximum Conducted Output Power	11b: 29.54 dBm ; 11g: 29.94 dBm ; 11a: 29.99 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

**Antenna & Band width**

Antenna	Two (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11a	V	X
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V

**IEEE 11n Spec.**

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	MCS 0-15
802.11n (HT40)	2	MCS 0-15

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40.

Note 2: Modulation modes consist of below configuration:  
HT20/HT40: IEEE 802.11n

### 3.2. Accessories

Power	Brand	Model	Rating
Adaptor 1 (Fixed plug)	OEM	ADS0271-W120200	Input:100-240Vac, 50-60Hz, 0.6A Output:12Vdc, 2.0A
Adaptor 2 (Removable plug)	Ktec	KSAS0241200200D5	Input:100-240Vac, 50-60Hz, 0.6A Output:12Vdc, 2.0A
<b>Others</b>			
FCC Plug*1 (Only for Adapter 2 use)			
Console Cable: Non-Shielded, 0.5m			
RJ-45 Cable: Non-Shielded, 1.8m			

## 3.3. Table for Filed Antenna

Ant.	Brand	Model No.	Antenna Type	Connector	Gain (dBi)		Loss of External Cable (dB)		True Gain (dBi)	
					2.4GHz	5GHz	2.4GHz	5GHz	2.4GHz	5GHz
1	UNI LINK	MCS-304-01	Dipole Antenna	Re-SMA(M)	2	-	0.3	-	1.7	-
2	UNI LINK	MCS-304-01	Dipole Antenna	Re-SMA(M)	2	-	0.3	-	1.7	-
3	UNI LINK	MCS-304-01	Dipole Antenna	Re-SMA(M)	-	3	-	0.3	-	2.7
4	UNI LINK	MCS-304-01	Dipole Antenna	Re-SMA(M)	-	3	-	0.3	-	2.7


Note: The EUT has four antennas.

**<For 2.4GHz Band>**

Chain 1 and Chain 2 could transmit/receive simultaneously.

**<For 5GHz Band>**

Chain 3 and Chain 4 could transmit/receive simultaneously.



### 3.4. Table for Carrier Frequencies

#### For 2.4GHz Band:

For IEEE 802.11b/g, use Channel 1~Channel 11.

There are two bandwidth systems for IEEE 802.11n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

#### For 5GHz Band:

For IEEE 802.11a, use Channel 149, 153, 157, 161, 165.

There are two bandwidth systems for IEEE 802.11n.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	159	5795 MHz
	151	5755 MHz	161	5805 MHz
	153	5765 MHz	165	5825 MHz
	157	5785 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

#### For 2.4GHz Band

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	11n 20MHz	MCS0	1/6/11	1+2
	11n 40MHz	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Power Spectral Density	11n 20MHz	MCS0	1/6/11	1&2
	11n 40MHz	MCS0	3/6/9	1&2
	11b/CCK	1 Mbps	1/6/11	1&2
	11g/BPSK	6 Mbps	1/6/11	1&2
6dB Spectrum Bandwidth	11n 20MHz	MCS0	1/6/11	1+2
	11n 40MHz	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Radiated Emissions Below 1GHz	CTX	-	-	-
Radiated Emissions Above 1GHz	11n 20MHz	MCS0	1/6/11	1+2
	11n 40MHz	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Band Edge Emissions	11n 20MHz	MCS0	1/6/11	1+2
	11n 40MHz	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2

**For 5GHz Band**

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	11n 20MHz	MCS0	149/157/165	3+4
	11n 40MHz	MCS0	151/159	3+4
	11a/BPSK	6 Mbps	149/157/165	3+4
Power Spectral Density	11n 20MHz	MCS0	149/157/165	3&4
	11n 40MHz	MCS0	151/159	3&4
	11a/BPSK	6 Mbps	149/157/165	3&4
6dB Spectrum Bandwidth	11n 20MHz	MCS0	149/157/165	3+4
	11n 40MHz	MCS0	151/159	3+4
	11a/BPSK	6 Mbps	149/157/165	3+4
Radiated Emissions Below 1GHz	CTX	-	-	-
Radiated Emissions Above 1GHz	11n 20MHz	MCS0	149/157/165	3+4
	11n 40MHz	MCS0	151/159	3+4
	11a/BPSK	6 Mbps	149/157/165	3+4
Band Edge Emissions	11n 20MHz	MCS0	149/157/165	3+4
	11n 40MHz	MCS0	151/159	3+4
	11a/BPSK	6 Mbps	149/157/165	3+4

The following test modes were performed for all tests:

**For AC Power Line Conducted Emissions test:**

The POE is for measurement only, would not be marketed, it's not necessary to apply to AC Power Line Conducted Emissions test.

Mode 1. CTX: EUT + Adaptor 1

Mode 2. CTX: EUT + Adaptor 2

Mode 1 is the worst case, so it was selected to record in this test report.

**For Radiated Emission test(30MHz~1GHz):**

Mode 1. CTX: Place EUT in X axis + Adapter 2

Mode 2. CTX: Place EUT in Y axis + Adapter 2

Mode 3. CTX: Place EUT in Z axis + Adapter 2

Mode 2 has been evaluated to be the worst case among Mode 1~3, thus measurement for Mode 4 will follow this same test mode.

Mode 4. CTX: Place EUT in Y axis + Adapter 1

Mode 4 has been evaluated to be the worst case among Mode 1~4, thus measurement for Mode 5 will follow this same test mode.

Mode 5. CTX: Place EUT in Y axis + POE

Mode 4 generated the worst test result, so it was recorded in this report.

**For Radiated Emission test(Above 1GHz):**

Mode 1. CTX: Place EUT in X axis

Mode 2. CTX: Place EUT in Y axis

Mode 3. CTX: Place EUT in Z axis

Mode 3 generated the worst test result, so it was recorded in this report.

**<For MPE and Co-location Test>:**

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Maximum Permissible Exposure (Please refer to Appendix B) and Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

**For Test Site No : CO01-CB / 03CH01-CB**

Support Unit	Brand	Model	FCC ID
Notebook	IBM	T60	QDS-BRCM1020

**For Test Site No : TH01-CB**

Support Unit	Brand	Model	FCC ID
Notebook	IBM	T60	QDS-BRCM1020

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### For 2.4GHz Band

##### Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	ART2-GUI Version 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	16	25.5	19.5

##### Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	ART2-GUI Version 2.3		
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	11.5	16.5	16

##### Power Parameters of IEEE 802.11b/g

Test Software Version	ART2-GUI Version 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	20	25	22
IEEE 802.11g	16	25.5	20

#### For 5GHz Band

##### Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	ART2-GUI Version 2.3		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	24.5	24.5	20

##### Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	ART2-GUI Version 2.3		
Frequency	5755 MHz	5795 MHz	
MCS0 40MHz	24.5	24.5	

##### Power Parameters of IEEE 802.11a


Test Software Version	ART2-GUI Version 2.3		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	24.5	22.5	20

### 3.9. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


### 3.10. Duty Cycle

#### IEEE 802.11n MCS0 20MHz / For 2.4GHz Band




Date: 16.APR.2013 07:48:40


#### IEEE 802.11n MCS0 40MHz / For 2.4GHz Band



Date: 16.APR.2013 07:49:28


**IEEE 802.11n MCS0 20MHz / For 5GHz Band**


Date: 16.APR.2013 09:10:38

**IEEE 802.11n MCS0 40MHz / For 5GHz Band**



Date: 16.APR.2013 09:11:13

**IEEE 802.11b**



Date: 16.APR.2013 07:46:50


**IEEE 802.11g**



Date: 16.APR.2013 07:47:50




## IEEE 802.11a



Date: 16.APR.2013 09:10:04


### 3.11. Test Configurations

#### 3.11.1. AC Power Line Conduction Emissions Configuration



Item	Connection	Shield	Length(m)
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m

### 3.11.2. Radiation Emissions Configuration



Item	Connection	Shield	Length(m)
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



##### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50 \Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


## 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	51%
Test Engineer	Sin Cheng	Phase	Line
Configuration	Mode 1		



Freq	Over Limit		Line	Read Level	LISN Factor	Cable Loss		Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	Factor	dBuV	dB		
1	0.15900	35.84	-19.67	55.52	35.50	0.16	0.18	LINE	AVERAGE
2	0.15900	45.73	-19.78	65.52	45.39	0.16	0.18	LINE	QP
3	0.58540	28.35	-17.65	46.00	27.99	0.16	0.20	LINE	AVERAGE
4	0.58540	34.99	-21.01	56.00	34.63	0.16	0.20	LINE	QP
5	2.088	25.45	-30.55	56.00	25.03	0.19	0.23	LINE	QP
6	2.088	18.54	-27.46	46.00	18.12	0.19	0.23	LINE	AVERAGE
7	7.290	20.83	-29.17	50.00	20.24	0.29	0.30	LINE	AVERAGE
8	7.290	26.31	-33.69	60.00	25.72	0.29	0.30	LINE	QP
9	12.852	25.02	-24.98	50.00	24.24	0.38	0.40	LINE	AVERAGE
10	12.852	30.33	-29.67	60.00	29.55	0.38	0.40	LINE	QP
11	24.659	31.42	-28.58	60.00	30.29	0.58	0.56	LINE	QP
12	24.659	27.66	-22.34	50.00	26.53	0.58	0.56	LINE	AVERAGE

Temperature	23°C	Humidity	51%
Test Engineer	Sin Cheng	Phase	Neutral
Configuration	Mode 1		



Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Line	dBuV	Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15567	35.92	-19.77	55.69	35.66	0.08	0.18 NEUTRAL AVERAGE
2	0.15567	48.65	-17.04	65.69	48.39	0.08	0.18 NEUTRAL QP
3	0.26303	41.11	-20.23	61.34	40.83	0.08	0.20 NEUTRAL QP
4	0.26303	31.77	-19.57	51.34	31.49	0.08	0.20 NEUTRAL AVERAGE
5	0.59478	42.80	-13.20	56.00	42.52	0.08	0.20 NEUTRAL QP
6	0.59478	35.93	-10.07	46.00	35.65	0.08	0.20 NEUTRAL AVERAGE
7	1.970	20.86	-25.14	46.00	20.52	0.11	0.23 NEUTRAL AVERAGE
8	1.970	27.88	-28.12	56.00	27.54	0.11	0.23 NEUTRAL QP
9	12.649	24.61	-25.39	50.00	23.93	0.28	0.40 NEUTRAL AVERAGE
10	12.649	30.19	-29.81	60.00	29.51	0.28	0.40 NEUTRAL QP
11	24.922	32.15	-27.85	60.00	31.10	0.49	0.56 NEUTRAL QP
12	24.922	28.46	-21.54	50.00	27.41	0.49	0.56 NEUTRAL AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the Chain exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Chain exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting Chains with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

### 4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	56%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n
Test Date	May 27, 2013		

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2			
1	2412 MHz	18.24	17.21	20.77	30.00	Complies
6	2437 MHz	26.73	26.66	29.71	30.00	Complies
11	2462 MHz	21.61	20.75	24.21	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2			
3	2422 MHz	13.47	12.42	15.99	30.00	Complies
6	2437 MHz	19.11	18.27	21.72	30.00	Complies
9	2452 MHz	19.14	18.48	21.83	30.00	Complies

For 5GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 3	Chain 4			
149	5745 MHz	26.36	27.23	29.83	30.00	Complies
157	5785 MHz	26.45	27.29	29.90	30.00	Complies
165	5825 MHz	22.18	22.07	25.14	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 3	Chain 4			
151	5755 MHz	26.18	27.17	29.71	30.00	Complies
159	5795 MHz	26.61	27.26	29.96	30.00	Complies

Temperature	25°C	Humidity	70%
Test Engineer	Robert Chang	Configurations	IEEE 802.11a/b/g
Test Date	May 27, 2013		

**Configuration IEEE 802.11b / Chain 1 + Chain 2**

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2			
1	2412 MHz	22.02	21.12	24.60	30.00	Complies
6	2437 MHz	26.61	26.45	29.54	30.00	Complies
11	2462 MHz	24.33	23.34	26.87	30.00	Complies

**Configuration IEEE 802.11g / Chain 1 + Chain 2**

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1	Chain 2			
1	2412 MHz	18.25	17.13	20.74	30.00	Complies
6	2437 MHz	26.88	26.98	29.94	30.00	Complies
11	2462 MHz	22.12	21.55	24.85	30.00	Complies

**Configuration IEEE 802.11a / Chain 3 + Chain 4**

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 3	Chain 4			
149	5745 MHz	26.61	27.32	29.99	30.00	Complies
157	5785 MHz	25.02	25.72	28.39	30.00	Complies
165	5825 MHz	22.16	22.32	25.25	30.00	Complies

#### 4.3. Power Spectral Density Measurement

##### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the Chain shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

##### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

##### 4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 10.2 Method PKPSD (peak PSD) & KDB 662911 D01 v01r02 section In-Band Power Spectral Density (PSD) Measurements option (2) Measure and add  $10 \log(\text{NANT})$  dB.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .

##### 4.3.4. Test Setup Layout



#### **4.3.5. Test Deviation**

There is no deviation with the original standard.

#### **4.3.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	56%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Chain 1 & Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
1	2412 MHz	-8.28	-8.44	4.99	Complies
6	2437 MHz	0.90	0.56	4.99	Complies
11	2462 MHz	-3.36	-4.52	4.99	Complies

Note: PSD Limit = $(8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$

Configuration IEEE 802.11n MCS0 40MHz / Chain 1 & Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
3	2422 MHz	-15.11	-16.25	4.99	Complies
6	2437 MHz	-10.18	-10.77	4.99	Complies
9	2452 MHz	-9.32	-10.20	4.99	Complies

Note: PSD Limit = $(8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$

For 5GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 3	Chain 4		
149	5745 MHz	0.04	0.18	4.99	Complies
157	5785 MHz	-0.31	0.28	4.99	Complies
165	5825 MHz	-4.66	-4.60	4.99	Complies

Note: PSD Limit = $(8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$

Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 3	Chain 4		
151	5755 MHz	-1.94	-1.39	4.99	Complies
159	5795 MHz	-2.20	-2.41	4.99	Complies

Note: PSD Limit = $(8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Robert Chang	<b>Configurations</b>	IEEE 802.11a/b/g

**Configuration IEEE 802.11b / Chain 1 & Chain 2**

<b>Channel</b>	<b>Frequency</b>	<b>Power Density (dBm/3kHz)</b>		<b>Single Port Limit (dBm/3kHz)</b>	<b>Result</b>
		<b>Chain 1</b>	<b>Chain 2</b>		
3	2422 MHz	-2.23	-3.64	4.99	Complies
6	2437 MHz	1.93	1.80	4.99	Complies
9	2452 MHz	-0.71	-1.16	4.99	Complies

Note: PSD Limit = $(8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$

**Configuration IEEE 802.11g / Chain 1 & Chain 2**

<b>Channel</b>	<b>Frequency</b>	<b>Power Density (dBm/3kHz)</b>		<b>Single Port Limit (dBm/3kHz)</b>	<b>Result</b>
		<b>Chain 1</b>	<b>Chain 2</b>		
3	2422 MHz	-8.20	-7.96	4.99	Complies
6	2437 MHz	1.14	0.91	4.99	Complies
9	2452 MHz	-4.31	-5.36	4.99	Complies

Note: PSD Limit = $(8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$


**Configuration IEEE 802.11a / Chain 3 + Chain 4**

<b>Channel</b>	<b>Frequency</b>	<b>Power Density (dBm/3kHz)</b>		<b>Single Port Limit (dBm/3kHz)</b>	<b>Result</b>
		<b>Chain 3</b>	<b>Chain 4</b>		
149	5745 MHz	0.59	1.26	4.99	Complies
157	5785 MHz	-2.78	-1.09	4.99	Complies
165	5825 MHz	-1.45	0.15	4.99	Complies


Note: PSD Limit = $(8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 1 / 2437 MHz**



Date: 27.MAY.2013 22:27:51

**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 1 / 2452 MHz**


Date: 27.MAY.2013 22:35:46

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 4 / 5785 MHz**



Date: 27.MAY.2013 18:54:10

**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 4 / 5755 MHz**


Date: 27.MAY.2013 18:49:49


**Power Density Plot on Configuration IEEE 802.11b / Chain 1 / 2437 MHz**


Date: 27.MAY.2013 22:16:36

**Power Density Plot on Configuration IEEE 802.11g / Chain 1 / 2437 MHz**


Date: 27.MAY.2013 22:21:09

**Power Density Plot on Configuration IEEE 802.11a / Chain 4 / 5745 MHz**



Date: 27.MAY.2013 18:59:35

#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times RBW$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

##### 4.4.3. Test Procedures

1. The transmitter output (Chain port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Multiple Chain system was performed in accordance with KDB 662911 D01 v01r02 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout



##### 4.4.5. Test Deviation

There is no deviation with the original standard.

##### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	25°C	Humidity	56%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	11.76	16.64	500	Complies
6	2437 MHz	11.92	16.96	500	Complies
11	2462 MHz	12.88	16.72	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.16	36.16	500	Complies
6	2437 MHz	35.52	36.00	500	Complies
9	2452 MHz	35.52	35.68	500	Complies

For 5GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	15.60	17.44	500	Complies
157	5785 MHz	15.04	17.28	500	Complies
165	5825 MHz	16.08	17.76	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	34.24	36.32	500	Complies
159	5795 MHz	34.56	36.16	500	Complies

<b>Temperature</b>	25°C	<b>Humidity</b>	70%
<b>Test Engineer</b>	Robert Chang	<b>Configurations</b>	IEEE 802.11a/b/g

**Configuration IEEE 802.11b / Chain 1 + Chain 2**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	9.04	13.12	500	Complies
6	2437 MHz	9.04	12.64	500	Complies
11	2462 MHz	8.08	13.04	500	Complies

**Configuration IEEE 802.11g / Chain 1 + Chain 2**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.16	15.76	500	Complies
6	2437 MHz	12.32	16.00	500	Complies
11	2462 MHz	14.80	15.76	500	Complies


**Configuration IEEE 802.11a / Chain 3 + Chain 4**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	15.04	16.24	500	Complies
157	5785 MHz	15.04	16.16	500	Complies
165	5825 MHz	15.28	16.48	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 1 + Chain 2 / 2412 MHz




Date: 27.MAY.2013 18:16:12

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 1 + Chain 2 / 2437 MHz




Date: 27.MAY.2013 18:20:05

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 3 + Chain 4 / 5785 MHz




Date: 27.MAY.2013 18:31:34

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 3 + Chain 4 / 5755MHz




Date: 27.MAY.2013 18:35:18

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / Chain 1 + Chain 2 / 2462 MHz




Date: 27.MAY.2013 18:11:02

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / Chain 1 + Chain 2 / 2412 MHz



Date: 27.MAY.2013 18:14:13

**6 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 3 + Chain 4 / 5745 MHz**



Date: 27.MAY.2013 18:28:04

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving Chain mounted on the top of a height-variable Chain tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving Chain was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the Chain tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop Chain has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	20°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	CTX
Test Date	May 23, 2013		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


## 4.5.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	23°C	Humidity	55%
Test Engineer	Jim Huang	Configurations	Mode 4

Horizontal



Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
		Line	dB			dBuV	dB	dB/m						
1	125.06	34.11	43.50	-9.39	52.62	1.33	11.73	31.57	150	271	HORIZONTAL	Peak		
2	500.45	30.53	46.00	-15.47	42.20	2.82	16.92	31.41	125	213	HORIZONTAL	Peak		
3	624.61	42.95	46.00	-3.05	52.56	3.18	18.61	31.40	100	250	HORIZONTAL	Peak		
4	675.05	42.16	46.00	-3.84	51.41	3.33	18.78	31.36	100	262	HORIZONTAL	Peak		
5	874.87	38.84	46.00	-7.16	45.86	3.89	20.24	31.15	150	276	HORIZONTAL	Peak		
6	900.09	35.34	46.00	-10.66	41.94	3.97	20.64	31.21	150	276	HORIZONTAL	Peak		

**Vertical**


Freq	Level	Limit		Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		Line	dB									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	pp	30.00	36.71	40.00	-3.29	49.90	0.64	17.98	31.81	100	154	VERTICAL Peak
2		69.77	33.23	40.00	-6.77	58.74	1.00	5.28	31.79	150	358	VERTICAL Peak
3		375.32	33.43	46.00	-12.57	47.49	2.44	14.93	31.43	125	244	VERTICAL Peak
4		624.61	34.15	46.00	-11.85	43.76	3.18	18.61	31.40	200	174	VERTICAL Peak
5		675.05	38.19	46.00	-7.81	47.44	3.33	18.78	31.36	100	58	VERTICAL Peak
6		874.87	34.72	46.00	-11.28	41.74	3.89	20.24	31.15	150	29	VERTICAL Peak

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Chain Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Temperature	25.6°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz Ch 1 / Chain 1 + Chain 2
Test Date	May 17, 2013		

## Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			Loss	Antenna	Factor					
		MHz	dBuV/m	dB	dBuV	dB	dB/m	dB			cm	deg	
1	4815.41	42.63	74.00	-31.37	41.34	3.31	33.02	35.04	Peak	100	191	HORIZONTAL	
2	4817.01	29.74	54.00	-24.26	28.45	3.31	33.02	35.04	Average	100	191	HORIZONTAL	

## Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			Loss	Antenna	Factor					
		MHz	dBuV/m	dB	dBuV	dB	dB/m	dB			cm	deg	
1	4818.17	29.89	54.00	-24.11	28.59	3.31	33.02	35.03	Average	100	240	VERTICAL	
2	4822.37	42.75	74.00	-31.25	41.41	3.31	33.06	35.03	Peak	100	240	VERTICAL	

Temperature	25.6°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz Ch 6 / Chain 1 + Chain 2
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	4867.24	47.96	74.00	-26.04	46.54	3.33	33.12	35.03	Peak	100	156	HORIZONTAL		
2	4871.89	34.20	54.00	-19.80	32.74	3.33	33.16	35.03	Average	100	156	HORIZONTAL		
3	7303.31	32.73	54.00	-21.27	28.15	4.06	35.92	35.40	Average	100	83	HORIZONTAL		
4	7321.66	43.78	74.00	-30.22	39.16	4.06	35.96	35.40	Peak	100	83	HORIZONTAL		

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	4872.32	42.90	54.00	-11.10	41.44	3.33	33.16	35.03	Average	110	69	VERTICAL		
2	4873.68	58.25	74.00	-15.75	56.79	3.33	33.16	35.03	Peak	110	69	VERTICAL		
3	7304.67	54.29	74.00	-19.71	49.71	4.06	35.92	35.40	Peak	100	193	VERTICAL		
4	7306.35	40.08	54.00	-13.92	35.50	4.06	35.92	35.40	Average	100	193	VERTICAL		

<b>Temperature</b>	25.6°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Jim Huang	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch11 / Chain 1 + Chain 2
<b>Test Date</b>	May 17, 2013		

**Horizontal**

Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor		cm	deg	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			
1	4915.89	42.43	74.00	-31.57	40.87	3.35	33.23	35.02	Peak	100	122 HORIZONTAL
2	4933.33	29.75	54.00	-24.25	28.15	3.35	33.26	35.01	Average	100	122 HORIZONTAL
3	7379.97	31.68	54.00	-22.32	26.93	4.06	36.09	35.40	Average	100	221 HORIZONTAL
4	7395.14	44.85	74.00	-29.15	40.06	4.06	36.13	35.40	Peak	100	221 HORIZONTAL

**Vertical**

Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor		cm	deg	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			
1	4920.96	42.66	74.00	-31.34	41.09	3.35	33.23	35.01	Peak	100	226 VERTICAL
2	4923.84	31.24	54.00	-22.76	29.64	3.35	33.26	35.01	Average	100	226 VERTICAL
3	7387.12	31.77	54.00	-22.23	27.02	4.06	36.09	35.40	Average	100	304 VERTICAL
4	7390.97	44.22	74.00	-29.78	39.47	4.06	36.09	35.40	Peak	100	304 VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz Ch 3 / Chain 1 + Chain 2
Test Date	May 17, 2013		

*Horizontal*

Freq	Level	Limit		Over	Read	CableAntenna Preamp			Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m				
1	4841.66	41.50	74.00	-32.50	40.12	3.32	33.09	35.03	Peak	100	265	HORIZONTAL
2	4842.08	29.43	54.00	-24.57	28.05	3.32	33.09	35.03	Average	100	265	HORIZONTAL

*Vertical*

Freq	Level	Limit		Over	Read	CableAntenna Preamp			Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m				
1	4840.31	29.27	54.00	-24.73	27.89	3.32	33.09	35.03	Average	100	178	VERTICAL
2	4853.90	41.91	74.00	-32.09	40.50	3.32	33.12	35.03	Peak	100	178	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz Ch 6 / Chain 1 + Chain 2
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
		MHz	dBuV/m	dBuV/m	dB			dB		cm	deg
1	4877.72	29.52	54.00	-24.48	28.06	3.33	33.16	35.03	Average	100	218 HORIZONTAL
2	4880.54	42.69	74.00	-31.31	41.23	3.33	33.16	35.03	Peak	100	218 HORIZONTAL
3	7302.54	31.54	54.00	-22.46	26.96	4.06	35.92	35.40	Average	100	266 HORIZONTAL
4	7310.30	44.58	74.00	-29.42	39.96	4.06	35.96	35.40	Peak	100	266 HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
		MHz	dBuV/m	dBuV/m	dB			dB		cm	deg
1	4877.08	29.56	54.00	-24.44	28.10	3.33	33.16	35.03	Average	100	186 VERTICAL
2	4880.57	42.30	74.00	-31.70	40.84	3.33	33.16	35.03	Peak	100	186 VERTICAL
3	7314.11	44.21	74.00	-29.79	39.59	4.06	35.96	35.40	Peak	100	220 VERTICAL
4	7318.66	31.70	54.00	-22.30	27.08	4.06	35.96	35.40	Average	100	220 VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz Ch 9 / Chain 1 + Chain 2
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
1	4902.30	29.46	54.00	-24.54	27.95	3.34	33.19	35.02	Average	100	275	HORIZONTAL		
2	4903.58	42.63	74.00	-31.37	41.12	3.34	33.19	35.02	Peak	100	275	HORIZONTAL		
3	7348.53	31.93	54.00	-22.07	27.25	4.06	36.02	35.40	Average	100	315	HORIZONTAL		
4	7362.76	45.75	74.00	-28.25	41.03	4.06	36.06	35.40	Peak	100	315	HORIZONTAL		

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
1	4900.92	29.48	54.00	-24.52	27.97	3.34	33.19	35.02	Average	100	198	VERTICAL		
2	4912.46	42.76	74.00	-31.24	41.21	3.34	33.23	35.02	Peak	100	198	VERTICAL		
3	7351.74	31.94	54.00	-22.06	27.26	4.06	36.02	35.40	Average	100	239	VERTICAL		
4	7354.75	45.04	74.00	-28.96	40.36	4.06	36.02	35.40	Peak	100	239	VERTICAL		

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 149 / Chain 3 + Chain 4
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m				
1	4999.96	52.45	74.00	-21.55	50.68	3.39	33.39	35.01	Peak	100	106	HORIZONTAL
2	5000.03	46.82	54.00	-7.18	45.05	3.39	33.39	35.01	Average	100	106	HORIZONTAL
3	11486.14	37.82	54.00	-16.18	29.21	5.11	38.78	35.28	Average	100	248	HORIZONTAL
4	11489.95	49.86	74.00	-24.14	41.25	5.11	38.78	35.28	Peak	100	248	HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m				
1	5000.02	53.85	54.00	-0.15	52.07	3.39	33.40	35.01	Average	118	334	VERTICAL
2	5000.09	59.04	74.00	-14.96	57.26	3.39	33.40	35.01	Peak	118	334	VERTICAL
3	11482.79	41.87	54.00	-12.13	33.26	5.11	38.78	35.28	Average	100	173	VERTICAL
4	11483.43	53.61	74.00	-20.39	45.00	5.11	38.78	35.28	Peak	100	173	VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 157 / Chain 3 + Chain 4
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
MHz		dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg	
1	5000.03	46.74	54.00	-7.26	44.97	3.39	33.39	35.01	Average	100	105 HORIZONTAL
2	5000.18	52.31	74.00	-21.69	50.54	3.39	33.39	35.01	Peak	100	105 HORIZONTAL
3	11567.28	38.23	54.00	-15.77	29.58	5.13	38.82	35.30	Average	100	139 HORIZONTAL
4	11580.58	50.76	74.00	-23.24	42.09	5.14	38.83	35.30	Peak	100	139 HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
MHz		dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	cm	deg	
1	5000.05	53.16	54.00	-0.84	51.38	3.39	33.40	35.01	Average	100	350 VERTICAL
2	5000.12	57.63	74.00	-16.37	55.85	3.39	33.40	35.01	Peak	100	350 VERTICAL
3	11563.43	40.51	54.00	-13.49	31.86	5.13	38.82	35.30	Average	100	233 VERTICAL
4	11566.07	52.38	74.00	-21.62	43.73	5.13	38.82	35.30	Peak	100	233 VERTICAL

<b>Temperature</b>	24°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Jim Huang	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz CH 165 / Chain 3 + Chain 4
<b>Test Date</b>	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
		MHz	dBuV/m	dBuV/m		dB							cm	deg
1	4999.74	49.86	74.00	-24.14	48.09	3.39	33.39	35.01	Peak			100	107	HORIZONTAL
2	5000.02	42.79	54.00	-11.21	41.02	3.39	33.39	35.01	Average			100	107	HORIZONTAL
3	11659.70	50.39	74.00	-23.61	41.67	5.16	38.86	35.30	Peak			100	100	HORIZONTAL
4	11664.74	37.60	54.00	-16.40	28.88	5.16	38.86	35.30	Average			100	100	HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
		MHz	dBuV/m	dBuV/m		dB							cm	deg
1	5000.02	50.11	54.00	-3.89	48.33	3.39	33.40	35.01	Average			117	334	VERTICAL
2	5000.07	55.97	74.00	-18.03	54.19	3.39	33.40	35.01	Peak			117	334	VERTICAL
3	11648.56	49.90	74.00	-24.10	41.18	5.16	38.86	35.30	Peak			100	158	VERTICAL
4	11649.28	37.60	54.00	-16.40	28.88	5.16	38.86	35.30	Average			100	158	VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 151 / Chain 3 + Chain 4
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
		MHz	dBuV/m	dBuV/m	dB			dB			
1	5000.03	46.08	54.00	-7.92	44.31	3.39	33.39	35.01	Average	100	107 HORIZONTAL
2	5000.12	52.56	74.00	-21.44	50.79	3.39	33.39	35.01	Peak	100	107 HORIZONTAL
3	11510.14	49.98	74.00	-24.02	41.35	5.12	38.79	35.28	Peak	100	268 HORIZONTAL
4	11510.59	37.46	54.00	-16.54	28.83	5.12	38.79	35.28	Average	100	268 HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
		MHz	dBuV/m	dBuV/m	dB			dB			
1	4999.79	58.87	74.00	-15.13	57.09	3.39	33.40	35.01	Peak	118	334 VERTICAL
2	5000.04	53.52	54.00	-0.48	51.74	3.39	33.40	35.01	Average	118	334 VERTICAL
3	11510.72	50.52	74.00	-23.48	41.89	5.12	38.79	35.28	Peak	100	116 VERTICAL
4	11510.85	37.45	54.00	-16.55	28.82	5.12	38.79	35.28	Average	100	116 VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 159 / Chain 3 + Chain 4
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	5000.04	45.90	54.00	-8.10	44.13	3.39	33.39	35.01	Average			100	105	HORIZONTAL
2	5000.14	52.72	74.00	-21.28	50.95	3.39	33.39	35.01	Peak			100	105	HORIZONTAL
3	11589.30	37.45	54.00	-16.55	28.78	5.14	38.83	35.30	Average			100	215	HORIZONTAL
4	11590.34	50.45	74.00	-23.55	41.78	5.14	38.83	35.30	Peak			100	215	HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	4999.95	58.10	74.00	-15.90	56.32	3.39	33.40	35.01	Peak			120	334	VERTICAL
2	5000.04	53.30	54.00	-0.70	51.52	3.39	33.40	35.01	Average			120	334	VERTICAL
3	11588.19	38.44	54.00	-15.56	29.77	5.14	38.83	35.30	Average			100	143	VERTICAL
4	11590.70	50.99	74.00	-23.01	42.32	5.14	38.83	35.30	Peak			100	143	VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over	Read	Cable			Preamp	A/Pos	T/Pos	Pol/Phase
		Line	Limit			Loss	Antenna	Factor				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg		
1	4823.98	30.26	54.00	-23.74	28.92	3.31	33.06	35.03	Average	100	307	HORIZONTAL
2	4826.26	42.01	74.00	-31.99	40.67	3.31	33.06	35.03	Peak	100	307	HORIZONTAL

**Vertical**

Freq	Level	Limit		Over	Read	Cable			Preamp	A/Pos	T/Pos	Pol/Phase
		Line	Limit			Loss	Antenna	Factor				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg		
1	4823.90	45.80	74.00	-28.20	44.46	3.31	33.06	35.03	Peak	112	219	VERTICAL
2	4823.98	40.19	54.00	-13.81	38.85	3.31	33.06	35.03	Average	112	219	VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		dB	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4874.01	41.64	54.00	-12.36	40.18	3.33	33.16	35.03	Average	101	44 HORIZONTAL
2	4874.18	47.71	74.00	-26.29	46.25	3.33	33.16	35.03	Peak	101	44 HORIZONTAL
3	7308.72	45.25	74.00	-28.75	40.63	4.06	35.96	35.40	Peak	100	47 HORIZONTAL
4	7308.77	33.06	54.00	-20.94	28.44	4.06	35.96	35.40	Average	100	47 HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		dB	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4873.96	55.29	74.00	-18.71	53.83	3.33	33.16	35.03	Peak	122	64 VERTICAL
2	4874.00	53.23	54.00	-0.77	51.77	3.33	33.16	35.03	Average	122	64 VERTICAL
3	7309.93	48.47	74.00	-25.53	43.85	4.06	35.96	35.40	Peak	100	193 VERTICAL
4	7310.26	40.54	54.00	-13.46	35.92	4.06	35.96	35.40	Average	100	193 VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		dB	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4924.03	36.66	54.00	-17.34	35.06	3.35	33.26	35.01	Average	113	163 HORIZONTAL
2	4924.22	44.86	74.00	-29.14	43.26	3.35	33.26	35.01	Peak	113	163 HORIZONTAL
3	7385.94	45.28	74.00	-28.72	40.53	4.06	36.09	35.40	Peak	100	202 HORIZONTAL
4	7388.42	31.74	54.00	-22.26	26.99	4.06	36.09	35.40	Average	100	202 HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		dB	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4923.96	49.40	74.00	-24.60	47.80	3.35	33.26	35.01	Peak	100	152 VERTICAL
2	4923.99	44.56	54.00	-9.44	42.96	3.35	33.26	35.01	Average	100	152 VERTICAL
3	7383.61	32.64	54.00	-21.36	27.89	4.06	36.09	35.40	Average	100	94 VERTICAL
4	7387.91	46.06	74.00	-27.94	41.31	4.06	36.09	35.40	Peak	100	94 VERTICAL



Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over	Read	Cable			Preamp	A/Pos	T/Pos	Pol/Phase
		Line	Limit			Loss	Antenna	Factor				
1	4816.53	29.75	54.00	-24.25	28.46	3.31	33.02	35.04	Average	100	144	HORIZONTAL
2	4817.01	42.07	74.00	-31.93	40.78	3.31	33.02	35.04	Peak	100	144	HORIZONTAL

**Vertical**

Freq	Level	Limit		Over	Read	Cable			Preamp	A/Pos	T/Pos	Pol/Phase
		Line	Limit			Loss	Antenna	Factor				
1	4817.91	29.83	54.00	-24.17	28.53	3.31	33.02	35.03	Average	100	236	VERTICAL
2	4819.51	43.37	74.00	-30.63	42.07	3.31	33.02	35.03	Peak	100	236	VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 6 / Chain 1 + Chain 2
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		dB	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4864.22	43.20	74.00	-30.80	41.78	3.33	33.12	35.03	Peak	100	60 HORIZONTAL
2	4876.72	34.10	54.00	-19.90	32.64	3.33	33.16	35.03	Average	100	60 HORIZONTAL
3	7304.35	48.37	74.00	-25.63	43.79	4.06	35.92	35.40	Peak	100	204 HORIZONTAL
4	7310.28	35.61	54.00	-18.39	30.99	4.06	35.96	35.40	Average	100	204 HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Line	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		dB	dB			Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4872.88	59.28	74.00	-14.72	57.82	3.33	33.16	35.03	Peak	112	66 VERTICAL
2	4873.28	43.68	54.00	-10.32	42.22	3.33	33.16	35.03	Average	112	66 VERTICAL
3	7309.64	40.24	54.00	-13.76	35.62	4.06	35.96	35.40	Average	100	193 VERTICAL
4	7309.88	55.59	74.00	-18.41	50.97	4.06	35.96	35.40	Peak	100	193 VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 11 / Chain 1 + Chain 2
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4931.40	42.78	74.00	-31.22	41.18	3.35	33.26	35.01	Peak	100	79 HORIZONTAL
2	4932.75	29.82	54.00	-24.18	28.22	3.35	33.26	35.01	Average	100	79 HORIZONTAL
3	7379.94	31.63	54.00	-22.37	26.88	4.06	36.09	35.40	Average	100	181 HORIZONTAL
4	7391.77	44.69	74.00	-29.31	39.94	4.06	36.09	35.40	Peak	100	181 HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			Loss	Factor	Factor			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4914.19	43.43	74.00	-30.57	41.88	3.34	33.23	35.02	Peak	100	173 VERTICAL
2	4923.65	31.79	54.00	-22.21	30.19	3.35	33.26	35.01	Average	100	173 VERTICAL
3	7377.83	31.82	54.00	-22.18	27.07	4.06	36.09	35.40	Average	100	286 VERTICAL
4	7387.73	44.29	74.00	-29.71	39.54	4.06	36.09	35.40	Peak	100	286 VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11a CH 149 / Chain 3 + Chain 4
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	4999.98	54.02	74.00	-19.98	52.25	3.39	33.39	35.01	Peak			100	106	HORIZONTAL
2	5000.02	48.73	54.00	-5.27	46.96	3.39	33.39	35.01	Average			100	106	HORIZONTAL
3	11488.69	38.38	54.00	-15.62	29.77	5.11	38.78	35.28	Average			100	295	HORIZONTAL
4	11491.41	51.28	74.00	-22.72	42.67	5.11	38.78	35.28	Peak			100	295	HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB/m						
1	4999.81	58.31	74.00	-15.69	56.53	3.39	33.40	35.01	Peak			119	334	VERTICAL
2	4999.97	53.54	54.00	-0.46	51.76	3.39	33.40	35.01	Average			119	334	VERTICAL
3	11487.60	54.84	74.00	-19.16	46.23	5.11	38.78	35.28	Peak			100	170	VERTICAL
4	11493.01	42.86	54.00	-11.14	34.25	5.11	38.78	35.28	Average			100	170	VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11a CH 157 / Chain 3 + Chain 4
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
		MHz	dBuV/m	dBuV/m	dB							cm	deg	
1	5000.00	47.76	54.00	-6.24	45.99	3.39	33.39	35.01	Average			100	107	HORIZONTAL
2	5000.14	53.31	74.00	-20.69	51.54	3.39	33.39	35.01	Peak			100	107	HORIZONTAL
3	11557.66	50.16	74.00	-23.84	41.51	5.13	38.82	35.30	Peak			100	216	HORIZONTAL
4	11567.28	37.90	54.00	-16.10	29.25	5.13	38.82	35.30	Average			100	216	HORIZONTAL

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
		MHz	dBuV/m	dBuV/m	dB							cm	deg	
1	4999.96	53.54	54.00	-0.46	51.76	3.39	33.40	35.01	Average			100	209	VERTICAL
2	5000.15	59.05	74.00	-14.95	57.27	3.39	33.40	35.01	Peak			100	209	VERTICAL
3	11563.83	50.08	74.00	-23.92	41.43	5.13	38.82	35.30	Peak			100	109	VERTICAL
4	11568.24	39.47	54.00	-14.53	30.81	5.13	38.83	35.30	Average			100	109	VERTICAL

Temperature	24°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11a CH 165 / Chain 3 + Chain 4
Test Date	May 17, 2013		

**Horizontal**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
1	5000.00	49.90	74.00	-24.10	48.13	3.39	33.39	35.01	Peak	100	107	HORIZONTAL		
2	5000.03	43.27	54.00	-10.73	41.50	3.39	33.39	35.01	Average	100	107	HORIZONTAL		
3	11637.98	49.82	74.00	-24.18	41.10	5.16	38.86	35.30	Peak	100	263	HORIZONTAL		
4	11653.21	37.54	54.00	-16.46	28.82	5.16	38.86	35.30	Average	100	263	HORIZONTAL		

**Vertical**

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
1	5000.02	49.99	54.00	-4.01	48.21	3.39	33.40	35.01	Average	117	334	VERTICAL		
2	5000.04	55.58	74.00	-18.42	53.80	3.39	33.40	35.01	Peak	117	334	VERTICAL		
3	11649.28	37.77	54.00	-16.23	29.05	5.16	38.86	35.30	Average	100	177	VERTICAL		
4	11659.21	49.65	74.00	-24.35	40.93	5.16	38.86	35.30	Peak	100	177	VERTICAL		

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Chain Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Emissions Measurement

### 4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

### 4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Conducted Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure
2. The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit. Only worst data of each operating mode is presented.

#### **4.6.4. Test Setup Layout**

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Conducted Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.4.4.

#### **4.6.5. Test Deviation**

There is no deviation with the original standard.

#### **4.6.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	25.6°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Chain 1 + Chain 2
Test date	May 17, 2013		

##### Channel 1

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			Loss	Antenna Factor	Factor					
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB	dB/m	dB			cm	deg	
1	2390.00	53.55	54.00	-0.45	23.16	2.22	28.17	0.00	Average		100	220	VERTICAL
2	2390.00	65.18	74.00	-8.82	34.79	2.22	28.17	0.00	Peak		100	220	VERTICAL
3	2406.87	102.78			72.35	2.22	28.21	0.00	Average		100	220	VERTICAL
4	2407.67	114.90			84.47	2.22	28.21	0.00	Peak		100	220	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			Loss	Antenna Factor	Factor					
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB	dB/m	dB			cm	deg	
1	2386.80	65.78	74.00	-8.22	35.40	2.21	28.17	0.00	Peak		101	189	VERTICAL
2	2390.00	51.47	54.00	-2.53	21.08	2.22	28.17	0.00	Average		101	189	VERTICAL
3	2442.77	111.11			80.58	2.24	28.29	0.00	Average		101	189	VERTICAL
4	2443.41	122.97			92.44	2.24	28.29	0.00	Peak		101	189	VERTICAL
5	2483.50	48.93	54.00	-5.07	18.30	2.26	28.37	0.00	Average		101	189	VERTICAL
6	2484.46	61.47	74.00	-12.53	30.84	2.26	28.37	0.00	Peak		101	189	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

##### Channel 11

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			Loss	Antenna Factor	Factor					
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB	dB/m	dB			cm	deg	
1	2457.51	117.47			86.90	2.24	28.33	0.00	Peak		100	166	VERTICAL
2	2461.04	104.49			73.92	2.24	28.33	0.00	Average		100	166	VERTICAL
3	2483.50	53.50	54.00	-0.50	22.87	2.26	28.37	0.00	Average		100	166	VERTICAL
4	2484.78	68.43	74.00	-5.57	37.80	2.26	28.37	0.00	Peak		100	166	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

<b>Temperature</b>	25.6°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Jim Huang	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 3, 6, 9 / Chain 1 + Chain 2
<b>Test date</b>	May 17, 2013		

### Channel 3

Freq	Level	Limit		Over Limit	Read Level	Cable Loss		Antenna Factor		Preamp Factor		Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB	dB/m	dB	dB				
1	2389.36	69.39	74.00	-4.61	39.01	2.21	28.17	0.00	Peak		118	212	VERTICAL		
2	2390.00	53.61	54.00	-0.39	23.22	2.22	28.17	0.00	Average		118	212	VERTICAL		
3	2428.09	95.08			64.60	2.23	28.25	0.00	Average		118	212	VERTICAL		
4	2438.03	107.77			77.25	2.23	28.29	0.00	Peak		118	212	VERTICAL		

Item 3, 4 are the fundamental frequency at 2422 MHz.

### Channel 6

Freq	Level	Limit		Over Limit	Read Level	Cable Loss		Antenna Factor		Preamp Factor		Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB	dB/m	dB	dB				
1	2390.00	53.88	54.00	-0.12	23.49	2.22	28.17	0.00	Average		100	165	VERTICAL		
2	2390.00	67.27	74.00	-6.73	36.88	2.22	28.17	0.00	Peak		100	165	VERTICAL		
3	2448.22	113.51			82.98	2.24	28.29	0.00	Peak		100	165	VERTICAL		
4	2449.50	100.70			70.17	2.24	28.29	0.00	Average		100	165	VERTICAL		
5	2490.23	48.84	54.00	-5.16	18.17	2.26	28.41	0.00	Average		100	165	VERTICAL		
6	2490.23	61.79	74.00	-12.21	31.12	2.26	28.41	0.00	Peak		100	165	VERTICAL		

Item 3, 4 are the fundamental frequency at 2437MHz.

### Channel 9

Freq	Level	Limit		Over Limit	Read Level	Cable Loss		Antenna Factor		Preamp Factor		Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dBuV	dB	dB	dB/m	dB	dB				
1	2445.27	98.37			67.84	2.24	28.29	0.00	Average		102	166	VERTICAL		
2	2445.27	110.93			80.40	2.24	28.29	0.00	Peak		102	166	VERTICAL		
3	2485.74	53.77	54.00	-0.23	23.10	2.26	28.41	0.00	Average		102	166	VERTICAL		
4	2486.39	72.60	74.00	-1.40	41.93	2.26	28.41	0.00	Peak		102	166	VERTICAL		

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Chain Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	25°C	Humidity	70%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 1, 6, 11 / Chain 1
Test Date	May 17, 2013		

### Channel 1

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB	dB/m				
1	2385.99	53.68	54.00	-0.32	23.30	2.21	28.17	0.00	Average		100	167	VERTICAL
2	2387.60	73.01	74.00	-0.99	42.63	2.21	28.17	0.00	Peak		100	167	VERTICAL
3	2409.12	111.94			81.51	2.22	28.21	0.00	Average		100	167	VERTICAL
4	2409.44	115.86			85.43	2.22	28.21	0.00	Peak		100	167	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

### Channel 6

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB	dB/m				
1	2387.76	68.83	74.00	-5.17	38.45	2.21	28.17	0.00	Peak		146	210	VERTICAL
2	2390.00	50.74	54.00	-3.26	20.35	2.22	28.17	0.00	Average		146	210	VERTICAL
3	2438.92	118.29			87.77	2.23	28.29	0.00	Average		146	210	VERTICAL
4	2439.56	121.92			91.40	2.23	28.29	0.00	Peak		146	210	VERTICAL
5	2483.50	49.42	54.00	-4.58	18.79	2.26	28.37	0.00	Average		146	210	VERTICAL
6	2484.46	71.73	74.00	-2.27	41.10	2.26	28.37	0.00	Peak		146	210	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

### Channel 11

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB	dB/m				
1	2460.08	118.31			87.74	2.24	28.33	0.00	Peak		100	168	VERTICAL
2	2460.24	114.76			84.19	2.24	28.33	0.00	Average		100	168	VERTICAL
3	2487.83	53.75	54.00	-0.25	23.08	2.26	28.41	0.00	Average		100	168	VERTICAL
4	2488.79	68.05	74.00	-5.95	37.38	2.26	28.41	0.00	Peak		100	168	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

<b>Temperature</b>	25°C	<b>Humidity</b>	70%
<b>Test Engineer</b>	Jim Huang	<b>Configurations</b>	IEEE 802.11g CH 1, 6, 11 / Chain 1 + Chain 2
<b>Test Date</b>	May 17, 2013		

### Channel 1

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
1	2390.00	53.86	54.00	-0.14	23.47	2.22	28.17	0.00	Average	100	163	VERTICAL		
2	2390.00	66.82	74.00	-7.18	36.43	2.22	28.17	0.00	Peak	100	163	VERTICAL		
3	2405.59	115.65			85.22	2.22	28.21	0.00	Peak	100	163	VERTICAL		
4	2405.75	103.89			73.46	2.22	28.21	0.00	Average	100	163	VERTICAL		

Item 3, 4 are the fundamental frequency at 2412 MHz.

### Channel 6


Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
1	2389.68	52.41	54.00	-1.59	22.03	2.21	28.17	0.00	Average	100	189	VERTICAL		
2	2389.68	64.49	74.00	-9.51	34.11	2.21	28.17	0.00	Peak	100	189	VERTICAL		
3	2443.41	111.93			81.40	2.24	28.29	0.00	Average	100	189	VERTICAL		
4	2443.41	123.28			92.75	2.24	28.29	0.00	Peak	100	189	VERTICAL		
5	2483.50	49.67	54.00	-4.33	19.04	2.26	28.37	0.00	Average	100	189	VERTICAL		
6	2485.10	61.70	74.00	-12.30	31.03	2.26	28.41	0.00	Peak	100	189	VERTICAL		

Item 3, 4 are the fundamental frequency at 2437 MHz.


### Channel 11

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
1	2457.51	107.15			76.58	2.24	28.33	0.00	Average	100	166	VERTICAL		
2	2457.67	118.82			88.25	2.24	28.33	0.00	Peak	100	166	VERTICAL		
3	2483.50	53.63	54.00	-0.37	23.00	2.26	28.37	0.00	Average	100	166	VERTICAL		
4	2483.50	69.54	74.00	-4.46	38.91	2.26	28.37	0.00	Peak	100	166	VERTICAL		


Item 1, 2 are the fundamental frequency at 2462 MHz.

**For Emission not in Restricted Band**
**Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level**



Date: 17.MAY.2013 14:42:29

**Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 / 30MHz~2400MHz (down 30dBc)**


Date: 17.MAY.2013 14:43:10


**Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 / 2500MHz~26500MHz (down 30dBc)**


Date: 17.MAY.2013 14:43:34

**Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 30MHz~2400MHz (down 30dBc)**



Date: 17.MAY.2013 14:44:32

### Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 2500MHz~26500MHz (down 30dBc)






Date: 17.MAY.2013 14:44:09

### Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level




Date: 17.MAY.2013 14:47:35


**Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 30MHz~2400MHz (down 30dBc)**

**Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 2500MHz~26500MHz (down 30dBc)**


**Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 30MHz~2400MHz (down 30dBc)**



Date: 17.MAY.2013 14:49:53

**Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 2500MHz~26500MHz (down 30dBc)**



Date: 17.MAY.2013 14:49:28

**Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level**



Date: 17.MAY.2013 15:01:11

**Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 30MHz~5725MHz (down 30dBc)**



Date: 17.MAY.2013 15:01:37

**Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 5850MHz~40000MHz (down 30dBc)**



Date: 17.MAY.2013 15:02:13

**Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 30MHz~5725MHz (down 30dBc)**



Date: 17.MAY.2013 15:03:07

**Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 5850MHz~40000MHz (down 30dBc)**



Date: 17.MAY.2013 15:02:46

**Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level**



Date: 17.MAY.2013 15:04:45

**Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 30MHz~5725MHz (down 30dBc)**



Date: 17.MAY.2013 15:05:22

**Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 5850MHz~40000MHz (down 30dBc)**


Date: 17.MAY.2013 15:05:47


**Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 30MHz~5725MHz (down 30dBc)**


Date: 17.MAY.2013 15:06:50

**Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 5850MHz~40000MHz (down 30dBc)**



Date: 17.MAY.2013 15:06:17

### Plot on Configuration IEEE 802.11b / Reference Level




Date: 17.MAY.2013 14:31:56


### Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)



Date: 17.MAY.2013 14:32:48


**Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)**


Date: 17.MAY.2013 14:33:28

**Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)**



Date: 17.MAY.2013 14:34:35

### Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 17.MAY.2013 14:34:09

### Plot on Configuration IEEE 802.11g / Reference Level




Date: 17.MAY.2013 14:47:35

**Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)**




Date: 17.MAY.2013 14:37:54

**Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)**




Date: 17.MAY.2013 14:38:19

### Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 17.MAY.2013 14:39:27

### Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 17.MAY.2013 14:39:00

### Plot on Configuration IEEE 802.11a / Reference Level




Date: 17.MAY.2013 14:55:12

### Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 17.MAY.2013 14:55:54

**Plot on Configuration IEEE 802.11a / CH 149 / 5850MHz~40000MHz (down 30dBc)**




Date: 17.MAY.2013 14:56:48

**Plot on Configuration IEEE 802.11a / CH 165 / 30MHz~5725MHz (down 30dBc)**



Date: 17.MAY.2013 14:57:50

**Plot on Configuration IEEE 802.11a / CH 165 / 5850MHz~40000MHz (down 30dBc)**



Date: 17.MAY.2013 14:57:29

## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an Chain with extension cable. An intentional radiator shall be designed to ensure that no Chain other than that furnished by the responsible party shall be used with the device. The use of a permanently attached Chain or of an Chain that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken Chain, but the use of a standard Chain jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.7.2. Chain Connector Construction

Please refer to section 3.3 in this test report; Chain connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 21, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 04, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG Antenna	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Apr. 15, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Chain Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

\*\* Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085