

14. Maximum Permissible Exposure (MPE)

Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section Part 22, subpart H and Part 24, subpart E of the FCC CFR 47 Rules. And RSS-102 issue 4 For 47 CFR 1.1310 Radio frequency Radiation Exposure requirement.

Special Accessories

Not available for this EUT intended for grant.

Equipment Modifications

Not available for this EUT intended for grant.

Limitation

4011				
Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm^2)	(minute)
	Limits for General	Population/Uncontr	olled Exposure	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	$*(180/f^2)$	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	1500-15000 /		1.0	30

F = frequency in MHz

^{* =} Plane-wave equipment power density

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m²)	Averaging Time (minutes)
0.003-1	280	2.19	-	6
1-10	280/f	2.19/f	-	6
10-30	28	2.19/f	-	6
30-300	28	0.073	2*	6
300-1500	1.585 f 0.5	0.0042 f 0.5	f/150	6
1500-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/f ^{1.2}
150000-300000	$0.158 f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	6.67 x 10 ⁻⁵ f	616000/f 1.2

Note: f is frequency in MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

Power density limit is applicable at frequencies greater than 100 MHz.



Maximum Permissible Exposure (MPE) Evaluation

In this application we seek approval to the VTC6110-ATT4. Based on the FCC OET Bulletin 65 Supplement C and 47 CFR §2.1091, we have concluded that the MC55i module will comply with the FCC rules on RF exposure for mobile devices in cellular band and PCS band. The following analysis will demonstrate such compliance. The analysis will be done in two US bands.

Operation in cellular band (824 – 849 MHz)

The ERP of VTC6110-ATT4 in cellular band is 22.16dBm max at GSM/GPRS mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
	824.20	1013	Н	V	20.13	3.96	-4.22	19.87	38.45
	824.20	1013	Н	Н	22.42	3.96	-4.22	22.16	38.45
GPRS 850	836.60	201	П	V	19.18	4.00	-4.24	18.94	38.45
GPKS 650	830.00	384	Н	Н	21.99	4.00	-4.24	21.75	38.45
	949 90	777	Н	V	20.03	4.03	-4.33	19.73	38.45
	848.80			Н	20.37	4.03	-4.33	20.07	38.45

ERP = 22.16 dBm = 164.43 mW
Power Density = ERP*Duty Cycle/
$$(4 R^2)$$

=164.43*0.25/ $(4* *20^2)$ = 0.0082 mW/cm²

where Duty Cycle is 0.25 for GPRS operation (class 10) and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit =
$$824/1500 = 0.55 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in cellular band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



The EIRP of VTC6110-ATT4 in PCS band is 26.69 dBm. max. The resulted EIRP can be expressed as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.		S.G. Output (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
	1850.20	512	Н	V	28.01	4.17	-5.49	26.69	33.00
	1630.20	512	Н	Н	21.24	4.51	-5.49	20.26	33.00
GPRS 1900	1880.00	661	11	V	25.79	4.13	-5.56	24.36	33.00
GPRS 1900	1000.00	661	Н	Н	19.93	4.44	-5.56	18.80	33.00
	1000.90	810	Н	V	26.41	4.10	-5.56	24.95	33.00
	1909.80			Н	18.25	4.36	-5.56	17.06	33.00

EIRP = 26.69 dBm = 466.65 mWPower Density = EIRP*Duty Cycle/ $(4 R^2)$ $=466.65*0.25/(4* *20^2) = 0.0232 \text{ mW/cm}^2$

where Duty Cycle is 0.25 for GPRS operation (class 10) and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:


MPE limit = 1.0 mW/cm^2

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in PCS band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
	1852.40	0262	E2	V	24.65	4.17	-5.49	23.34	33.00
	1852.40	9262	E2	Н	17.81	4.51	-5.49	16.83	33.00
HCDDA H	1000.00	9400	E2	V	23.83	4.14	-5.56	22.41	33.00
HSDPA II	1880.00			Н	17.60	4.44	-5.56	16.47	33.00
	1007.60	9538	E2	V	23.90	4.10	-5.62	22.38	33.00
	1907.60			Н	14.95	4.37	-5.62	13.70	33.00

EIRP =
$$23.34dBm = 215.77 \text{ mW}$$

Power Density = EIRP*Duty Cycle/ $(4 R^2)$
= $215.77*1/(4* *20^2) = 0.0429 \text{ mW/cm}^2$

Where Duty Cycle is 1 for HSDPA Band 2 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit = 1.0 mW/cm^2

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in cellular band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Operation in cellular band (826.40–846.60 MHz)

The ERP of VTC6110-ATT4 in cellular band is 16.04dBm max at HSDPA Band 5 mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
	926.40	4122	E2	V	14.16	3.97	-4.22	13.91	38.45
826.40	820.40	4132	E2	Н	16.30	3.97	-4.22	16.04	38.45
HSDPA V	836.60	1102		V	12.88	4.00	-4.24	12.64	38.45
I I SDFA V	830.00	4183	E2	Н	15.94	4.00	-4.24	15.70	38.45
84	946 60	4233	E2	V	14.10	4.02	-4.24	13.89	38.45
	846.60			Н	13.89	4.02	-4.24	13.67	38.45

$$\begin{split} ERP &= 16.04 dBm = 40.17 \ mW \\ Power Density &= EIRP*Duty \ Cycle/(4 \ R^2) \\ &= 40.17*1/(4* \ *20^2) = 0.00799 \ mW/cm^2 \end{split}$$

where Duty Cycle is 1 for HSDPA Band 5 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit =826.40/1500=0.55093mW/cm²

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in cellular band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Operation in LTE band (1712.5 – 1752.5 MHz)

The EIRP of VTC6110-ATT4 in LTE band 4 5MHz /QPSK/RB 1 is 20.69dBm max at LTE mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
	1510.5		E2	V	18.83	4.39	-5.40	17.82	30.00
5MHz BW	1712.5	19975	E2	Н	16.68	4.79	-5.40	16.07	30.00
LTE-Band 4	1732.5	20175		V	18.94	4.35	-5.42	17.86	30.00
(QPSK RB	1732.3	20175	E2	Н	17.97	4.78	-5.42	17.33	30.00
1 Offset 24)	′	20375	E2	V	21.82	4.31	-5.44	20.69	30.00
	1752.5			Н	18.21	4.76	-5.44	17.53	30.00

$$\begin{split} EIRP &= 20.69 dBm = 117.22 mW \\ Power Density &= ERP*Duty Cycle/(4 R^2) \\ &= 117.22*1/(4* *20^2) = 0.02332 \ mW/cm^2 \end{split}$$

where Duty Cycle is 1 for LTE band 4 5MHz /QPSK/RB 1 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit = 1.0 mW/cm^2

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in cellular band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Operation in LTE band (1712.5 – 1752.5 MHz)

The EIRP of VTC6110-ATT4 in LTE band 4 5MHz /16QAM/RB 1 band is 24.82dBm. max. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
			EO	V	25.33	4.39	-5.40	24.32	30.00
5MHz BW	1712.5	19975	E2	Н	23.15	4.79	-5.40	22.54	30.00
LTE-Band 4	1722.5	20175		V	25.90	4.35	-5.42	24.82	30.00
(16QAM RB 1 Offset	1732.5	20175	E2	Н	22.62	4.78	-5.42	21.98	30.00
24)))	20375	E2	V	23.46	4.31	-5.44	22.33	30.00
				Н	22.30	4.76	-5.44	21.63	30.00

EIRP = 23.34 dBm = 303.39 mW
Power Density = EIRP*Duty Cycle/(4
$$R^2$$
)
=303.39*1/(4* *20²) = 0.0604mW/cm²

where Duty Cycle is 1 for LTE band 4 5MHz /16QAM/RB 1 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit =
$$1.0 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in PCS band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



The EIRP of VTC6110-ATT4 LTE band 14 10MHz /QPSK/RB 1 band is 21.05 dBm. max. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
	1515	•	E2	V	18.81	4.38	-5.40	17.79	30.00
10MHz BW	1715	20000	E2	Н	17.14	4.79	-5.40	16.53	30.00
LTE-Band 4	1732.5	20175		V	19.06	4.34	-5.42	17.98	30.00
(QPSK RB 1	1/32.3	20173	E2	Н	17.61	4.78	-5.42	16.96	30.00
Offset 49)	1750	20350		V	22.18	4.31	-5.44	21.05	30.00
	1730	20330	E2	Н	21.47	4.76	-5.44	20.79	30.00

EIRP = 21.05dBm = 127.35mWPower Density = ERP*Duty Cycle/ $(4 R^2)$ $=127.35*1/(4* *20^2) = 0.02534 \text{ mW/cm}^2$

where Duty Cycle is 1 for LTE band 14 10MHz /QPSK/RB 1 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit = 1.0 mW/cm^2

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in LTE band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



The EIRP of VTC6110-ATT4 in LTE band 4 10MHz /16QAM/RB 1 is 23.95 dBm max at LTE mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
	1515	20000	E2	V	24.97	4.38	-5.40	23.95	30.00
10MHz BW	1715	20000	E2	Н	22.39	4.79	-5.40	21.78	30.00
LTE-Band 4	1722 5	20175		V	24.69	4.34	-5.42	23.61	30.00
(16QAM RB	1732.5	20175	E2	Н	21.41	4.78	-5.42	20.76	30.00
1 Offset 49)	1750	20350		V	23.10	4.31	-5.44	21.97	30.00
	1730	20330	E2	Н	22.49	4.76	-5.44	21.81	30.00

EIRP = 23.95dBm = 248.31mWPower Density = ERP*Duty Cycle/ $(4 R^2)$ $=248.31*1/(4* *20^2) = 0.0494 \text{ mW/cm}^2$

where Duty Cycle is 1 for LTE band 4 10MHz /16QAM/RB 1 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit = 1.0 mW/cm^2

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in LTE band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKunqRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com

台灣檢驗科技股份有限公司

f (886-2) 2298-0488



The ERP of VTC6110-ATT4 in LTE band 17 5MHz/QPSK/RB 1 is 15.36dBm max at LTE mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
	706.5	2277	E2	V	13.87	4.10	-3.98	13.98	34.70
5MHz BW	706.5	23755	E2	Н	13.40	4.10	-3.98	13.52	34.70
LTE-Band 17	710	23790	F-2	V	15.08	4.05	-3.98	15.15	34.70
(QPSK RB 1	710	23190	E2	Н	13.81	4.05	-3.98	13.88	34.70
Offset 24)	713.5	23825	F-2	V	15.34	4.01	-3.98	15.36	34.70
	/13.3	23825	E2	Н	14.15	4.01	-3.98	14.18	34.70

ERP =
$$15.36$$
dBm = 34.36 mW
Power Density = ERP*Duty Cycle/(4 R²)
= $34.36*1/(4* *20^2) = 0.00684$ mW/cm²

where Duty Cycle is 1 for LTE band 17 5MHz /QPSK/RB 1 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit = $706.5/1500=0.471 \text{ mW/cm}^2$

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in LTE band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



The ERP of VTC6110-ATT4 in LTE band 17 5MHz /16QAM/RB 1 is 15.86dBm max at LTE mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
	706.5	2277	E2	V	15.80	4.05	-3.98	15.86	34.70
5MHz BW	706.5	23755	E2	Н	14.40	4.04	-3.98	14.45	34.70
LTE-Band 17	710	23790		V	15.77	4.00	-3.98	15.79	34.70
(16 QAM RB		23790	E2	Н	14.77	4.00	-3.98	14.78	34.70
1 Offset 24)	713.5	22825		V	15.14	3.95	-3.98	15.11	34.70
	/13.3	23825	E2	Н	14.33	3.95	-3.98	14.30	34.70

ERP = 15.86dBm = 38.55mWPower Density = ERP*Duty Cycle/ $(4 R^2)$ $=38.55*1/(4* *20^2) = 0.00767 \text{ mW/cm}^2$

where Duty Cycle is 1 for LTE band 17 5MHz /16QAM/RB 1 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit =706.5/1500=0.471mW/cm²

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in LTE band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKunqRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279

台灣檢驗科技股份有限公司

f (886-2) 2298-0488 www.tw.sgs.com Member of SGS Group



Operation in LTE band (709 – 711 MHz)

The ERP of VTC6110-ATT4 in LTE band 17 10MHz/QPSK/RB 1 is 16.30dBm max at LTE mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
	709	23780	E2	V	15.14	3.98	-3.98	15.14	34.70
10MHz BW				Н	14.06	3.98	-3.98	14.06	34.70
LTE-Band 17	710	23790	E2	V	16.31	3.97	-3.98	16.30	34.70
(16 QPSK RB				Н	14.20	3.97	-3.98	14.19	34.70
1 Offset 49)	711	23800	E2	V	15.25	3.95	-3.98	15.22	34.70
				Н	14.39	3.96	-3.98	14.37	34.70

$$\begin{split} ERP &= 16.30 dBm = 42.66 mW \\ Power Density &= ERP*Duty Cycle/(4 R^2) \\ &= 42.66*1/(4* *20^2) = 0.00849 \ mW/cm^2 \end{split}$$

where Duty Cycle is 1 for LTE band 17 10MHz /QPSK/RB 1 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit =709/1500=0.473 mW/cm²

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in cellular band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

GS Taiwan Ltd.



The ERP of VTC6110-ATT4 in LTE band 17 10MHz/16QAM/RB 1 is 16.17dBm max at LTE mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT Mode	Frequency (MHz)	СН	EUT Pol.	Antenna Pol.	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
	709	23780	E2	V	16.17	3.98	-3.98	16.17	34.70
10MHz BW				Н	15.07	3.98	-3.98	15.07	34.70
LTE-Band 17	710	23790	E2	V	15.78	3.97	-3.98	15.77	34.70
(16 QPSK RB				Н	14.31	3.97	-3.98	14.30	34.70
1 Offset 49)	711	23800	E2	V	15.80	3.96	-3.98	15.77	34.70
				Н	14.40	3.96	-3.98	14.38	34.70

ERP = 16.17dBm = 41.40mWPower Density = ERP*Duty Cycle/ $(4 R^2)$ $=41.40*1/(4* *20^2) = 0.00824 \text{ mW/cm}^2$

where Duty Cycle is 1 for LTE band 17 10MHz /16QAM/RB 1 operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

MPE limit =709/1500=0.473 mW/cm²

As we can see the resulted power density is below the MPE limit, therefore VTC6110-ATT4 in cellular band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.