

# **FCC SAR Test Report**

APPLICANT : CT Asia

**EQUIPMENT**: **GSM** mobile phone

BRAND NAME : ACE

MODEL NAME : Caracas Pro

FCC ID : YHLACECCSPR

STANDARD : FCC 47 CFR Part 2 (2.1093)

IEEE C95.1-1991 IEEE 1528-2003

FCC OET Bulletin 65 Supplement C (Edition 01-01)

The product was received on Dec. 13, 2011 and completely tested on Dec. 29, 2011. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:

ilac-MRA



Jones Tsai / Manager

SPORTON INTERNATIONAL (KUNSHAN) INC. No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 1 of 34
Report Issued Date : Jan. 10, 2012

# **Table of Contents**

1. Statement of Compliance	
2. Administration Data	
2.1 Testing Laboratory	
2.2 Applicant	5
2.3 Manufacturer	
2.4 Application Details	5
3. General Information	6
3.1 Description of Device Under Test (DUT)	6
3.2 Product Photos	7
3.3 Applied Standards	
3.4 Device Category and SAR Limits	7
3.5 Test Conditions	
4. Specific Absorption Rate (SAR)	
4.1 Introduction	
4.2 SAR Definition	
5. SAR Measurement System	
5.1 E-Field Probe	
5.2 Data Acquisition Electronics (DAE)	
5.3 Robot	
5.4 Measurement Server	
5.5 Phantom	
5.6 Device Holder	
5.7 Data Storage and Evaluation	
5.8 Test Equipment List	16
6. Tissue Simulating Liquids	
7. Uncertainty Assessment	
8. SAR Measurement Evaluation	
8.1 Purpose of System Performance check	
8.2 System Setup	
8.3 Validation Results	
9. DUT Testing Position	
10. Measurement Procedures	
10.1 Spatial Peak SAR Evaluation	26
10.2 Area & Zoom Scan Procedures	
10.3 Volume Scan Procedures	
10.4 SAR Averaged Methods	
10.5 Power Drift Monitoring	
11. SAR Test Configurations	
12. SAR Test Results	
12.1 Conducted Power (Unit: dBm)	
12.2 Test Records for Head SAR Test	32
12.3 Test Records for Body-worn SAR Test	33
12.4 Simultaneous Multi-band Transmission	
13. References	34

Appendix A. Plots of System Performance Check

Appendix B. Plots of SAR Measurement Appendix C. DASY Calibration Certificate

**Appendix D. Product Photos** 

**Appendix E. Test Setup Photos** 

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Report Issued Date: Jan. 10, 2012 : Rev. 01

Report Version



# **Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA1D1302	Rev. 01	Initial issue of report	Jan. 10, 2012

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR

: 3 of 34 Page Number Report Issued Date: Jan. 10, 2012 Report Version : Rev. 01



# 1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for CT Asia GSM mobile phone ACE Caracas Pro are as follows.

#### <Standalone SAR>

Band	Position	SAR <sub>1g</sub> (W/kg)
COMOSO	Head	0.304
GSM850	Body-worn (1.5 cm Gap)	0.292
CSM4000	Head	0.567
GSM1900	Body-worn (1.5 cm Gap)	0.455
000 44 h/m	Head	0.058
802.11 b/g	Body-worn (1.5 cm Gap)	0.037

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1991, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003 and FCC OET Bulletin 65 Supplement C (Edition 01-01).

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR

: 4 of 34 Page Number Report Issued Date: Jan. 10, 2012



# 2. Administration Data

# 2.1 Testing Laboratory

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	

# 2.2 Applicant

Company Name	CT Asia
Address	RMA2011, 20/F, GOLDEN CENTRAL TOWER, NO.3037# JINTIAN ROAD,
	FUTIAN DISTRICT

# 2.3 Manufacturer

Company Name	Shenzhen Sanmeng Communication Technolo GY CO., LTD	
	1503, Blk. East, Shengtang Bldg. Tairan 9th Road, Chegongmiao, Futian District, Shenzhen, Guangdong	

# 2.4 Application Details

Date of Receipt of Application	Dec. 13, 2011
Date of Start during the Test	Dec. 15, 2011
Date of End during the Test	Dec. 29, 2011

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 5 of 34
Report Issued Date : Jan. 10, 2012

Report No. : FA1D1302



3. General Information

### 3.1 Description of Device Under Test (DUT)

	Product Feature & Specification
DUT Type	GSM mobile phone
Brand Name	ACE
Model Name	Caracas Pro
FCC ID	YHLACECCSPR
	GSM850: 824 MHz ~ 849 MHz
Tx Frequency	GSM1900: 1850 MHz ~ 1910 MHz 802.11b/g : 2400 MHz ~ 2483.5 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869 MHz ~ 894 MHz GSM1900: 1930 MHz ~ 1990 MHz 802.11b/g: 2400 MHz ~ 2483.5 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Maximum Output Power to Antenna	GSM850: 32.39 dBm GSM1900: 30.10 dBm 802.11b: 15.31 dBm 802.11g: 20.25 dBm Bluetooth: 9.84 dBm
Antenna Type	WWAN : Fixed Internal Antenna WLAN : PIFA Antenna Bluetooth : Dipole Antenna
HW Version	HEXING36 10A GEMINI HW
SW Version	E200_BLU_LEN_BT_FM_FL_SC_004_V017
Type of Modulation	GSM / GPRS : GMSK 802.11b : DSSS (BPSK / QPSK / CCK) 802.11g : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π/4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
Dual Transfer Mode	Class B – DUT cannot support Packet Switched and Circuit Switched Network simultaneously
(DTM) Category	but can automatically switch between Packet and Circuit Switched Network.
DUT Stage	Identical Prototype
Remark: The above DU manual for more detailed	T's information was declared by manufacturer. Please refer to the specifications or user's

#### Remark:

- 1. DTM Mode not supported.
- 2. The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 3. There are two different types of EUT. They are single SIM card mobile and dual SIM card mobile. The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we choose dual SIM card mobile to perform all test. For the dual SIM card mobile, after pre-scan two SIM cards, we found test result with SIM1 card was the worst, so we choose SIM1 card to perform all test.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 6 of 34

Report Issued Date : Jan. 10, 2012

Report Version : Rev. 01

#### 3.2 Product Photos

Please refer to Appendix D.

#### 3.3 Applied Standards

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- IEEE C95.1-1991
- IEEE 1528-2003
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- FCC KDB 447498 D01 v04
- FCC KDB 648474 D01 v01r05
- FCC KDB 941225 D03 v01
- FCC KDB 248227 D01 v01r02

### 3.4 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

### 3.5 Test Conditions

#### 3.5.1 Ambient Condition

Ambient Temperature	20 to 24 $^{\circ}\mathrm{C}$
Humidity	< 60 %

#### 3.5.2 Test Configuration

The device was controlled by using a base station emulator. Communication between the device and the emulator was established by air link. The distance between the DUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of DUT. The DUT was set from the emulator to radiate maximum output power during all tests.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 7 of 34

Report Issued Date : Jan. 10, 2012

Report Version : Rev. 01



# 4. Specific Absorption Rate (SAR)

#### 4.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

#### 4.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C\left(\frac{\delta T}{\delta t}\right)$$

Where: C is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 8 of 34
Report Issued Date : Jan. 10, 2012

Report No.: FA1D1302



# 5. SAR Measurement System




Fig 5.1 SPEAG DASY4 or DASY5 System Configurations

The DASY4 or DASY5 system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- > The electro-optical converter (ECO) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- > A computer operating Windows XP
- DASY4 or DASY5 software
- > Remove control with teach pendant and additional circuitry for robot safety such as warming lamps, etc.
- The SAM twin phantom
- A device holder
- > Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Some of the components are described in details in the following sub-sections.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 9 of 34
Report Issued Date : Jan. 10, 2012

Report No.: FA1D1302



#### 5.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

#### 5.1.1 E-Field Probe Specification

#### <EX3DV4 Probe>

~EX3DV4 PIODE>			_
Construction	Symmetrical design with triangular core		
	Built-in shielding against static charges		
	PEEK enclosure material (resistant to		
	organic solvents, e.g., DGBE)		The second secon
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB		
Directivity	± 0.3 dB in HSL (rotation around probe		
	axis)		
	± 0.5 dB in tissue material (rotation		30
	normal to probe axis)		
Dynamic Range	10 μW/g to 100 mW/g; Linearity: ± 0.2 dB		
	(noise: typically < 1 μW/g)		
Dimensions	Overall length: 330 mm (Tip: 20 mm)		
	Tip diameter: 2.5 mm (Body: 12 mm)		
	Typical distance from probe tip to dipole		
	centers: 1 mm		
			T
			* -
		Fig 5.2	Photo of EX3DV4
		1 19 3.2	I HOLO OI EXODYT

#### 5.1.2 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm$  10%. The spherical isotropy shall be evaluated and within  $\pm$  0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

# 5.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Report No.: FA1D1302

Fig 5.3 Photo of DAE

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 10 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01



### 5.3 Robot

The SPEAG DASY system uses the high precision robots (DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- ➤ High precision (repeatability ±0.035 mm)
- High reliability (industrial design)
- > Jerk-free straight movements
- > Low ELF interference (the closed metallic construction shields against motor control fields)



Fig 5.4 Photo of DASY5

#### 5.4 Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5: 128 MB), RAM (DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Fig 5.5 Photo of Server for DASY5

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 11 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01

#### 5.5 Phantom

#### <SAM Twin Phantom>

2 ± 0.2 mm;	
Center ear point: 6 ± 0.2 mm	
Approx. 25 liters	The state of the s
Length: 1000 mm; Width: 500 mm;	
Height: adjustable feet	<u> </u>
Left Hand, Right Hand, Flat Phantom	
	EL EO DI 1 COMBI
	Fig 5.6 Photo of SAM Phantom
	Center ear point: 6 ± 0.2 mm  Approx. 25 liters  Length: 1000 mm; Width: 500 mm;  Height: adjustable feet

Report No.: FA1D1302

: 12 of 34

: Rev. 01

Report Issued Date: Jan. 10, 2012

Page Number

Report Version

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

#### <ELI4 Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	W/ 100 100 100 100 100 100 100 100 100 10
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	Fig 5.7 Photo of ELI4 Phantom

The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR



#### 5.6 <u>Device Holder</u>

### <Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\varepsilon = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Fig 5.8 **Device Holder** 

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 13 of 34 Report Issued Date: Jan. 10, 2012

#### 5.7 Data Storage and Evaluation

### 5.7.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

#### 5.7.2 Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

**Probe parameters**: - Sensitivity Norm<sub>i</sub>, a<sub>i0</sub>, a<sub>i1</sub>, a<sub>i2</sub>

Conversion factor ConvF<sub>i</sub>
 Diode compression point dcp<sub>i</sub>

**Device parameters**: - Frequency f

- Density ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 14 of 34
Report Issued Date : Jan. 10, 2012

Report No.: FA1D1302

The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Report No.: FA1D1302

with  $V_i$  = compensated signal of channel i, (i = x, y, z)

 $U_i$  = input signal of channel i, (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp<sub>i</sub> = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated:

$$\text{E-field Probes}: E_i = \sqrt{\frac{v_i}{\text{Norm}_i\text{-ConvF}}}$$

H-field Probes : 
$$H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with  $V_i$  = compensated signal of channel i, (i = x, y, z)

Norm<sub>i</sub> = sensor sensitivity of channel i, (i = x, y, z),  $\mu V/(V/m)^2$  for E-field Probes

ConvF = sensitivity enhancement in solution

a<sub>ij</sub> = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E<sub>i</sub> = electric field strength of channel i in V/m

H<sub>i</sub> = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g

 $E_{tot}$  = total field strength in V/m

 $\sigma$  = conductivity in [mho/m] or [Siemens/m]

ρ = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

Page Number

Report Version

: 15 of 34

: Rev. 01

Report Issued Date: Jan. 10, 2012



### 5.8 Test Equipment List

Manufacturer	Name of Equipment	Type/Madel	Serial Number	Calib	ration
Wanuracturer	Name of Equipment	Type/Model	Serial Number	Last Cal.	Due Date
SPEAG	Dosimetric E-Field Probe	EX3DV4	3697	Sep. 02, 2011	Sep. 01, 2012
SPEAG	Data Acquisition Electronics	DAE4	1210	Nov. 18, 2011	Nov. 17, 2012
SPEAG	835MHz System Validation Kit	D835V2	499	Mar. 22, 2010	Mar. 21, 2012
SPEAG	1900MHz System Validation Kit	D1900V2	5d142	Jul. 22, 2011	Jul. 21, 2012
SPEAG	2450MHz System Validation Kit	D2450V2	840	Mar. 18, 2010	Mar. 17, 2012
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1477	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1479	NCR	NCR
Agilent	ENA Series Network Analyzer	E5071C	MY46111157	Apr. 07, 2011	Apr. 06, 2012
Agilent	Wireless Communication Test Set	E5515C	MY50264165	Mar. 30, 2011	Mar. 29, 2012
Agilent	Dielectric Probe Kit	85070E	MY44300475	NCR	NCR
Agilent	Base Station	E5515C	GB47050646	Aug. 18, 2011	Aug. 17, 2012
AR	Amplifier	551G4	333096	NCR	NCR
R&S	Spectrum Analyzer	FSP30	101400	Jun. 02, 2011	Jun. 01, 2012
R&S	Signal Generator	SMR40	100455	Jan. 06, 2011	Jan. 05, 2012

**Table 5.1 Test Equipment List** 

#### Note:

- 1. The calibration certificate of DASY can be referred to appendix C of this report.
- 2. Referring to KDB450824 D02, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
- The justification data of dipole D835V2, SN: 499, D2450V2, SN: 840 can be found in appendix C. 3. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR

: 16 of 34 Page Number Report Issued Date: Jan. 10, 2012

Report No. : FA1D1302

: Rev. 01 Report Version



# 6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.





Fig 6.1 Photo of Liquid Height for Head SAR

Fig 6.2 Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency	Water	Sugar	Cellulose	Salt	Preventol	DGBE	Conductivity	Permittivity		
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	(σ)	(ε <sub>r</sub> )		
For Head										
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5		
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0		
2450	55.0	0	0	0	0	45.0	1.80	39.2		
				For Body						
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2		
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3		
2450	68.6	0	0	0	0	31.4	1.95	52.7		

Table 6.1 Recipes of Tissue Simulating Liquid

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 17 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

The following table shows the measuring results for simulating liquid.

Freq.	Liquid Type	Temp. (°C)	Conductivity (σ)	Permittivity (ε <sub>r</sub> )	Conductivity Target (σ)	Permittivity Target $(\epsilon_r)$	Delta (σ) (%)	Delta (ε <sub>r</sub> ) (%)	Limit (%)	Date
835	Head	21.5	0.903	41.606	0.9	41.5	0.33	0.26	±5	Dec. 15, 2011
1900	Head	21.3	1.427	41.191	1.4	40.0	1.93	2.98	±5	Dec. 15, 2011
2450	Head	21.4	1.834	39.654	1.8	39.2	1.89	1.16	±5	Dec. 29, 2011
835	Body	21.2	0.977	54.395	0.97	55.2	0.72	-1.46	±5	Dec. 15, 2011
1900	Body	21.1	1.535	54.565	1.52	53.3	0.99	2.37	±5	Dec. 15, 2011
2450	Body	21.2	1.976	54.13	1.95	52.7	1.33	2.71	±5	Dec. 29, 2011

Table 6.2 Measuring Results for Simulating Liquid

СН	Frequency (MHz)	Liquid Type	Conductivity (σ)	Permittivity $(\epsilon_r)$	Conductivity Target (σ)	Permittivity Target (ε <sub>r</sub> )	Conductivity delta (%) (σ)	Permittivity delta (%) (ε <sub>r</sub> )	Measurement Date
251	848.8	Head	0.917	41.426	0.90	41.6	1.89	-0.42	Dec. 15, 2011
512	1850.2	Head	1.365	41.266	1.39	40.0	-1.80	3.17	Dec. 15, 2011
1	2412	Head	1.791	39.777	1.76	39.2	1.76	1.47	Dec. 29, 2011
128	824.2	Body	0.967	54.473	0.97	55.2	-0.31	-1.32	Dec. 15, 2011
512	1850.2	Body	1.472	54.669	1.51	53.3	-2.52	2.57	Dec. 15, 2011
1	2412	Body	1.906	54.182	1.9	52.7	0.32	2.81	Dec. 29, 2011

Table 6.3 Low/mid/High channel for liquid validation

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 18 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01

### 7. Uncertainty Assessment

The component of uncertainly may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainly by the statistical analysis of a series of observations is termed a Type An evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 7.1

<b>Uncertainty Distributions</b>	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor <sup>(a)</sup>	1/k <sup>(b)</sup>	1/√3	1/√6	1/√2

<sup>(</sup>a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b)  $\kappa$  is the coverage factor

**Table 7.1 Standard Uncertainty for Assumed Distribution** 

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is showed in Table 7.2.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 19 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01

a B	FCC SAR Test Repor
	1 00 OAK TEST KEPOT

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Standard Uncertainty (1g)				
Measurement System	Measurement System								
Probe Calibration	6.0	Normal	1	1	± 6.0 %				
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %				
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %				
Boundary Effects	1.0	Rectangular	√3	1	± 0.6 %				
Linearity	4.7	Rectangular	√3	1	± 2.7 %				
System Detection Limits	1.0	Rectangular	√3	1	± 0.6 %				
Readout Electronics	0.3	Normal	1	1	± 0.3 %				
Response Time	0.8	Rectangular	√3	1	± 0.5 %				
Integration Time	2.6	Rectangular	√3	1	± 1.5 %				
RF Ambient Noise	3.0	Rectangular	√3	1	± 1.7 %				
RF Ambient Reflections	3.0	Rectangular	√3	1	± 1.7 %				
Probe Positioner	0.4	Rectangular	√3	1	± 0.2 %				
Probe Positioning	2.9	Rectangular	√3	1	± 1.7 %				
Max. SAR Eval.	1.0	Rectangular	√3	1	± 0.6 %				
Test Sample Related									
Device Positioning	2.9	Normal	1	1	± 2.9 %				
Device Holder	3.6	Normal	1	1	± 3.6 %				
Power Drift	5.0	Rectangular	√3	1	± 2.9 %				
Phantom and Setup									
Phantom Uncertainty	4.0	Rectangular	√3	1	± 2.3 %				
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	± 1.8 %				
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	± 1.6 %				
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	± 1.7 %				
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	± 1.5 %				
Combined Standard Uncertainty									
Coverage Factor for 95 %									
Expanded Uncertainty									

Table 7.2 Uncertainty Budget of DASY for frequency range 300 MHz to 3 GHz

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 20 of 34 Report Issued Date: Jan. 10, 2012

Report No. : FA1D1302



# 8. SAR Measurement Evaluation

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

### 8.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

#### 8.2 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig 8.1 System Setup for System Evaluation

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 21 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01



- 1. Signal Generator
- 2. Amplifier
- 3. Directional Coupler
- 4. Power Meter
- 5. Calibrated Dipole

The output power on dipole port must be calibrated to 24 dBm (250 mW) before dipole is connected.



Fig 8.2 Photo of Dipole Setup

# 8.3 Validation Results

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %. Table 8.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Measurement Date	Frequency (MHz)	Liquid Type	Targeted SAR <sub>1g</sub> (W/kg)	Measured SAR <sub>1g</sub> (W/kg)	Normalized SAR <sub>1g</sub> (W/kg)	Deviation (%)
Dec. 15, 2011	835	Head	9.71	2.25	9.00	-7.31
Dec. 15, 2011	1900	Head	39.4	10.1	40.40	2.54
Dec. 29, 2011	2450	Head	52.7	14.2	56.80	7.78
Dec. 15, 2011	835	Body	9.82	2.37	9.48	-3.46
Dec. 15, 2011	1900	Body	40.5	10.1	40.40	-0.25
Dec. 29, 2011	2450	Body	52.1	13.7	54.80	5.18

**Table 8.1 Target and Measurement SAR after Normalized** 

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 22 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01



# 9. <u>DUT Testing Position</u>

This DUT was tested in six different positions. They are right cheek, right tilted, and left cheek, left tilted, Face of the DUT with phantom 1.5 cm gap, Bottom of the DUT with phantom 1.5 cm gap, as illustrated below:

#### 1. Define two imaginary lines on the handset

- (a) The vertical centerline passes through two points on the front side of the handset the midpoint of the width w<sub>t</sub> of the handset at the level of the acoustic output, and the midpoint of the width w<sub>b</sub> of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig 9.1 Illustration for Handset Vertical and Horizontal Reference Lines

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 23 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01



#### 2. Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 9.2).




Fig 9.2 Illustration for Cheek Position

#### 3. Tilted Position

- (a) To position the device in the "cheek" position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 9.3).




Fig 9.3 Illustration for Tilted Position

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 24 of 34 Report Issued Date : Jan. 10, 2012



### 4. Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.5 cm.




Fig 9.4 Illustration for Body Worn Position

#### <DUT Setup Photos>

Please refer to Appendix E for the test setup photos.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 25 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01

# 10. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station or engineering software (if applicable) to transmit RF power continuously (continuous Tx) in the highest power channel Set base station emulator to allow DUT to radiate maximum output power.
- (b) Measure output power through RF cable and power meter.
- (c) Place the DUT in the positions as Appendix E demonstrates.
- (d) Set scan area, grid size and other setting on the DASY software.
- (e) Measure SAR results for the highest power channel on each testing position.
- (f) Find out the largest SAR result on these testing positions of each band
- (g) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

#### 10.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 26 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01

# 10.2 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

### 10.3 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the DUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 10.4 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

#### 10.5 Power Drift Monitoring

All SAR testing is under the DUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of DUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 27 of 34


Report Issued Date : Jan. 10, 2012

Report No.: FA1D1302



# 11. SAR Test Configurations

# 11.1 Exposure Positions Consideration



WWAN antenna	WWAN TX/RX
WLAN antenna	WLAN TX/RX
Bluetooth antenna	Bluetooth TX/RX

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 28 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01

### 11.2 Simultaneous Transmitting Configurations

	Applicable Combination
	GSM+WLAN
	GSM+BT
	GSM+WLAN+BT
Simultaneous Transmission	GPRS +WLAN
	GPRS +BT
	GPRS +WLAN+BT
	WLAN+BT

#### Note:

- 1. Per KDB 648474 D01, Bluetooth output power ≤ 30/f and each other antennas SAR is less than 1.2 W/kg, therefore stand-alone SAR is not required.
- 2. According to KDB 648474, Simultaneous transmission SAR for WWAN and Bluetooth, WLAN and Bluetooth, are not required, because Bluetooth standalone SAR is not required and the maximum WWAN SAR (0.567 W/kg), thus the SAR summation is less than 1.6 W/kg.
- 3. According to KDB 648474, the simultaneous transmission SAR for WWAN and WLAN are not required, because the maximum SAR summation (Head: 0.62 W/kg; Body: 0.49 W/kg) is less than 1.6 W/kg.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 29 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01



### 12. SAR Test Results

### 12.1 Conducted Power (Unit: dBm)

#### <GSM/GPRS>

Burst Average Power											
Band		GSM850		GSM1900							
Channel	128	189	251	512	661	810					
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8					
GSM (1 Uplink)	32.21	32.32	<mark>32.39</mark>	<mark>30.10</mark>	30.04	29.84					
GPRS 8 (1 Uplink) – CS1	32.17	32.27	32.36	30.06	30.01	29.81					
GPRS 10 (2 Uplink) - CS1	31.64	31.63	31.63	29.34	29.28	29.07					
GPRS 11 (3 Uplink) – CS1	30.16	30.12	30.10	27.88	27.80	27.56					
GPRS 12 (4 Uplink) – CS1	29.34	29.30	29.28	27.05	27.00	26.80					

Source-Based Time-Averaged Power											
Band		GSM850		GSM1900							
Channel	128	128 189 251			661	810					
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8					
GSM (1 Uplink)	23.21	23.32	23.39	21.10	21.04	20.84					
GPRS 8 (1 Uplink) – CS1	23.17	23.27	23.36	21.06	21.01	20.81					
GPRS 10 (2 Uplink) - CS1	25.64	25.63	25.63	23.34	23.28	23.07					
GPRS 11 (3 Uplink) - CS1	25.90	25.86	25.84	23.62	23.54	23.30					
GPRS 12 (4 Uplink) - CS1	<mark>26.34</mark>	26.30	26.28	<mark>24.05</mark>	24.00	23.80					

Remark: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time averaged power = Maximum burst averaged power (1 Uplink) - 9 dB

Source based time averaged power = Maximum burst averaged power (2 Uplink) - 6 dB

Source based time averaged power = Maximum burst averaged power (3 Uplink) - 4.26 dB

Source based time averaged power = Maximum burst averaged power (4 Uplink) - 3 dB

### Note:

- 1. For Head SAR testing, GSM should be evaluated, therefore the DUT was set in GSM for GSM850 and set in GSM for GSM1900 due to its highest source-based time-average power.
- 2. For Body-worn SAR testing, GPRS should be evaluated, therefore the DUT was set in GPRS 12 for GSM850 and set in GPRS 12 for GSM1900 due to its highest source-based time-average power.
- 3. Per 2010/10 workshop, the maximum output power channel is used for SAR testing and for further SAR test reduction.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR

: 30 of 34 Page Number Report Issued Date: Jan. 10, 2012



#### <WLAN>

Band		802.11b		802.11g		
Channel	1	6	11	1 6 11		
Frequency (MHz)	2412	2437	2462	2412	2437	2462
Average Power	<mark>13.45</mark>	13.26	13.24	<mark>12.13</mark>	11.53	11.51
Peak Power	15.31	15.07	15.04	20.25	20.16	20.05

#### Note:

- 1. Per KDB 248227, 11g output power is less than 1/4 dB higher than 11b mode, thus the SAR can be excluded.
- 2. Per 2010/4 TCB workshop, choose the highest output power channel to test SAR and determine further SAR exclusion, and CH 1 is chosen here.

#### <Bluetooth>

Band	Bluetooth						
Channel	0	0 39 78					
Frequency	2402	2441	2480				
Average Power	8.73	9.15	9.21				
Peak Power	9.27	9.72	9.84				

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 31 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01

# 12.2 Test Records for Head SAR Test

#### <GSM>

Plot No.	Band	Mode	Test Position	Ch.	SAR <sub>1g</sub> (W/kg)
5	GSM850	GSM	Right Cheek	251	<mark>0.304</mark>
6	GSM850	GSM	Right Tilted	251	0.113
7	GSM850	GSM	Left Cheek	251	0.259
8	GSM850	GSM	Left Tilted	251	0.127
1	GSM1900	GSM	Right Cheek	512	<mark>0.567</mark>
2	GSM1900	GSM	Right Tilted	512	0.196
3	GSM1900	GSM	Left Cheek	512	0.527
4	GSM1900	GSM	Left Tilted	512	0.179

**Note:** Per KDB 648474, if the highest output channel SAR for each exposure position  $\leq 0.8$  W/kg other channels SAR tests are not necessary.

#### <WLAN>

Plot No.	Band	Mode	Test Position	Ch.	Data Rate	Power Rate	SAR <sub>1g</sub> (W/kg)
13	802.11b	ı	Right Cheek	1	1M	2C	0.052
14	802.11b	1	Right Tilted	1	1M	2C	0.048
15	802.11b	-	Left Cheek	1	1M	2C	<mark>0.058</mark>
16	802.11b	1	Left Tilted	1	1M	2C	0.020

**Note:** Per KDB 648474, if the highest output channel SAR for each exposure position  $\leq 0.8$  W/kg other channels SAR tests are not necessary.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 32 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01

### 12.3 Test Records for Body-worn SAR Test

#### <GSM>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	SAR <sub>1g</sub> (W/kg)
9	GSM850	GPRS12	Face	1.5	128	0.131
10	GSM850	GPRS12	Bottom	1.5	128	<mark>0.292</mark>
11	GSM1900	GPRS12	Face	1.5	512	0.121
12	GSM1900	GPRS12	Bottom	1.5	512	<mark>0.455</mark>

**Note:** Per KDB 648474, if the highest output channel SAR for each exposure position  $\leq 0.8$  W/kg other channels SAR tests are not necessary.

#### <WLAN>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Data Rate	Power Rate	SAR <sub>1g</sub> (W/kg)
17	802.11b	-	Face	1.5	1	1M	2C	0.026
18	802.11b	-	Bottom	1.5	1	1M	2C	0.037

**Note:** Per KDB 648474, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

### 12.4 Simultaneous Multi-band Transmission

#### <Simultaneous Transmission - Head SAR>

	GSM 850	GSM 1900	802.11b/g	Max. SAR Summation	Result
Right Cheek	0.304	0.567	0.052	0.62	PASS
Right Tilted	0.113	0.196	0.048	0.24	PASS
Left Cheek	0.259	0.527	0.058	0.59	PASS
Left Tilted	0.127	0.179	0.02	0.20	PASS

#### <Simultaneous Transmission -Body-worn SAR>

	GSM 850	GSM 1900	802.11b/g	Max. SAR Summation	Result
Face	0.131	0.121	0.026	0.16	PASS
Bottom	0.292	0.455	0.037	0.49	PASS

#### Note:

1 The maximum SAR summation is calculated based on the same configuration and test position.

**2** For 1g-SAR scalar summation < 1.6W/kg, simultaneous SAR measurement is not necessary.

Test Engineer: Sage Lu

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 33 of 34
Report Issued Date : Jan. 10, 2012
Report Version : Rev. 01



# 13. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] IEEE Std. C95.1-1991, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", 1991
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", June 2001
- [5] SPEAG DASY System Handbook
- [6] FCC KDB 248227 D01 v01r02, "SAR Measurement Procedures for 802.11 a/b/g Transmitters", May 2007
- [7] FCC KDB 447498 D01 v04, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", November 2009
- [8] FCC KDB 447498 D02 v02, "SAR Measurement Procedures for USB Dongle Transmitters", November 2009
- [9] FCC KDB 616217 D01 v01r01, "SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens", November 2009
- [10] FCC KDB 616217 D03 v01, "SAR Evaluation Considerations for Laptop/Notebook/Netbook and Tablet Computers", November 2009
- [11] FCC KDB 648474 D01 v01r05, "SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas", September 2008
- [12] FCC KDB 941225 D01 v02, "SAR Measurement Procedures for 3G Devices CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA", October 2007
- [13] FCC KDB 941225 D02 v02 "3GPP R6 HSPA and R7 HSPA+ SAR Guidance", December 2009.
- [14] FCC KDB 941225 D03 v01, "Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE", December 2008
- [15] FCC KDB 941225 D04 v01, "Evaluating SAR for GSM/(E)GPRS Dual Transfer Mode", January 27 2010

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: YHLACECCSPR Page Number : 34 of 34
Report Issued Date : Jan. 10, 2012

Report No.: FA1D1302