



# TEST REPORT

**APPLICANT** : BLU Products, Inc.  
**PRODUCT NAME** : Smart Phone  
**MODEL NAME** : N4  
**BRAND NAME** : BOLD  
**FCC ID** : YHLBLU4NC  
**STANDARD(S)** : 47 CFR Part 2  
: 47 CFR Part 90, Subpart S  
**RECEIPT DATE** : 2025-07-08  
**TEST DATE** : 2025-07-09 to 2025-08-14  
**ISSUE DATE** : 2025-08-18

Edited by:

*Zeng Xiaoying*  
Zeng Xiaoying (Rapporteur)

Approved by:

*Shen Junsheng*  
Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# DIRECTORY

- 1. Technical Information ..... 3**
- 1.1. Applicant and Manufacturer Information ..... 3**
- 1.2. Equipment Under Test (EUT) Description ..... 3**
- 1.3. Maximum E.R.P./E.I.R.P. and Emission Designator ..... 4**
- 1.4. Test Standards and Results ..... 5**
- 1.5. Environmental Conditions ..... 6**
- 2. 47 CFR Part 2, Part 90S Requirements ..... 7**
- 2.1. Transmitter Conducted Output Power and E.R.P./E.I.R.P. .... 7**
- 2.2. Occupied Bandwidth ..... 16**
- 2.3. Frequency Stability ..... 27**
- 2.4. Conducted Spurious Emissions ..... 29**
- 2.5. Band Edge ..... 32**
- 2.6. Radiated Spurious Emissions ..... 36**
- Annex A Test Uncertainty ..... 45**
- Annex B Testing Laboratory Information ..... 46**

<b>Change History</b>		
<b>Version</b>	<b>Date</b>	<b>Reason for change</b>
1.0	2025-08-18	First edition



# 1. Technical Information

Note: Provide by applicant.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	BLU Products, Inc.
<b>Applicant Address:</b>	8600 NW 36th Street, Suite #300   Miami, FL 33166 USA
<b>Manufacturer:</b>	BLU Products, Inc.
<b>Manufacturer Address:</b>	8600 NW 36th Street, Suite #300   Miami, FL 33166 USA

## 1.2. Equipment Under Test (EUT) Description

<b>Product Name:</b>	Smart Phone	
<b>Sample No.:</b>	1#, 7#	
<b>Hardware Version:</b>	KX10GF_06	
<b>Software Version:</b>	BOLD_N0090_V15.0.03.00_GENERIC 01-08-2025 21:45	
<b>Modulation Type:</b>	QPSK, 16QAM, 64QAM, 256QAM	
<b>Operation Band:</b>	Band 26	
<b>Frequency Range:</b>	LTE Band 26	Tx: 814MHz–824MHz
		Rx: 859MHz–869MHz
<b>Channel Bandwidth</b>	LTE Band 26	1.4MHz, 3MHz, 5MHz, 10MHz
<b>Antenna Type:</b>	PIFA Antenna	
<b>Antenna Gain:</b>	LTE Band 26	-4.30dBi
<b>Accessory Information:</b>	Battery	
	Brand Name:	BOLD
	Model No.:	C865255500P
	Serial No.:	N/A
	Capacity:	4900mAh
	Rated Voltage:	3.87V
	Charge Limit:	4.45V
	Manufacturer:	Guangdong Highpower New Energy Technology Co. , Ltd.
	AC Adapter	
	Brand Name:	BOLD
	Model No.:	US-BJ-6625Q
	Serial No.:	N/A



	Rated Output:	5.0V=3000mA, 9.0V=3000mA, 12.0V=3000mA, 15.0V=3000mA, 20.0V=3250mA, 5.0-11.0V=6000mA, 5.0-20.0V=3250mA
	Rated Input:	100-240V~50/60Hz, 1.6A
	Manufacturer:	ShenZhen BaiJunDa Electronics Co., Ltd

**Note 1:** SIM 1 and SIM 2 is a chipset unit and tested as a single chipset. The SIM 1 is chosen for test.

**Note 2:** The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

### 1.3. Maximum E.R.P./E.I.R.P. and Emission Designator

LTE Band 26	Maximum E.R.P./E.I.R.P. (W)				Emission Designator (99%OBW)			
	BW(MHz)	QPSK	16QAM	64QAM	256QAM	QPSK	16QAM	64QAM
10	0.050	0.043	0.033	0.016	8M97G7D	8M94W7D	8M97W7D	8M96W7D
5	0.050	0.043	0.033	0.017	4M48G7D	4M48W7D	4M49W7D	4M49W7D
3	0.051	0.043	0.033	0.016	2M70G7D	2M71W7D	2M71W7D	2M71W7D
1.4	0.050	0.043	0.033	0.017	1M10G7D	1M10W7D	1M10W7D	1M09W7D



## 1.4. Test Standards and Results

The objective of the report is to perform testing according to Part 2 and Part 90 for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 90	Miscellaneous Wireless Communications Services

Test detailed items/section required by FCC rules and results are as below:

Section	Description	Test Date	Test Engineer	Result	Remark
2.1046, 90.635(b)	Transmitter Conducted Output Power and E.R.P./E.I.R.P.	Aug. 14, 2025	Shen Biaohong Liu Huiyan	PASS	/
2.1049, 90.209	Occupied Bandwidth	Jul. 15, 2025	Liu Huiyan	PASS	/
2.1055, 90.213	Frequency Stability	Aug. 14, 2025	Liu Huiyan	PASS	/
2.1051, 90.691	Conducted Spurious Emissions	Jul. 15, 2025	Liu Huiyan	PASS	/
2.1051, 90.691	Band Edge	Jul. 15, 2025	Liu Huiyan	PASS	/
2.1053, 90.691	Radiated Spurious Emissions	Aug. 10, 2025	Gao Jianrou	PASS	/

**Note 1:** The tests were performed according to the method of measurements prescribed in KDB 971168 D01 v03 and ANSI/TIA-603-E-2016.

**Note 2:** Any additions, deviation, or exclusions from the method shall be noted in the "Remark".

**Note 3:** The antenna gain presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information.



## 1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

## 2.47 CFR Part 2, Part 90S Requirements


### 2.1. Transmitter Conducted Output Power and E.R.P./E.I.R.P.

#### 2.1.1. Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

According to FCC section 90.635(b) for LTE Band 26, the maximum output power of the transmitter for mobile stations is 100 watts.

#### 2.1.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

#### 2.1.3. Test procedure

KDB 971168 D01v03 Section 5.2 and ANSI/TIA-603-E-2016.

$EIRP \text{ (dBm)} = \text{Conducted Output Power (dBm)} + \text{Antenna Gain (dBi)}$

$ERP \text{ (dBm)} = EIPR \text{ (dBm)} - 2.15$



2.1.4. Result

Conducted Output Power

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				/	26740	/
Frequency (MHz)				/	819.0	/
10	QPSK	1	0	/	23.28	/
10	QPSK	1	25	/	23.42	/
10	QPSK	1	49	/	23.42	/
10	QPSK	25	0	/	22.53	/
10	QPSK	25	12	/	22.55	/
10	QPSK	25	25	/	22.60	/
10	QPSK	50	0	/	22.55	/
10	16QAM	1	0	/	22.72	/
10	16QAM	1	25	/	22.66	/
10	16QAM	1	49	/	22.78	/
10	16QAM	25	0	/	21.44	/
10	16QAM	25	12	/	21.50	/
10	16QAM	25	25	/	21.60	/
10	16QAM	50	0	/	21.45	/
10	64QAM	1	0	/	21.60	/
10	64QAM	1	25	/	21.67	/
10	64QAM	1	49	/	21.62	/
10	64QAM	25	0	/	20.44	/
10	64QAM	25	12	/	20.47	/
10	64QAM	25	25	/	20.57	/
10	64QAM	50	0	/	20.47	/
10	256QAM	1	0	/	18.60	/
10	256QAM	1	25	/	18.60	/
10	256QAM	1	49	/	18.60	/
10	256QAM	25	0	/	18.45	/
10	256QAM	25	12	/	18.51	/
10	256QAM	25	25	/	18.56	/
10	256QAM	50	0	/	18.52	/



LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26715	26740	26765
Frequency (MHz)				816.5	819.0	821.5
5	QPSK	1	0	23.41	23.34	23.34
5	QPSK	1	12	23.45	23.45	23.42
5	QPSK	1	24	23.35	23.45	23.39
5	QPSK	12	0	22.50	22.42	22.58
5	QPSK	12	7	22.49	22.47	22.56
5	QPSK	12	13	22.48	22.55	22.59
5	QPSK	25	0	22.51	22.56	22.58
5	16QAM	1	0	22.63	22.69	22.76
5	16QAM	1	12	22.70	22.72	22.76
5	16QAM	1	24	22.67	22.69	22.76
5	16QAM	12	0	21.54	21.54	21.63
5	16QAM	12	7	21.52	21.55	21.59
5	16QAM	12	13	21.55	21.64	21.64
5	16QAM	25	0	21.54	21.53	21.55
5	64QAM	1	0	21.56	21.59	21.65
5	64QAM	1	12	21.67	21.67	21.68
5	64QAM	1	24	21.65	21.67	21.67
5	64QAM	12	0	20.54	20.54	20.51
5	64QAM	12	7	20.53	20.54	20.58
5	64QAM	12	13	20.55	20.58	20.59
5	64QAM	25	0	20.52	20.53	20.57
5	256QAM	1	0	18.60	18.54	18.58
5	256QAM	1	12	18.58	18.62	18.61
5	256QAM	1	24	18.67	18.66	18.66
5	256QAM	12	0	18.50	18.49	18.53
5	256QAM	12	7	18.47	18.49	18.49
5	256QAM	12	13	18.53	18.54	18.44
5	256QAM	25	0	18.50	18.47	18.56



LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26705	26740	26775
Frequency (MHz)				815.5	819.0	822.5
3	QPSK	1	0	23.37	23.44	23.51
3	QPSK	1	8	23.35	23.38	23.37
3	QPSK	1	14	23.33	23.41	23.41
3	QPSK	8	0	22.42	22.47	22.47
3	QPSK	8	4	22.44	22.49	22.54
3	QPSK	8	7	22.45	22.48	22.50
3	QPSK	15	0	22.45	22.40	22.46
3	16QAM	1	0	22.65	22.76	22.62
3	16QAM	1	8	22.69	22.68	22.71
3	16QAM	1	14	22.66	22.63	22.67
3	16QAM	8	0	21.52	21.60	21.62
3	16QAM	8	4	21.51	21.58	21.56
3	16QAM	8	7	21.60	21.59	21.51
3	16QAM	15	0	21.45	21.45	21.54
3	64QAM	1	0	21.59	21.54	21.57
3	64QAM	1	8	21.58	21.59	21.56
3	64QAM	1	14	21.39	21.64	21.62
3	64QAM	8	0	20.46	20.48	20.53
3	64QAM	8	4	20.47	20.51	20.52
3	64QAM	8	7	20.50	20.50	20.53
3	64QAM	15	0	20.46	20.52	20.54
3	256QAM	1	0	18.49	18.51	18.56
3	256QAM	1	8	18.54	18.49	18.37
3	256QAM	1	14	18.54	18.56	18.53
3	256QAM	8	0	18.48	18.48	18.55
3	256QAM	8	4	18.44	18.48	18.54
3	256QAM	8	7	18.45	18.46	18.55
3	256QAM	15	0	18.47	18.41	18.49



LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26697	26740	26783
Frequency (MHz)				814.7	819.0	823.3
1.4	QPSK	1	0	23.26	23.37	23.45
1.4	QPSK	1	3	23.27	23.35	23.45
1.4	QPSK	1	5	23.31	23.39	23.48
1.4	QPSK	3	0	23.29	23.36	23.48
1.4	QPSK	3	1	23.39	23.43	23.40
1.4	QPSK	3	3	23.25	23.37	23.38
1.4	QPSK	6	0	22.44	22.38	22.50
1.4	16QAM	1	0	22.63	22.70	22.70
1.4	16QAM	1	3	22.65	22.67	22.76
1.4	16QAM	1	5	22.60	22.66	22.75
1.4	16QAM	3	0	22.44	22.45	22.53
1.4	16QAM	3	1	22.51	22.54	22.54
1.4	16QAM	3	3	22.38	22.55	22.56
1.4	16QAM	6	0	21.46	21.51	21.58
1.4	64QAM	1	0	21.59	21.63	21.64
1.4	64QAM	1	3	21.57	21.58	21.62
1.4	64QAM	1	5	21.53	21.53	21.69
1.4	64QAM	3	0	21.46	21.51	21.58
1.4	64QAM	3	1	21.46	21.51	21.54
1.4	64QAM	3	3	21.46	21.45	21.57
1.4	64QAM	6	0	20.41	20.44	20.45
1.4	256QAM	1	0	18.55	18.49	18.64
1.4	256QAM	1	3	18.51	18.57	18.65
1.4	256QAM	1	5	18.56	18.57	18.63
1.4	256QAM	3	0	18.51	18.59	18.62
1.4	256QAM	3	1	18.53	18.56	18.59
1.4	256QAM	3	3	18.50	18.58	18.54
1.4	256QAM	6	0	18.39	18.52	18.42



**Effective Radiated Power and Effective Isotropic Radiated Power**

LTE Band 26				Measured E.R.P.			
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.	Middle Ch. / Freq.	High Ch. / Freq.	
Channel				/	26740	/	
Frequency (MHz)				/	819	/	
				/	dBm	W	/
10	QPSK	1	0	/	16.83	0.048	/
10	QPSK	1	25	/	16.97	0.050	/
10	QPSK	1	49	/	16.97	0.050	/
10	QPSK	25	0	/	16.08	0.041	/
10	QPSK	25	12	/	16.10	0.041	/
10	QPSK	25	25	/	16.15	0.041	/
10	QPSK	50	0	/	16.10	0.041	/
10	16QAM	1	0	/	16.27	0.042	/
10	16QAM	1	25	/	16.21	0.042	/
10	16QAM	1	49	/	16.33	0.043	/
10	16QAM	25	0	/	14.99	0.032	/
10	16QAM	25	12	/	15.05	0.032	/
10	16QAM	25	25	/	15.15	0.033	/
10	16QAM	50	0	/	15.00	0.032	/
10	64QAM	1	0	/	15.15	0.033	/
10	64QAM	1	25	/	15.22	0.033	/
10	64QAM	1	49	/	15.17	0.033	/
10	64QAM	25	0	/	13.99	0.025	/
10	64QAM	25	12	/	14.02	0.025	/
10	64QAM	25	25	/	14.12	0.026	/
10	64QAM	50	0	/	14.02	0.025	/
10	256QAM	1	0	/	12.15	0.016	/
10	256QAM	1	25	/	12.15	0.016	/
10	256QAM	1	49	/	12.15	0.016	/
10	256QAM	25	0	/	12.00	0.016	/
10	256QAM	25	12	/	12.06	0.016	/
10	256QAM	25	25	/	12.11	0.016	/
10	256QAM	50	0	/	12.07	0.016	/



LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26715		26740		26765	
Frequency (MHz)				816.5		819.0		821.5	
				dBm	W	dBm	W	dBm	W
5	QPSK	1	0	16.96	0.050	16.89	0.049	16.89	0.049
5	QPSK	1	12	17.00	0.050	17.00	0.050	16.97	0.050
5	QPSK	1	24	16.90	0.049	17.00	0.050	16.94	0.049
5	QPSK	12	0	16.05	0.040	15.97	0.040	16.13	0.041
5	QPSK	12	7	16.04	0.040	16.02	0.040	16.11	0.041
5	QPSK	12	13	16.03	0.040	16.10	0.041	16.14	0.041
5	QPSK	25	0	16.06	0.040	16.11	0.041	16.13	0.041
5	16QAM	1	0	16.18	0.041	16.24	0.042	16.31	0.043
5	16QAM	1	12	16.25	0.042	16.27	0.042	16.31	0.043
5	16QAM	1	24	16.22	0.042	16.24	0.042	16.31	0.043
5	16QAM	12	0	15.09	0.032	15.09	0.032	15.18	0.033
5	16QAM	12	7	15.07	0.032	15.10	0.032	15.14	0.033
5	16QAM	12	13	15.10	0.032	15.19	0.033	15.19	0.033
5	16QAM	25	0	15.09	0.032	15.08	0.032	15.10	0.032
5	64QAM	1	0	15.11	0.032	15.14	0.033	15.20	0.033
5	64QAM	1	12	15.22	0.033	15.22	0.033	15.23	0.033
5	64QAM	1	24	15.20	0.033	15.22	0.033	15.22	0.033
5	64QAM	12	0	14.09	0.026	14.09	0.026	14.06	0.025
5	64QAM	12	7	14.08	0.026	14.09	0.026	14.13	0.026
5	64QAM	12	13	14.10	0.026	14.13	0.026	14.14	0.026
5	64QAM	25	0	14.07	0.026	14.08	0.026	14.12	0.026
5	256QAM	1	0	12.15	0.016	12.09	0.016	12.13	0.016
5	256QAM	1	12	12.13	0.016	12.17	0.016	12.16	0.016
5	256QAM	1	24	12.22	0.017	12.21	0.017	12.21	0.017
5	256QAM	12	0	12.05	0.016	12.04	0.016	12.08	0.016
5	256QAM	12	7	12.02	0.016	12.04	0.016	12.04	0.016
5	256QAM	12	13	12.08	0.016	12.09	0.016	11.99	0.016
5	256QAM	25	0	12.05	0.016	12.02	0.016	12.11	0.016



LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26705		26740		26775	
Frequency (MHz)				815.5		819.0		822.5	
				dBm	W	dBm	W	dBm	W
3	QPSK	1	0	16.92	0.049	16.99	0.050	17.06	0.051
3	QPSK	1	8	16.90	0.049	16.93	0.049	16.92	0.049
3	QPSK	1	14	16.88	0.049	16.96	0.050	16.96	0.050
3	QPSK	8	0	15.97	0.040	16.02	0.040	16.02	0.040
3	QPSK	8	4	15.99	0.040	16.04	0.040	16.09	0.041
3	QPSK	8	7	16.00	0.040	16.03	0.040	16.05	0.040
3	QPSK	15	0	16.00	0.040	15.95	0.039	16.01	0.040
3	16QAM	1	0	16.20	0.042	16.31	0.043	16.17	0.041
3	16QAM	1	8	16.24	0.042	16.23	0.042	16.26	0.042
3	16QAM	1	14	16.21	0.042	16.18	0.041	16.22	0.042
3	16QAM	8	0	15.07	0.032	15.15	0.033	15.17	0.033
3	16QAM	8	4	15.06	0.032	15.13	0.033	15.11	0.032
3	16QAM	8	7	15.15	0.033	15.14	0.033	15.06	0.032
3	16QAM	15	0	15.00	0.032	15.00	0.032	15.09	0.032
3	64QAM	1	0	15.14	0.033	15.09	0.032	15.12	0.033
3	64QAM	1	8	15.13	0.033	15.14	0.033	15.11	0.032
3	64QAM	1	14	14.94	0.031	15.19	0.033	15.17	0.033
3	64QAM	8	0	14.01	0.025	14.03	0.025	14.08	0.026
3	64QAM	8	4	14.02	0.025	14.06	0.025	14.07	0.026
3	64QAM	8	7	14.05	0.025	14.05	0.025	14.08	0.026
3	64QAM	15	0	14.01	0.025	14.07	0.026	14.09	0.026
3	256QAM	1	0	12.04	0.016	12.06	0.016	12.11	0.016
3	256QAM	1	8	12.09	0.016	12.04	0.016	11.92	0.016
3	256QAM	1	14	12.09	0.016	12.11	0.016	12.08	0.016
3	256QAM	8	0	12.03	0.016	12.03	0.016	12.10	0.016
3	256QAM	8	4	11.99	0.016	12.03	0.016	12.09	0.016
3	256QAM	8	7	12.00	0.016	12.01	0.016	12.10	0.016
3	256QAM	15	0	12.02	0.016	11.96	0.016	12.04	0.016




LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26697		26740		26783	
Frequency (MHz)				814.7		819.0		823.3	
				dBm	W	dBm	W	dBm	W
1.4	QPSK	1	0	16.81	0.048	16.92	0.049	17.00	0.050
1.4	QPSK	1	3	16.82	0.048	16.90	0.049	17.00	0.050
1.4	QPSK	1	5	16.86	0.049	16.94	0.049	17.03	0.050
1.4	QPSK	3	0	16.84	0.048	16.91	0.049	17.03	0.050
1.4	QPSK	3	1	16.94	0.049	16.98	0.050	16.95	0.050
1.4	QPSK	3	3	16.80	0.048	16.92	0.049	16.93	0.049
1.4	QPSK	6	0	15.99	0.040	15.93	0.039	16.05	0.040
1.4	16QAM	1	0	16.18	0.041	16.25	0.042	16.25	0.042
1.4	16QAM	1	3	16.20	0.042	16.22	0.042	16.31	0.043
1.4	16QAM	1	5	16.15	0.041	16.21	0.042	16.30	0.043
1.4	16QAM	3	0	15.99	0.040	16.00	0.040	16.08	0.041
1.4	16QAM	3	1	16.06	0.040	16.09	0.041	16.09	0.041
1.4	16QAM	3	3	15.93	0.039	16.10	0.041	16.11	0.041
1.4	16QAM	6	0	15.01	0.032	15.06	0.032	15.13	0.033
1.4	64QAM	1	0	15.14	0.033	15.18	0.033	15.19	0.033
1.4	64QAM	1	3	15.12	0.033	15.13	0.033	15.17	0.033
1.4	64QAM	1	5	15.08	0.032	15.08	0.032	15.24	0.033
1.4	64QAM	3	0	15.01	0.032	15.06	0.032	15.13	0.033
1.4	64QAM	3	1	15.01	0.032	15.06	0.032	15.09	0.032
1.4	64QAM	3	3	15.01	0.032	15.00	0.032	15.12	0.033
1.4	64QAM	6	0	13.96	0.025	13.99	0.025	14.00	0.025
1.4	256QAM	1	0	12.10	0.016	12.04	0.016	12.19	0.017
1.4	256QAM	1	3	12.06	0.016	12.12	0.016	12.20	0.017
1.4	256QAM	1	5	12.11	0.016	12.12	0.016	12.18	0.017
1.4	256QAM	3	0	12.06	0.016	12.14	0.016	12.17	0.016
1.4	256QAM	3	1	12.08	0.016	12.11	0.016	12.14	0.016
1.4	256QAM	3	3	12.05	0.016	12.13	0.016	12.09	0.016
1.4	256QAM	6	0	11.94	0.016	12.07	0.016	11.97	0.016

## 2.2. Occupied Bandwidth

### 2.2.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. Occupied bandwidth is also known as the 99% emission bandwidth.

### 2.2.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

### 2.2.3. Test procedure

KDB 971168 D01v03 Section 4.1 and ANSI/TIA-603-E-2016.




## 2.2.4. Test Result

LTE Band	BW(MHz)	Channel Level	Channel	Frequency (MHz)	Modulation	99% BW (MHz)	26dB BW (MHz)	Verdict
B26	1.4	Low	26697	814.7	QPSK	1.0958	1.2638	PASS
B26	1.4	Low	26697	814.7	16QAM	1.1011	1.2852	PASS
B26	1.4	Low	26697	814.7	64QAM	1.0967	1.2862	PASS
B26	1.4	Low	26697	814.7	256QAM	1.0903	1.2704	PASS
B26	1.4	Mid	26740	819	QPSK	1.0954	1.2741	PASS
B26	1.4	Mid	26740	819	16QAM	1.1032	1.2862	PASS
B26	1.4	Mid	26740	819	64QAM	1.0979	1.2913	PASS
B26	1.4	Mid	26740	819	256QAM	1.0909	1.2830	PASS
B26	1.4	High	26783	823.3	QPSK	1.0945	1.2746	PASS
B26	1.4	High	26783	823.3	16QAM	1.1034	1.2709	PASS
B26	1.4	High	26783	823.3	64QAM	1.0975	1.2859	PASS
B26	1.4	High	26783	823.3	256QAM	1.0901	1.2675	PASS
B26	3	Low	26705	815.5	QPSK	2.6920	2.9450	PASS
B26	3	Low	26705	815.5	16QAM	2.7090	2.9641	PASS
B26	3	Low	26705	815.5	64QAM	2.7037	2.9710	PASS
B26	3	Low	26705	815.5	256QAM	2.7024	2.9595	PASS
B26	3	Mid	26740	819	QPSK	2.6963	2.9669	PASS
B26	3	Mid	26740	819	16QAM	2.7108	2.9863	PASS
B26	3	Mid	26740	819	64QAM	2.7028	2.9458	PASS
B26	3	Mid	26740	819	256QAM	2.7087	2.9757	PASS
B26	3	High	26775	822.5	QPSK	2.6910	2.9627	PASS
B26	3	High	26775	822.5	16QAM	2.7103	2.9712	PASS
B26	3	High	26775	822.5	64QAM	2.7067	2.9662	PASS
B26	3	High	26775	822.5	256QAM	2.7025	2.9815	PASS
B26	5	Low	26715	816.5	QPSK	4.4743	4.8725	PASS
B26	5	Low	26715	816.5	16QAM	4.4744	4.8440	PASS
B26	5	Low	26715	816.5	64QAM	4.4929	4.9196	PASS
B26	5	Low	26715	816.5	256QAM	4.4750	4.8785	PASS
B26	5	Mid	26740	819	QPSK	4.4809	4.8988	PASS
B26	5	Mid	26740	819	16QAM	4.4778	4.8636	PASS
B26	5	Mid	26740	819	64QAM	4.4924	4.9142	PASS
B26	5	Mid	26740	819	256QAM	4.4885	4.8791	PASS
B26	5	High	26765	821.5	QPSK	4.4819	4.9444	PASS




B26	5	High	26765	821.5	16QAM	4.4818	4.9165	PASS
B26	5	High	26765	821.5	64QAM	4.4916	4.9007	PASS
B26	5	High	26765	821.5	256QAM	4.4909	4.9211	PASS
B26	10	Low	26740	819	QPSK	8.9686	9.7154	PASS
B26	10	Low	26740	819	16QAM	8.9403	9.7166	PASS
B26	10	Low	26740	819	64QAM	8.9666	9.6557	PASS
B26	10	Low	26740	819	256QAM	8.9598	9.7182	PASS
B26	10	Mid	26740	819	QPSK	8.9526	9.6576	PASS
B26	10	Mid	26740	819	16QAM	8.9290	9.6318	PASS
B26	10	Mid	26740	819	64QAM	8.9616	9.7047	PASS
B26	10	Mid	26740	819	256QAM	8.9464	9.7304	PASS
B26	10	High	26740	819	QPSK	8.9623	9.7112	PASS
B26	10	High	26740	819	16QAM	8.9285	9.7505	PASS
B26	10	High	26740	819	64QAM	8.9559	9.6976	PASS
B26	10	High	26740	819	256QAM	8.9380	9.6709	PASS




B26 / 1.4MHz / QPSK / Low CH




B26 / 1.4MHz / 16QAM / Low CH




B26 / 1.4MHz / 64QAM / Low CH



B26 / 1.4MHz / 256QAM / Low CH



B26 / 1.4MHz / QPSK / Mid CH



B26 / 1.4MHz / 16QAM / Mid CH



B26 / 1.4MHz / 64QAM/ Mid CH



B26 / 1.4MHz / 256QAM/ Mid CH



B26 / 1.4MHz / QPSK/ High CH



B26 / 1.4MHz / 16QAM/ High CH



B26 / 1.4MHz / 64QAM/ High CH




B26 / 1.4MHz / 256QAM/ High CH




B26 / 3MHz / QPSK/ Low CH




B26 / 3MHz / 16QAM/ Low CH



B26 / 3MHz / 64QAM/ Low CH




B26 / 3MHz / 256QAM/ Low CH



B26 / 3MHz / QPSK/ Mid CH




B26 / 3MHz / 16QAM/ Mid CH




B26 / 3MHz / 64QAM/ Mid CH




B26 / 3MHz / 256QAM/ Mid CH




B26 / 3MHz / QPSK/ High CH




B26 / 3MHz / 16QAM/ High CH




B26 / 3MHz / 64QAM/ High CH



B26 / 3MHz / 256QAM/ High CH




B26 / 5MHz / QPSK/ Low CH




B26 / 5MHz / 16QAM/ Low CH




B26 / 5MHz / 64QAM/ Low CH




B26 / 5MHz / 256QAM/ Low CH



B26 / 5MHz / QPSK/ Mid CH



B26 / 5MHz / 16QAM/ Mid CH




B26 / 5MHz / 64QAM/ Mid CH



B26 / 5MHz / 256QAM/ Mid CH



B26 / 5MHz / QPSK/ High CH



B26 / 5MHz / 16QAM/ High CH



B26 / 5MHz / 64QAM/ High CH




B26 / 5MHz / 256QAM/ High CH



B26 / 10MHz / QPSK/ Low CH



B26 / 10MHz / 16QAM/ Low CH



B26 / 10MHz / 64QAM/ Low CH



B26 / 10MHz / 256QAM/ Low CH




B26 / 10MHz / QPSK/ Mid CH




B26 / 10MHz / 16QAM/ Mid CH




B26 / 10MHz / 64QAM/ Mid CH



B26 / 10MHz / 256QAM/ Mid CH



B26 / 10MHz / QPSK/ High CH



B26 / 10MHz / 16QAM/ High CH



B26 / 10MHz / 64QAM/ High CH



B26 / 10MHz / 256QAM/ High CH

## 2.3. Frequency Stability


### 2.3.1. Requirement

According to FCC section 2.1055 & 90.213, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  at intervals of not more than  $10^{\circ}\text{C}$ .
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

**Note:** The operating temperature of EUT is from  $0^{\circ}\text{C}$  to  $60^{\circ}\text{C}$ , which are specified by the applicant.

### 2.3.2. Test Description



The EUT which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power. A call is established between the EUT and the SS via a Common Antenna.

### 2.3.3. Test procedure

KDB 971168 D01v03 Section 9.0 and ANSI/TIA-603-E-2016.



2.3.4. Test Result

The nominal, highest and lowest extreme voltages are separately 3.87V, 4.45V and 3.4V, which are specified by the applicant; the normal temperature here used is 20°C.


LTE Band 26, 256QAM, Channel 26740, Frequency 819MHz					
Limit =±2.5ppm					
Voltage (%)	Power (VDC)	Temp(°C)	Fre. Dev.(Hz)	Deviation (ppm)	Result
Normal	3.87	+20(Ref)	18	0.022	PASS
Normal		0	14	0.017	
Normal		+10	18	0.022	
Normal		+20	20	0.024	
Normal		+30	15	0.018	
Normal		+40	22	0.026	
Normal		+50	2	0.002	
Normal		+60	15	0.018	
High	4.45	+20	17	0.020	
BATT.ENDPOINT	3.40	+20	-23	-0.027	

## 2.4. Conducted Spurious Emissions

### 2.4.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm.

### 2.4.2. Test Description




The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.


### 2.4.3. Test procedure

KDB 971168 D01v03 Section 6.0 and ANSI/TIA-603-E-2016.




2.4.4. Test Result







B26 / 5MHz / Low CH / QPSK




B26 / 5MHz / Mid CH / QPSK




B26 / 5MHz / High CH / QPSK



B26 / 10MHz / Low CH / QPSK



B26 / 10MHz / Mid CH / QPSK



B26 / 10MHz / High CH / QPSK





2.5.4. Test Result







B26 / 3MHz / High CH / QPSK / 1 RB



B26 / 3MHz / High CH / QPSK / FULL RB



B26 / 5MHz / Low CH / QPSK / 1 RB



B26 / 5MHz / Low CH / QPSK / FULL RB



B26 / 5MHz / High CH / QPSK / 1 RB



B26 / 5MHz / High CH / QPSK / FULL RB




B26 / 10MHz / Low CH / QPSK / 1 RB



B26 / 10MHz / Low CH / QPSK / FULL RB



B26 / 10MHz / High CH / QPSK / 1 RB




B26 / 10MHz / High CH / QPSK / FULL RB


## 2.6. Radiated Spurious Emissions

### 2.6.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm.

### 2.6.2. Test Description





(For the test frequency above 1GHz)

The EUT is located in a 3m Full-Anechoic Chamber, the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power, and only the test result of the maximum output power was recorded.

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground and the Turn Table is actuated to turn from 0° to 360° to determine the maximum value of the radiated power. The emission levels at both horizontal and vertical polarizations should be tested. The Filters consists of Notch Filters and High Pass Filter.

**Note:** when doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

### 2.6.3. Test procedure

KDB 971168 D01v03 Section 5.8 and ANSI/TIA-603-E-2016.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements.



#### 2.6.4. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

The substitution corrections are obtained as described below:

$$A_{\text{SUBST}} = P_{\text{SUBST\_TX}} - P_{\text{SUBST\_RX}} - L_{\text{SUBST\_CABLES}} + G_{\text{SUBST\_TX\_ANT}}$$

$$A_{\text{TOT}} = L_{\text{CABLES}} + A_{\text{SUBST}}$$

Where  $A_{\text{SUBST}}$  is the final substitution correction including receive antenna gain.

$P_{\text{SUBST\_TX}}$  is signal generator level,

$P_{\text{SUBST\_RX}}$  is receiver level,

$L_{\text{SUBST\_CABLES}}$  is cable losses including TX cable,

$G_{\text{SUBST\_TX\_ANT}}$  is substitution antenna gain.

$A_{\text{TOT}}$  is total correction factor including cable loss and substitution correction

During the test, the data of  $A_{\text{TOT}}$  was added in the test spectrum analyze, so spectrum analyze reading is the final values which contain the data of  $A_{\text{TOT}}$ .

**Note1:** The power of the EUT transmitting frequency should be ignored.

**Note2:** All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

**Note3:** All bandwidth and modulation were considered and evaluated respectively by performing full test for each band, only the worst cases (Max Bandwidth and QPSK mode) were recorded in this test report.


**Note 4:** N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.

**Note 5:** The amplitude of emissions (18GHz to 10th harmonics) which are attenuated more than 20 dB below the limit are not be reported.




**LTE Band 26**

Plot for Low Channel




Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
194.6172	-44.19	-62.73	-18.5	-13.0	49.7	Horizontal	PK	PASS
814.6237	-48.47	-54.42	-6.0	-	-	Horizontal	PK	NA
1858.9718	-58.71	-53.52	5.2	-13.0	40.5	Horizontal	PK	PASS
3660.108	-57.16	-55.43	1.7	-13.0	42.4	Horizontal	PK	PASS
7033.7767	-61.91	-50.11	11.8	-13.0	37.1	Horizontal	PK	PASS
12555.477	-69.95	-46.63	23.3	-13.0	33.6	Horizontal	PK	PASS




Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
46.1513	-39.58	-59.36	-19.8	-13.0	46.4	Vertical	PK	PASS
814.3327	-53.67	-59.41	-5.7	-	-	Vertical	PK	NA
1891.7784	-58.94	-53.04	5.9	-13.0	40.0	Vertical	PK	PASS
3660.5955	-56.93	-55.27	1.7	-13.0	42.3	Vertical	PK	PASS
6969.911	-61.67	-50.63	11.0	-13.0	37.6	Vertical	PK	PASS
11034.401	-67.45	-45.31	22.1	-13.0	32.3	Vertical	PK	PASS

Plot for Mid Channel




Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
193.9382	-44.51	-63.17	-18.7	-13.0	50.2	Horizontal	PK	PASS
819.183	-50.74	-56.63	-5.9	-	-	Horizontal	PK	NA
1544.5089	-57.64	-55.26	2.4	-13.0	42.3	Horizontal	PK	PASS
3658.6454	-57.59	-55.87	1.7	-13.0	42.9	Horizontal	PK	PASS
7079.1165	-62.49	-50.46	12.0	-13.0	37.5	Horizontal	PK	PASS
12477.961	-68.55	-45.63	22.9	-13.0	32.6	Horizontal	PK	PASS




Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
819.086	-56.21	-62.03	-5.8	-	-	Vertical	PK	NA
866.1818	-52.27	-57.25	-5.0	-	-	Vertical	PK	NA
1914.1828	-58.95	-53.50	5.5	-13.0	40.5	Vertical	PK	PASS
3672.2961	-57.08	-55.39	1.7	-13.0	42.4	Vertical	PK	PASS
7481.8116	-62.06	-50.07	12.0	-13.0	37.1	Vertical	PK	PASS
11044.639	-67.59	-45.41	22.2	-13.0	32.4	Vertical	PK	PASS

Plot for High Channel



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
823.3057	-47.04	-52.86	-5.8	-	-	Horizontal	PK	NA
868.4129	-57.70	-62.57	-4.9	-	-	Horizontal	PK	NA
1851.3703	-59.04	-54.05	5.0	-13.0	41.1	Horizontal	PK	PASS
3759.563	-57.13	-55.94	1.2	-13.0	42.9	Horizontal	PK	PASS
7039.1395	-62.69	-50.86	11.8	-13.0	37.9	Horizontal	PK	PASS
12539.389	-69.39	-46.05	23.3	-13.0	33.1	Horizontal	PK	PASS



Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Polarity	Detector	Verdict
823.3542	-53.32	-59.20	-5.9	-	-	Vertical	PK	NA
868.6554	-42.36	-47.25	-4.9	-	-	Vertical	PK	NA
1890.9782	-59.20	-53.30	5.9	-13.0	40.3	Vertical	PK	PASS
3660.108	-57.67	-56.01	1.7	-13.0	43.0	Vertical	PK	PASS
7503.2627	-62.60	-50.58	12.0	-13.0	37.6	Vertical	PK	PASS
11122.643	-67.38	-45.29	22.1	-13.0	32.3	Vertical	PK	PASS



## Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Output Power	$\pm 2.22$ dB
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77$ dB
Band Edge	$\pm 2.77$ dB
Equivalent Isotropic Radiated Power	$\pm 2.22$ dB
Radiated Spurious Emissions	$\pm 6$ dB

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .



## Annex B Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

<b>Laboratory Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Laboratory Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



#### 4. Test Equipment Utilized

##### 4.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY51511149	N9020A	Agilent	2024.06.19	2025.06.18
Communication Test Station	6200995016	MT8820C	Anritsu	2024.09.11	2025.09.10
Temperature Chamber	S022177101 00089002	KMT-36LF 1A0	KOMEG	2024.09.11	2025.09.10

##### 4.2 List of Software Used

Description	Manufacturer	Software Version
MOR-2023E Test System	MORLAB	V7.99
JS36-RSE	Tonscend	5.0.0

**4.3 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
System Simulator	152038	CMW500	R&S	2024.09.11	2025.09.10
Receiver	MY56060145	N9020A	Agilent	2025.05.13	2026.05.12
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2025.06.22	2026.06.20
Test Antenna - Horn	9120D-963	BBHA 9120D	Schwarzbeck	2025.05.16	2026.05.15
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2024.09.11	2025.09.10
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2024.09.11	2025.09.10
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-N N-5	Qualwave	2024.09.11	2025.09.10
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118- 40C-S	Decentest	2025.05.13	2026.05.12
Notch Filter	N/A	WRCGV -LTE 26	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.06.21	2028.06.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.11.30	2025.11.29

END OF REPORT