

FCC CERTIFICATION REPORT

REPORT NO.: FC120628C18

MODEL NO.: Click Plus

RECEIVED: Jun. 28, 2012

TESTED: Jul. 12 ~ Jul. 13, 2012

ISSUED: Jul. 16, 2012

APPLICANT: CT Asia

ADDRESS: Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun

road, Kwun Tong, Kowloon, Hongkong

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan

This report should not be used by the client to claim product certification, approval, or endorsement by TAF, NVLAP, NIST or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Report No.: FC120628C18 1 of 26 Report Format Version 5.0.0



Table of Contents

RELE	ASE CONTROL RECORD	3
1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	DESCRIPTION OF SUPPORT UNITS	7
3.4	CONFIGURATION OF SYSTEM UNDER TEST	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES1	0
4.1.4	DEVIATION FROM TEST STANDARD1	0
4.1.5	TEST SETUP1	1
4.1.6	EUT OPERATING CONDITIONS1	1
4.1.7	TEST RESULTS1	2
4.2	RADIATED EMISSION MEASUREMENT1	4
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT1	4
4.2.2	TEST INSTRUMENTS1	5
4.2.3	TEST PROCEDURES1	7
4.2.4	DEVIATION FROM TEST STANDARD1	8
4.2.5	TEST SETUP 1	9
4.2.6	EUT OPERATING CONDITIONS1	9
4.2.7	TEST RESULTS2	20
5	PHOTOGRAPHS OF THE TEST CONFIGURATION2	24
6	INFORMATION ON THE TESTING LABORATORIES2	25
7	APPENDIX A – MODIFICATION RECORDERS FOR ENGINEERING CHANGES TO	С
	THE EUT BY THE LAB2	26



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FD120628C18	Original release.	Jul. 16, 2012



1 CERTIFICATION

PRODUCT: GSM mobile

BRAND: Blu

MODEL NO.: Click Plus **APPLICANT: CT Asia**

TESTED: Jul. 12 ~ Jul. 13, 2012

TEST SAMPLE: ENGINEERING SAMPLE

STANDARD: FCC Part 15, Subpart B, Class B

ICES-003:2004, Class B

ANSI C63.4:2009

The above equipment (model: Click Plus) has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

APPROVED BY: _______, DATE: ______, Jul. 16, 2012



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications.

	EMISSION		
Standard	Test Type	Result	Remarks
FCC Part 15, Subpart B,	Conducted emission test	PASS	Meet the requirement of limit Minimum passing margin is -9.43dB at 0.15391MHz
Class B ICES-003:2004, Class B	Radiated emission test (30MHz~18GHz)	PASS	Meet the requirement of limit Minimum passing margin is -4.61dB at 37.78MHz

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emission	150kHz ~ 30MHz	2.44 dB
De dieta de arriaciona	30MHz ~ 1GHz	3.65 dB
Radiated emission	Above 1GHz	2.26 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	GSM mobile	
MODEL NO.	Click Plus	
POWER SUPPLY	3.7Vdc from battery 5.0Vdc from adapter	
DATA CABLE	Refer to Note as below	
ACCESSORY DEVICE	Refer to Note as below	

NOTE:

1. The EUT contains the following accessories.

ITEM	BRAND	MODEL	SPECIFICATION
Adapter	BLU	US300507	Input: 100-240Vac, 150mA Output: 5Vdc, 500mA
Battery	BLU	N5C60T	Rating: 3.7Vdc, 600mAh Type: Li-ion
USB Cable	BLU	NA	0.93m non-shielded cable w/o core
Earphone	BLU	NA	1.29m non-shielded cable w/o core

2. The above EUT information is declared by manufacturer and for more detailed feature description, please refer to the manufacturer's specifications or user's manual.



3.2 DESCRIPTION OF TEST MODES

The EUT was tested with the following modes.

Test Mode	Test Condition
	Conducted Emission
1	GSM850 Idle + BT Idle + Adapter + Battery + Camera
2	GSM1900 Idle + BT Idle + Adapter + Battery + MPEG4
3	USB charging + Battery
	Radiated Emission
1	GSM850 Idle + BT Idle + Adapter + Battery + Camera
2	GSM1900 Idle + BT Idle + Earphone + Battery + MPEG4
3	USB charging + Battery

Note:

- 1. For conducted emission test, test mode 1 was the worst case and only this mode was presented in this report.
- 2. For radiated emission test, test mode 1 was the worst case and only this mode was presented in this report.

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	UNIVERSAL RADIO COMMUNICATION TESTER	R&S	CMU 200	123121	NA
2	BLUETOOTH EARPHONE	ELECOM	LBT-MPHS400	NA	NA


NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA


NOTE:

- 1. All power cords of the above support units are non-shielded (1.8m).
- 2. Items 1-2 acted as a communication partner to transfer data.



3.4 CONFIGURATION OF SYSTEM UNDER TEST







4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD:

FCC Part 15, Subpart B (section: 15.107) ICES-003:2004 (Class A: section 5.2) (Class B: section 5.3)

Erogueney (MH=)	Class A	(dBuV)	Class B (dBuV)		
Frequency (MHz)	Quasi-peak	Average	Quasi-peak	Average	
0.15-0.5	79	66	66-56	56-46	
0.5-5	73	60	56	46	
5-30	73	60	60	50	

NOTE: 1. The lower limit shall apply at the transition frequencies.

- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 23, 2011	Nov. 22, 2012
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 22, 2011	Dec. 21, 2012
V-LISN SCHWARZBECK (Peripheral)	NNBL 8226-2	8226-142	Jun. 22, 2012	Jun. 21, 2013
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 07, 2012	Feb. 06, 2013
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 1.
- 3. The VCCI Site Registration No. is C-2040.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

 c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under Limit - 20dB was not recorded.
4.1.4 DEVIATION FROM TEST STANDARD
No deviation.



4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. The EUT ran test program to enable all functions.
- c. The EUT played Camera.
- d. The EUT linked with CMU200 and BT earphone, which acted as communication partners.
- e. Steps b~d were repeated.




4.1.7 TEST RESULTS

INPUT POWER	120 Vac, 60 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	22 deg. C, 55% RH	PHASE	Line 1
TESTED BY	Skys Huang		

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB	(uV)]	[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	0.15	53.33	37.85	53.48	38.00	65.58	55.58	-12.10	-17.58
2	0.20859	0.23	47.61	32.43	47.84	32.66	63.26	53.26	-15.42	-20.60
3	0.25938	0.21	44.16	30.07	44.37	30.28	61.45	51.45	-17.08	-21.17
4	1.91797	0.24	34.81	22.34	35.05	22.58	56.00	46.00	-20.95	-23.42
5	3.05469	0.29	20.85	6.72	21.14	7.01	56.00	46.00	-34.86	-38.99
6	4.83203	0.37	19.70	7.61	20.07	7.98	56.00	46.00	-35.93	-38.02

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






INPUT POWER	120 Vac, 60 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	22 deg. C, 55% RH	PHASE	Line 2
TESTED BY	Skys Huang		

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB	(uV)]	[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	0.24	56.12	40.27	56.36	40.51	65.79	55.79	-9.43	-15.28
2	0.20859	0.31	49.34	33.59	49.65	33.90	63.26	53.26	-13.61	-19.36
3	0.25938	0.29	43.98	29.41	44.27	29.70	61.45	51.45	-17.18	-21.75
4	1.80859	0.33	27.86	15.68	28.19	16.01	56.00	46.00	-27.81	-29.99
5	2.99609	0.39	15.94	-1.54	16.33	-1.15	56.00	46.00	-39.67	-47.15
6	7.97656	0.58	15.03	0.99	15.61	1.57	60.00	50.00	-44.39	-48.43

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD:

FCC Part 15, Subpart B (section: 15.109) ICES-003:2004 (Class A: section 5.4) (Class B: section 5.5)

Francisco (MIII-)	Class A (at 10m)	Class B (at 10m)		
Frequency (MHz)	Quasi-peak (dBuV/m)	Quasi-peak (dBuV/m)		
30-230	40	30		
230-1000	47	37		

NOTE: The limit for radiated test was performed according to FCC PART 15B 15.109(g). Also the limit of ICES-003 is same.

	Class A	(at 3m)	Class B (at 3m)		
Frequency (MHz)	Peak Average		Peak	Average	
	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
Above 1000	80	60	74	54	

NOTE: 1. The lower limit shall apply at the transition frequencies.

- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower



4.2.2 TEST INSTRUMENTS

Frequency range 30MHz~1GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ (V)	ESIB7	100187	Jan. 30, 2012	Jan. 29, 2013
Test Receiver ROHDE & SCHWARZ (H)	ESIB7	100186	Nov. 29, 2011	Nov. 28, 2012
Spectrum Analyzer Agilent	E4446A	MY48250266	Aug. 24, 2011	Aug. 23, 2012
BILOG Antenna SCHWARZBECK (V)	VULB9168	9168-148	Apr. 02, 2012	Apr. 01, 2013
BILOG Antenna SCHWARZBECK (H)	VULB9168	9168-149	Apr. 06, 2012	Apr. 05, 2013
Preamplifier Agilent (V)	8447D	2944A10636	Oct. 29, 2011	Oct. 28, 2012
Preamplifier Agilent (H)	8447D	2944A10637	Oct. 29, 2011	Oct. 28, 2012
Preamplifier Agilent	8449B	3008A01959	Oct. 29, 2011	Oct. 28, 2012
RF signal cable Woken (V)	8D-FB	Cable-Hych1-01	Oct. 29, 2011	Oct. 28, 2012
RF signal cable Woken (H)	8D-FB	Cable-Hych1-02	Oct. 29, 2011	Oct. 28, 2012
Software ADT	BV ADT_Radiated_ V 7.7.03.7	NA	NA	NA
Antenna Tower (V)	MFA-440	9707	NA	NA
Antenna Tower (H)	MFA-440	970705	NA	NA
Turn Table	DS430	50303	NA	NA
Controller (V)	MF7802	074	NA	NA
Controller (H)	MF7802	08093	NA	NA
RF signal cable EAST COST Microwave	HP 160S-29	NA	Oct. 29, 2011	Oct. 28, 2012
Fix tool for Boresight antenna tower	BAF-01	1	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 1.
- 3. The FCC Site Registration No. is 477732.
- 4. The IC Site Registration No. is IC 7450F-1.
- 5. The VCCI Site Registration No. is R-1893.



Frequency range above 1GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	May 11, 2012	May 10, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSP 40	100041	Jul. 21, 2011	Jul. 20, 2012
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Apr. 02, 2012	Apr. 01, 2013
RF signal cable Woken	8D-FB	N/A	Mar. 24, 2012	Mar. 23, 2013
HORN Antenna SCHWARZBECK	BBHA 9120 D *	9120D-405	Feb. 03, 2012	Feb. 02, 2013
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Jan. 03, 2012	Jan. 02, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent (Below 1GHz)	8447D	2944A10629	Oct. 29, 2011	Oct. 28, 2012
Preamplifier Agilent (Above 1GHz)	8449B	3008A01959	Oct. 29, 2011	Oct. 28, 2012
RF signal cable HUBER+SUHNER	SUCOFLEX 104	230132/4	Nov. 03, 2011	Nov. 02, 2012
RF signal cable HUBER+SUHNER	SUCOFLEX 104	309223/4+309 218/4	Nov. 03, 2011	Nov. 02, 2012
Software ADT.	BV ADT_Radiated_ V7.6.15.9.3	NA	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA	NA
Turn Table ADT.	TT100	TT93021702	NA	NA
Controller ADT.	SC100	SC93021702	NA	NA
Fix tool for Boresight antenna tower	BAF-01	2	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 3. The test was performed in HwaYa Chamber 2.
- 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 5. The FCC Site Registration No. is 686814.
- 6. The IC Site Registration No. is IC 7450F-2.
- 7. The VCCI Site Registration No. is G-18.



4.2.3 TEST PROCEDURES

Frequency range 30MHz~1GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE: The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-Peak (QP) detection at frequency below 1GHz.



Frequency range above 1GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from 1 meter to 4 meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.

NOTE:

- 1. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak (PK) detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz for Average (AV) detection at frequency above 1GHz.
- 2. For measurement of frequency above 1000MHz, the EUT was set 3 meters away from the receiver antenna.


4.2.4 DEVIATION FROM TEST STANDARD

No deviation.		




4.2.5 TEST SETUP

Frequency range 30MHz~1GHz



Frequency range above 1GHz



*: depends on the EUT height and the antenna 3dB beamwidth both, refer to section 8.3.1.2 of ANSI C63.4:2009

For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.




4.2.7 TEST RESULTS

INPUT POWER	120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23 deg. C, 65% RH	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak , 120 kHz
TESTED BY	Ben Huang		

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	41.66	15.30 QP	30.00	-14.70	1.50 H	0	1.58	13.72	
2	61.10	14.32 QP	30.00	-15.68	2.50 H	0	0.82	13.50	
3	92.20	11.05 QP	30.00	-18.95	3.50 H	357	2.29	8.76	
4	148.58	15.40 QP	30.00	-14.60	2.00 H	333	0.57	14.83	
5	187.45	14.44 QP	30.00	-15.56	2.00 H	20	1.76	12.68	
6	234.11	13.76 QP	37.00	-23.24	1.00 H	57	0.66	13.10	

- 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.






INPUT POWER	120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz	
ENVIRONMENTAL CONDITIONS		DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak , 120 kHz	
TESTED BY	Ben Huang			

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	37.78	25.39 QP	30.00	-4.61	3.00 V	256	12.24	13.15	
2	88.32	13.26 QP	30.00	-16.74	2.00 V	20	4.43	8.83	
3	109.70	12.79 QP	30.00	-17.21	1.00 V	20	1.92	10.87	
4	158.30	14.70 QP	30.00	-15.30	1.50 V	54	0.14	14.56	
5	175.79	18.40 QP	30.00	-11.60	1.00 V	80	4.55	13.85	
6	296.31	16.58 QP	37.00	-20.42	2.00 V	20	0.89	15.69	

- 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.






INPUT POWER	120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz	
ENVIRONMENTAL CONDITIONS	25 deg. C, 64% RH	DETECTOR FUNCTION & BANDWIDTH	Peak/Average, 1 MHz	
TESTED BY	Ariel Lin			

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	2342.13	39.58 PK	74.00	-34.42	1.23 H	167	7.45	32.13	
2	2342.13	32.23 AV	54.00	-21.77	1.23 H	167	0.10	32.13	
3	2482.97	40.82 PK	74.00	-33.18	1.00 H	135	8.09	32.73	
4	2482.97	33.03 AV	54.00	-20.97	1.00 H	135	0.30	32.73	
5	2673.11	40.56 PK	74.00	-33.44	1.12 H	95	7.27	33.29	
6	2673.11	33.53 AV	54.00	-20.47	1.12 H	95	0.24	33.29	

- 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.






INPUT POWER	PUT POWER 120 Vac, 60 Hz		1-18 GHz	
ENVIRONMENTAL CONDITIONS	25 deg. C, 64% RH	DETECTOR FUNCTION & BANDWIDTH	Peak/Average, 1 MHz	
TESTED BY	Ariel Lin			

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M							
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1509.66	44.30 PK	74.00	-29.70	1.20 V	141	14.84	29.46
2	1509.66	30.04 AV	54.00	-23.96	1.20 V	141	0.58	29.46
3	2432.23	44.23 PK	74.00	-29.77	1.00 V	189	11.71	32.52
4	2432.23	33.05 AV	54.00	-20.95	1.00 V	189	0.53	32.52
5	4927.23	44.01 PK	74.00	-29.99	1.00 V	211	5.13	38.88
6	4927.23	38.95 AV	54.00	-15.05	1.00 V	211	0.07	38.88

- 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.





PHOTOGRAPHS OF THE TEST CONFIGURATION Please refer to the attached file (Test Setup Photo).



6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Hsin Chu EMC/RF Lab

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180 Tel: 886-3-5935343 Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



7 APPENDIX A - MODIFICATION RECORDERS FOR **ENGINEERING CHANGES TO THE EUT BY THE LAB** No modifications were made to the EUT by the lab during the test. --- END ---