

FCC TEST REPORT (PART 24)

REPORT NO.: RF120628C18-1

MODEL NO.: Click Plus

FCC ID: YHLBLUCLICKPUS

RECEIVED: Jun. 28, 2012

TESTED: Jun. 29 ~ Jun. 30, 2012

ISSUED: Jul. 16, 2012

APPLICANT: CT Asia

ADDRESS: Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun

road, Kwun Tong, Kowloon, Hongkong

ISSUED BY: Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New

Taipei City, Taiwan (R.O.C.)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Report No.: RF120628C18-1 1 of 28 Report Format Version 5.0.0



TABLE OF CONTENTS

RELEAS	SE CONTROL RECORD	
1	CERTIFICATION	. 4
2	SUMMARY OF TEST RESULTS	. 5
2.1	MEASUREMENT UNCERTAINTY	. 5
2.2	TEST SITE AND INSTRUMENTS	. 6
3	GENERAL INFORMATION	. 7
3.1	GENERAL DESCRIPTION OF EUT	. 7
3.2	CONFIGURATION OF SYSTEM UNDER TEST	. 8
3.3	DESCRIPTION OF SUPPORT UNITS	
3.4	TEST ITEM AND TEST CONFIGURATION	
3.5	EUT OPERATING CONDITIONS	10
3.6	GENERAL DESCRIPTION OF APPLIED STANDARDS	
4	TEST TYPES AND RESULTS	
4.1	OUTPUT POWER MEASUREMENT	
4.1.1	LIMITS OF OUTPUT POWER MEASUREMENT	
4.1.2	TEST PROCEDURES	
4.1.3	TEST SETUP	
4.1.4	TEST RESULTS	
4.2	FREQUENCY STABILITY MEASUREMENT	
4.2.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT	
4.2.2	TEST PROCEDURE	
4.2.3	TEST SETUP	
4.2.4	TEST RESULTS	
4.3	OCCUPIED BANDWIDTH MEASUREMENT	
4.3.1	TEST PROCEDURES	_
4.3.2	TEST SETUP	
4.3.3	TEST RESULTS	
4.4	BAND EDGE MEASUREMENT	
4.4.1	LIMITS OF BAND EDGE MEASUREMENT	
4.4.2	TEST SETUP	
4.4.3	TEST PROCEDURES	
4.4.4	TEST RESULTS	
4.5	CONDUCTED SPURIOUS EMISSIONS	
4.5.1	LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	
4.5.2	TEST PROCEDURE	
4.5.3	TEST SETUP	
4.5.4	TEST RESULTS	
4.6	RADIATED EMISSION MEASUREMENT	
4.6.1	LIMITS OF RADIATED EMISSION MEASUREMENT	22
4.6.2	TEST PROCEDURES	
4.6.3	DEVIATION FROM TEST STANDARD	
4.6.4	TEST SETUP	
4.6.5	TEST RESULTS	
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	
6	INFORMATION ON THE TESTING LABORATORIES	
7	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES 1	
=	THE EUT BY THE LAB	

2 of 28



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120628C18-1	Original release	Jul. 16, 2012

Report No.: RF120628C18-1 3 of 28 Report Format Version 5.0.0



CERTIFICATION

PRODUCT: GSM mobile

MODEL: Click Plus

BRAND: Blu

APPLICANT: CT Asia

TESTED: Jun. 29 ~ Jun. 30, 2012

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 24, Subpart E

The above equipment (model: Click Plus) has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: Jul. 16, 2012

Ivonne Wu / Senior Specialist

Jul. 16, 2012

APPROVED BY



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

	APPLIED STANDARD: FCC Part 24 & Part 2						
STANDARD SECTION	TEST TYPE	RESULT	REMARK				
2.1046 24.232	Equivalent isotropically radiated power	PASS	Meet the requirement of limit.				
24.232(d)	Peak to Average Ratio	PASS	Meet the requirement of limit.				
2.1055 24.235	Frequency Stability	PASS	Meet the requirement of limit.				
2.1049 24.238(b)	Occupied Bandwidth	PASS	Meet the requirement of limit.				
24.238(b)	Band Edge Measurements	PASS	Meet the requirement of limit.				
2.1051 24.238	Conducted Spurious Emissions	PASS	Meet the requirement of limit.				
2.1053 24.238	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -16.44 dB at 11280.0MHz.				

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver Agilent	N9038A	MY51210203	Dec. 22, 2011	Dec. 21, 2012
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 21, 2011	Dec. 20, 2012
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 20, 2011	Dec. 19, 2012
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Dec. 20, 2011	Dec. 19, 2012
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 20, 2011	Dec. 19, 2012
Preamplifier EMCI	EMC 012645	980115	Dec. 30, 2011	Dec. 29, 2012
Preamplifier EMCI	EMC 330H	980112	Dec. 30, 2011	Dec. 29, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4	Oct. 21, 2011	Oct. 20, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Jan. 02, 2012	Jan. 01, 2013
RF signal cable Worken	RG-213	NA	Jan. 02, 2012	Jan. 01, 2013
Software	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
Mini-Circuits Power Splitter	ZN2PD-9G	NA	Mar. 23, 2012	Mar. 22, 2013
JFW 20Db attenuation	50HF-020-SMA	NA	NA	NA
Communications Tester-Wireless	E5515C	MY50266653	Sep. 28, 2011	Sep. 27, 2012
Radio Communication Analyzer	MT8820C	6201010284	Aug. 01, 2011	Jul. 31, 2012

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 9.
- 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 460141.
- 5. The IC Site Registration No. is IC 7450F-4.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	GSM mobile
MODEL NO.	Click Plus
POWER SUPPLY	5.0Vdc (adapter)
TOWER GOTTE	3.7Vdc (battery)
MODULATION TYPE	GMSK
FREQUENCY RANGE	1850.2MHz ~ 1909.8MHz
MAX. EIRP POWER	0.707Watts
EMISSION DESIGNATOR	245KGXW
ANTENNA TYPE	Fixed Internal antenna with 1.26 dBi gain
I/O PORTS	Refer to users' manual
DATA CABLE	Refer to Note as below
ACCESSORY DEVICES	Refer to Note as below

NOTE:

1. The EUT contains the following accessories.


ITEM	BRAND	MODEL	SPECIFICATION
Adapter	BLU	US300507	Input: 100-240Vac, 150mA Output: 5Vdc, 500mA
Battery	BLU	N5C60T	Rating: 3.7Vdc, 600mAh Type: Li-ion
USB Cable	BLU	NA	0.93m non-shielded cable w/o core
Earphone	BLU	NA	1.29m non-shielded cable w/o core

2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.




3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR E.I.R.P. TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.



3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Z-plane for EIRP and X-axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
-	EIRP	512 to 810	512, 661, 810	GSM
-	FREQUENCY STABILITY	512 to 810	661	GSM
-	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM
-	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GSM
-	BAND EDGE	512 to 810	512, 810	GSM
-	CONDCUDETED EMISSION	512 to 810	661	GSM
-	RADIATED EMISSION	512 to 810	661	GSM

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	25deg. C, 65%RH	3.7Vdc	Phoenix Chen
FREQUENCY STABILITY	25deg. C, 65%RH	3.7Vdc	Phoenix Chen
OCCUPIED BANDWIDTH	25deg. C, 65%RH	3.7Vdc	Phoenix Chen
PEAK TO AVERAGE RATIO	25deg. C, 65%RH	3.7Vdc	Phoenix Chen
BAND EDGE	25deg. C, 65%RH	3.7Vdc	Phoenix Chen
CONDCUDETED EMISSION	25deg. C, 65%RH	3.7Vdc	Phoenix Chen
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu



3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2 FCC 47 CFR Part 24 ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.



4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP

4.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G
- d. EIRP = Output power level of S.G TX cable loss + Antenna gain of substitution horn.


CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with GSM link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.



4.1.3 TEST SETUP

EIRP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).



4.1.4 TEST RESULTS

AVERAGE CONDUCTED OUTPUT POWER (dBm)

Band	GSM1900			
Channel	512 661 810			
Frequency (MHz)	1850.2	1880.0	1909.8	
GSM (GMSK, 1 slot)	28.55	28.54	28.66	

AVERAGE EIRP POWER (dBm)

GSM 1900

Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(W)	Polarization (H/V)
	512	1850.2	-24.76	53.09	28.33	0.681	Н
	661	1880.0	-25.01	53.51	28.50	0.707	Н
Z	810	1909.8	-25.75	54.01	28.26	0.669	Н
	512	1850.2	-33.02	53.66	20.64	0.116	V
	661	1880.0	-34.01	54.03	20.02	0.100	V
	810	1909.8	-34.40	54.37	19.97	0.099	V

Report No.: RF120628C18-1 13 of 28 Report Format Version 5.0.0



4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

4.2.2 TEST PROCEDURE

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}$ C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP





4.2.4 TEST RESULTS

FREQUENCY ERROR VS. VOLTAGE

\\O TACE (\\o to)	FREQUENCY ERROR (ppm)	LIBAIT (10 to 100)	
VOLTAGE (Volts)	GSM	LIMIT (ppm)	
3.7	0.01	2.5	
3.5	0.02	2.5	
4.2	0.02	2.5	

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)	LIMIT (nom)
TEMP. (C)	GSM	LIMIT (ppm)
-10	0.01	2.5
0	0.02	2.5
10	0.02	2.5
20	0.02	2.5
30	0.02	2.5
40	0.01	2.5
50	0.02	2.5




4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.


4.3.2 TEST SETUP





4.3.3 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (kHz) GSM
512	1850.2	243.92
661	1880.0	244.90
810	1909.8	243.22






4.4 BAND EDGE MEASUREMENT

4.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 TEST SETUP




4.4.3 TEST PROCEDURES

- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1.0 MHz. RB of the spectrum is 3kHz and VB of the spectrum is 10kHz.
- c. Record the max trace plot into the test report.



4.4.4 TEST RESULTS





4.5 CONDUCTED SPURIOUS EMISSIONS


4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$. The emission limit equal to -13dBm.

4.5.2 TEST PROCEDURE


- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 30MHz to 19.1GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.5.3 TEST SETUP





4.5.4 TEST RESULTS





4.6 RADIATED EMISSION MEASUREMENT

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$. The emission limit equal to -13dBm.

4.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. EIRP = Output power level of S.G TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power 2.15dBi.


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.6.3 DEVIATION FROM TEST STANDARD

No deviation



4.6.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).




4.6.5 TEST RESULTS

GSM



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Site : 966 Chamber 5

Condition : PART22/24 3m EIRP_RSE_1G~19G_3 HORIZONTAL

Brand/Model: Click Plus Remark : PCS1900 Link Tested by : Anson Lin Temprature : 25℃


Humidity : 65% Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
112	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	40.80	-55.73	-54.27	-13.00	-42.73	-1.46	Peak
2	92.10	-55.72	-45.18	-13.00	-42.72	-10.54	Peak
3	192.27	-57.84	-50.80	-13.00	-44.84	-7.04	Peak
4	339.90	-64.81	-58.72	-13.00	-51.81	-6.09	Peak
5	566.00	-66.62	-65.34	-13.00	-53.62	-1.28	Peak
6	935.60	-61.71	-65.12	-13.00	-48.71	3.41	Peak
7 pp	3760.00	-29.70	-22.97	-13.00	-16.70	-6.73	Peak
8	5640.00	-37.88	-38.09	-13.00	-24.88	0.21	Peak
9	9400.00	-37.55	-47.09	-13.00	-24.55	9.54	Peak
10	11280.00	-33.93	-45.06	-13.00	-20.93	11.13	Peak





Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Site : 966 Chamber 5

Condition : PART22/24 3m EIRP_RSE_1G~19G_3 VERTICAL

Brand/Model: Click Plus
Remark : PCS1900 Link
Tested by : Anson Lin
Temprature : 25°C
Humidity : 65%
Plane : X

		Freq	Level		Limit Line		Factor	Remark
	(1 <u>2</u>	MHz	dBm/m	dBm	dBm/m	dB	dB/m	<u> </u>
1		33.24	-42.52	-41.41	-13.00	-29.52	-1.11	Peak
2		42.15	-39.11	-37.78	-13.00	-26.11	-1.33	Peak
3		91.29	-53.51	-42.95	-13.00	-40.51	-10.56	Peak
4		430.90	-69.78	-64.92	-13.00	-56.78	-4.86	Peak
5		624.80	-65.10	-65.19	-13.00	-52.10	0.09	Peak
6		832.70	-62.40	-64.72	-13.00	-49.40	2.32	Peak
7		3760.00	-33.17	-26.44	-13.00	-20.17	-6.73	Peak
8		5640.00	-32.01	-32.22	-13.00	-19.01	0.21	Peak
9		9400.00	-32.03	-41.57	-13.00	-19.03	9.54	Peak
10	pp	11280.00	-29.44	-40.57	-13.00	-16.44	11.13	Peak



PHOTOGRAPHS OF THE TEST CONFIGURATION Please refer to the attached file (Test Setup Photo).



6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab: Hsin Chu EMC/RF Lab:

Tel: 886-2-26052180 Tel: 886-3-5935343 Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING

CHANGES TO THE EUT BY THE LAB
No any modifications are made to the EUT by the lab during the test.
END
END