FCC SAR Test Report

APPLICANT : CT Asia

EQUIPMENT : Smart phone

BRAND NAME : BLU

MODEL NAME : ENERGY X

FCC ID : YHLBLUENERGYX

STANDARD : FCC 47 CFR Part 2 (2.1093)

ANSI/IEEE C95.1-1992

IEEE 1528-2003

We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Eric Huang / Deputy Manager

Erle huan?

Approved by: Jones Tsai / Manager

2353

Report No. : FA561807

SPORTON INTERNATIONAL (SHENZHEN) INC.

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595

Issued Date: Jul. 22, 2015 Form version.: 150415 FCC ID: YHLBLUENERGYX Page 1 of 44

Table of Contents

1. Statement of Compliance	
2. Administration Data	
3. Guidance Standard	5
4. Equipment Under Test (EUT)	6
4.1 General Information	6
4.2 Maximum Tune-up Limit	7
5. RF Exposure Limits	8
5.1 Uncontrolled Environment	8
5.2 Controlled Environment	
6. Specific Absorption Rate (SAR)	
6.1 Introduction	
6.2 SAR Definition	
7. System Description and Setup	
8. Measurement Procedures	11
8.1 Spatial Peak SAR Evaluation	11
8.2 Power Reference Measurement	12
8.3 Area Scan	
8.4 Zoom Scan	
8.5 Volume Scan Procedures	
8.6 Power Drift Monitoring	
9. Test Equipment List	
10. System Verification	15
10.1 Tissue Verification	
10.2 System Performance Check Results	
11. RF Exposure Positions	
11.1 Ear and handset reference point	17
11.2 Definition of the cheek position	
11.3 Definition of the tilt position	
11.4 Body Worn Accessory	
11.5 Wireless Router	20
12. Conducted RF Output Power (Unit: dBm)	
13. Bluetooth Exclusions Applied	28
14. Antenna Location	
15. SAR Test Results	
15.1 Head SAR	
15.2 Hotspot SAR	
15.3 Body Worn Accessory SAR	34
15.4 Repeated SAR Measurement	
16. Simultaneous Transmission Analysis	36
16.1 Head Exposure Conditions	
16.2 Hotspot Exposure Conditions	
16.3 Body-Worn Accessory Exposure Conditions	41
17. Uncertainty Assessment	42
18. References	
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

Revision History

Report No. : FA561807

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA561807	Rev. 01	Initial issue of report	Jul. 22, 2015

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595

Issued Date : Jul. 22, 2015 Form version. : 150415 FCC ID: YHLBLUENERGYX Page 3 of 44

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **CT Asia**, **Smart phone**, **ENERGY X** are as follows.

Report No. : FA561807

		Highest SAR Summary			
Equipment Class	Frequency Band	Head (Separation 0mm) 1g SAR (W/kg)	Body-worn (Separation 10mm) 1g SAR (W/kg)	Wireless Router (Separation 10mm) 1g SAR (W/kg)	Highest Simultaneous Transmission 1g SAR (W/kg)
	GSM850	0.34	0.58	0.74	
	GSM1900	0.27	0.73	1.03	
PCE	WCDMA Band V	0.30	0.51	0.57	1.30
	WCDMA Band IV	0.42	1.01	1.20	
	WCDMA Band II	0.29	0.71	0.87	
DTS	WLAN 2.4GHz Band	0.88	0.17	0.17	1.30
Date of Testing:			Jun. 1	8, 2015 ~ Jul. 11	, 2015

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2. Administration Data

Testing Laboratory			
Test Site SPORTON INTERNATIONAL (SHENZHEN) INC.			
Test Site Location	1F & 2F,Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China		
	TEL: +86-755-8637-9589		
	FAX: +86-755-8637-9595		

Report No. : FA561807

Applicant Applicant		
Company Name CT Asia		
Address	Unit1309-11, 13th Floor 9 Wing Hong Street Cheung Sha Wan Kowloon, Hong Kong	

Manufacturer			
Company Name Longcheer Technology (Shanghai) Co., Ltd.			
Address Building 1, No.401, Caobao Rd., Xuhui District, Shanghai, P.R.China			

3. Guidance Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r02
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r02
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r01
- FCC KDB 941225 D01 3G SAR Procedures v03
- FCC KDB 941225 D06 Hotspot Mode SAR v02

4. Equipment Under Test (EUT)

4.1 General Information

Product Feature & Specification				
Equipment Name	Smart phone			
Brand Name	LU			
Model Name	NERGY X			
FCC ID	ILBLUENERGYX			
IMEI Code SIM1: 865843022788159 SIM2: 865843022786302				
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz			
Mode	· GSM/GPRS/EGPRS · RMC/AMR 12.2Kbps · HSDPA · HSUPA · HSPA+ (Downlink Only) · 802.11b/g/n HT20/HT40 · Bluetooth v3.0+EDR, Bluetooth v4.0 LE			
HW Version	LWDM034			
SW Version BLU_E010U_V01_GENERIC				
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.			
EUT Stage	Pre-Production			
Domorks				

Report No. : FA561807

Remark:

- 1. This device 2.4GHz supports hotspot operation.

- This device 2.4GH2 supports hotspot operation.
 The EUT do not support DTM function.
 This device supported VoIP in GPRS, EGPRS, WCDMA (e.g. 3rd party VoIP).
 This device supports GRPS/EGPRS mode up to multi-slot class 12.
 This device has 2 SIM slots and supports dual SIM dual Standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active).

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595 Issued Date: Jul. 22, 2015 FCC ID: YHLBLUENERGYX Form version.: 150415 Page 6 of 44

4.2 Maximum Tune-up Limit

Mode	Burst average power(dBm)		
Wode	GSM 850	GSM 1900	
GSM (GMSK, 1 Tx slot)	33.50	30.50	
GPRS (GMSK, 1 Tx slot)	33.50	30.50	
GPRS (GMSK, 2 Tx slots)	32.50	29.50	
GPRS (GMSK, 3 Tx slots)	30.50	28.00	
GPRS (GMSK, 4 Tx slots)	29.50	27.00	
EDGE (8PSK, 1 Tx slot)	27.00	26.00	
EDGE (8PSK, 2 Tx slots)	26.00	25.00	
EDGE (8PSK, 3 Tx slots)	24.50	23.00	
EDGE (8PSK, 4 Tx slots)	23.00	22.00	

Report No. : FA561807

Mode	Average power (dBm)			
Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	
AMR 12.2Kbps	23.50	23.50	23.50	
RMC 12.2Kbps	23.50	23.50	23.50	
HSDPA Subtest-1	22.50	22.00	22.00	
HSDPA Subtest-2	22.50	22.00	22.00	
HSDPA Subtest-3	22.00	21.50	21.50	
HSDPA Subtest-4	22.00	21.50	21.50	
HSUPA Subtest-1	21.00	21.00	21.00	
HSUPA Subtest-2	20.50	20.00	20.00	
HSUPA Subtest-3	21.50	21.00	21.00	
HSUPA Subtest-4	20.50	20.00	20.00	
HSUPA Subtest-5	22.50	22.00	22.00	

Mode			Maximum Average Power (dBm)
		CH 1	13.00
	802.11b	CH 6	12.50
		CH 11	13.00
		CH 1	12.00
2.404-	802.11g 2.4GHz	CH 6	13.00
2.4GHZ		CH 11	12.00
		CH 1	11.50
	802.11n-HT20	CH 6	10.50
		CH 11	11.50
802.11n-HT40		n-HT40	10.50
Bluetooth v3.0+EDR		EDR	6.00
Bluetooth v4.0 LE		LE	-1.50

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Report No. : FA561807

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

Report No.: FA561807

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



Report No. : FA561807

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing,
 AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps,
- The phantom, the device holder and other accessories according to the targeted measurement.

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.

Report No.: FA561807

- Read the WWAN RF power level from the base station simulator.
- For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power
- Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- Measure SAR results for the highest power channel on each testing position.
- Find out the largest SAR result on these testing positions of each band (e)
- Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- Zoom scan (c)
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- Extraction of the measured data (grid and values) from the Zoom Scan
- Calculation of the SAR value at every measurement point based on all stored data (A/D values and (b) measurement parameters)
- Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface (e)
- Calculation of the averaged SAR within masses of 1g and 10g

SPORTON INTERNATIONAL (SHENZHEN) INC. TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595 Issued Date : Jul. 22, 2015 Form version.: 150415

FCC ID: YHLBLUENERGYX

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Report No.: FA561807

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz				
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$				
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°				
	\leq 2 GHz: \leq 15 mm 2 – 3 GHz: \leq 12 mm	$3 - 4 \text{ GHz:} \le 12 \text{ mm}$ $4 - 6 \text{ GHz:} \le 10 \text{ mm}$				
Maximum area scan spatial resolution: $\Delta x_{\text{Area}},\Delta y_{\text{Area}}$	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.					

SPORTON INTERNATIONAL (SHENZHEN) INC.

8.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Report No. : FA561807

Zoom scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan s	spatial reso	lution: Δx _{Zoom} , Δy _{Zoom}	\leq 2 GHz: \leq 8 mm 2 – 3 GHz: \leq 5 mm [*]	$3 - 4 \text{ GHz: } \le 5 \text{ mm}^*$ $4 - 6 \text{ GHz: } \le 4 \text{ mm}^*$
	uniform	grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	$3 - 4 \text{ GHz: } \le 4 \text{ mm}$ $4 - 5 \text{ GHz: } \le 3 \text{ mm}$ $5 - 6 \text{ GHz: } \le 2 \text{ mm}$
Maximum zoom scan spatial resolution, normal to phantom surface	graded	Δz _{Zoom} (1): between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4 \text{ GHz: } \le 3 \text{ mm}$ $4 - 5 \text{ GHz: } \le 2.5 \text{ mm}$ $5 - 6 \text{ GHz: } \le 2 \text{ mm}$
	grid	Δz _{Zoom} (n>1): between subsequent points	≤ 1.5·Δz	Z _{Oom} (n-1)
Minimum zoom scan volume x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

8.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is $\leq 1.4 \text{ W/kg}$, $\leq 8 \text{ mm}$, $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

9. Test Equipment List

Manufacturer	Name of Equipment	Type/Medal	Carial Number	Calib	ration
Manufacturer	Name of Equipment	Type/Model	Serial Number	Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d091	Nov. 21, 2014	Nov. 20, 2015
SPEAG	1750MHz System Validation Kit	D1750V2	1069	Nov. 21, 2014	Nov. 20, 2015
SPEAG	1900MHz System Validation Kit	D1900V2	5d118	Nov. 21, 2014	Nov. 20, 2015
SPEAG	2450MHz System Validation Kit	D2450V2	840	Nov. 19, 2014	Nov. 18, 2015
SPEAG	Data Acquisition Electronics	DAE4	1303	Dec. 11, 2014	Dec. 10, 2015
SPEAG	Data Acquisition Electronics	DAE4	1386	Feb. 19, 2015	Feb. 18, 2016
SPEAG	Dosimetric E-Field Probe	EX3DV4	3819	Nov. 13, 2014	Nov. 12, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	7346	Jan. 08, 2015	Jan. 07, 2016
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1670	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1671	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Agilent	Wireless Communication Test Set	E5515C	MY50267224	Sep. 29, 2014	Sep. 28, 2015
R&S	Network Analyzer	ZVB8	100106	Sep. 29, 2014	Sep. 28, 2015
Speag	Dielectric Assessment KIT	DAK-3.5	1032	NCR	NCR
R&S	Signal Generator	SMBV100A	258305	Jan. 23, 2015	Jan. 22, 2016
Anritsu	Power Sensor	MA2411B	1207253	Jan. 28, 2015	Jan. 27, 2016
Anritsu	Power Meter	ML2495A	1218010	Jan. 28, 2015	Jan. 27, 2016
ARRA	Power Divider	A3200-2	N/A	NA	NA
R&S	Spectrum Analyzer	FSP30	101362	Sep. 29, 2014	Sep. 28, 2015
Agilent	Dual Directional Coupler	778D	50422	No	te1
Woken	Attenuator 1	WK0602-XX	N/A	No	te1
PE	Attenuator 2	PE7005-10	N/A	No	te1
PE	Attenuator 3	PE7005- 3	N/A	No	te1
AR	Power Amplifier	5S1G4M2	0328767	No	te1
Mini-Circuits	Power Amplifier	ZVE-3W	162601250	No	te1
Mini-Circuits	Power Amplifier	ZHL-42W+	13440021344	No	te1

Report No.: FA561807

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

10. System Verification

10.1 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target

Report No. : FA561807

tissue parameters required for routine SAR evaluation.

Frequency	Water	Sugar	Cellulose	Salt	Preventol	DGBE	Conductivity	Permittivity				
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	(σ)	(ɛr)				
	For Head											
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5				
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0				
2450	55.0	0	0	0	0	45.0	1.80	39.2				
				For Body								
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2				
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3				
2450	68.6	0	0	0	0	31.4	1.95	52.7				

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ε _r)	Conductivity Target (σ)	Permittivity Target (ε _r)	Delta (σ) (%)	Delta (ε _r) (%)	Limit (%)	Date
835	Head	22.7	0.904	41.212	0.90	41.50	0.44	-0.69	±5	Jun. 20, 2015
1750	Head	22.6	1.378	41.340	1.37	40.10	0.58	3.09	±5	Jun. 20, 2015
1900	Head	22.9	1.417	40.994	1.40	40.00	1.21	2.49	±5	Jun. 20, 2015
2450	Head	22.9	1.809	37.604	1.80	39.20	0.50	-4.07	±5	Jul. 10, 2015
835	Body	22.6	0.991	55.697	0.97	55.20	2.16	0.90	±5	Jun. 19, 2015
1750	Body	22.8	1.514	53.575	1.49	53.40	1.61	0.33	±5	Jun. 18, 2015
1900	Body	22.7	1.529	53.216	1.52	53.30	0.59	-0.16	±5	Jun. 18, 2015
2450	Body	22.8	1.977	51.617	1.95	52.70	1.38	-2.06	±5	Jul. 11, 2015

10.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured SAR (W/kg)	Targeted SAR (W/kg)	Normalized SAR (W/kg)	Deviation (%)
Jun. 20, 2015	835	Head	250	4d091	7346	1386	2.21	9.11	8.84	-2.96
Jun. 20, 2015	1750	Head	250	1069	3819	1303	9.55	37.10	38.2	2.96
Jun. 20, 2015	1900	Head	250	5d118	3819	1303	10.50	40.10	42	4.74
Jul. 10, 2015	2450	Head	250	840	3819	1303	14.20	52.30	56.8	8.60
Jun. 19, 2015	835	Body	250	4d091	7346	1386	2.24	9.60	8.96	-6.67
Jun. 18, 2015	1750	Body	250	1069	3819	1303	10.10	38.10	40.4	6.04
Jun. 18, 2015	1900	Body	250	5d118	3819	1303	10.70	40.00	42.8	7.00
Jul. 11, 2015	2450	Body	250	840	3819	1303	13.20	51.00	52.8	3.53




Fig 8.3.1 System Performance Check Setup

Fig 8.3.2 Setup Photo

Report No. : FA561807

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595

Issued Date: Jul. 22, 2015 FCC ID: YHLBLUENERGYX Form version.: 150415 Page 16 of 44

11. RF Exposure Positions

11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.



Fig 9.1.1 Front, back, and side views of SAM twin phantom





Fig 9.1.2 Close-up side view of phantom showing the ear region.



Report No. : FA561807

Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595 Issued Date: Jul. 22, 2015 Page 17 of 44 Form version.: 150415

FCC ID: YHLBLUENERGYX

SPORTON LAB. FCC SAR Test Report

11.2 Definition of the cheek position

- Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
- Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width wt of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width wb of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2). especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
- Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
- Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
- While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
- Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
- While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.





Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case



Report No.: FA561807

Fig 9.2.2 Handset vertical and horizontal reference lines-"clam-shell case"








Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

SPORTON INTERNATIONAL (SHENZHEN) INC. TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595 Issued Date: Jul. 22, 2015 Form version.: 150415

FCC ID: YHLBLUENERGYX

SPORTON LAB. FCC SAR Test Report

11.3 Definition of the tilt position

Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.

Report No.: FA561807

- While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
- Rotate the handset around the horizontal line by 15°.
- 4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595 Issued Date: Jul. 22, 2015 Form version.: 150415 FCC ID: YHLBLUENERGYX Page 19 of 44

11.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB 648474 D04v01r02, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v05r02 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is < 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Report No.: FA561807

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-chip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

11.5 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC HDB Publication 941225 D06 v02 where SAR test considerations for handsets (L \times W \ge 9 cm \times 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined form general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05r02 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

12. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

1. Per KDB 447498 D01v05r02, the maximum output power channel is used for SAR testing and for further SAR test reduction.

Report No. : FA561807

- 2. Per KDB 941225 D01v03, considering the possibility of e.g. 3rd party VoIP operation for Head and body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.
- 3. Per KDB 941225 D01v03, for Hotspot SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance, for modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested, therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.

SIM1:

Burst Ave	erage Pov	ver (dBm)	Tune-up	Frame-Av	erage Pov	wer (dBm)	Tune-up
128	189	251	Limit	128	189	251	Limit
824.2	836.4	848.8	(dBm)	824.2	836.4	848.8	(dBm)
32.66	32.69	32.72	33.50	23.66	23.69	23.72	24.50
32.68	32.69	32.71	33.50	23.68	23.69	23.71	24.50
31.91	31.92	31.95	32.50	25.91	25.92	25.95	26.50
30.09	30.17	30.19	30.50	25.83	25.91	25.93	26.24
28.94	29.05	29.07	29.50	25.94	26.05	<mark>26.07</mark>	26.50
26.73	26.65	26.63	27.00	17.73	17.65	17.63	18.00
25.82	25.73	25.67	26.00	19.82	19.73	19.67	20.00
23.92	23.78	23.72	24.50	19.66	19.52	19.46	20.24
22.75	22.68	22.61	23.00	19.75	19.68	19.61	20.00
Burst Ave	erage Pov	ver (dBm)	Tune-up	Frame-Av	erage Pov	wer (dBm)	Tune-up
512	661	810	Limit	512	661	810	Limit
1850.2	1880	1909.8	(dBm)	1850.2	1880	1909.8	(dBm)
1850.2 29.78	1880 29.75	1909.8 29.73	(dBm) 30.50	1850.2 20.78	1880 20.75		(dBm) 21.50
						1909.8	
<mark>29.78</mark>	29.75	29.73	30.50	20.78	20.75	1909.8 20.73	21.50
29.78 29.77	29.75 29.76	29.73 29.74	30.50 30.50	20.78 20.77	20.75 20.76	1909.8 20.73 20.74	21.50 21.50
29.78 29.77 29.04	29.75 29.76 29.04	29.73 29.74 29.03	30.50 30.50 29.50	20.78 20.77 23.04	20.75 20.76 23.04	1909.8 20.73 20.74 23.03	21.50 21.50 23.50
29.78 29.77 29.04 27.30	29.75 29.76 29.04 27.28	29.73 29.74 29.03 27.27	30.50 30.50 29.50 28.00	20.78 20.77 23.04 23.04	20.75 20.76 23.04 23.02	1909.8 20.73 20.74 23.03 23.01	21.50 21.50 23.50 23.74
29.78 29.77 29.04 27.30 26.21	29.75 29.76 29.04 27.28 26.18	29.73 29.74 29.03 27.27 26.17	30.50 30.50 29.50 28.00 27.00	20.78 20.77 23.04 23.04 23.21	20.75 20.76 23.04 23.02 23.18	1909.8 20.73 20.74 23.03 23.01 23.17	21.50 21.50 23.50 23.74 24.00
29.78 29.77 29.04 27.30 26.21 25.74	29.75 29.76 29.04 27.28 26.18 25.72	29.73 29.74 29.03 27.27 26.17 25.61	30.50 30.50 29.50 28.00 27.00 26.00	20.78 20.77 23.04 23.04 23.21 16.74	20.75 20.76 23.04 23.02 23.18 16.72	1909.8 20.73 20.74 23.03 23.01 23.17 16.61	21.50 21.50 23.50 23.74 24.00 17.00
	128 824.2 32.66 32.68 31.91 30.09 28.94 26.73 25.82 23.92 22.75 Burst Ave	128 189 824.2 836.4 32.66 32.69 32.68 32.69 31.91 31.92 30.09 30.17 28.94 29.05 26.73 26.65 25.82 25.73 23.92 23.78 22.75 22.68 Burst Average Pow	128 189 251 824.2 836.4 848.8 32.66 32.69 32.72 32.68 32.69 32.71 31.91 31.92 31.95 30.09 30.17 30.19 28.94 29.05 29.07 26.73 26.65 26.63 25.82 25.73 25.67 23.92 23.78 23.72 22.75 22.68 22.61 Burst Average Power (dBm)	128 189 251 Limit (dBm) 824.2 836.4 848.8 (dBm) 32.66 32.69 32.72 33.50 32.68 32.69 32.71 33.50 31.91 31.92 31.95 32.50 30.09 30.17 30.19 30.50 28.94 29.05 29.07 29.50 26.73 26.65 26.63 27.00 25.82 25.73 25.67 26.00 23.92 23.78 23.72 24.50 22.75 22.68 22.61 23.00 Burst Average Power (dBm) Tune-up 512 661 810 Limit	128 189 251 Limit (dBm) 128 824.2 836.4 848.8 (dBm) 824.2 32.66 32.69 32.72 33.50 23.66 32.68 32.69 32.71 33.50 23.68 31.91 31.92 31.95 32.50 25.91 30.09 30.17 30.19 30.50 25.83 28.94 29.05 29.07 29.50 25.94 26.73 26.65 26.63 27.00 17.73 25.82 25.73 25.67 26.00 19.82 23.92 23.78 23.72 24.50 19.66 22.75 22.68 22.61 23.00 19.75 Burst Average Power (dBm) Tune-up Frame-Av	128 189 251 Limit 128 189 824.2 836.4 848.8 (dBm) 824.2 836.4 32.66 32.69 32.72 33.50 23.66 23.69 31.91 31.92 31.95 32.50 25.91 25.92 30.09 30.17 30.19 30.50 25.83 25.91 28.94 29.05 29.07 29.50 25.94 26.05 26.73 26.65 26.63 27.00 17.73 17.65 25.82 25.73 25.67 26.00 19.82 19.73 23.92 23.78 23.72 24.50 19.66 19.52 22.75 22.68 22.61 23.00 19.75 19.68 Burst Average Power (dBm) Tune-up Frame-Average Powerage	824.2 836.4 848.8 (dBm) 824.2 836.4 848.8 32.66 32.69 32.72 33.50 23.66 23.69 23.72 32.68 32.69 32.71 33.50 23.68 23.69 23.71 31.91 31.92 31.95 32.50 25.91 25.92 25.95 30.09 30.17 30.19 30.50 25.83 25.91 25.93 28.94 29.05 29.07 29.50 25.94 26.05 26.07 26.73 26.65 26.63 27.00 17.73 17.65 17.63 25.82 25.73 25.67 26.00 19.82 19.73 19.67 23.92 23.78 23.72 24.50 19.66 19.52 19.46 22.75 22.68 22.61 23.00 19.75 19.68 19.61 Burst Average Power (dBm)

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

SPORTON INTERNATIONAL (SHENZHEN) INC.TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595



SPORTON LAB. FCC SAR Test Report

Report No.: FA561807

SIM2:								
Band GSM850	Burst Ave	erage Pov	ver (dBm)	Tune-up	Frame-Av	rerage Pov	wer (dBm)	Tune-up
TX Channel	128	189	251	Limit	128	189	251	Limit
Frequency (MHz)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8	(dBm)
GSM (GMSK, 1 Tx slot)	32.66	32.68	32.71	33.50	23.66	23.68	23.71	24.50
GPRS (GMSK, 1 Tx slot) – CS1	32.59	32.61	32.66	33.50	23.59	23.61	23.66	24.50
GPRS (GMSK, 2 Tx slots) – CS1	31.83	31.87	31.89	32.50	25.83	25.87	25.89	26.50
GPRS (GMSK, 3 Tx slots) – CS1	30.07	30.08	30.14	30.50	25.81	25.82	25.88	26.24
GPRS (GMSK, 4 Tx slots) – CS1	28.94	28.97	29.04	29.50	25.94	25.97	<mark>26.04</mark>	26.50
EDGE (8PSK, 1 Tx slot) – MCS5	26.62	26.61	26.51	27.00	17.62	17.61	17.51	18.00
EDGE (8PSK, 2 Tx slots) – MCS5	25.65	25.64	25.56	26.00	19.65	19.64	19.56	20.00
EDGE (8PSK, 3 Tx slots) – MCS5	23.71	23.68	23.55	24.50	19.45	19.42	19.29	20.24
EDGE (8PSK, 4 Tx slots) – MCS5	22.62	22.57	22.47	23.00	19.62	19.57	19.47	20.00
Band GSM1900	Burst Ave	erage Pov	ver (dBm)	Tune-up	Frame-Av	erage Pov	wer (dBm)	Tune-up
TX Channel	512	661	810	Limit	512	661	810	Limit
Frequency (MHz)	1850.2	1880	1909.8	(dBm)	1850.2	1880	1909.8	(dBm)
GSM (GMSK, 1 Tx slot)	<mark>29.76</mark>	29.74	29.72	30.50	20.76	20.74	20.72	21.50
GPRS (GMSK, 1 Tx slot) – CS1	29.72	29.71	29.70	30.50	20.72	20.71	20.70	21.50
GPRS (GMSK, 2 Tx slots) – CS1	28.98	28.94	28.97	29.50	22.98	22.94	22.97	23.50
GPRS (GMSK, 3 Tx slots) – CS1	27.25	27.23	27.22	28.00	22.99	22.97	22.96	23.74
GPRS (GMSK, 4 Tx slots) – CS1	26.15	26.13	26.12	27.00	<mark>23.15</mark>	23.13	23.12	24.00
EDGE (8PSK, 1 Tx slot) – MCS5	25.65	25.60	25.42	26.00	16.65	16.60	16.42	17.00
EDGE (8PSK, 2 Tx slots) – MCS5	24.56	24.59	24.23	25.00	18.56	18.59	18.23	19.00
EDGE (8PSK, 3 Tx slots) – MCS5	22.43	22.46	22.07	23.00	18.17	18.20	17.81	18.74
EDGE (8PSK, 4 Tx slots) – MCS5	21.28	21.18	20.73	22.00	18.28	18.18	17.73	19.00

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (1 Tx Slots) - 6 dB
Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB
Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB
Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595 Issued Date : Jul. 22, 2015 FCC ID: YHLBLUENERGYX Form version.: 150415 Page 22 of 44

<WCDMA Conducted Power>

- 1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
- 2. The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.

Report No. : FA561807

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	βο	βd	βd (SF)	β₀/βа	βнs (Note1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and Δ_{NACK} = 30/15 with β_{hs} = 30/15 * β_c , and Δ_{CQI} = 24/15

with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for β_c/β_d =12/15, β_{hs}/β_c =24/15. For all other combinations of DPDCH, DPCCH and HSDPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to β_c = 11/15 and β_d = 15/15.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting *:
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121

Report No.: FA561807

- iii. Set Cell Power = -86 dBm
- iv. Set Channel Type = 12.2k + HSPA
- v. Set UE Target Power
- vi. Power Ctrl Mode= Alternating bits
- vii. Set and observe the E-TFCI
- viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub- test	βс	βa	β _d (SF)	βc/βd	βнs (Note1)	βес	β _{ed} (Note 5) (Note 6)	β _{ed} (SF)	β _{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E- TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/2 25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β _{ed} 1: 47/15 β _{ed} 2: 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

- Note 1: Δ_{ACK} , Δ_{NACK} and Δ_{CQI} = 30/15 with β_{hs} = 30/15 * β_c .
- Note 2: CM = 1 for $\beta_0/\beta_d = 12/15$, $\beta_{1s}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.
- Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to β_c = 10/15 and β_d = 15/15.
- Note 4: For subtest 5 the β_0/β_0 ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by
- setting the signalled gain factors for the reference TFC (TF1, TF1) to β_c = 14/15 and β_d = 15/15. Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.
- Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

 SPORTON INTERNATIONAL (SHENZHEN) INC.

 TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595
 Issued Date: Jul. 22, 2015

FCC ID : YHLBLUENERGYX Page 24 of 44 Form version. : 150415



<WCDMA Conducted Power>

General Note:

1. Per KDB 941225 D01v03, SAR for Head / Hotspot / Body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".

Report No. : FA561807

2. Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is ≤ ¼ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

SIM1:

<u> </u>	Oiiii 1.											
	Band	t	WC	DMA Ba	nd V	WC	DMA Ba	nd II	WCE	DMA Bar	nd IV	
	TX Cha	nnel	4132	4182	4233	9262	9400	9538	1312	1413	1513	
Rx Channel				4407	4458	9662	9800	9938	1537	1638	1738	
Frequency (MHz)			826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6	
MPR			23.04	22.98	23.00	22.96	23.02	23.06	22.84	22.83	22.86	
(dB)	3GPP Rel 99	RMC 12.2Kbps	23.05	22.99	23.02	22.98	23.04	23.08	22.85	22.84	22.89	
0	3GPP Rel 6	HSDPA Subtest-1	21.86	22.06	21.93	21.76	21.81	21.83	21.57	21.74	21.72	
0	3GPP Rel 6	HSDPA Subtest-2	21.83	22.05	21.89	21.73	21.78	21.79	21.54	21.69	21.70	
0.5	3GPP Rel 6	HSDPA Subtest-3	21.36	21.56	21.45	21.28	21.29	21.28	21.00	21.22	21.25	
0.5	3GPP Rel 6	HSDPA Subtest-4	21.33	21.54	21.44	21.25	21.24	21.28	20.98	21.18	21.19	
0	3GPP Rel 6	HSUPA Subtest-1	19.88	20.06	19.93	19.67	19.69	19.82	19.58	19.70	19.73	
2	3GPP Rel 6	HSUPA Subtest-2	19.85	20.05	19.94	19.61	19.72	19.83	19.56	19.68	19.70	
1	3GPP Rel 6	HSUPA Subtest-3	20.85	21.03	20.88	20.74	20.76	20.83	20.53	20.73	20.68	
2	3GPP Rel 6	HSUPA Subtest-4	19.28	19.54	19.41	19.14	19.13	19.27	19.05	19.17	19.19	
0	3GPP Rel 6	HSUPA Subtest-5	21.90	22.00	22.00	21.80	21.80	21.80	21.60	21.80	21.80	

SIM2:

	Band	b	WCI	DMA Ba	nd V	WCI	DMA Ba	nd II	WCE	DMA Bar	nd IV
	TX Chai	nnel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Rx Channel				4407	4458	9662	9800	9938	1537	1638	1738
	Frequency (MHz)			836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
MPR	3GPP Rel 99	AMR 12.2Kbps	23.01	22.96	23.00	22.95	23.02	23.01	22.83	22.76	22.84
(dB)	3GPP Rel 99	RMC 12.2Kbps	23.03	22.98	22.97	22.97	22.93	23.06	22.84	22.80	22.88
0	3GPP Rel 6	HSDPA Subtest-1	21.86	22.04	21.93	21.62	21.82	21.78	21.54	21.67	21.75
0	3GPP Rel 6	HSDPA Subtest-2	21.82	22.02	21.90	21.68	21.77	21.77	21.50	21.64	21.75
0.5	3GPP Rel 6	HSDPA Subtest-3	21.33	21.58	21.47	21.24	21.31	21.27	21.03	21.17	21.27
0.5	3GPP Rel 6	HSDPA Subtest-4	21.33	21.54	21.42	21.18	21.27	21.23	21.03	21.14	21.26
0	3GPP Rel 6	HSUPA Subtest-1	19.86	20.05	19.90	19.65	19.64	19.77	19.53	19.68	19.74
2	3GPP Rel 6	HSUPA Subtest-2	19.83	20.01	19.90	19.67	19.67	19.86	19.46	19.65	19.74
1	3GPP Rel 6	HSUPA Subtest-3	20.85	20.99	20.88	20.67	20.76	20.80	20.50	20.74	20.72
2	3GPP Rel 6	HSUPA Subtest-4	19.28	19.50	19.40	19.11	19.08	19.25	19.01	19.18	19.18
0	3GPP Rel 6	HSUPA Subtest-5	21.90	22.00	22.00	21.70	21.80	21.80	21.60	21.70	21.90



<WLAN Conducted Power>

General Note:

1. Per KDB 248227 D01v02r01, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.

Report No.: FA561807

- 2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
- 3. For OFDM transmission configurations in the 2.4 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
- 4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

 SPORTON INTERNATIONAL (SHENZHEN) INC.

 TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595
 Issued Date: Jul. 22, 2015

FCC ID : YHLBLUENERGYX Page 26 of 44 Form version. : 150415



<2.4GHz WLAN>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Tune-Up Limit	Duty Cycle %
		CH 1	2412		12.47	13.00	
	802.11b	CH 6	2437	1Mbps	11.89	12.50	100.00
		CH 11	2462		12.32	13.00	
	802.11g	CH 1	2412		11.55	12.00	95.72
2.4GHz WLAN		CH 6	2437	6Mbps	12.42	13.00	
		CH 11	2462		11.59	12.00	
		CH 1	2412		11.05	11.50	
	802.11n-HT20	CH 6	2437	MCS0	10.30	10.50	96.30
		CH 11	2462		11.03	11.50	
		CH 3	2422		10.28	10.50	
	802.11n-HT40	CH 6	2437	MCS0	10.03	10.50	94.75
		CH 9	2452		9.99	10.50	

Report No. : FA561807

13. Bluetooth Exclusions Applied

Mode Band	Average power(dBm)							
IVIOUE DAIIU	Bluetooth v3.0+EDR	Bluetooth v4.0 LE						
2.4GHz Bluetooth	6.00	-1.50						

Report No. : FA561807

Note:

1. Per KDB 447498 D01v05r02, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
6.00	< 5	2.48	1.3


Note:

Per KDB 447498 D01v05r02, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 1.3 which is <= 3, SAR testing is not required.

 SPORTON INTERNATIONAL (SHENZHEN) INC.

 TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595
 Issued Date: Jul. 22, 2015

14. Antenna Location



Report No.: FA561807

Distance of the Antenna to the EUT surface/edge											
Antennas Back Front Top Side Bottom Side Right Side Left Side											
WWAN Main	≤ 25mm	≤ 25mm	131mm	≤ 25mm	28mm	≤ 25mm					
BT&WLAN	BT&WLAN ≤ 25mm ≤ 25mm 131mm 54mm ≤ 25mm										

Positions for SAR tests; Hotspot mode											
Antennas Back Front Top Side Bottom Side Right Side Left Side											
WWAN Main	Yes	Yes	No	Yes	No	Yes					
BT&WLAN											

Referring to KDB 941225 D06 v02, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595

Issued Date: Jul. 22, 2015 FCC ID: YHLBLUENERGYX Page 29 of 44 Form version.: 150415

15. SAR Test Results

General Note:

- Per KDB 447498 D01v05r02, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.

Report No.: FA561807

- b. Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- Per KDB 447498 D01v05r02, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
- Per KDB 648474 D04v01r02, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg. SAR testing with a headset connected to the handset is not required.
- Per KDB 941225 D01v03, considering the possibility of e.g. 3rd party VoIP operation for Head and body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.
- Per KDB 941225 D01v03, for Hotspot SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance, for modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested, therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.
- Per KDB 941225 D01v03, SAR for next to the ear head / Hotspot / Body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
- Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is ≤ ¼ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA /
- 8. Per KDB 248227 D01v02r01, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
- When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
- 10. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
- 11. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595 Issued Date: Jul. 22, 2015 Page 30 of 44 Form version.: 150415

SPORTON INTERNATIONAL (SHENZHEN) INC.



15.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS(4 Tx slots)	Right Cheek	251	848.8	29.07	29.50	1.104	0.01	0.282	0.311
	GSM850	GPRS(4 Tx slots)	Right Tilted	251	848.8	29.07	29.50	1.104	0.01	0.190	0.210
#01	GSM850	GPRS(4 Tx slots)	Left Cheek	251	848.8	29.07	29.50	1.104	-0.07	0.310	0.342
	GSM850	GPRS(4 Tx slots)	Left Tilted	251	848.8	29.07	29.50	1.104	-0.07	0.205	0.226
	GSM850	GPRS(4 Tx slots)	Left Cheek	128	824.2	28.94	29.50	1.138	-0.11	0.298	0.339
	GSM850	GPRS(4 Tx slots)	Left Cheek	189	836.4	29.05	29.50	1.109	-0.07	0.293	0.325
#02	GSM1900	GPRS(4 Tx slots)	Right Cheek	512	1850.2	26.21	27.00	1.199	0.05	0.227	0.272
	GSM1900	GPRS(4 Tx slots)	Right Tilted	512	1850.2	26.21	27.00	1.199	0.02	0.051	0.061
	GSM1900	GPRS(4 Tx slots)	Left Cheek	512	1850.2	26.21	27.00	1.199	0.08	0.208	0.249
	GSM1900	GPRS(4 Tx slots)	Left Tilted	512	1850.2	26.21	27.00	1.199	0.07	0.060	0.072
	GSM1900	GPRS(4 Tx slots)	Right Cheek	661	1880	26.18	27.00	1.208	0.06	0.200	0.242
	GSM1900	GPRS(4 Tx slots)	Right Cheek	810	1909.8	26.17	27.00	1.211	-0.02	0.179	0.217

Report No. : FA561807

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA Band V	RMC 12.2Kbps	Right Cheek	4132	826.4	23.05	23.50	1.109	0.01	0.189	0.210
	WCDMA Band V	RMC 12.2Kbps	Right Tilted	4132	826.4	23.05	23.50	1.109	0.03	0.128	0.142
	WCDMA Band V	RMC 12.2Kbps	Left Cheek	4132	826.4	23.05	23.50	1.109	-0.02	0.216	0.240
	WCDMA Band V	RMC 12.2Kbps	Left Tilted	4132	826.4	23.05	23.50	1.109	-0.02	0.142	0.158
#03	WCDMA Band V	RMC 12.2Kbps	Left Cheek	4182	836.4	22.99	23.50	1.125	-0.07	0.263	<mark>0.296</mark>
	WCDMA Band V	RMC 12.2Kbps	Left Cheek	4233	846.6	23.02	23.50	1.117	-0.06	0.191	0.213
	WCDMA Band IV	RMC 12.2Kbps	Right Cheek	1513	1752.6	22.89	23.50	1.151	-0.05	0.341	0.392
	WCDMA Band IV	RMC 12.2Kbps	Right Tilted	1513	1752.6	22.89	23.50	1.151	0.09	0.131	0.151
	WCDMA Band IV	RMC 12.2Kbps	Left Cheek	1513	1752.6	22.89	23.50	1.151	-0.07	0.323	0.372
	WCDMA Band IV	RMC 12.2Kbps	Left Tilted	1513	1752.6	22.89	23.50	1.151	-0.03	0.052	0.060
	WCDMA Band IV	RMC 12.2Kbps	Right Cheek	1312	1712.4	22.85	23.50	1.161	-0.01	0.304	0.353
#04	WCDMA Band IV	RMC 12.2Kbps	Right Cheek	1413	1732.6	22.84	23.50	1.164	-0.02	0.359	<mark>0.418</mark>
	WCDMA Band II	RMC 12.2Kbps	Right Cheek	9538	1907.6	23.08	23.50	1.102	-0.02	0.194	0.214
	WCDMA Band II	RMC 12.2Kbps	Right Tilted	9538	1907.6	23.08	23.50	1.102	0.08	0.048	0.053
#05	WCDMA Band II	RMC 12.2Kbps	Left Cheek	9538	1907.6	23.08	23.50	1.102	-0.07	0.267	0.294
	WCDMA Band II	RMC 12.2Kbps	Left Tilted	9538	1907.6	23.08	23.50	1.102	0.02	0.031	0.034
	WCDMA Band II	RMC 12.2Kbps	Left Cheek	9262	1852.4	22.98	23.50	1.127	-0.02	0.139	0.157
	WCDMA Band II	RMC 12.2Kbps	Left Cheek	9400	1880	23.04	23.50	1.112	0.05	0.181	0.201

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 2.4GHz	802.11b 1Mbps	Right Cheek	1	2412	12.47	13.00	1.130	-0.03	0.627	0.708
	WLAN 2.4GHz	802.11b 1Mbps	Right Tilted	1	2412	12.47	13.00	1.130	-0.08	0.416	0.470
	WLAN 2.4GHz	802.11b 1Mbps	Left Cheek	1	2412	12.47	13.00	1.130	0.06	0.315	0.356
	WLAN 2.4GHz	802.11b 1Mbps	Left Tilted	1	2412	12.47	13.00	1.130	0.04	0.288	0.325
	WLAN 2.4GHz	802.11b 1Mbps	Right Cheek	6	2437	11.89	12.50	1.151	-0.04	0.626	0.720
#06	WLAN 2.4GHz	802.11b 1Mbps	Right Cheek	11	2462	12.32	13.00	1.169	-0.04	0.756	<mark>0.884</mark>

FCC ID : YHLBLUENERGYX Page 31 of 44 Form version. : 150415



15.2 Hotspot SAR

Distance of the Antenna to the EUT surface/edge										
Antennas Back Front Top Side Bottom Side Right Side Left Side										
WWAN Main ≤ 25mm ≤ 25mm 131mm ≤ 25mm 28mm ≤ 25m										
BT&WLAN ≤ 25mm ≤ 25mm 131mm 54mm ≤ 25mm										

Report No. : FA561807

Positions for SAR tests; Hotspot mode										
Antennas Back Front Top Side Bottom Side Right Side Left Side										
WWAN Main	Yes	Yes	No	Yes	No	Yes				
BT&WLAN Yes Yes Yes No No Yes										

General Note:

Referring to KDB 941225 D06 v02, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)		Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS(4 Tx slots)	Front	1	251	848.8	29.07	29.50	1.104	-0.02	0.339	0.374
	GSM850	GPRS(4 Tx slots)	Back	1	251	848.8	29.07	29.50	1.104	-0.09	0.407	0.449
	GSM850	GPRS(4 Tx slots)	Left Side	1	251	848.8	29.07	29.50	1.104	-0.08	0.566	0.625
	GSM850	GPRS(4 Tx slots)	Bottom Side	1	251	848.8	29.07	29.50	1.104	-0.1	0.258	0.285
#07	GSM850	GPRS(4 Tx slots)	Left Side	1	128	824.2	28.94	29.50	1.138	-0.07	0.647	0.736
	GSM850	GPRS(4 Tx slots)	Left Side	1	189	836.4	29.05	29.50	1.109	0.01	0.627	0.695
	GSM850	GPRS(4 Tx slots)	Back	1	128	824.2	28.94	29.50	1.138	0.01	0.512	0.582
	GSM850	GPRS(4 Tx slots)	Back	1	189	836.4	29.05	29.50	1.109	0.04	0.517	0.573
	GSM1900	GPRS(4 Tx slots)	Front	1	512	1850.2	26.21	27.00	1.199	0.08	0.508	0.609
	GSM1900	GPRS(4 Tx slots)	Back	1	512	1850.2	26.21	27.00	1.199	0.01	0.606	0.727
	GSM1900	GPRS(4 Tx slots)	Left Side	1	512	1850.2	26.21	27.00	1.199	0.03	0.147	0.176
#08	GSM1900	GPRS(4 Tx slots)	Bottom Side	1	512	1850.2	26.21	27.00	1.199	-0.1	0.858	1.029
	GSM1900	GPRS(4 Tx slots)	Bottom Side	1	661	1880	26.18	27.00	1.208	-0.09	0.788	0.952
	GSM1900	GPRS(4 Tx slots)	Bottom Side	1	810	1909.8	26.17	27.00	1.211	-0.16	0.681	0.824
	GSM1900	GPRS(4 Tx slots)	Back	1	661	1880	26.18	27.00	1.208	0.08	0.608	0.734
	GSM1900	GPRS(4 Tx slots)	Back	1	810	1909.8	26.17	27.00	1.211	0.02	0.565	0.684

SPORTON INTERNATIONAL (SHENZHEN) INC.



SPORTON LAB. FCC SAR Test Report

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA Band V	RMC 12.2Kbps	Front	1	4132	826.4	23.05	23.50	1.109	-0.06	0.251	0.278
	WCDMA Band V	RMC 12.2Kbps	Back	1	4132	826.4	23.05	23.50	1.109	0.08	0.325	0.360
	WCDMA Band V	RMC 12.2Kbps	Left Side	1	4132	826.4	23.05	23.50	1.109	-0.02	0.413	0.458
	WCDMA Band V	RMC 12.2Kbps	Bottom Side	1	4132	826.4	23.05	23.50	1.109	-0.06	0.151	0.167
#09	WCDMA Band V	RMC 12.2Kbps	Left Side	1	4182	836.4	22.99	23.50	1.125	-0.02	0.506	<mark>0.569</mark>
	WCDMA Band V	RMC 12.2Kbps	Left Side	1	4233	846.6	23.02	23.50	1.117	0.07	0.392	0.438
	WCDMA Band V	RMC 12.2Kbps	Back	1	4182	836.4	22.99	23.50	1.125	0.05	0.457	0.514
	WCDMA Band V	RMC 12.2Kbps	Back	1	4233	846.6	23.02	23.50	1.117	0.02	0.322	0.360
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1513	1752.6	22.89	23.50	1.151	0.09	0.733	0.844
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1513	1752.6	22.89	23.50	1.151	0.05	0.714	0.822
	WCDMA Band IV	RMC 12.2Kbps	Left Side	1	1513	1752.6	22.89	23.50	1.151	0.01	0.221	0.254
	WCDMA Band IV	RMC 12.2Kbps	Bottom Side	1	1513	1752.6	22.89	23.50	1.151	-0.01	0.887	1.021
	WCDMA Band IV	RMC 12.2Kbps	Bottom Side	1	1312	1712.4	22.85	23.50	1.161	-0.12	0.794	0.922
#10	WCDMA Band IV	RMC 12.2Kbps	Bottom Side	1	1413	1732.6	22.84	23.50	1.164	0.04	1.030	<mark>1.199</mark>
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1312	1712.4	22.85	23.50	1.161	0.17	0.670	0.778
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1413	1732.6	22.84	23.50	1.164	-0.06	0.867	1.009
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1312	1712.4	22.85	23.50	1.161	0.04	0.649	0.754
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1413	1732.6	22.84	23.50	1.164	0.04	0.834	0.971
	WCDMA Band II	RMC 12.2Kbps	Front	1	9538	1907.6	23.08	23.50	1.102	0.11	0.462	0.509
	WCDMA Band II	RMC 12.2Kbps	Back	1	9538	1907.6	23.08	23.50	1.102	0.05	0.641	0.706
	WCDMA Band II	RMC 12.2Kbps	Left Side	1	9538	1907.6	23.08	23.50	1.102	0.08	0.150	0.165
#11	WCDMA Band II	RMC 12.2Kbps	Bottom Side	1	9538	1907.6	23.08	23.50	1.102	-0.09	0.791	0.871
	WCDMA Band II	RMC 12.2Kbps	Bottom Side	1	9262	1852.4	22.98	23.50	1.127	-0.03	0.624	0.703
	WCDMA Band II	RMC 12.2Kbps	Bottom Side	1	9400	1880	23.04	23.50	1.112	-0.11	0.781	0.868
	WCDMA Band II	RMC 12.2Kbps	Back	1	9262	1852.4	22.98	23.50	1.127	0.05	0.442	0.498
	WCDMA Band II	RMC 12.2Kbps	Back	1	9400	1880	23.04	23.50	1.112	0.05	0.582	0.647

Report No. : FA561807

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 2.4GHz	802.11b 1Mbps	Front	1	1	2412	12.47	13.00	1.130	0.06	0.135	0.153
	WLAN 2.4GHz	802.11b 1Mbps	Back	1	1	2412	12.47	13.00	1.130	0.07	0.090	0.102
	WLAN 2.4GHz	802.11b 1Mbps	Left Side	1	1	2412	12.47	13.00	1.130	-0.09	0.072	0.081
	WLAN 2.4GHz	802.11b 1Mbps	Top Side	1	1	2412	12.47	13.00	1.130	-0.02	0.109	0.123
	WLAN 2.4GHz	802.11b 1Mbps	Front	1	6	2437	11.89	12.50	1.151	0.03	0.129	0.148
#12	WLAN 2.4GHz	802.11b 1Mbps	Front	1	11	2462	12.32	13.00	1.169	-0.01	0.142	<mark>0.166</mark>

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595 Issued Date : Jul. 22, 2015 Form version. : 150415

FCC ID: YHLBLUENERGYX Page 33 of 44



15.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS(4 Tx slots)	Front	1	251	848.8	29.07	29.50	1.104	-0.02	0.339	0.374
	GSM850	GPRS(4 Tx slots)	Back	1	251	848.8	29.07	29.50	1.104	-0.09	0.407	0.449
#13	GSM850	GPRS(4 Tx slots)	Back	1	128	824.2	28.94	29.50	1.138	0.01	0.512	<mark>0.582</mark>
	GSM850	GPRS(4 Tx slots)	Back	1	189	836.4	29.05	29.50	1.109	0.04	0.517	0.573
	GSM1900	GPRS(4 Tx slots)	Front	1	512	1850.2	26.21	27.00	1.199	0.08	0.508	0.609
	GSM1900	GPRS(4 Tx slots)	Back	1	512	1850.2	26.21	27.00	1.199	0.01	0.606	0.727
#14	GSM1900	GPRS(4 Tx slots)	Back	1	661	1880	26.18	27.00	1.208	0.08	0.608	0.734
	GSM1900	GPRS(4 Tx slots)	Back	1	810	1909.8	26.17	27.00	1.211	0.02	0.565	0.684

Report No. : FA561807

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA Band V	RMC 12.2Kbps	Front	1	4132	826.4	23.05	23.50	1.109	-0.06	0.251	0.278
	WCDMA Band V	RMC 12.2Kbps	Back	1	4132	826.4	23.05	23.50	1.109	0.08	0.325	0.360
#15	WCDMA Band V	RMC 12.2Kbps	Back	1	4182	836.4	22.99	23.50	1.125	0.05	0.457	<mark>0.514</mark>
	WCDMA Band V	RMC 12.2Kbps	Back	1	4233	846.6	23.02	23.50	1.117	0.02	0.322	0.360
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1513	1752.6	22.89	23.50	1.151	0.09	0.733	0.844
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1513	1752.6	22.89	23.50	1.151	0.05	0.714	0.822
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1312	1712.4	22.85	23.50	1.161	0.17	0.670	0.778
#16	WCDMA Band IV	RMC 12.2Kbps	Front	1	1413	1732.6	22.84	23.50	1.164	-0.06	0.867	1.009
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1312	1712.4	22.85	23.50	1.161	0.04	0.649	0.754
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1413	1732.6	22.84	23.50	1.164	0.04	0.834	0.971
	WCDMA Band II	RMC 12.2Kbps	Front	1	9538	1907.6	23.08	23.50	1.102	0.11	0.462	0.509
#17	WCDMA Band II	RMC 12.2Kbps	Back	1	9538	1907.6	23.08	23.50	1.102	0.05	0.641	<mark>0.706</mark>
	WCDMA Band II	RMC 12.2Kbps	Back	1	9262	1852.4	22.98	23.50	1.127	0.05	0.442	0.498
	WCDMA Band II	RMC 12.2Kbps	Back	1	9400	1880	23.04	23.50	1.112	0.05	0.582	0.647

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 2.4GHz	802.11b 1Mbps	Front	1	1	2412	12.47	13.00	1.130	0.06	0.135	0.153
	WLAN 2.4GHz	802.11b 1Mbps	Back	1	1	2412	12.47	13.00	1.130	0.07	0.090	0.102
	WLAN 2.4GHz	802.11b 1Mbps	Front	1	6	2437	11.89	12.50	1.151	0.03	0.129	0.148
#12	WLAN 2.4GHz	802.11b 1Mbps	Front	1	11	2462	12.32	13.00	1.169	-0.01	0.142	<mark>0.166</mark>



SPORTON LAB. FCC SAR Test Report

15.4 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor		Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	GSM1900	GPRS(4 Tx slots)	Bottom Side	1	512	1850.2	26.21	27.00	1.199	-0.1	0.858	1	1.029
2nd	GSM1900	GPRS(4 Tx slots)	Bottom Side	1	512	1850.2	26.21	27.00	1.199	-0.01	0.828	1.036	0.993
1st	WCDMA Band IV	RMC 12.2Kbps	Bottom Side	1	1413	1732.6	22.84	23.50	1.164	0.04	1.030	1	1.199
2nd	WCDMA Band IV	RMC 12.2Kbps	Bottom Side	1	1413	1732.6	22.84	23.50	1.164	0.04	1.010	1.020	1.176

Report No.: FA561807

General Note:

- 1. Per KDB 865664 D01v01r03, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥0.8W/kg.
- 2. Per KDB 865664 D01v01r03, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR <1.45W/kg, only one repeated measurement is required.
- 3. The ratio is the difference in percentage between original and repeated measured SAR.
- 4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

SPORTON INTERNATIONAL (SHENZHEN) INC.

SPORTON LAB. FCC SAR Test Report

16. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Ро	rtable Hands	Note	
NO.	Simultaneous Transmission Configurations	Head	Body-worn	Hotspot	Note
1.	GSM(Voice) + WLAN2.4GHz(data)	Yes	Yes		
2.	WCDMA(Voice) + WLAN2.4GHz(data)	Yes	Yes		
3.	GSM(Voice) + Bluetooth(data)	Yes	Yes		
4.	WCDMA((Voice) + Bluetooth(data)	Yes	Yes		
5.	GPRS/EDGE(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
6.	WCDMA(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
7.	GPRS/EDGE(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
8.	WCDMA(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering

Report No. : FA561807

General Note:

- This device supported VoIP in GPRS, EGPRS, WCDMA (e.g. 3rd party VoIP). 1.
- 2. This device 2.4GHz WLAN supports hotspot operation.
- WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously. 3.
- EUT will choose each GSM and WCDMA according to the network signal condition; therefore, they will not operate 4. simultaneously at any moment.
- 5. The reported SAR summation is calculated based on the same configuration and test position.
- The Scaled SAR summation is calculated based on the same configuration and test position. 6.
- Per KDB 447498 D01v05r02, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.

SPORTON INTERNATIONAL (SHENZHEN) INC.

- ii) SPLSR = (SAR₁ + SAR₂)^{1.5} / (min. separation distance, mm), and the peak separation distance is determined from the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
- iii) If SPLSR ≤ 0.04, simultaneously transmission SAR measurement is not necessary.
- iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
- For simultaneous transmission analysis. Bluetooth SAR is estimated per KDB 447498 D01v05r02 based on the formula below.
 - i) (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· [√f(GHz)/x] W/kg for test separation distances \leq 50 mm; where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.
 - ii) When the minimum separation distance is < 5mm, the distance is used 5mm to determine SAR test exclusion.
 - iii) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Bluetooth	Exposure Position	Head	Hotspot	Body worn
Max Power	Test separation	0 mm	10 mm	10 mm
6.00 dBm	Estimated SAR (W/kg)	0.168 W/kg	0.084 W/kg	0.084 W/kg



16.1 Head Exposure Conditions

<WWAN + WLAN>

		Exposure	WWAN PCE	WLAN DTS	Summed		
WWAN	WWAN Band		Max. WWAN SAR (W/kg)	Max. SAR WLAN SAR (W/kg) (W/kg)		SPLSR	Case No
		Right Cheek	0.311	0.884	1.20		
	GSM850	Right Tilted	0.210	0.470	0.68		
	GSIVIOSU	Left Cheek	0.342	0.356	0.70		
GSM		Left Tilted	0.226	0.325	0.55		
GOW		Right Cheek	0.272	0.884	1.16		
	GSM1900	Right Tilted	0.061	0.470	0.53		
	G3W1900	Left Cheek	0.249	0.356	0.61		
		Left Tilted	0.072	0.325	0.40		
	Band V	Right Cheek	0.210	0.884	1.09		
		Right Tilted	0.142	0.470	0.61		
		Left Cheek	0.296	0.356	0.65		
		Left Tilted	0.158	0.325	0.48		
		Right Cheek	0.418	0.884	<mark>1.30</mark>		
WCDMA	Band IV	Right Tilted	0.151	0.470	0.62		
WCDIVIA	Danu IV	Left Cheek	0.372	0.356	0.73		
		Left Tilted	0.060	0.325	0.39		
		Right Cheek	0.214	0.884	1.10		
	Band II	Right Tilted	0.053	0.470	0.52		
	Dailu II	Left Cheek	0.294	0.356	0.65		
		Left Tilted	0.034	0.325	0.36		

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595
FCC ID: YHLBLUENERGYX Page 37 of 44

Issued Date : Jul. 22, 2015 Form version. : 150415

Report No. : FA561807



FCC SAR Test Report

<WWAN + Bluetooth>

			WWAN PCE	Bluetooth DSS	Summed		
1AWW	N Band	Exposure Position	Max. WWAN SAR (W/kg)	Estimated (W/kg)	Summed SAR (W/kg)	SPLSR	Case No
		Right Cheek	0.311	0.168	0.48		
	GSM850	Right Tilted	0.210	0.168	0.38		
	GSIVIOSU	Left Cheek	0.342	0.168	0.51		
GSM		Left Tilted	0.226	0.168	0.39		
GSIVI		Right Cheek	0.272	0.168	0.44		
	GSM1900	Right Tilted	0.061	0.168	0.23		
'	G3W1900	Left Cheek	0.249	0.168	0.42		
		Left Tilted	0.072	0.168	0.24		
		Right Cheek	0.210	0.168	0.38		
	Band V	Right Tilted	0.142	0.168	0.31		
		Left Cheek	0.296	0.168	0.46		
		Left Tilted	0.158	0.168	0.33		
		Right Cheek	0.418	0.168	0.59		
WCDMA	Band IV	Right Tilted	0.151	0.168	0.32		
WCDIVIA	Dallu IV	Left Cheek	0.372	0.168	0.54		
		Left Tilted	0.060	0.168	0.23		
		Right Cheek	0.214	0.168	0.38		
	Band II	Right Tilted	0.053	0.168	0.22		
	Dailu II	Left Cheek	0.294	0.168	0.46		
		Left Tilted	0.034	0.168	0.20		

Report No.: FA561807

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595

Issued Date : Jul. 22, 2015 Form version. : 150415 FCC ID : YHLBLUENERGYX Page 38 of 44



16.2 Hotspot Exposure Conditions

<WWAN + WLAN>

			WWAN PCE	WLAN DTS	Summed		
WWAN Band		Exposure Position	Max. WWAN SAR (W/kg)	Max. SAR WLAN SAR (W/kg)		SPLSR	Case No
		Front	0.374	0.166	0.54		
		Back	0.582	0.102	0.68		
	GSM850	Left side	0.736	0.081	0.82		
		Top side		0.123	0.12		
GSM		Bottom side	0.285		0.29		
GOW		Front	0.609	0.166	0.78		
		Back	0.734	0.102	0.84		
	GSM1900	Left side	0.176	0.081	0.26		
		Top side		0.123	0.12		
		Bottom side	1.029		1.03		
	Band V	Front	0.278	0.166	0.44		
		Back	0.514	0.102	0.62		
		Left side	0.569	0.081	0.65		
		Top side		0.123	0.12		
		Bottom side	0.167		0.17		
		Front	1.009	0.166	1.18		
		Back	0.971	0.102	1.07		
WCDMA	Band IV	Left side	0.254	0.081	0.34		
		Top side		0.123	0.12		
		Bottom side	1.199		1.20		
		Front	0.509	0.166	0.68		
		Back	0.706	0.102	0.81		
	Band II	Left side	0.165	0.081	0.25		
		Top side		0.123	0.12		
		Bottom side	0.871		0.87		

Report No. : FA561807



SPORTON LAB. FCC SAR Test Report

<WWAN + Bluetooth>

<wwan +="" i<="" th=""><th>Siuetootii></th><th></th><th>WWAN PCE</th><th>Bluetooth DSS</th><th></th><th></th><th></th></wwan>	Siuetootii>		WWAN PCE	Bluetooth DSS			
1AWW	N Band	Exposure Position	Max. WWAN SAR (W/kg)	Estimated (W/kg)	Summed SAR (W/kg)	SPLSR	Case No
		Front	0.374	0.084	0.46		
		Back	0.582	0.084	0.67		
	GSM850	Left side	0.736	0.084	0.82		
		Top side		0.084	0.08		
GSM		Bottom side	0.285		0.29		
GSIVI		Front	0.609	0.084	0.69		
		Back	0.734	0.084	0.82		
	GSM1900	Left side	0.176	0.084	0.26		
		Top side		0.084	0.08		
		Bottom side	1.029		1.03		
	Band V	Front	0.278	0.084	0.36		
		Back	0.514	0.084	0.60		
		Left side	0.569	0.084	0.65		
		Top side		0.084	0.08		
		Bottom side	0.167		0.17		
		Front	1.009	0.084	1.09		
		Back	0.971	0.084	1.06		
WCDMA	Band IV	Left side	0.254	0.084	0.34		
		Top side		0.084	0.08		
		Bottom side	1.199		1.20		
		Front	0.509	0.084	0.59		
		Back	0.706	0.084	0.79		
	Band II	Left side	0.165	0.084	0.25		
		Top side		0.084	0.08		
		Bottom side	0.871		0.87		

Report No. : FA561807

TEL: 86-755-8637-9589/ FAX: 86-755-8637-9595

Issued Date : Jul. 22, 2015 Form version. : 150415 FCC ID: YHLBLUENERGYX Page 40 of 44



16.3 Body-Worn Accessory Exposure Conditions

<WWAN + WLAN>

			WWAN PCE	WLAN DTS	Summed		
WWA	N Band	Exposure Position	Max. WWAN SAR (W/kg)	Max. WLAN SAR (W/kg)	SAR (W/kg)	SPLSR	Case No
	GSM850	Front	0.374	0.166	0.54		
GSM		Back	0.582	0.102	0.68		
GSIVI	GSM1900	Front	0.609	0.166	0.78		
		Back	0.734	0.102	0.84		
	Daniel V	Front	0.278	0.166	0.44		
	Band V	Back	0.514	0.102	0.62		
WCDMA	Band IV	Front	1.009	0.166	1.18		
VVCDIVIA	Band IV	Back	0.971	0.102	1.07		
	Band II	Front	0.509	0.166	0.68		
	Band II	Back	0.706	0.102	0.81		

Report No.: FA561807

<WWAN + Bluetooth>

			WWAN PCE	Bluetooth DSS	Summed		
WWA	N Band	Exposure Position	Max. WWAN SAR (W/kg)	Estimated (W/kg)	SAR (W/kg)	SPLSR	Case No
	CCMOEO	Front	0.374	0.084	0.46		
GSM	GSM850	Back	0.582	0.084	0.67		
GSIVI	GSM1900	Front	0.609	0.084	0.69		
		Back	0.734	0.084	0.82		
	Band V	Front	0.278	0.084	0.36		
	Dailu V	Back	0.514	0.084	0.60		
WCDMA	Pand IV	Front	1.009	0.084	1.09		
WCDIVIA	Band IV	Back	0.971	0.084	1.06		
	Band II	Front	0.509	0.084	0.59		
	Dailu II	Back	0.706	0.084	0.79		

Test Engineer: Luke Lu

17. Uncertainty Assessment

The component of uncertainly may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainly by the statistical analysis of a series of observations is termed a Type An evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

Report No. : FA561807

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	1/k ^(b)	1/√3	1/√6	1/√2

- (a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity
- (b) κ is the coverage factor

Table 17.1. Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

FCC ID : YHLBLUENERGYX Page 42 of 44 Form version. : 150415

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K:	=2
Expanded Uncertainty						± 22.0 %	± 21.5 %

Report No. : FA561807

Table 17.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz

18. References

[1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"

Report No. : FA561807

- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r01, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Jun 2015.
- [6] FCC KDB 447498 D01 v05r02, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Feb 2014
- [7] FCC KDB 648474 D04 v01r02, "SAR Evaluation Considerations for Wireless Handsets", Dec 2013.
- [8] FCC KDB 941225 D01 v03, "3G SAR MEAUREMENT PROCEDURES", Oct 2014
- [9] FCC KDB 941225 D06 v02, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2014.
- [10] FCC KDB 865664 D01 v01r03, "SAR Measurement Requirements for 100 MHz to 6 GHz", Feb 2014
- [11] FCC KDB 865664 D02 v01r01, "RF Exposure Compliance Reporting and Documentation Considerations" May 2013.

Appendix A. Plots of System Performance Check

Report No.: FA561807

The plots are shown as follows.

SPORTON INTERNATIONAL (SHENZHEN) INC.

System Check_Head_835MHz_150620

DUT: D835V2-SN:4d091

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1 Medium: HSL_835_150620 Medium parameters used: f = 835 MHz; σ = 0.904 S/m; ϵ_r = 41.212; ρ = 1000 kg/m³

Date: 2015.06.20


Ambient Temperature: 23.4 °C; Liquid Temperature: 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 SN7346; ConvF(9.78, 9.78, 9.78); Calibrated: 2015.01.08;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1386; Calibrated: 2015.02.19
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 2.80 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 56.69 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 3.30 W/kg SAR(1 g) = 2.21 W/kg; SAR(10 g) = 1.44 W/kg Maximum value of SAR (measured) = 2.79 W/kg



System Check_Head_1750MHz_150620

DUT: D1750V2-SN:1069

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1 Medium: HSL_1800_150620 Medium parameters used: f = 1750 MHz; σ = 1.378 S/m; ϵ_r = 41.34; ρ = 1000 kg/m³

Date: 2015.06.20

Ambient Temperature: 23.3 °C; Liquid Temperature: 22.6 °C


DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(8.01, 8.01, 8.01); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 13.7 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 100.1 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 17.6 W/kg SAR(1 g) = 9.55 W/kg; SAR(10 g) = 5.02 W/kg

Maximum value of SAR (measured) = 13.6 W/kg



0 dB = 13.7 W/kg

System Check Head 1900MHz 150620

DUT: D1900V2-SN:5d118

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

 $Medium: HSL_1900_150620 \ Medium \ parameters \ used: \ f = 1900 \ MHz; \ \sigma = 1.417 \ S/m; \ \epsilon_r = 40.994;$

Date: 2015.06.20

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.3 °C ; **Liquid Temperature**: 22.9 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.66, 7.66, 7.66); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)


Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 15.1 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 104.0 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 19.5 W/kg

SAR(1 g) = 10.5 W/kg; SAR(10 g) = 5.4 W/kg

Maximum value of SAR (measured) = 14.7 W/kg



System Check_Head_2450MHz_150710

DUT: D2450V2-SN:840

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1 Medium: HSL_2450_150710 Medium parameters used: f = 2450 MHz; σ = 1.809 S/m; ϵ_r = 37.604; ρ = 1000 kg/m³

Date: 2015.07.10


Ambient Temperature: 23.4 °C ; **Liquid Temperature**: 22.9 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.01, 7.01, 7.01); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=12mm, dy=12mm Maximum value of SAR (interpolated) = 25.1 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 100.4 V/m; Power Drift = -0.06 dB Peak SAR (extrapolated) = 34.9 W/kg SAR(1 g) = 14.2 W/kg; SAR(10 g) = 5.29 W/kg Maximum value of SAR (measured) = 25.3 W/kg



System Check_Body_835MHz_150619

DUT: D835V2-SN:4d091

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1 Medium: MSL_835_150619 Medium parameters used: f = 835 MHz; $\sigma = 0.991$ S/m; $\epsilon_r = 55.697$; $\rho = 1000$ kg/m³

Date: 2015.06.19


Ambient Temperature: 23.5 °C; Liquid Temperature: 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 SN7346; ConvF(9.8, 9.8, 9.8); Calibrated: 2015.01.08;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1386; Calibrated: 2015.02.19
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 2.41 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 49.45 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 3.27 W/kg SAR(1 g) = 2.24 W/kg; SAR(10 g) = 1.48 W/kg Maximum value of SAR (measured) = 2.40 W/kg



System Check_Body_1750MHz_150618

DUT: D1750V2-SN:1069

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: MSL_1800_150618 Medium parameters used: f = 1750 MHz; $\sigma = 1.514$ S/m; $\epsilon_r = 53.575$;

Date: 2015.06.18

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.3 °C; Liquid Temperature: 22.8 °C


DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.74, 7.74, 7.74); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 14.2 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 98.064 V/m; Power Drift = 0.04 dB Peak SAR (extrapolated) = 17.8 W/kg SAR(1 g) = 10.1 W/kg; SAR(10 g) = 5.42 W/kg

Maximum value of SAR (measured) = 14.2 W/kg



System Check Body 1900MHz 150618

DUT: D1900V2-SN:5d118

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL 1900 150618 Medium parameters used: f = 1900 MHz; $\sigma = 1.529$ S/m; $\varepsilon_r = 53.216$;

Date: 2015.06.18

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.5 °C ; **Liquid Temperature**: 22.7 °C


DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.39, 7.39, 7.39); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 15.7 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 89.995 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 19.6 W/kg SAR(1 g) = 10.7 W/kg; SAR(10 g) = 5.54 W/kg

Maximum value of SAR (measured) = 15.4 W/kg



0 dB = 15.7 W/kg

System Check_Body_2450MHz_150711

DUT: D2450V2-SN:840

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL_2450_150711 Medium parameters used: f = 2450 MHz; $\sigma = 1.977$ S/m; $\varepsilon_r = 51.617$;

Date: 2015.07.11

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.4 °C ; **Liquid Temperature**: 22.8 °C


DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(6.95, 6.95, 6.95); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=12mm, dy=12mm Maximum value of SAR (interpolated) = 19.8 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 85.209 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 26.5 W/kg SAR(1 g) = 13.2 W/kg; SAR(10 g) = 6.22 W/kg

Maximum value of SAR (measured) = 19.9 W/kg



Appendix B. Plots of High SAR Measurement

Report No.: FA561807

The plots are shown as follows.

SPORTON INTERNATIONAL (SHENZHEN) INC.

#01_GSM850_GPRS(4 Tx slots)_Left Cheek_Ch251

Communication System: UID 0, GPRS/EDGE12 (0); Frequency: 848.8 MHz; Duty Cycle: 1:2.08 Medium: HSL_835_150620 Medium parameters used: f = 848.8 MHz; $\sigma = 0.915$ S/m; $\varepsilon_r = 41.067$; $\rho = 1000$ kg/m³

Date: 2015.06.20


Ambient Temperature: 23.4 °C; Liquid Temperature: 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 SN7346; ConvF(9.78, 9.78, 9.78); Calibrated: 2015.01.08;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1386; Calibrated: 2015.02.19
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch251/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.351 W/kg

Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 2.121 V/m; Power Drift = -0.07 dB Peak SAR (extrapolated) = 0.392 W/kg SAR(1 g) = 0.310 W/kg; SAR(10 g) = 0.238 W/kg Maximum value of SAR (measured) = 0.355 W/kg



#02_GSM1900_GPRS(4 Tx slots)_Right Cheek_Ch512

Communication System: UID 0, GPRS/EDGE12 (0); Frequency: 1850.2 MHz; Duty Cycle: 1:2.08 Medium: HSL_1900_150620 Medium parameters used: f = 1850.2 MHz; σ = 1.363 S/m; ϵ_r = 41.24; ρ = 1000 kg/m³

Date: 2015.06.20


Ambient Temperature: 23.3 °C; Liquid Temperature: 22.9 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.66, 7.66, 7.66); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch512/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.280 W/kg

Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 3.541 V/m; Power Drift = 0.05 dB Peak SAR (extrapolated) = 0.337 W/kg SAR(1 g) = 0.227 W/kg; SAR(10 g) = 0.143 W/kg Maximum value of SAR (measured) = 0.283 W/kg



Communication System: UID 0, UMTS (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: HSL_835_150620 Medium parameters used: f = 836.4 MHz; σ = 0.905 S/m; ϵ_r = 41.197;

Date: 2015.06.20

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.4 °C; **Liquid Temperature**: 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 SN7346; ConvF(9.78, 9.78, 9.78); Calibrated: 2015.01.08;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1386; Calibrated: 2015.02.19
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)


Ch4182/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.299 W/kg

Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 1.274 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.339 W/kg

SAR(1 g) = 0.263 W/kg; SAR(10 g) = 0.202 W/kg

Maximum value of SAR (measured) = 0.302 W/kg



Communication System: UID 0, UMTS (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium: HSL_1800_150620 Medium parameters used: f = 1732.6 MHz; $\sigma = 1.361$ S/m; $\epsilon_r = 41.422$;

Date: 2015.06.20

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.3 °C; Liquid Temperature: 22.6 °C


DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(8.01, 8.01, 8.01); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch1413/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.456 W/kg

Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 2.657 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 0.513 W/kg SAR(1 g) = 0.359 W/kg; SAR(10 g) = 0.236 W/kg

Maximum value of SAR (measured) = 0.441 W/kg



Communication System: UID 0, UMTS (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: HSL_1900_150620 Medium parameters used: f = 1907.6 MHz; $\sigma = 1.426$ S/m; $\epsilon_r = 40.977$; $\rho = 1000$ kg/m³

Date: 2015.06.20

 $\rho = 1000 \text{ kg/m}$


Ambient Temperature: 23.3 °C; Liquid Temperature: 22.9 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.66, 7.66, 7.66); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch9538/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.478 W/kg

Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 3.650 V/m; Power Drift = -0.07 dB Peak SAR (extrapolated) = 0.632 W/kg SAR(1 g) = 0.267 W/kg; SAR(10 g) = 0.140 W/kg Maximum value of SAR (measured) = 0.394 W/kg



Communication System: UID 0, WIFI (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL_2450_150710 Medium parameters used: f = 2462 MHz; σ = 1.819 S/m; ϵ_r = 37.507;

Date: 2015.07.10

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.4 °C; Liquid Temperature: 22.9 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.01, 7.01, 7.01); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch11/Area Scan (81x141x1): Interpolated grid: dx=12mm, dy=12mm Maximum value of SAR (interpolated) = 1.21 W/kg


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.397 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 0.756 W/kg; SAR(10 g) = 0.344 W/kg

Maximum value of SAR (measured) = 1.15 W/kg



#07_GSM850_GPRS(4 Tx slots)_Left Side_10mm_Ch128

Communication System: UID 0, GPRS/EDGE12 (0); Frequency: 824.2 MHz; Duty Cycle: 1:2.08 Medium: MSL_835_150619 Medium parameters used: f = 824.2 MHz; $\sigma = 0.981$ S/m; $\epsilon_r = 55.787$; $\rho = 1000$ kg/m³

Date: 2015.06.19


Ambient Temperature: 23.5 °C; Liquid Temperature: 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 SN7346; ConvF(9.8, 9.8, 9.8); Calibrated: 2015.01.08;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1386; Calibrated: 2015.02.19
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch128/Area Scan (41x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.792 W/kg

Ch128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 4.192 V/m; Power Drift = -0.07 dB Peak SAR (extrapolated) = 0.898 W/kg SAR(1 g) = 0.647 W/kg; SAR(10 g) = 0.437 W/kg Maximum value of SAR (measured) = 0.791 W/kg



Communication System: UID 0, GPRS/EDGE12 (0); Frequency: 1850.2 MHz; Duty Cycle: 1:2.08 Medium: MSL_1900_150618 Medium parameters used: f = 1850.2 MHz; $\sigma = 1.462$ S/m; $\epsilon_r = 53.541$; $\rho = 1000$ kg/m³

Date: 2015.06.18


Ambient Temperature: 23.5 °C ; **Liquid Temperature**: 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.39, 7.39, 7.39); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch512/Area Scan (41x61x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 1.24 W/kg

Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 5.780 V/m; Power Drift = -0.1 dB Peak SAR (extrapolated) = 1.47 W/kg SAR(1 g) = 0.858 W/kg; SAR(10 g) = 0.454 W/kg Maximum value of SAR (measured) = 1.20 W/kg



Communication System: UID 0, UMTS (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: MSL_835_150619 Medium parameters used: f = 836.4 MHz; $\sigma = 0.992$ S/m; $\varepsilon_r = 55.684$;

Date: 2015.06.19

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.5 °C; Liquid Temperature: 22.6 °C

DASY5 Configuration:


- Probe: EX3DV4 SN7346; ConvF(9.8, 9.8, 9.8); Calibrated: 2015.01.08;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1386; Calibrated: 2015.02.19

Maximum value of SAR (measured) = 0.619 W/kg

- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch4182/Area Scan (41x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.621 W/kg

Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 4.958 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 0.705 W/kg SAR(1 g) = 0.506 W/kg; SAR(10 g) = 0.351 W/kg



Communication System: UID 0, UMTS (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium: MSL_1800_150618 Medium parameters used: f = 1732.6 MHz; $\sigma = 1.496$ S/m; $\epsilon_r = 53.644$;

Date: 2015.06.18

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.3 °C; Liquid Temperature: 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.74, 7.74, 7.74); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch1413/Area Scan (41x61x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 1.63 W/kg


Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.049 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.95 W/kg

SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.611 W/kg

Maximum value of SAR (measured) = 1.61 W/kg



Communication System: UID 0, UMTS (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: MSL_1900_150618 Medium parameters used: f = 1907.6 MHz; $\sigma = 1.538$ S/m; $\epsilon_r = 53.208$; $\rho = 1000$ kg/m³

Date: 2015.06.18

Ambient Temperature: 23.5 °C ; **Liquid Temperature**: 22.7 °C


DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.39, 7.39, 7.39); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch9538/Area Scan (41x61x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 1.15 W/kg

Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 5.198 V/m; Power Drift = -0.09 dB Peak SAR (extrapolated) = 1.40 W/kg SAR(1 g) = 0.791 W/kg; SAR(10 g) = 0.410 W/kg

Maximum value of SAR (measured) = 1.13 W/kg



#12_WLAN2.4GHz_802.11b 1Mbps_Front_10mm_Ch11

Communication System: UID 0, WIFI (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_150711 Medium parameters used: f = 2462 MHz; $\sigma = 1.992$ S/m; $\varepsilon_r = 51.558$;

Date: 2015.07.11

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.4 °C; Liquid Temperature: 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(6.95, 6.95, 6.95); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch11/Area Scan (81x141x1): Interpolated grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.200 W/kg


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.484 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.259 W/kg

SAR(1 g) = 0.142 W/kg; SAR(10 g) = 0.082 W/kg

Maximum value of SAR (measured) = 0.195 W/kg



#13_GSM850_GPRS(4 Tx slots)_Back_10mm_Ch128

Communication System: UID 0, GPRS/EDGE12 (0); Frequency: 824.2 MHz; Duty Cycle: 1:2.08 Medium: MSL_835_150619 Medium parameters used: f = 824.2 MHz; $\sigma = 0.981$ S/m; $\epsilon_r = 55.787$; $\rho = 1000$ kg/m³

Date: 2015.06.19


Ambient Temperature: 23.5 °C; Liquid Temperature: 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 SN7346; ConvF(9.8, 9.8, 9.8); Calibrated: 2015.01.08;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1386; Calibrated: 2015.02.19
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch128/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.585 W/kg

Ch128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 2.547 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 0.631 W/kg SAR(1 g) = 0.512 W/kg; SAR(10 g) = 0.404 W/kg Maximum value of SAR (measured) = 0.581 W/kg



#14_GSM1900_GPRS(4 Tx slots)_Back_10mm_Ch661

Communication System: UID 0, GPRS/EDGE12 (0); Frequency: 1880 MHz; Duty Cycle: 1:2.08 Medium: MSL_1900_150618 Medium parameters used: f = 1880 MHz; $\sigma = 1.501$ S/m; $\epsilon_r = 53.351$; $\rho = 1000$ kg/m³

Date: 2015.06.18


Ambient Temperature: 23.5 °C; Liquid Temperature: 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.39, 7.39, 7.39); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch661/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.883 W/kg

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 2.680 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 1.03 W/kg SAR(1 g) = 0.608 W/kg; SAR(10 g) = 0.347 W/kg Maximum value of SAR (measured) = 0.798 W/kg



Communication System: UID 0, UMTS (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: MSL_835_150619 Medium parameters used: f = 836.4 MHz; $\sigma = 0.992$ S/m; $\epsilon_r = 55.684$;

Date: 2015.06.19

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.5 °C; Liquid Temperature: 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 SN7346; ConvF(9.8, 9.8, 9.8); Calibrated: 2015.01.08;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1386; Calibrated: 2015.02.19
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch4182/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.528 W/kg


Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.301 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.561 W/kg

SAR(1 g) = 0.457 W/kg; SAR(10 g) = 0.361 W/kg

Maximum value of SAR (measured) = 0.517 W/kg



Communication System: UID 0, UMTS (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium: MSL_1800_150618 Medium parameters used: f = 1732.6 MHz; $\sigma = 1.496$ S/m; $\epsilon_r = 53.644$; $\rho = 1000$ kg/m³

Date: 2015.06.18

Ambient Temperature: 23.3 °C; Liquid Temperature: 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.74, 7.74, 7.74); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch1413/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 1.22 W/kg


Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.543 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.867 W/kg; SAR(10 g) = 0.482 W/kg

Maximum value of SAR (measured) = 1.17 W/kg



Communication System: UID 0, UMTS (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: MSL_1900_150618 Medium parameters used: f = 1907.6 MHz; $\sigma = 1.538$ S/m; $\epsilon_r = 53.208$;

Date: 2015.06.18

 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 23.5 °C; Liquid Temperature: 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 SN3819; ConvF(7.39, 7.39, 7.39); Calibrated: 2014.11.13;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2014.12.11
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Ch9538/Area Scan (71x111x1): Interpolated grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.911 W/kg

Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 2.992 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.641 W/kg; SAR(10 g) = 0.355 W/kg

Maximum value of SAR (measured) = 0.887 W/kg

