

FCC PART 15B, CLASS B **TEST REPORT**

For

BLU Products, Inc.

10814 NW 33rd St # 100 Doral, FL 33172, United States

FCC ID: YHLBLUJOY

Report Type: **Product Type:**

Original Report Mobile phone

Report Number: RSZ160819004-00A

Report Date: 2016-10-17

Oscar Ye

Reviewed By: Engineer

Bay Area Compliance Laboratories Corp. (Kunshan) Chenghu Road, Kunshan Development Zone

Oscar. Ye

No.248, Kunshan, Jiangsu, China Prepared By:

Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

| GENERAL INFORMATION | 3 |
|--|----------------------|
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3 |
| Objective | |
| RELATED SUBMITTAL(S)/GRANT(S) | |
| TEST METHODOLOGY | |
| MEASUREMENT UNCERTAINTY | |
| TEST FACILITY | 4 |
| SYSTEM TEST CONFIGURATION | 5 |
| DESCRIPTION OF TEST CONFIGURATION | 5 |
| EUT Exercise Software | 5 |
| SPECIAL ACCESSORIES | |
| EQUIPMENT MODIFICATIONS | 5 |
| SUPPORT EQUIPMENT LIST AND DETAILS | |
| External I/O Cable | |
| BLOCK DIAGRAM OF TEST SETUP | 6 |
| SUMMARY OF TEST RESULTS | 7 |
| | |
| TEST EQUIPMENT LIST | 8 |
| FCC §15.107 – AC LINE CONDUCTED EMISSIONS | 9 |
| APPLICABLE STANDARD | |
| EUT SETUP. | |
| EMI TEST RECEIVER SETUP | |
| TEST PROCEDURE | |
| CORRECTED FACTOR & MARGIN CALCULATION | 10 |
| TEST RESULTS SUMMARY | 10 |
| Test Data | 10 |
| | |
| FCC §15.109 - RADIATED SPURIOUS EMISSIONS | 10 |
| FCC §15.109 - RADIATED SPURIOUS EMISSIONS | 10 |
| APPLICABLE STANDARD | 10 13 |
| APPLICABLE STANDARDEUT SETUP | 10 13 13 |
| APPLICABLE STANDARDEUT SETUPEMI TEST RECEIVER SETUP | 10 13 13 14 |
| APPLICABLE STANDARDEUT SETUP | 1313131414 |
| APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE | 101313131414 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *BLU Products, Inc.*'s product, model number: JOY (*FCC ID: YHLBLUJOY*) or the "EUT" in this report was a Mobile phone, which was measured approximately: 11.3 cm (L) × 6.7 cm (W) × 1.3 cm (H), rated with input voltage: DC 3.7V rechargeable Li-ion battery or DC 5.0V from adapter. The highest operating frequency is 2480 MHz.

Report No.: RSZ160819004-00A

Adapter Information: Model: US-ZC-0750

Input: AC 100-240V, 50/60Hz, 0.2A

Output: DC 5.0V, 750mA

*All measurement and test data in this report was gathered from production sample serial number: 1603016 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2016-08-19.

Objective

This test report is prepared on behalf of *BLU Products*, *Inc*. in accordance with Part 2-Subpart J, Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS and Part 22H & 24E PCE submissions with FCC ID: YHLBLUJOY.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

| | Item | Uncertainty |
|--------------------|-----------------------|-------------|
| AC Power Lines | s Conducted Emissions | ±3.26 dB |
| Dadistal amississa | 30MHz~1GHz | ±5.91dB |
| Radiated emission | Above 1G | ±4.92dB |

FCC Part 15B, Class B Page 3 of 15

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Lake Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China

Report No.: RSZ160819004-00A

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15B, Class B Page 4 of 15

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode: Downloading (data transfer with computer)

EUT Exercise Software

"BurnIn test v5.3" exercise software was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|--------|---------------|
| DELL | PC | E6410 | GYXJ3A00 JSD2 |
| DELL | Mouse | MOC5UO | G1900NKD |
| DELL | Adapter | E6410 | 10912240373 |
| Kingston | U disk | 4 GB | N/A |

Report No.: RSZ160819004-00A

External I/O Cable


| Cable Description | Length (m) | From/Port | То |
|-------------------------------------|------------|-----------|--------|
| Un-Shielding Detachable USB Cable | 0.5 | PC | U disk |
| Un-Shielding Detachable USB Cable | 1.5 | PC | Mouse |
| Un-shielding Detachable USB Cable | 1.0 | EUT | PC |
| Un-shielding Detachable AC Cable | 0.9 | Adapter | LISN 1 |
| Un-shielding Un-detachable DC Cable | 0.9 | Adapter | PC |

FCC Part 15B, Class B Page 5 of 15

Report No.: RSZ160819004-00A

Block Diagram of Test Setup

For conducted emission:



FCC Part 15B, Class B Page 6 of 15

SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Results |
|-----------|-----------------------------|------------|
| §15.107 | AC Line Conducted Emissions | Compliance |
| §15.109 | Radiated Spurious Emissions | Compliance |

Report No.: RSZ160819004-00A

FCC Part 15B, Class B Page 7 of 15

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date | | | |
|-------------------|---------------------------------|---------------------------|---------------|---------------------|-------------------------|--|--|--|
| | AC Line Conducted Emission Test | | | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESCS30 | 934115/007 | 2015-11-12 | 2016-11-11 | | | |
| Rohde & Schwarz | LISN | ESH3-Z5 | 862770/011 | 2015-11-12 | 2016-11-11 | | | |
| Rohde & Schwarz | LISN | ESH3-Z5 | 892239/018 | 2016-06-23 | 2017-06-22 | | | |
| Rohde & Schwarz | Pulse limiter | ESH3-Z2 | 879940/0058 | 2016-06-19 | 2017-06-18 | | | |
| MICRO-COAX | Coaxial line | UFB-293B-1- 0480-50X50 | 97F0173 | 2016-09-01 | 2017-09-01 | | | |
| Rohde & Schwarz | CE Test software | EMC 32 | V 09.10.0 | NCR | NCR | | | |
| | R | Radiated Emission | n Test | | | | | |
| Sonoma Instrunent | Amplifier | 330 | 171377 | 2016-09-16 | 2017-09-16 | | | |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100195 | 2015-11-12 | 2016-11-11 | | | |
| Sunol Sciences | Broadband Antenna | JB3 | A090314-2 | 2015-11-07 | 2016-11-06 | | | |
| ETS | Horn Antenna | 3115 | 6229 | 2015-11-07 | 2016-11-06 | | | |
| EMCO | Horn Antenna | 3116 | 9510-2384 | 2015-11-07 | 2016-11-06 | | | |
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 100048 | 2015-11-12 | 2016-11-11 | | | |
| Mini | Pre-amplifier | ZVA-183-S+ | 857001418 | 2016-09-16 | 2017-09-16 | | | |
| R&S | Auto test Software | EMC32 | V 09.10.0 | NCR | NCR | | | |
| BACL | RF cable | KS-LAB-012 | KS-LAB-012 | 2015-12-15 | 2016-12-15 | | | |

Report No.: RSZ160819004-00A

FCC Part 15B, Class B Page 8 of 15


^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI)

FCC §15.107 - AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC §15.107

EUT Setup



Report No.: RSZ160819004-00A

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

FCC Part 15B, Class B Page 9 of 15

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Report No.: RSZ160819004-00A

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


| Temperature: | 25℃ |
|--------------------|-----------|
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Peter Jiang on 2016-10-05.

FCC Part 15B, Class B Page 10 of 15

EUT Operation Mode: Downloading

AC 120V/60 Hz, Line:




Report No.: RSZ160819004-00A

| Frequency (MHz) | QuasiPeak (dBµV) | Average (dB µ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) | Comment |
|--------------------|---------------------|---------------------|--------------------|------|------------|----------------|-----------------|------------|
| 0.170000 | | 33.01 | 9.000 | L1 | 10.3 | 21.95 | 54.96 | Compliance |
| 0.170000 | 51.31 | | 9.000 | L1 | 10.3 | 13.65 | 64.96 | Compliance |
| 0.240000 | | 28.99 | 9.000 | L1 | 10.3 | 23.11 | 52.10 | Compliance |
| 0.240000 | 43.15 | | 9.000 | L1 | 10.3 | 18.95 | 62.10 | Compliance |
| 0.460000 | | 23.04 | 9.000 | L1 | 10.3 | 23.65 | 46.69 | Compliance |
| 0.460000 | 35.81 | | 9.000 | L1 | 10.3 | 20.88 | 56.69 | Compliance |
| 0.555000 | | 23.45 | 9.000 | L1 | 10.3 | 22.55 | 46.00 | Compliance |
| 0.555000 | 36.86 | | 9.000 | L1 | 10.3 | 19.14 | 56.00 | Compliance |
| 4.985000 | | 29.64 | 9.000 | L1 | 10.5 | 16.36 | 46.00 | Compliance |
| 4.985000 | 35.95 | | 9.000 | L1 | 10.5 | 20.05 | 56.00 | Compliance |
| 18.810000 | | 20.44 | 9.000 | L1 | 10.5 | 29.56 | 50.00 | Compliance |
| 18.810000 | 25.92 | | 9.000 | L1 | 10.5 | 34.08 | 60.00 | Compliance |

FCC Part 15B, Class B Page 11 of 15

AC 120V/60 Hz, Neutral:



Report No.: RSZ160819004-00A

| Frequency (MHz) | QuasiPeak (dBµV) | Average (dB \mu V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) | Comment |
|--------------------|---------------------|-----------------------|-----------------|------|------------|-------------|-----------------|------------|
| 0.170000 | | 39.32 | 9.000 | N | 10.3 | 15.64 | 54.96 | Compliance |
| 0.170000 | 57.59 | | 9.000 | N | 10.3 | 7.37 | 64.96 | Compliance |
| 0.225000 | | 30.70 | 9.000 | N | 10.3 | 21.93 | 52.63 | Compliance |
| 0.225000 | 49.73 | | 9.000 | N | 10.3 | 16.90 | 62.63 | Compliance |
| 0.560000 | | 21.08 | 9.000 | N | 10.3 | 24.92 | 46.00 | Compliance |
| 0.560000 | 33.93 | | 9.000 | N | 10.3 | 22.07 | 56.00 | Compliance |
| 2.770000 | | 22.54 | 9.000 | N | 10.5 | 23.46 | 46.00 | Compliance |
| 2.770000 | 31.59 | | 9.000 | N | 10.5 | 24.41 | 56.00 | Compliance |
| 4.945000 | | 30.57 | 9.000 | N | 10.6 | 15.43 | 46.00 | Compliance |
| 4.945000 | 37.24 | | 9.000 | N | 10.6 | 18.76 | 56.00 | Compliance |
| 18.440000 | | 20.21 | 9.000 | N | 10.5 | 29.79 | 50.00 | Compliance |
| 18.440000 | 25.51 | | 9.000 | N | 10.5 | 34.49 | 60.00 | Compliance |

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation 2) Corrected Amplitude = Reading + Correction Factor 3) Margin = Limit Corrected Amplitude

FCC Part 15B, Class B Page 12 of 15


FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §15.109


EUT Setup

Below 1GHz:



Report No.: RSZ160819004-00A

Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

FCC Part 15B, Class B Page 13 of 15

EMI Test Receiver Setup

The system was investigated from 30 MHz to 12.4 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz | 120 kHz | QP |
| Above 1 GHz | 1MHz | 3 MHz | / | PK |
| Above I GHZ | 1MHz | 10 Hz | / | Ave. |

Report No.: RSZ160819004-00A

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit - Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

FCC Part 15B, Class B Page 14 of 15

Test Data

Environmental Conditions

| Temperature: | 25℃ |
|--------------------|-----------|
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Peter Jiang on 2016-10-05.

EUT Operation Mode: Downloading

30 MHz~12.4GHz

| Frequency (MHz) | Receiver | | | Rx Antenna | | Corrected | Corrected | FCC Part 15B | |
|-----------------|----------------|--------------------------|---------------------|------------|----------------|-----------|--------------------|-------------------|-------------|
| | Reading (dBµV) | Detector (PK/QP/Ave.) | Turntable Degree | Height (m) | Polar (H/V) | | Amplitude (dBµV/m) | Limit (dBµV/m) | Margin (dB) |
| 65.90 | 53.56 | QP | 0 | 1.6 | V | -16.90 | 36.66 | 40.0 | 3.34 |
| 96.16 | 48.38 | QP | 192 | 3.6 | Н | -16.76 | 31.62 | 43.5 | 11.88 |
| 155.86 | 42.58 | QP | 321 | 1.9 | Н | -12.21 | 30.37 | 43.5 | 13.13 |
| 228.66 | 44.49 | QP | 266 | 1.3 | Н | -12.15 | 32.34 | 46.0 | 13.66 |
| 341.68 | 46.51 | QP | 193 | 1.1 | Н | -9.52 | 36.99 | 46.0 | 9.01 |
| 465.08 | 40.79 | QP | 191 | 1.1 | V | -6.40 | 34.39 | 46.0 | 11.61 |
| 1854.82 | 38.00 | PK | 18 | 1.4 | Н | -4.32 | 33.68 | 74 | 40.32 |
| 1854.82 | 27.62 | Ave. | 18 | 1.4 | Н | -4.32 | 23.30 | 54 | 30.70 |
| 1854.82 | 39.16 | PK | 54 | 1.4 | V | -4.32 | 34.84 | 74 | 39.16 |
| 1854.82 | 28.35 | Ave. | 54 | 1.4 | V | -4.32 | 24.03 | 54 | 29.97 |

Report No.: RSZ160819004-00A

Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss amplifier factor
- 2) Corrected Amplitude = Correction Factor + Reading
- 3) Margin = Limit Corrected Amplitude

***** END OF REPORT *****

FCC Part 15B, Class B Page 15 of 15