

FCC PART 15B, CLASS B TEST REPORT

For

BLU Products, Inc.

10814 NW 33rd St # 100 Doral, FL 33172, United States

FCC ID: YHLBLULIFEONEX2

Report Type: Product Type: Original Report Smartphone Report Number: RSZ160817007-00A **Report Date:** 2016-10-28 Oscar Ye Gscar. Ye **Reviewed By:** Engineer Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China Tel: +86-0512-86175000 Fax: +86-0512-88934268

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

www.baclcorp.com.cn

TABLE OF CONTENTS

	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	3
Measurement Uncertainty	
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT Exercise Software	5
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	
External I/O Cable	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	8
TEST EQUIPMENT LISTFCC §15.107 – AC LINE CONDUCTED EMISSIONS	
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	9
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	9 9
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	9 9
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	9 9 9
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION	
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION	99 99 99 99 99 99 99 99 99 99 99 99 99
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY	
FCC §15.107 - AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS	99 99 99 100 100 100 100 100 100 100 100
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA	99 99 99 99 99 99 99 99 99 99 99 99 99
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS APPLICABLE STANDARD	
APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE	
APPLICABLE STANDARD EUT SETUP EMI TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP	
APPLICABLE STANDARD EUT SETUP EMI TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE	

Report No.: RSZ160817007-00A

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *BLU Products, Inc.*'s product, model number: *LIFE ONE X2(FCC ID: YHLBLULIFEONEX2)* or the "EUT" in this report was a *Smartphone*, which was measured approximately: $14.8 \text{ cm } (L) \times 7.3 \text{ cm } (W) \times 0.9 \text{ cm } (H)$, rated with input voltage: DC 3.85 V rechargeable Li-ion battery or DC 5.0/9.0/12.0 V from adapter. The higest operating frequency is 2690 MHz.

Report No.: RSZ160817007-00A

Adapter Information: Model: US-BM-2002

Input: AC 100-240V, 50/60Hz, 0.5A

Output: DC 5 V, 3A; DC 9 V, 2A; DC 12V, 1.5A

*All measurement and test data in this report was gathered from production sample serial number: 1603001 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2016-08-17.

Objective

This test report is prepared on behalf of *BLU Products, Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS & DTS and Part 22H & 24E & 27 PCE submissions with FCC ID: YHLBLULIFEONEX2.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

	Item	Uncertainty
AC Power Lines	s Conducted Emissions	±3.26 dB
Dadistal amississa	30MHz~1GHz	±5.91dB
Radiated emission	Above 1G	±4.92dB

FCC Part 15B, Class B Page 3 of 15

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Lake Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China

Report No.: RSZ160817007-00A

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15B, Class B Page 4 of 15

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode: Downloading (data transfer with computer)

EUT Exercise Software

"BurnIn test v5.3" exercise software was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	PC	E6410	GYXJ3A00 JSD2
DELL	Mouse	MOC5UO	G1900NKD
DELL	Adapter	E6410	10912240373
Kingston	U disk	4 GB	N/A

Report No.: RSZ160817007-00A

FCC Part 15B, Class B Page 5 of 15


External I/O Cable

Cable Description	Length (m)	From/Port	То
Un-Shielding Detachable USB Cable	0.5	PC	U disk
Un-Shielding Detachable USB Cable	1.5	PC	Mouse
Un-shielding Detachable USB Cable	1.0	EUT	PC
Un-shielding Detachable AC Cable	0.9	Adapter	LISN 1
Un-shielding Un-detachable DC Cable	0.9	Adapter	PC

Report No.: RSZ160817007-00A

Block Diagram of Test Setup

For conducted emission:



FCC Part 15B, Class B Page 6 of 15

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Spurious Emissions	Compliance

Report No.: RSZ160817007-00A

FCC Part 15B, Class B Page 7 of 15

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date			
	AC Line Conducted Emission Test							
Rohde & Schwarz	EMI Test Receiver	ESCS30	934115/007	2015-11-12	2016-11-11			
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2015-11-12	2016-11-11			
Rohde & Schwarz	LISN	ESH3-Z5	892239/018	2016-06-23	2017-06-22			
Rohde & Schwarz	Pulse limiter	ESH3-Z2	879940/0058	2016-06-19	2017-06-18			
MICRO-COAX	Coaxial line	UFB-293B-1- 0480-50X50	97F0173	2016-09-01	2017-09-01			
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	NCR	NCR			
	R	Radiated Emission	n Test					
Sonoma Instrunent	Amplifier	330	171377	2016-09-16	2017-09-16			
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-11-12	2016-11-11			
Sunol Sciences	Broadband Antenna	ЈВ3	A090314-2	2015-11-07	2016-11-06			
ETS	Horn Antenna	3115	6229	2015-11-07	2016-11-06			
EMCO	Horn Antenna	3116	9510-2384	2015-11-07	2016-11-06			
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2015-11-12	2016-11-11			
Mini	Pre-amplifier	ZVA-183-S+	857001418	2016-09-16	2017-09-16			
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR			
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-12-15	2016-12-15			

Report No.: RSZ160817007-00A

FCC Part 15B, Class B Page 8 of 15


^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI)

FCC §15.107 - AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC §15.107

EUT Setup



Report No.: RSZ160817007-00A

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the host PC was connected to the first LISN and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

FCC Part 15B, Class B Page 9 of 15

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Report No.: RSZ160817007-00A

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	25 ℃
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa

The testing was performed by Chris Wang on 2016-10-26.

FCC Part 15B, Class B Page 10 of 15

EUT Operation Mode: Downloading

AC 120V/60 Hz, Line




Report No.: RSZ160817007-00A

Frequency (MHz)	QuasiPeak (dBµV)	Average (dB \mu V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.165000		34.36	9.000	L1	10.3	20.85	55.21	Compliance
0.165000	57.15		9.000	L1	10.3	8.06	65.21	Compliance
0.175000		36.85	9.000	L1	10.3	17.87	54.72	Compliance
0.175000	57.49		9.000	L1	10.3	7.23	64.72	Compliance
0.230000		28.30	9.000	L1	10.3	24.15	52.45	Compliance
0.230000	48.56		9.000	L1	10.3	13.89	62.45	Compliance
0.290000		25.87	9.000	L1	10.3	24.65	50.52	Compliance
0.290000	42.98		9.000	L1	10.3	17.54	60.52	Compliance
0.520000		18.84	9.000	L1	10.3	27.16	46.00	Compliance
0.520000	32.46		9.000	L1	10.3	23.54	56.00	Compliance
4.970000		31.26	9.000	L1	10.5	14.74	46.00	Compliance
4.970000	35.91		9.000	L1	10.5	20.09	56.00	Compliance

FCC Part 15B, Class B Page 11 of 15

AC 120V/60 Hz, Neutral



Report No.: RSZ160817007-00A

Frequency (MHz)	QuasiPeak (dBµV)	Average (dB µ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.165000		35.41	9.000	N	10.3	19.80	55.21	Compliance
0.165000	50.04		9.000	N	10.3	15.17	65.21	Compliance
0.175000		35.34	9.000	N	10.3	19.38	54.72	Compliance
0.175000	50.85		9.000	N	10.3	13.87	64.72	Compliance
0.225000		23.44	9.000	N	10.3	29.19	52.63	Compliance
0.225000	43.15		9.000	N	10.3	19.48	62.63	Compliance
0.455000		21.52	9.000	N	10.3	25.26	46.78	Compliance
0.455000	34.83		9.000	N	10.3	21.95	56.78	Compliance
0.545000		23.79	9.000	N	10.3	22.21	46.00	Compliance
0.545000	36.27		9.000	N	10.3	19.73	56.00	Compliance
4.880000		30.67	9.000	N	10.6	15.33	46.00	Compliance
4.880000	37.43		9.000	N	10.6	18.57	56.00	Compliance

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation 2) Corrected Amplitude = Reading + Correction Factor 3) Margin = Limit Corrected Amplitude

FCC Part 15B, Class B Page 12 of 15


FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §15.109


EUT Setup

Below 1GHz:



Report No.: RSZ160817007-00A

Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

FCC Part 15B, Class B Page 13 of 15

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Report No.: RSZ160817007-00A

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 13.45 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above I GHZ	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

FCC Part 15B, Class B Page 14 of 15

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	47 %
ATM Pressure:	101.0 kPa

The testing was performed by Chris Wang on 2016-10-25.

EUT Operation Mode: Downloading

30 MHz – 13.45 GHz:

Frequency (MHz)	Receiver			Rx Antenna		C	C	FCC Part 15B	
	Reading (dBµV)	Detector (PK/QP/Ave.)	Turntable Degree	Height (m)	Polar (H/V)	Corrected Factor (dB/m)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
149.51	29.57	QP	209	2.2	Н	-12.07	17.50	43.5	26.00
180.16	36.90	QP	219	1.5	V	-11.90	25.00	43.5	18.50
240.50	43.85	QP	108	1.3	Н	-12.05	31.80	46	14.20
269.88	49.33	QP	238	1.5	Н	-11.33	38.00	46	8.00
398.12	44.78	QP	165	1.0	V	-8.38	36.40	46	9.60
720.19	32.48	QP	82	2.0	V	-2.28	30.20	46	15.80
1658.00	43.32	PK	57	1.0	Н	-5.69	37.63	74	36.37
1658.00	26.61	Ave.	57	1.0	Н	-5.69	20.92	54	33.08
1658.00	41.92	PK	149	1.1	V	-5.69	36.23	74	37.77
1658.00	25.23	Ave.	149	1.1	V	-5.69	19.54	54	34.46

Report No.: RSZ160817007-00A

Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss amplifier factor
- 2) Corrected Amplitude = Correction Factor + Reading
- 3) Margin = Limit Corrected Amplitude

***** END OF REPORT *****

FCC Part 15B, Class B Page 15 of 15