

FCC TEST REPORT (PART 27)

REPORT NO.: RF120723C24A-2

MODEL NO.: Quattro 4.5 HD

FCC ID: YHLBLUQT45HD

RECEIVED: Jul. 23, 2012

TESTED: Aug. 30, 2012

ISSUED: Sep. 11, 2012

APPLICANT: CT Asia

ADDRESS: Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun

road, Kwun Tong, Kowloon, Hongkong

ISSUED BY: Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New

Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: RF120723C24A-2 1 of 29 Report Format Version 5.0.0

Reference No.: 120723C24, 120910C18



TABLE OF CONTENTS

RELEA	SE CONTROL RECORD	
1	CERTIFICATION	
2	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
2.2	TEST SITE AND INSTRUMENTS	6
3	GENERAL INFORMATION	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	CONFIGURATION OF SYSTEM UNDER TEST	8
3.3	DESCRIPTION OF SUPPORT UNITS	8
3.4	TEST ITEM AND TEST CONFIGURATION	9
3.5	EUT OPERATING CONDITIONS	. 10
3.6	GENERAL DESCRIPTION OF APPLIED STANDARDS	. 10
4	TEST TYPES AND RESULTS	. 11
4.1	OUTPUT POWER MEASUREMENT	. 11
4.1.1	LIMITS OF OUTPUT POWER MEASUREMENT	. 11
4.1.2	TEST PROCEDURES	. 11
4.1.3	TEST SETUP	. 11
4.1.4	TEST RESULTS	. 12
4.2	FREQUENCY STABILITY MEASUREMENT	. 13
4.2.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT	. 13
4.2.2	TEST PROCEDURE	. 13
4.2.3	TEST SETUP	
4.2.4	TEST RESULTS	. 14
4.3	OCCUPIED BANDWIDTH MEASUREMENT	. 15
4.3.1	TEST PROCEDURES	. 15
4.3.2	TEST SETUP	. 15
4.3.3	TEST RESULTS	. 16
4.4	BAND EDGE MEASUREMENT	. 17
4.4.1	LIMITS OF BAND EDGE MEASUREMENT	. 19
4.4.2	TEST SETUP	. 19
4.4.3	TEST PROCEDURES	. 19
4.4.4	TEST RESULTS	. 20
4.5	CONDUCTED SPURIOUS EMISSIONS	. 21
4.5.1	LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	. 21
4.5.2	TEST PROCEDURE	. 21
4.5.3	TEST SETUP	. 21
4.5.4	TEST RESULTS	. 22
4.6	RADIATED EMISSION MEASUREMENT	. 23
4.6.1	LIMITS OF RADIATED EMISSION MEASUREMENT	. 23
4.6.2	TEST PROCEDURES	. 23
4.6.3	DEVIATION FROM TEST STANDARD	. 23
4.6.4	TEST SETUP	. 24
4.6.5	TEST RESULTS	. 25
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	. 27
6	INFORMATION ON THE TESTING LABORATORIES	. 28
7	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE E	
	BY THE LAB	. 29



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120723C24A-2	Original release	Sep. 11, 2012

3 of 29



1 CERTIFICATION

PRODUCT: GSM/WCDMA mobile

MODEL: Quattro 4.5 HD

BRAND: BLU

APPLICANT: CT Asia

TESTED: Aug. 30, 2012

TEST SAMPLE: Identical Prototype

STANDARDS: FCC Part 27

The above equipment (model: Quattro 4.5 HD) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :_______, DATE : Sep. 11, 2012

Pettie Chen / Senior Specialist

APPROVED BY: , DATE: Sep. 11, 2012

Gary Chang / Technical/Manager



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 27 & Part 2					
STANDARD TEST TYPE R		RESULT	REMARK		
2.1046 27.50(d)(4)	Equivalent isotropically radiated power	PASS	Meet the requirement of limit.		
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.		
2.1049 27.53(h)	Occupied Bandwidth	PASS	Meet the requirement of limit.		
27.50(d)(5)	Peak to average ratio	PASS	Meet the requirement of limit.		
27.53(h)	Band Edge Measurements	PASS	Meet the requirement of limit.		
2.1051 27.53(h)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.		
2.1053 27.53(h)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -29.98dB at 30.27MHz.		

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
	30MHz ~ 200MHz	2.93 dB
Dadiated emissions	200MHz ~1000MHz	2.95 dB
Radiated emissions	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver Agilent	N9038A	MY51210203	Dec. 22, 2011	Dec. 21, 2012
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 21, 2011	Dec. 20, 2012
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 20, 2011	Dec. 19, 2012
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Dec. 20, 2011	Dec. 19, 2012
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 20, 2011	Dec. 19, 2012
Preamplifier EMCI	EMC 012645	980115	Dec. 30, 2011	Dec. 29, 2012
Preamplifier EMCI	EMC 330H	980112	Dec. 30, 2011	Dec. 29, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4	Oct. 21, 2011	Oct. 20, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Jan. 02, 2012	Jan. 01, 2013
RF signal cable Worken	RG-213	NA	Jan. 02, 2012	Jan. 01, 2013
Software	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
Mini-Circuits Power Splitter	ZN2PD-9G	NA	Mar. 23, 2012	Mar. 22, 2013
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
Communications Tester-Wireless	E5515C	MY50266653	Sep. 28, 2011	Sep. 27, 2012
Radio Communication Analyzer	MT8820C	6201127458	May 25, 2012	May 24, 2013

NOTE:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 2. The test was performed in HwaYa Chamber 9.
- 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 460141.
- 5. The IC Site Registration No. is IC 7450F-4.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	GSM/WCDMA mobile
MODEL NO.	Quattro 4.5 HD
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.7Vdc (battery)
MODULATION TYPE	QPSK, BPSK
FREQUENCY RANGE	1712.4MHz ~1752.6MHz
MAX. EIRP POWER	0.191Watts
EMISSION DESIGNATOR	4M08F9W
WCDMA RELEASE VERSION	6
ANTENNA TYPE	Fixed Internal antenna with -0.3dBi gain
DATA CABLE	Refer to Note as below
I/O PORTS	Refer to users' manual
ACCESSORY DEVICES	Refer to Note as below

NOTE:


1. The EUT contains the following accessories.

ITEM	BRAND	MODEL	SPECIFICATION
Adapter	BIT 118-02-001 '		Input: 100-240Vac, 150mA Output: 5Vdc, 800mA
Battery	BLU	NA	Rating: 3.7Vdc, 1820mAh Type: Li-ion
Earphone	BLU	NA	1.1m non-shielded cable without ferrite core
USB Cable	BLU	NA	0.9m shielded cable without ferrite core


2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 CONFIGURATION OF SYSTEM UNDER TEST



<For Output Power Test>



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.



3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case was found when positioned on Z-plane for EIRP and Y-axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

WCDMA MODE

TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
EIRP	1312 to 1513	1312, 1413, 1513	WCDMA
FREQUENCY STABILITY	1312 to 1513	1413	WCDMA
OCCUPIED BANDWIDTH	1312 to 1513	1413	WCDMA
BAND EDGE	1312 to 1513	1312, 1513	WCDMA
CONDCUDETED EMISSION	1312 to 1513	1413	WCDMA
RADIATED EMISSION BELOW 1 GHz	1312 to 1513	1413	WCDMA

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	26deg. C, 58%RH	3.7Vdc	Phoenix Chen
FREQUENCY STABILITY	26deg. C, 58%RH	3.7Vdc	Phoenix Chen
OCCUPIED BANDWIDTH	26deg. C, 58%RH	3.7Vdc	Phoenix Chen
BAND EDGE	26deg. C, 58%RH	3.7Vdc	Phoenix Chen
CONDCUDETED EMISSION	26deg. C, 58%RH	3.7Vdc	Phoenix Chen
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu



3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2 FCC 47 CFR Part 27 ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.



4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Fixed, mobile, and portable (hand-held) stat ions operating in the 1710–1755 MHz band are limited to 1 watt EIRP


4.1.2 TEST PROCEDURES

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 TEST SETUP

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

11 of 29



4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band		WCDMA IV			
Channel	1312	1413	1513		
Frequency (MHz)	1712.4	1732.6	1752.6		
RMC 12.2K	23.59	23.56	23.72		
HSDPA Subtest-1	23.25	23.22	23.38		
HSDPA Subtest-2	22.28	22.25	22.41		
HSDPA Subtest-3	22.11	22.08	22.24		
HSDPA Subtest-4	21.82	21.79	21.95		
HSUPA Subtest-1	20.03	20.00	20.16		
HSUPA Subtest-2	20.36	20.33	20.49		
HSUPA Subtest-3	20.42	20.39	20.55		
HSUPA Subtest-4	20.64	20.61	20.77		
HSUPA Subtest-5	19.78	19.75	19.91		

EIRP POWER (dBm)

Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
	1312	1712.4	-16.13	37.90	21.77	150.314	Н
	1413	1732.6	-16.44	37.99	21.55	142.889	Н
Z	1513	1752.6	-16.06	38.31	22.25	167.880	Н
	1312	1712.4	-16.72	37.81	21.09	128.529	V
	1413	1732.6	-15.92	37.40	21.48	140.605	V
	1513	1752.6	-15.40	38.22	22.82	191.426	V



4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 TEST PROCEDURE

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5 ^{\circ}$ C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP





4.2.4 TEST RESULTS

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)	LIMIT (ppm)
3.7	-0.0122	2.5
3.5	-0.0115	2.5
4.2	-0.0116	2.5

NOTE: The applicant defined the normal working voltage of the adapter is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)	LIMIT (ppm)
50	-0.0114	2.5
40	-0.0136	2.5
30	-0.0128	2.5
20	-0.0129	2.5
10	-0.0146	2.5
0	-0.0117	2.5
-10	-0.0125	2.5
-20	-0.0116	2.5
-30	-0.0131	2.5




4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.


4.3.2 TEST SETUP





4.3.3 TEST RESULTS

CHANNEL	EDECLIENCY (MILE)	99% OCCUPIED BANDWIDTH (MHz)
CHANNEL	FREQUENCY (MHz)	WCDMA
1312	1712.4	4.0758
1413	1732.6	4.0795
1513	1752.6	4.0759






4.4 PEAK TO AVERAGE RATIO

4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.4.2 TEST SETUP



4.4.3 TEST PROCEDURES


- 1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- 2. Set the number of counts to a value that stabilizes the measured CCDF curve;
- 3. Record the maximum PAPR level associated with a probability of 0.1%.



4.4.4 TEST RESULTS

WCDMA

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
1312	1712.4	2.68
1413	1732.6	2.63
1513	1752.6	2.68






4.5 BAND EDGE MEASUREMENT

4.5.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.5.2 TEST SETUP



4.5.3 TEST PROCEDURES


- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 10MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).

19 of 29

c. Record the max trace plot into the test report.



4.5.4 TEST RESULTS





4.6 CONDUCTED SPURIOUS EMISSIONS


4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$. The emission limit equal to -13dBm.

4.6.2 TEST PROCEDURE


- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 30MHz to 18GHz. 20dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.6.3 TEST SETUP





4.6.4 TEST RESULTS





4.7 RADIATED EMISSION MEASUREMENT

4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$. The emission limit equal to -13dBm.

4.7.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. EIRP = Output power level of S.G TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power 2.15dBi.


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.7.3 DEVIATION FROM TEST STANDARD

No deviation



4.7.4 TEST SETUP




For the actual test configuration, please refer to the attached file (Test Setup Photo).



4.7.5 TEST RESULTS



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Site : 966 Chamber 5

Condition : PART22/24/27 3m EIRP_RSE_1G~19G_3 HORIZONTAL

Brand/Model: Quattro 4.5HD

Remark : Band IV Link CH1413

Tested by : Kay Wu Temprature : 25°C Humidity : 65% Plane : Y


20110							
			Read	Limit	0ver		
	Freq	Level	Level	Line	Limit	Factor	Remark
_	MII-	-ID /		-ID /			
	MHZ	abm/m	abm	dBm/m	ав	dB/m	
1	30.81	-58.16	-58.50	-13.00	-45.16	0.34	Peak
2	104.52	-61.29	-50.79	-13.00	-48.29	-10.50	Peak
3 рр	171.21	-48.01	-41.28	-13.00	-35.01	-6.73	Peak
4	328.00	-63.16	-56.99	-13.00	-50.16	-6.17	Peak
5	426.70	-65.73	-60.78	-13.00	-52.73	-4.95	Peak
6	640.90	-64.10	-64.48	-13.00	-51.10	0.38	Peak
7	3464.00	-49.47	-41.84	-13.00	-36.47	-7.63	Peak





Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch





Site : 966 Chamber 5

Condition : PART22/24/27 3m EIRP_RSE_1G~19G_3 VERTICAL

Brand/Model: Quattro 4.5HD Remark : Band IV Link CH1413

Remark : Band IV Link CH1413 Tested by : Kay Wu

Temprature : 25°C Humidity : 65% Plane : Y

Read Limit Over
Freq Level Level Line Limit Factor Remark

	MHz di	Bm/m dE	Bm dBm/m	dB	dB/m	
	0.27 -43	2.98 -44.6	95 -13.00	-29.98	1.07	Peak
2 6	6.45 -5	6.34 -47.9	97 -13.00	-43.34	-8.37	Peak
3 16	5.54 -49	9.67 -43.6	05 -13.00	-36.67	-6.62	Peak
4 55	5.50 -6	6.75 -65.1	18 -13.00	-53.75	-1.57	Peak
5 64	1.60 -64	4.47 -64.8	37 -13.00	-51.47	0.40	Peak
6 80	9.60 -6	2.42 -64.6	51 -13.00	-49.42	2.19	Peak

3468.00 -47.86 -40.23 -13.00 -34.86 -7.63 Peak



5 PHOTOGRAPHS OF THE TEST CONFIGURATION
Please refer to the attached file (Test Setup Photo).



6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab: Hsin Chu EMC/RF Lab:

Tel: 886-2-26052180 Tel: 886-3-5935343 Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING

CHANGES TO THE EUT BY THE LAB
No any modifications are made to the EUT by the lab during the test.
END