

# **FCC SAR Test Report**

Report No. : SA120723C24A

Applicant : CT Asia

Address : Unit 01, 15/F, Seaview Centre,139-141 Hoi bun road, Kwun Tong, Kowloon,Hongkong

Product : GSM/WCDMA mobile

FCC ID : YHLBLUQT45HD

Brand : BLU

Model No. : Quattro 4.5 HD

Standards FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1991 / IEEE 1528:2003

FCC OET Bulletin 65 Supplement C (Edition 01-01)

KDB 248227 D01 v01r02 / KDB 648474 D01 v01r05 / KDB 941225 D01 v02

KDB 941225 D03 v01 / KDB 941225 D04 v01 / KDB 941225 D06 v01

Date of Testing : Aug. 23, 2012 ~ Sep. 04, 2012

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch - Taiwan HwaYa Lab**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :

Pettile Chen / Senior Specialist

Annroyed By

Roy Wu / Manager



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report Format Version 5.0.0 Page No. : 1 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



# **Table of Contents**

		onitro Record	
1.		nary of Maximum SAR Value	
2.		ription of Equipment Under Test	
3.		Measurement System	
	3.1	Definition of Specific Absorption Rate (SAR)	
	3.2	SPEAG DASY System	
		3.2.1 Robot	7
		3.2.2 Probes	
		3.2.3 Data Acquisition Electronics (DAE)	8
		3.2.4 Phantoms	
		3.2.5 Device Holder	10
		3.2.6 System Validation Dipoles	10
		3.2.7 Tissue Simulating Liquids	11
	3.3	SAR System Verification	13
	3.4	SAR Measurement Procedure	
		3.4.1 Area & Zoom Scan Procedure	14
		3.4.2 Volume Scan Procedure	14
		3.4.3 Power Drift Monitoring	
		3.4.4 Spatial Peak SAR Evaluation	15
		3.4.5 SAR Averaged Methods	15
4.	SAR	Measurement Evaluation	16
	4.1	EUT Configuration and Setting	16
	4.2	EUT Testing Position	18
	4.3	Tissue Verification	21
	4.4	System Verification	21
	4.5	Conducted Power Results	22
	4.6	SAR Testing Results	24
		4.6.1 SAR Results for Head	24
		4.6.2 SAR Results for Body	
		4.6.3 Simultaneous Multi-band Transmission Evaluation	27
5.	Calib	ration of Test Equipment	
6.	Meas	urement Uncertainty	30
7.	Infor	nation on the Testing Laboratories	31

Appendix A. SAR Plots of System Verification

Appendix B. SAR Plots of SAR Measurement

Appendix C. Calibration Certificate for Probe and Dipole

Appendix D. Photographs of EUT and Setup



## **Release Control Record**

Issue No.	Reason for Change	Date Issued
R01	Original release	Sep. 11, 2012

Report Format Version 5.0.0 Page No. : 3 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 1. Summary of Maximum SAR Value

Mode / Band	Test Position	SAR-1g (W/kg)
	Head	0.388
GSM850	Body Worn (1 cm Gap)	0.799
	Hotspot Mode (1 cm Gap)	1.19
	Head	0.568
GSM1900	Body Worn (1 cm Gap)	0.725
	Hotspot Mode (1 cm Gap)	0.797
	Head	0.481
WCDMA Band II	Body Worn (1 cm Gap)	0.691
	Hotspot Mode (1 cm Gap)	1.06
	Head	0.538
WCDMA Band IV	Body Worn (1 cm Gap)	1.18
	Hotspot Mode (1 cm Gap)	0.941
	Head	0.175
WCDMA Band V	Body Worn (1 cm Gap)	0.402
	Hotspot Mode (1 cm Gap)	0.518
	Head	0.216
WLAN 2.4GHz	Body Worn (1 cm Gap)	0.084
	Hotspot Mode (1 cm Gap)	0.134
	Head	N/A
Bluetooth	Body Worn (1 cm Gap)	N/A
	Hotspot Mode (1 cm Gap)	N/A

#### Note:

- 1. The SAR limit **(1.6 W/kg)** for general population/uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1991.
- 2. Since the Bluetooth maximum power is less than  $2P_{\text{Ref}}$ , SAR testing for Bluetooth is not required.

Report Format Version 5.0.0 Page No. : 4 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 2. <u>Description of Equipment Under Test</u>

	001404/00144
EUT Type	GSM/WCDMA mobile
FCC ID	YHLBLUQT45HD
Brand Name	BLU
Model Name	Quattro 4.5 HD
	GSM850 : 824 ~ 849
	GSM1900 : 1850 ~ 1910
Ty Francisco Dondo	WCDMA Band II: 1850 ~ 1910
Tx Frequency Bands	WCDMA Band IV : 1710 ~ 1755
(Unit: MHz)	WCDMA Band V : 824 ~ 849
	WLAN: 2400 ~ 2483.5
	Bluetooth : 2400 ~ 2483.5
	GSM & GPRS : GMSK
	EDGE: 8PSK
Unlink Madulations	WCDMA: QPSK
Uplink Modulations	802.11b: DSSS
	802.11g/n: OFDM
	Bluetooth : GFSK
	GSM850 : 31.79
	GSM1900: 29.13
	WCDMA Band II: 23.59
Maximum AVG Conducted Power	WCDMA Band IV: 23.72
(Unit: dBm)	WCDMA Band V : 22.42
,	802.11b : 14.99
	802.11g : 13.50
	802.11n HT20 : 10.94
Antenna Type	Fixed Internal Antenna
EUT Stage	Identical Prototype

#### Note:

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

#### **List of Accessory:**

	Brand Name	BLU	
AC Adapter	Model Name	US-02-001	
AC Adapter	Power Rating	I/P:100-240Vac, 50-60Hz, 150mA; O/P: 5Vdc, 800mA	
	Brand Name	BLU	
Battery	Model Name	NA	
Dattery	Power Rating	3.7Vdc, 1820mAh	
	Туре	Li-ion	
	Brand Name	BLU	
Earphone	Model Name	NA	
	Signal Line Type	1.1 meter non-shielded cable without ferrite core	
	Brand Name	BLU	
USB Cable	Model Name	NA	
	Signal Line Type	0.9 meter non-shielded cable without ferrite core	

Report Format Version 5.0.0 Page No. : 5 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 3. SAR Measurement System

## 3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

## 3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY4/5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion form the optical into digital electric signal of the DAE and transfers data to the PC.

Report Format Version 5.0.0 Page No. : 6 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012







Fig-3.1 DASY System Setup

#### 3.2.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB; DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ±0.035 mm)
- · High reliability (industrial design)
- · Jerk-free straight movements
- · Low ELF interference (the closed metallic construction shields against motor control fields)



Report Format Version 5.0.0 F
Report No.: SA120723C24A Reference No.: 120910C18

Revision: R01

Page No. : 7 of 31 Issued Date : Sep. 11, 2012



#### 3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μW/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μW/g)	All I
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μW/g to 100 mW/g Linearity: ± 0.2 dB	AND TO
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

## 3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	a labor
Input Offset Voltage	< 5µV (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

Report Format Version 5.0.0 Page No. : 8 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 3.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material Vinylester, glass fiber reinforced (VE-GF)		
Shell Thickness $2 \pm 0.2 \text{ mm } (6 \pm 0.2 \text{ mm at ear point})$		
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume approx. 25 liters		



Model	ELI
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.
Material	Vinylester, glass fiber reinforced (VE-GF)
Shell Thickness	2.0 ± 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	approx. 30 liters



Report Format Version 5.0.0 Page No. : 9 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 3.2.5 Device Holder

Model	Mounting Device	700
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	



Model	Laptop Extensions Kit
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.
Material	POM, Acrylic glass, Foam



## 3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with I/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	L.
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	


 Report Format Version 5.0.0
 Page No.
 : 10 of 31

 Report No.: SA120723C24A
 Reference No.: 120910C18
 Issued Date
 : Sep. 11, 2012



#### 3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528 and FCC OET 65 Supplement C Appendix C. For the body tissue simulating liquids, the dielectric properties are defined in FCC OET 65 Supplement C Appendix C. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of ±5%	Target Conductivity	Range of ±5%
		For Head		
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
		For Body		
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05

Report Format Version 5.0.0 Page No. : 11 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012





The following table gives the recipes for tissue simulating liquids.

**Table-3.2 Recipes of Tissue Simulating Liquid** 


Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono- hexylether
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1900	-	44.5	1	0.2	-	-	55.3	-
H2450	-	45.0	ı	0.1	-	-	54.9	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B1750	-	31.0	1	0.2	-	-	68.8	-
B1900	-	29.5	ı	0.3	-	-	70.2	-
B2450	-	31.4	-	0.1	-	-	68.5	-

Report Format Version 5.0.0 Page No. : 12 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The power meter PM1 measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter PM2 is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

Report Format Version 5.0.0 Page No. : 13 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



#### 3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

#### 3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for below 3 GHz, and 7x7x9 points with step size 4, 4 and 2.5 mm for above 5 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

#### 3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

#### 3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

Report Format Version 5.0.0 Page No. : 14 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



#### 3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

#### 3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.


Report Format Version 5.0.0 Page No. : 15 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 4. SAR Measurement Evaluation

## 4.1 EUT Configuration and Setting

#### <Antenna Location>



This device supports WiFi hotspot function, so body SAR was tested under 1 cm for the surfaces / slide edges where a transmitting antenna is within 2.5 cm from the edge. Since the SAR is required for antenna located within 2.5 cm from edge, SAR testing for each antenna is listed as below.

WWAN Antenna: Front Face, Rear Face, Left Side, Right Side, Bottom Side

WLAN / BT Antenna: Front Face, Rear Face, Right Side, Top Side

The simultaneous transmission possibilities are listed as below.

Simultaneous TX Combination	Configuration	Head (Voice / VoIP)	Body Worn (Voice / VoIP)	Hotspot (Data)
1	GSM850 (Voice / Data) + WLAN / BT (Data)	Yes	Yes	Yes
2	GSM1900 (Voice / Data) + WLAN / BT (Data)	Yes	Yes	Yes
3	WCDMA II (Voice / Data) + WLAN / BT (Data)	Yes	Yes	Yes
4	WCDMA IV (Voice / Data) + WLAN / BT (Data)	Yes	Yes	Yes
5	WCDMA V (Voice / Data) + WLAN / BT (Data)	Yes	Yes	Yes

The WLAN and BT cannot transmit simultaneously, so there is no co-location test requirement for WLAN and BT.

Report Format Version 5.0.0 Page No. : 16 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012





Per KDB 941225 D04 requirement, the required test configuration for this device is as below:

- 1. This DUT is class B device
- 2. This DUT supports (E)GPRS multi-slot class 12 (max. uplink: 4, max. downlink: 4, total timeslots: 5)
- 3. This DUT supports DTM multi-slot class 11 (max. uplink: 3 for 1 CS & 2 PS, max. downlink: 4, total timeslots: 5)
- 4. The measured maximum conducted power can be referred to section 11.1 of this report
- 5. For DTM multi-slot class 11 link mode, the device was linked with system emulator (Agilent E5515C) and transmit maximum power on maximum number of Tx slots (one CS timeslot and two PS timeslots per frame).

For WWAN SAR testing, the EUT was linked and controlled by base station emulator. Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

The EUT is communicated with base station simulator (Agilent E5515C is used for GSM/WCDMA) by air link. During SAR testing, the base station simulator is set to make the EUT to radiate maximum output power.

For GSM850, the power control level is set to 5. For GPRS850 (GMSK, CS1), the power control level is set to 5. For EDGE850 (GMSK: MCS1, 8PSK:MCS9), the power control level is set to 8. For GSM1900, the power control level is set to 0. For GPRS1900 (GMSK, CS1), the power control level is set to 0. For EDGE1900 (GMSK: MCS1, 8PSK:MCS9), the power control level is set to 2. Head SAR is tested under GSM link mode. Body SAR is tested under maximum source-based time-average power mode of GPRS/EDGE.

For WCDMA, head and body SAR is tested under 12.2k RMC mode with power control set all up bits. SAR for AMR is not required since its power is less than 1/4 dB higher than RMC. SAR for HSDPA/HSUPA is not required since its power is less than 1/4 dB higher than RMC without HSDPA/HSUPA.

For WLAN SAR testing, the EUT has installed WLAN engineering testing software which can provide continuous transmitting RF signal. This RF signal utilized in SAR measurement has almost 100% duty cycle. The data rates for WLAN SAR testing were set in 1 Mbps for 802.11b due to the highest RF output power.

Report Format Version 5.0.0 Page No. : 17 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 4.2 EUT Testing Position

This EUT was tested in Right Cheek, Right Tilted, Left Cheek, Left Tilted, Front Face, Rear Face, Right Side, Left Side, Top Side and Bottom Side positions as illustrated below:

#### 1. Define two imaginary lines on the handset

- (a) The vertical centerline passes through two points on the front side of the handset the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig-4.1 Illustration for Handset Vertical and Horizontal Reference Lines

Report Format Version 5.0.0 Page No. : 18 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



#### 2. Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig-4.2).




Fig-4.2 Illustration for Cheek Position

#### 3. Tilted Position

- (a) To position the device in the "cheek" position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig-4.3).



Fig-4.3 Illustration for Tilted Position

Report Format Version 5.0.0 Page No. : 19 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 4. Body Worn Position

- (a) To position the EUT parallel to the phantom surface.
- (b) To adjust the EUT parallel to the flat phantom.
- (c) To adjust the distance between the EUT surface and the flat phantom to 1.0 cm.




Fig-4.4 Illustration for Body Worn Position

Report Format Version 5.0.0 Page No. : 20 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Tissue Type	Frequency (MHz)	Liquid Temp. (℃)	Measured Conductivity (σ)	Measured Permittivity $(\epsilon_r)$	Target Conductivity (σ)	Target Permittivity (ε <sub>r</sub> )	Conductivity Deviation (%)	Permittivity Deviation (%)	Test Date
H835	835	20.9	0.909	42.3	0.90	41.5	1.00	1.93	Aug. 24, 2012
H1750	1750	20.5	1.34	41.8	1.37	40.1	-2.19	4.24	Aug. 25, 2012
H1900	1900	20.8	1.44	39.7	1.40	40.0	2.86	-0.75	Aug. 24, 2012
H2450	2450	20.7	1.79	40.1	1.80	39.2	-0.56	2.30	Aug. 23, 2012
B835	835	20.5	0.978	55.6	0.97	55.2	0.82	0.72	Aug. 24, 2012
B1750	1750	20.4	1.47	53.8	1.49	53.4	-1.34	0.75	Aug. 25, 2012
B1750	1750	21.3	1.52	54.6	1.49	53.4	2.01	2.25	Sep. 04, 2012
B1900	1900	21.3	1.55	52.9	1.52	53.3	1.97	-0.75	Aug. 24, 2012
B2450	2450	20.5	2.01	53.1	1.95	52.7	3.08	0.76	Aug. 23, 2012

#### Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within  $\pm 5\%$  of the target values. Liquid temperature during the SAR testing must be within  $\pm 2\%$ .

## 4.4 System Verification

The measuring results for system check are shown as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Aug. 24, 2012		835	9.46	2.41	9.64	1.90	4d021	3864	1277
Aug. 25, 2012	Head	1750	35.80	8.95	35.80	0.00	1023	3864	1277
Aug. 24, 2012	Heau	1900	38.90	9.73	38.92	0.05	5d036	3864	1277
Aug. 23, 2012		2450	52.90	13.1	52.40	-0.95	737	3864	1277
Aug. 24, 2012		835	9.60	2.38	9.52	-0.83	4d021	3864	1277
Aug. 25, 2012		1750	37.00	9.29	37.16	-0.43	1023	3864	1277
Sep. 04, 2012	Body	1750	37.00	9.74	38.96	5.30	1023	3864	1277
Aug. 24, 2012		1900	38.90	9.7	38.80	-0.26	5d036	3864	1277
Aug. 23, 2012		2450	50.00	12.2	48.80	-2.40	737	3864	1277

#### Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Report Format Version 5.0.0 Page No. : 21 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 4.5 Conducted Power Results

The measuring conducted power (Unit: dBm) are shown as below.

Band		GSM850			GSM1900	
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
		Maximum Burst	-Averaged Outp	ut Power		
GSM (GMSK, 1 Uplink)	31.75	31.74	31.79	29.13	28.87	28.78
GPRS 8 (GMSK, 1 Uplink)	31.71	31.70	31.75	29.09	28.83	28.74
GPRS 10 (GMSK, 2 Uplink)	27.70	27.69	27.74	29.07	28.81	28.72
GPRS 11 (GMSK, 3 Uplink)	27.69	27.68	27.73	28.22	27.96	27.87
GPRS 12 (GMSK, 4 Uplink)	27.68	27.67	27.72	26.99	26.73	26.64
EDGE 8 (GMSK, 1 Uplink)	31.73	31.72	31.77	29.12	28.86	28.77
EDGE 10 (GMSK, 2 Uplink)	27.69	27.68	27.73	29.08	28.82	28.73
EDGE 11 (GMSK, 3 Uplink)	27.68	27.67	27.72	28.23	27.97	27.88
EDGE 12 (GMSK, 4 Uplink)	27.67	27.66	27.71	26.98	26.72	26.63
EDGE 8 (8PSK, 1 Uplink)	26.69	26.68	26.73	25.06	24.80	24.71
EDGE 10 (8PSK, 2 Uplink)	26.63	26.62	26.67	25.22	24.96	24.87
EDGE 11 (8PSK, 3 Uplink)	25.75	25.74	25.79	24.41	24.15	24.06
EDGE 12 (8PSK, 4 Uplink)	24.54	24.53	24.58	23.26	23.00	22.91
DTM 9 (GMSK, 2 Uplink)	27.63	27.61	27.66	29.11	28.85	28.76
DTM 11 (GMSK, 3 Uplink)	27.65	27.64	27.69	28.23	27.97	27.88
DTM 9 (8PSK, 2 Uplink)	27.62	27.61	27.63	29.09	28.83	28.74
DTM 11 (8PSK, 3 Uplink)	27.63	27.62	27.65	28.22	27.96	27.87
		Maximum Frame				
GSM (GMSK, 1 Uplink)	22.75	22.74	22.79	20.13	19.87	19.78
GPRS 8 (GMSK, 1 Uplink)	22.71	22.70	22.75	20.09	19.83	19.74
GPRS 10 (GMSK, 2 Uplink)	21.70	21.69	21.74	23.07	22.81	22.72
GPRS 11 (GMSK, 3 Uplink)	23.43	23.42	23.47	23.96	23.70	23.61
GPRS 12 (GMSK, 4 Uplink)	24.68	24.67	24.72	23.99	23.73	23.64
EDGE 8 (GMSK, 1 Uplink)	22.73	22.72	22.77	20.12	19.86	19.77
EDGE 10 (GMSK, 2 Uplink)	21.69	21.68	21.73	23.08	22.82	22.73
EDGE 11 (GMSK, 3 Uplink)	23.42	23.41	23.46	23.97	23.71	23.62
EDGE 12 (GMSK, 4 Uplink)	24.67	24.66	24.71	23.98	23.72	23.63
EDGE 8 (8PSK, 1 Uplink)	17.69	17.68	17.73	16.06	15.80	15.71
EDGE 8 (8PSK, 1 Uplink)	20.63	20.62	20.67	19.22	18.96	18.87
EDGE 10 (8PSK, 2 Uplink)	21.49	21.48	21.53	20.15	19.89	19.80
EDGE 11 (8PSK, 3 Uplink)	21.54	21.53	21.58	20.26	20.00	19.91
EDGE 12 (8PSK, 4 Uplink)	22.73	22.72	22.77	20.12	19.86	19.77
DTM 9 (GMSK, 2 Uplink)	21.63	21.61	21.66	23.11	22.85	22.76
DTM 11 (GMSK, 3 Uplink)	23.39	23.38	23.43	23.97	23.71	23.62
DTM 9 (8PSK, 2 Uplink)	21.62	21.61	21.63	23.09	22.83	22.74
DTM 11 (8PSK, 3 Uplink)	23.37	23.36	23.39	23.96	23.70	23.61

#### Note:

- 1. SAR testing for GSM/GPRS/EDGE/DTM was performed on the maximum frame-averaged power mode.
- 2. The frame-averaged power is linearly scaled the maximum burst-averaged power based on time slots. The calculated methods are shown as below:

Frame-averaged power = Burst-averaged power (1 Uplink) - 9 dBm Frame-averaged power = Burst averaged power (2 Uplink) - 6 dBm Frame-averaged power = Burst averaged power (3 Uplink) - 2.67 dBm Frame-averaged power = Burst averaged power (4 Uplink) - 3 dBm

Report Format Version 5.0.0 Page No. : 22 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## FCC SAR Test Report

Band		WCDMA Band II			WCDMA Band V	
Channel	9262	9400	9538	4132	4182	4233
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.4	846.6
RMC 12.2K	23.59	23.53	23.52	22.33	22.42	22.39
HSDPA Subtest-1	23.35	23.29	23.28	22.29	22.38	22.35
HSDPA Subtest-2	22.36	22.30	22.29	22.06	22.15	22.12
HSDPA Subtest-3	22.17	22.11	22.10	21.83	21.92	21.89
HSDPA Subtest-4	21.89	21.83	21.82	21.58	21.67	21.64
HSUPA Subtest-1	21.73	21.67	21.66	20.22	20.31	20.28
HSUPA Subtest-2	20.44	20.38	20.37	20.57	20.66	20.63
HSUPA Subtest-3	20.92	20.86	20.85	20.52	20.61	20.58
HSUPA Subtest-4	20.97	20.91	20.90	20.86	20.95	20.92
HSUPA Subtest-5	20.76	20.70	20.69	20.31	20.40	20.37

Band	1	WCDMA Band IV	
Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
RMC 12.2K	23.59	23.56	23.72
HSDPA Subtest-1	23.25	23.22	23.38
HSDPA Subtest-2	22.28	22.25	22.41
HSDPA Subtest-3	22.11	22.08	22.24
HSDPA Subtest-4	21.82	21.79	21.95
HSUPA Subtest-1	20.03	20.00	20.16
HSUPA Subtest-2	20.36	20.33	20.49
HSUPA Subtest-3	20.42	20.39	20.55
HSUPA Subtest-4	20.64	20.61	20.77
HSUPA Subtest-5	19.78	19.75	19.91

Band	802.11b			802.11g		
Channel	1	6	11	1	6	11
Frequency (MHz)	2412	2437	2462	2412	2437	2462
Average Power	14.20	14.74	14.99	12.62	13.21	13.50

Band	802.11n (HT20)				-	
Channel	1	6	11	-	-	-
Frequency (MHz)	2412	2437	2462	•	•	-
Average Power	10.01	10.40	10.94	-	-	-

Report Format Version 5.0.0 Page No. : 23 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 4.6 SAR Testing Results

#### 4.6.1 SAR Results for Head

Plot No.	Band	Mode	Test Position	Channel	SAR-1g (W/kg)
1	GSM850	GPRS12	Right Cheek	251	0.388
2	GSM850	GPRS12	Right Tilted	251	0.232
3	GSM850	GPRS12	Left Cheek	251	0.329
4	GSM850	GPRS12	Left Tilted	251	0.192
5	GSM1900	GPRS12	Right Cheek	512	0.328
6	GSM1900	GPRS12	Right Tilted	512	0.228
7	GSM1900	GPRS12	Left Cheek	512	0.568
8	GSM1900	GPRS12	Left Tilted	512	0.218
17	WCMDA II	RMC12.2K	Right Cheek	9262	0.289
18	WCMDA II	RMC12.2K	Right Tilted	9262	0.187
19	WCMDA II	RMC12.2K	Left Cheek	9262	0.481
20	WCMDA II	RMC12.2K	Left Tilted	9262	0.201
13	WCMDA IV	RMC12.2K	Right Cheek	1513	0.292
14	WCMDA IV	RMC12.2K	Right Tilted	1513	0.146
15	WCMDA IV	RMC12.2K	Left Cheek	1513	0.538
16	WCMDA IV	RMC12.2K	Left Tilted	1513	0.133
9	WCMDA V	RMC12.2K	Right Cheek	4182	0.175
10	WCMDA V	RMC12.2K	Right Tilted	4182	0.104
11	WCMDA V	RMC12.2K	Left Cheek	4182	0.148
12	WCMDA V	RMC12.2K	Left Tilted	4182	0.099
101	802.11b	-	Right Cheek	11	0.058
102	802.11b	-	Right Tilted	11	0.071
103	802.11b	-	Left Cheek	11	0.216
104	802.11b	-	Left Tilted	11	0.119

#### Note:

- 1. SAR is performed on the highest power channel. When the SAR value of highest power channel is less than 0.8 W/kg, SAR testing for optional channel is not required.
- 2. Since GPRS/EDGE and WLAN of this device supports VOIP capability through 3<sup>rd</sup> party apps software, we have evaluated data mode for head SAR.
- 3. SAR testing for 802.11g/n is not required because its maximum power is less than 1/4 dB higher than 802.11b.

Report Format Version 5.0.0 Page No. : 24 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



#### 4.6.2 SAR Results for Body

#### <Body Worn Mode>

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Channel	SAR-1g (W/kg)
55	GSM850	GPRS12	Front Face	1	251	0.264
56	GSM850	GPRS12	Rear Face	1	251	0.799
62	GSM1900	GPRS12	Front Face	1	512	0.595
63	GSM1900	GPRS12	Rear Face	1	512	0.725
83	WCMDA II	RMC12.2K	Front Face	1	9262	0.529
84	WCMDA II	RMC12.2K	Rear Face	1	9262	0.691
76	WCMDA IV	RMC12.2K	Front Face	1	1513	0.434
77	WCMDA IV	RMC12.2K	Rear Face	1	1513	0.934
111	WCMDA IV	RMC12.2K	Rear Face	1	1312	1.18
112	WCMDA IV	RMC12.2K	Rear Face	1	1413	1.06
69	WCMDA V	RMC12.2K	Front Face	1	4182	0.154
70	WCMDA V	RMC12.2K	Rear Face	1	4182	0.402
109	802.11b	-	Front Face	1	11	0.036
110	802.11b	-	Rear Face	1	11	0.084

#### Note:

- 1. SAR is performed on the highest power channel. When the SAR value of highest power channel is less than 0.8 W/kg, SAR testing for optional channel is not required.
- 2. Since GPRS/EDGE, WCDMA and WLAN of this device supports VOIP capability through 3<sup>rd</sup> party apps software, we have evaluated data mode for body worn mode.
- 3. SAR testing for 802.11g/n is not required because its maximum power is less than 1/4 dB higher than 802.11b.

 Report Format Version 5.0.0
 Page No.
 : 25 of 31

 Report No. : SA120723C24A
 Reference No.: 120910C18
 Issued Date
 : Sep. 11, 2012



### <Hotspot Mode>

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Channel	SAR-1g (W/kg)
50	GSM850	GPRS12	Front Face	1	251	0.485
51	GSM850	GPRS12	Rear Face	1	251	1.19
52	GSM850	GPRS12	Left Side	1	251	0.643
53	GSM850	GPRS12	Right Side	1	251	0.636
54	GSM850	GPRS12	Bottom Side	1	251	0.131
87	GSM850	GPRS12	Rear Face	1	128	0.912
88	GSM850	GPRS12	Rear Face	1	189	1.02
57	GSM1900	GPRS12	Front Face	1	512	0.589
58	GSM1900	GPRS12	Rear Face	1	512	0.797
59	GSM1900	GPRS12	Left Side	1	512	0.452
60	GSM1900	GPRS12	Right Side	1	512	0.051
61	GSM1900	GPRS12	Bottom Side	1	512	0.454
78	WCMDA II	RMC12.2K	Front Face	1	9262	0.559
79	WCMDA II	RMC12.2K	Rear Face	1	9262	1.06
80	WCMDA II	RMC12.2K	Left Side	1	9262	0.394
91	WCMDA II	RMC12.2K	Right Side	1	9262	0.362
82	WCMDA II	RMC12.2K	Bottom Side	1	9262	0.393
92	WCMDA II	RMC12.2K	Rear Face	1	9400	0.677
93	WCMDA II	RMC12.2K	Rear Face	1	9538	0.764
71	WCMDA IV	RMC12.2K	Front Face	1	1513	0.483
72	WCMDA IV	RMC12.2K	Rear Face	1	1513	0.941
73	WCMDA IV	RMC12.2K	Left Side	1	1513	0.466
74	WCMDA IV	RMC12.2K	Right Side	1	1513	0.035
75	WCMDA IV	RMC12.2K	Bottom Side	1	1513	0.446
95	WCMDA IV	RMC12.2K	Rear Face	1	1312	0.824
96	WCMDA IV	RMC12.2K	Rear Face	1	1413	0.918
64	WCMDA V	RMC12.2K	Front Face	1	4182	0.225
65	WCMDA V	RMC12.2K	Rear Face	1	4182	0.518
66	WCMDA V	RMC12.2K	Left Side	1	4182	0.235
67	WCMDA V	RMC12.2K	Right Side	1	4182	0.314
68	WCMDA V	RMC12.2K	Bottom Side	1	4182	0.056
105	802.11b	-	Front Face	1	11	0.047
106	802.11b	-	Rear Face	1	11	0.134
107	802.11b	-	Right Side	1	11	0.056
108	802.11b	-	Top Side	1	11	0.052

#### Note:

- 1. SAR is performed on the highest power channel. When the SAR value of highest power channel is less than 0.8 W/kg, SAR testing for optional channel is not required.
- 2. SAR testing for 802.11g/n is not required because its maximum power is less than 1/4 dB higher than 802.11b.

Test Engineer: Match Tsui, and Sam Onn

Report Format Version 5.0.0 Page No. : 26 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 4.6.3 Simultaneous Multi-band Transmission Evaluation

No.	Conditions (SAR1 + SAR2)	Mode	Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR
			Right Cheek	0.388	0.058	0.446	-
		llaad	Right Tilted	0.232	0.071	0.303	-
		Head	Left Cheek	0.329	0.216	0.545	-
			Left Tilted	0.192	0.119	0.311	-
	COMOSO	Body-Worn	Front Face	0.264	0.036	0.3	-
1	GSM850 +	Body-Worn	Rear Face	0.799	0.084	0.883	-
•	WLAN 2.4G		Front Face	0.485	0.047	0.532	-
	WLAN 2.40		Rear Face	1.19	0.134	1.324	-
		Hotspot	Left Side	0.643	0	0.643	-
		Ποιδροί	Right Side	0.636	0.056	0.692	-
			Top Side	0	0.052	0.052	-
			Bottom Side	0.131	0	0.131	-
			Right Cheek	0.328	0.058	0.386	-
		Head	Right Tilted	0.228	0.071	0.299	-
		пеац	Left Cheek	0.568	0.216	0.784	-
			Left Tilted	0.218	0.119	0.337	-
	CCM4000	Body-Worn	Front Face	0.595	0.036	0.631	-
2	GSM1900	Body-Worli	Rear Face	0.725	0.084	0.809	-
_	WLAN 2.4G		Front Face	0.589	0.047	0.636	-
	WEAN 2.40		Rear Face	0.797	0.134	0.931	-
		Hotspot	Left Side	0.452	0	0.452	-
		поіѕроі	Right Side	0.051	0.056	0.107	-
			Top Side	0	0.052	0.052	-
			Bottom Side	0.454	0	0.454	-
			Right Cheek	0.289	0.058	0.347	-
		Head	Right Tilted	0.187	0.071	0.258	-
		ricau	Left Cheek	0.481	0.216	0.697	-
			Left Tilted	0.201	0.119	0.32	-
	WCDMA II	Body-Worn	Front Face	0.529	0.036	0.565	-
3	+	Body World	Rear Face	0.691	0.084	0.775	-
	WLAN 2.4G		Front Face	0.559	0.047	0.606	-
			Rear Face	1.06	0.134	1.194	-
		Hotspot	Left Side	0.394	0	0.394	-
		··otopot	Right Side	0.362	0.056	0.418	-
			Top Side	0	0.052	0.052	-
			Bottom Side	0.393	0	0.393	-
			Right Cheek	0.292	0.058	0.35	-
		Head	Right Tilted	0.146	0.071	0.217	-
		riodd	Left Cheek	0.538	0.216	0.754	-
			Left Tilted	0.133	0.119	0.252	-
	WCDMA IV	Body-Worn	Front Face	0.434	0.036	0.47	-
4	+		Rear Face	1.18	0.084	1.264	-
	WLAN 2.4G		Front Face	0.483	0.047	0.53	-
	-	Hotspot	Rear Face	0.941	0.134	1.075	-
			Left Side	0.466	0	0.466	-
			Right Side	0.035	0.056	0.091	-
			Top Side	0	0.052	0.052	-
			Bottom Side	0.446	0	0.446	-

Report Format Version 5.0.0 Page No. : 27 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## **FCC SAR Test Report**

No.	Conditions (SAR1 + SAR2)	Mode	Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR
	WCDMA V + WLAN 2.4G	Head	Right Cheek	0.175	0.058	0.233	-
			Right Tilted	0.104	0.071	0.175	-
			Left Cheek	0.148	0.216	0.364	-
			Left Tilted	0.099	0.119	0.218	-
		Body-Worn	Front Face	0.154	0.036	0.19	-
_			Rear Face	0.402	0.084	0.486	-
5			Front Face	0.225	0.047	0.272	-
	WLAN 2.4G		Rear Face	0.518	0.134	0.652	-
		I latanat	Left Side	0.235	0	0.235	-
		Hotspot	Right Side	0.314	0.056	0.056 0.37	-
	Top Side Bottom Side	0	0.052	0.052	-		
			Bottom Side	0.056	0	0.056	-

#### Note:

1. The maximum SAR summation is calculated based on the same configuration and test position.

#### **Summary:**

According to KDB 648474, the simultaneous transmission SAR for WWAN and WLAN was not required, because the SAR summation is less than 1.6 W/kg. The BT standalone SAR and WWAN/BT simultaneous transmission SAR were not required, because the maximum output power of Bluetooth is less than  $2P_{Ref}$  (13.8 dBm) and the closest separation distance of these antennas is larger than 5 cm.

Report Format Version 5.0.0 Page No. : 28 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



# 5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Kit	SPEAG	D835V2	4d021	Apr. 20, 2012	Annual
System Validation Kit	SPEAG	D1750V2	D1750V2 1023 Ju		Annual
System Validation Kit	SPEAG	D1900V2	5d036	Jan. 26, 2012	Annual
System Validation Kit	SPEAG	D2450V2	737	Jan. 24, 2012	Annual
Dosimetric E-Field Probe	SPEAG	EX3DV4	3864	Jul. 19, 2012	Annual
Data Acquisition Electronics	SPEAG	DAE4	1277	Jul. 19, 2012	Annual
SAM Phantom	SPEAG	QD000P40CD	TP-1652	N/A	N/A
SAM Phantom	SPEAG	QD000P40CD	TP-1654	N/A	N/A
Radio Communication Tester	Agilent	E5515C	MY50266628	Sep. 26, 2011	Biennial
ENA Series Network Analyzer	Agilent	E5071C	MY46214281	May 14, 2012	Annual
MXG Analog Signal Generator	Agilent	N5181A	MY50143868	May 06, 2012	Annual
Power Meter	Anritsu	ML2495A	1218009	May 07, 2012	Annual
Power Sensor	Anritsu	MA2411B	1207252	May 07, 2012	Annual
EXA Spectrum Analyzer	Agilent	N9010A	MY52100136	Apr. 23, 2012	Annual
Dielectric Probe Kit	Agilent	85070D	E2-020018	May 14, 2012	Annual
Thermometer	YFE	YF-160A	110600361	Feb. 21, 2012	Annual
Directional Coupler	Woken	0110A05602O-10	11122702	Apr. 19, 2012	Annual
Power Amplifier	AR	5S1G4	0339656	Apr. 23, 2012	Annual
Power Amplifier	Mini-Circuit	ZVE-8G	001000422	Apr. 23, 2012	Annual
Attenuator	Woken	00800A1G01L-03	N/A	Apr. 19, 2012	Annual

 Report Format Version 5.0.0
 Page No.
 : 29 of 31

 Report No.: SA120723C24A
 Reference No.: 120910C18
 Issued Date
 : Sep. 11, 2012



## 6. Measurement Uncertainty

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Standard Uncertainty (1g)	Vi
Measurement System						
Probe Calibration	6.0	Normal	1	1	± 6.0 %	$\infty$
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %	$\infty$
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %	$\infty$
Boundary Effects	1.0	Rectangular	√3	1	± 0.6 %	∞
Linearity	4.7	Rectangular	√3	1	± 2.7 %	∞
System Detection Limits	1.0	Rectangular	√3	1	± 0.6 %	∞
Readout Electronics	0.6	Normal	1	1	± 0.6 %	∞
Response Time	0.0	Rectangular	√3	1	± 0.0 %	∞
Integration Time	1.7	Rectangular	√3	1	± 1.0 %	∞
RF Ambient Noise	3.0	Rectangular	√3	1	± 1.7 %	∞
RF Ambient Reflections	3.0	Rectangular	√3	1	± 1.7 %	∞
Probe Positioner	0.5	Rectangular	√3	1	± 0.3 %	∞
Probe Positioning	2.9	Rectangular	√3	1	± 1.7 %	∞
Max. SAR Eval.	2.3	Rectangular	√3	1	± 1.3 %	∞
Test Sample Related						
Device Positioning	3.9	Normal	1	1	± 3.9 %	31
Device Holder	2.7	Normal	1	1	± 2.7 %	19
Power Drift	5.0	Rectangular	√3	1	± 2.9 %	∞
Phantom and Setup						
Phantom Uncertainty	4.0	Rectangular	√3	1	± 2.3 %	∞
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	± 1.8 %	∞
Liquid Conductivity (Meas.)	5.0	Normal	1	0.64	± 3.2 %	29
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	± 1.7 %	∞
Liquid Permittivity (Meas.)	5.0	Normal	1	0.6	± 3.0 %	29
Combined Standard Uncertai	Combined Standard Uncertainty					
Expanded Uncertainty (K=2)	± 23.4 %					

Uncertainty budget for frequency range 300 MHz to 3 GHz

Report Format Version 5.0.0 Page No. : 30 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012



## 7. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation and authorization certificates of our laboratories obtained from approval agencies can be downloaded from our web site. If you have any comments, please feel free to contact us at the following:

#### Taiwan HwaYa EMC/RF/Safety/Telecom Lab:

Add: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-318-3232 Fax: 886-3-327-0892

#### Taiwan LinKo EMC/RF Lab:

Add: No. 47, 14th Ling, Chia Pau Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C.

Tel: 886-2-2605-2180 Fax: 886-2-2605-1924

#### Taiwan HsinChu EMC/RF Lab:

Add: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Vil., Chiung Lin Township, Hsinchu County 307, Taiwan, R.O.C.

Tel: 886-3-593-5343 Fax: 886-3-593-5342

Email: <a href="mailto:service.adt@tw.bureauveritas.com">service.adt@tw.bureauveritas.com</a>
Web Site: <a href="mailto:service.adt@tw.bureauveritas.com">www.bureauveritas.com</a>

The road map of all our labs can be found in our web site also.

---END---

Report Format Version 5.0.0 Page No. : 31 of 31
Report No.: SA120723C24A Reference No.: 120910C18 Issued Date : Sep. 11, 2012