



# FCC RF Test Report

APPLICANT : BLU Products, Inc.  
EQUIPMENT : mobile phone  
BRAND NAME : BLU  
MODEL NAME : VIVO 8  
FCC ID : YHLBLUVIVO8  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on May 05, 2017 and testing was completed on Jun. 06, 2017. We, SPORTON International (ShenZhen) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON International (ShenZhen) INC., the test report shall not be reproduced except in full.

Prepared by: Eric Shih / Manager

Approved by: Jones Tsai / Manager



**SPORTON International (ShenZhen) INC.**

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District, Shenzhen City,  
Guangdong Province, China



# TABLE OF CONTENTS

**1 GENERAL DESCRIPTION..... 5**

1.1 Applicant ..... 5

1.2 Manufacturer..... 5

1.3 Product Feature of Equipment Under Test..... 5

1.4 Product Specification of Equipment Under Test..... 5

1.5 Modification of EUT ..... 6

1.6 Testing Location ..... 6

1.7 Applicable Standards..... 6

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 7**

2.1 Descriptions of Test Mode ..... 7

2.2 Test Mode..... 8

2.3 Connection Diagram of Test System..... 9

2.4 Support Unit used in test configuration and system ..... 10

2.5 EUT Operation Test Setup ..... 10

2.6 Measurement Results Explanation Example..... 11

**3 TEST RESULT ..... 12**

3.1 Number of Channel Measurement ..... 12

3.2 Hopping Channel Separation Measurement ..... 14

3.3 Dwell Time Measurement..... 21

3.4 20dB Bandwidth Measurement ..... 24

3.5 Peak Output Power Measurement ..... 31

3.6 Conducted Band Edges Measurement..... 33

3.7 Conducted Spurious Emission Measurement ..... 40

3.8 Radiated Band Edges and Spurious Emission Measurement ..... 50

3.9 AC Conducted Emission Measurement..... 56

3.10 Antenna Requirements..... 60

**4 LIST OF MEASURING EQUIPMENT..... 61**

**5 UNCERTAINTY OF EVALUATION..... 62**

**APPENDIX A. RADIATED SPURIOUS EMISSION**

**APPENDIX B. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.72 dB at 93.050 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 4.70 dB at 0.520 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

BLU Products, Inc.  
10814 NW 33rd St # 100 Doral, FL 33172

## 1.2 Manufacturer

BLU Products, Inc.  
10814 NW 33rd St # 100 Doral, FL 33172

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	mobile phone
Brand Name	BLU
Model Name	VIVO 8
FCC ID	YHLBLUVIVO8
EUT supports Radios application	GSM/GPRS/EGPRS WCDMA/HSPA/DC-HSDPA/HSPA+/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth 3.0+EDR/ Bluetooth 4.0+LE
IMEI Code	Conducted: 354147042340480/354147042340485 Conduction: 354147042340795/354147042340790 Radiation: 354147042342445/354147042392440
HW Version	Vivo 8_Mainboard_P3
SW Version	Vivo 8_2305_V6811
EUT Stage	Pre-Production

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 6.81 dBm (0.0048 W) Bluetooth EDR (2Mbps) : 5.89 dBm (0.0039 W) Bluetooth EDR (3Mbps) : 6.24 dBm (0.0042 W)
Antenna Type / Gain	FPC Antenna with gain -4.25 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Testing Location

<b>Test Site</b>	SPORTON International (ShenZhen) INC.	
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District, Shenzhen City, Guangdong Province, China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH01-SZ	CO01-SZ

<b>Test Site</b>	SPORTON International (ShenZhen) INC.	
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Registration No.</b>
	03CH03-SZ	565805

**Note:** The test site complies with ANSI C63.4 2014 requirement.

### 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	6.40 dBm	5.47 dBm	5.82 dBm
Ch39	2441MHz	<b>6.81 dBm</b>	5.89 dBm	6.24 dBm
Ch78	2480MHz	6.35 dBm	5.40 dBm	5.74 dBm

**Remark:**

1. All the test data for each data rate were verified, but only the worst case was reported.
  2. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Z plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.




## 2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
<b>Conducted Test Cases</b>	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
<b>Radiated Test Cases</b>	<b>Bluetooth BR 1Mbps GFSK</b>		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
<b>AC Conducted Emission</b>	Mode 1 :GSM 1900 Idle + Earphone + Bluetooth Link + USB Cable(Charging from Adapter) + WLAN Link		
<b>Remark:</b> <ol style="list-style-type: none"> <li>For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.</li> <li>For Radiated Test Cases, The tests were performed with Adapter, Earphone, and USB Cable.</li> </ol>			

## 2.3 Connection Diagram of Test System

### <Bluetooth Tx Mode>



### <AC Conducted Emission Mode>





## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	Bluetooth Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



## 2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 5.0 + 10 = 15.0 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency


<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24 ~ 26°C
<b>Test Engineer :</b>	Wilson Chen	<b>Relative Humidity :</b>	50 ~ 53%
<b>Number of Hopping (Channel)</b>	<b>Adaptive Frequency Hopping (Channel)</b>	<b>Limits (Channel)</b>	<b>Pass/Fail</b>
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 18.MAY.2017 12:02:36



Date: 18.MAY.2017 12:06:57

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup






### 3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6053	Pass
39	2441	1.002	0.6027	Pass
78	2480	1.002	0.5947	Pass


Channel Separation Plot on Channel 00 - 01



Date: 18.MAY.2017 11:18:40




### Channel Separation Plot on Channel 39 - 40



Date: 18.MAY.2017 11:20:03

### Channel Separation Plot on Channel 77 - 78




Date: 18.MAY.2017 11:40:21



Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8440	Pass
39	2441	1.008	0.8440	Pass
78	2480	1.002	0.8160	Pass


Channel Separation Plot on Channel 00 - 01



Date: 18.MAY.2017 11:45:20




### Channel Separation Plot on Channel 39 - 40



Date: 18.MAY.2017 14:42:07

### Channel Separation Plot on Channel 77 - 78




Date: 18.MAY.2017 10:51:24



Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8320	Pass
39	2441	1.038	0.8320	Pass
78	2480	1.008	0.8400	Pass


Channel Separation Plot on Channel 00 - 01



Date: 18.MAY.2017 14:39:25




### Channel Separation Plot on Channel 39 - 40



Date: 18.MAY.2017 10:52:46

### Channel Separation Plot on Channel 77 - 78



Date: 18.MAY.2017 11:00:08

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup





3.3.5 Test Result of Dwell Time

Test Mode :	DH5	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.877	0.31	0.4	Pass
AFH	20	53.33	2.877	0.15	0.4	Pass

Remark:

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 11.MAY.2017 16:34:44

### 3.4 20dB Bandwidth Measurement

#### 3.4.1 Limit of 20dB Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Measure and record the results in the test report.

#### 3.4.4 Test Setup






3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.908
39	2441	0.904
78	2480	0.892


20 dB Bandwidth Plot on Channel 00



Date: 18.MAY.2017 11:03:12




20 dB Bandwidth Plot on Channel 39



Date: 18.MAY.2017 11:04:13

20 dB Bandwidth Plot on Channel 78




Date: 18.MAY.2017 11:04:45



Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.266
39	2441	1.266
78	2480	1.224


20 dB Bandwidth Plot on Channel 00



Date: 18.MAY.2017 11:05:29




20 dB Bandwidth Plot on Channel 39



Date: 18.MAY.2017 11:05:42

20 dB Bandwidth Plot on Channel 78




Date: 18.MAY.2017 11:05:52



Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.248
39	2441	1.248
78	2480	1.260


20 dB Bandwidth Plot on Channel 00



Date: 18.MAY.2017 11:07:12




20 dB Bandwidth Plot on Channel 39



Date: 18.MAY.2017 11:07:28

20 dB Bandwidth Plot on Channel 78



Date: 18.MAY.2017 11:08:54

### 3.5 Peak Output Power Measurement

#### 3.5.1 Limit of Peak Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:  
(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

#### 3.5.4 Test Setup





3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	6.40	20.97	Pass
39	2441	6.81	20.97	Pass
78	2480	6.35	20.97	Pass

Note: For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	5.47	20.97	Pass
39	2441	5.89	20.97	Pass
78	2480	5.40	20.97	Pass

Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	5.82	20.97	Pass
39	2441	6.24	20.97	Pass
78	2480	5.74	20.97	Pass

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Channel :	00 and 78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

Low Band Edge Plot on Channel 00



Date: 18.MAY.2017 12:07:21

High Band Edge Plot on Channel 78




Date: 18.MAY.2017 12:15:49




Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Channel :	00 and 78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

Low Band Edge Plot on Channel 00



Date: 18.MAY.2017 12:36:29

High Band Edge Plot on Channel 78




Date: 18.MAY.2017 12:36:55




Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Channel :	00 and 78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

Low Band Edge Plot on Channel 00



Date: 18.MAY.2017 12:33:36

High Band Edge Plot on Channel 78




Date: 18.MAY.2017 12:37:58



### 3.6.6 Test Result of Conducted Hopping Mode Band Edges


Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

#### 1Mbps Hopping Mode Low Band Edge Plot



Date: 18.MAY.2017 12:10:22

#### 1Mbps Hopping Mode High Band Edge Plot




Date: 18.MAY.2017 12:18:59




Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

2Mbps Hopping Mode Low Band Edge Plot



Date: 18.MAY.2017 12:24:35

2Mbps Hopping Mode High Band Edge Plot




Date: 18.MAY.2017 12:32:02




Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Wilson Chen	Relative Humidity :	50 ~ 53%

### 3Mbps Hopping Mode Low Band Edge Plot



Date: 18.MAY.2017 12:36:04

### 3Mbps Hopping Mode High Band Edge Plot



Date: 18.MAY.2017 12:40:18

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.7.4 Test Setup






### 3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Channel :	00	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 18.MAY.2017 12:46:54

1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 18.MAY.2017 12:47:16




Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Channel :	39	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 18.MAY.2017 12:48:00

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 18.MAY.2017 12:48:22




Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Channel :	78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 18.MAY.2017 12:48:56

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 18.MAY.2017 12:49:17




Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Channel :	00	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 18.MAY.2017 12:50:49

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 18.MAY.2017 12:51:11




Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Channel :	39	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 18.MAY.2017 12:52:32

2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 18.MAY.2017 12:52:53




Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Channel :	78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 18.MAY.2017 12:53:37

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 18.MAY.2017 12:53:59




Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Channel :	00	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 18.MAY.2017 12:55:43

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 18.MAY.2017 12:56:05




Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Channel :	39	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 18.MAY.2017 12:56:42

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 18.MAY.2017 12:57:04




Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Channel :	78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Wilson Chen

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 18.MAY.2017 14:36:15

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 18.MAY.2017 14:36:37



### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.82dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

### 3.8.6 Duty cycle correction factor for average measurement

DH5 on time (One Pulse) Plot on Channel 39



DH5 on time (Count Pulses) Plot on Channel 39



**Note:**

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.87 / 100 = 5.74 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.82 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.



**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.87 \text{ ms} \times 20 \text{ channels} = 57.4 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.4\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.87 \text{ ms} \times 2 = 5.74 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.74 \text{ ms}/100\text{ms}) = -24.82 \text{ dB}$$

**3.8.7 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix A.

**3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix A.



### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.9.4 Test Setup





3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Tao Cheng	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM 1900 Idle + Earphone + Bluetooth Link + USB Cable(Charging from Adapter) + WLAN Link		




Site : CO01-SZ  
 Condition: FCC 15C\_QP LISN\_20170301\_L LINE

Mode : Mode 1  
 IMEI : 354147042340795/354147042340790

	Freq	Level	Over Limit	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.29	32.45	-18.14	50.59	22.20	0.03	10.22	Average
2	0.29	50.15	-10.44	60.59	39.90	0.03	10.22	QP
3	0.44	30.61	-16.37	46.98	20.39	0.03	10.19	Average
4	0.44	43.41	-13.57	56.98	33.19	0.03	10.19	QP
5	0.52	38.00	-8.00	46.00	27.80	0.02	10.18	Average
6 *	0.52	51.30	-4.70	56.00	41.10	0.02	10.18	QP
7	0.63	36.69	-9.31	46.00	26.50	0.02	10.17	Average
8	0.63	50.49	-5.51	56.00	40.30	0.02	10.17	QP
9	0.72	33.09	-12.91	46.00	22.91	0.02	10.16	Average
10	0.72	48.39	-7.61	56.00	38.21	0.02	10.16	QP
11	1.20	33.13	-12.87	46.00	22.90	0.08	10.15	Average
12	1.20	47.13	-8.87	56.00	36.90	0.08	10.15	QP
13	2.41	35.02	-10.98	46.00	24.71	0.13	10.18	Average
14	2.41	47.12	-8.88	56.00	36.81	0.13	10.18	QP
15	5.42	37.79	-12.21	50.00	27.30	0.20	10.29	Average
16	5.42	49.29	-10.71	60.00	38.80	0.20	10.29	QP



Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Tao Cheng	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM 1900 Idle + Earphone + Bluetooth Link + USB Cable(Charging from Adapter) + WLAN Link		



Site : CO01-SZ  
 Condition: FCC 15C\_QP LISN\_20170301\_N NEUTRAL

Mode : Mode 1  
 IMEI : 354147042340795/354147042340790

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.21	38.85	-14.25	53.10	28.60	0.03	10.22	Average
2 *	0.21	56.55	-6.55	63.10	46.30	0.03	10.22	QP
3	0.28	29.65	-21.03	50.68	19.40	0.03	10.22	Average
4	0.28	48.55	-12.13	60.68	38.30	0.03	10.22	QP
5	0.43	33.01	-14.28	47.29	22.80	0.02	10.19	Average
6	0.43	46.51	-10.78	57.29	36.30	0.02	10.19	QP
7	0.57	32.29	-13.71	46.00	22.10	0.02	10.17	Average
8	0.57	46.39	-9.61	56.00	36.20	0.02	10.17	QP
9	0.65	35.09	-10.91	46.00	24.90	0.02	10.17	Average
10	0.65	47.29	-8.71	56.00	37.10	0.02	10.17	QP
11	0.80	32.49	-13.51	46.00	22.30	0.03	10.16	Average
12	0.80	45.39	-10.61	56.00	35.20	0.03	10.16	QP
13	4.90	34.35	-11.65	46.00	24.00	0.07	10.28	Average
14	4.90	44.95	-11.05	56.00	34.60	0.07	10.28	QP



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 06, 2017	May 11, 2017~ May 18, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr. 20, 2017	May 11, 2017~ May 18, 2017	Apr. 19, 2018	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 06, 2017	May 11, 2017~ May 18, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 06, 2017	May 11, 2017~ May 18, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 20, 2017	Jun. 06, 2017	Apr. 19, 2018	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 20, 2017	Jun. 06, 2017	Apr. 19, 2018	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 14, 2017	Jun. 06, 2017	May 13, 2018	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 14, 2017	Jun. 06, 2017	May 13, 2018	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 16, 2016	Jun. 06, 2017	Jul. 15, 2017	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Aug. 10, 2016	Jun. 06, 2017	Aug. 09, 2017	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz~3000MHz	Oct. 11, 2016	Jun. 06, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 06, 2017	Jun. 06, 2017	Jan. 05, 2018	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jun. 06, 2017	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jun. 06, 2017	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jun. 06, 2017	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jan. 06, 2017	May 15, 2017	Jan. 05, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103892	9kHz~30MHz	Jan. 05, 2017	May 15, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103912	9kHz~30MHz	Jan. 05, 2017	May 15, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 16, 2016	May 15, 2017	Jul. 15, 2017	Conduction (CO01-SZ)
Pulse Limiter	COM-POWER	LIT-153 Transient Limiter	53139	150kHz~30MHz	Oct. 11, 2016	May 15, 2017	Oct. 10, 2017	Conduction (CO01-SZ)
RF Cable	Woken	B0720#0001	CO01SZ0007	150kHz~30MHz	Oct. 08, 2016	May 15, 2017	Oct. 07, 2017	Conduction (CO01-SZ)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.5dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1dB
---	-------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0dB
---	-------



## Appendix A. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH00 2402MHz		2389.04	47.22	-26.78	74	48.87	27.51	5.06	34.22	195	173	P	H
		2389.04	22.4	-31.6	54	-	-	-	-	195	173	A	H
	*	2402	99.52	-	-	101.15	27.51	5.06	34.2	195	173	P	H
	*	2402	74.7	-	-	-	-	-	-	195	173	A	H
		2389.04	46.69	-27.31	74	48.34	27.51	5.06	34.22	198	277	P	V
		2389.04	21.87	-32.13	54	-	-	-	-	198	277	A	V
	*	2402	100.27	-	-	101.9	27.51	5.06	34.2	198	277	P	V
	*	2402	75.45	-	-	-	-	-	-	198	277	A	V
BT CH 39 2441MHz		2357.6	40.75	-33.25	74	42.59	27.38	5.02	34.24	158	230	P	H
		2357.6	15.93	-38.07	54	-	-	-	-	158	230	A	H
	*	2441	99.46	-	-	100.79	27.7	5.12	34.15	158	230	P	H
	*	2441	74.64	-	-	-	-	-	-	158	230	A	H
		2495.52	39.68	-34.32	74	40.7	27.9	5.19	34.11	158	230	P	H
		2495.52	14.86	-39.14	54	-	-	-	-	158	230	A	H
		2339.54	39.39	-34.61	74	41.34	27.31	4.98	34.24	164	257	P	V
		2339.54	14.57	-39.43	54	-	-	-	-	164	257	A	V
	*	2441	102.03	-	-	103.36	27.7	5.12	34.15	164	257	P	V
	*	2441	77.21	-	-	-	-	-	-	164	257	A	V
		2494.54	39.87	-34.13	74	40.89	27.9	5.19	34.11	164	257	P	V
	2494.54	15.05	-38.95	54	-	-	-	-	164	257	A	V	



<b>BT CH 78 2480MHz</b>	*	2480	98.38	-	-	99.49	27.83	5.19	34.13	150	175	P	H
	*	2480	73.56	-	-	-	-	-	-	150	175	A	H
		2483.5	58.76	-15.24	74	59.87	27.83	5.19	34.13	150	175	P	H
		2483.5	33.94	-20.06	54	-	-	-	-	150	175	A	H
	*	2480	100.22	-	-	101.33	27.83	5.19	34.13	150	228	P	V
	*	2480	75.4	-	-	-	-	-	-	150	228	A	V
		2483.55	60.43	-13.57	74	61.54	27.83	5.19	34.13	150	228	P	V
		2483.55	35.61	-18.39	54	-	-	-	-	150	228	A	V
<b>Remark</b>	<ol style="list-style-type: none"> <li>No other spurious found.</li> <li>All results are PASS against Peak and Average limit line.</li> </ol>												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH 00 2402MHz		4804	42.93	-31.07	74	61.14	31.54	8.59	58.34	250	0	P	H
		4804	18.11	-35.89	54	-	-	-	-	250	0	A	H
		4804	42.56	-31.44	74	60.77	31.54	8.59	58.34	250	0	P	V
		4804	17.74	-36.26	54	-	-	-	-	250	0	A	V
BT CH 39 2441MHz		4882	41.9	-32.1	74	59.9	31.71	8.62	58.33	250	0	P	H
		4882	17.08	-36.92	54	-	-	-	-	250	0	A	H
		7323	49.51	-24.49	74	62.39	36.29	10.24	59.41	150	0	P	H
		7323	24.69	-29.31	54	-	-	-	-	150	0	A	H
		4882	42.32	-31.68	74	60.32	31.71	8.62	58.33	250	0	P	V
		4882	17.5	-36.5	54	-	-	-	-	250	0	A	V
		7323	48.3	-25.7	74	61.18	36.29	10.24	59.41	150	0	P	V
		7323	23.48	-30.52	54	-	-	-	-	150	0	A	V
BT CH 78 2480MHz		4960	42.77	-31.23	74	60.52	31.92	8.65	58.32	250	0	P	H
		4960	17.95	-36.05	54	-	-	-	-	250	0	A	H
		7440	47.87	-26.13	74	60.65	36.44	10.25	59.47	150	0	P	H
		7440	23.05	-30.95	54	-	-	-	-	150	0	A	H
		4960	42.95	-31.05	74	60.7	31.92	8.65	58.32	250	0	P	V
		4960	18.13	-35.87	54	-	-	-	-	250	0	A	V
		7440	46.62	-27.38	74	59.4	36.44	10.25	59.47	150	0	P	V
		7440	21.8	-32.2	54	-	-	-	-	150	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Emission below 1GHz**

**2.4GHz BT (LF)**

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BT LF		94.99	34.44	-9.06	43.5	46.9	18.3	1	31.76			P	H
		168.71	35.19	-8.31	43.5	48.31	16.98	1.34	31.44	120	50	P	H
		203.63	34.71	-8.79	43.5	48.78	15.78	1.48	31.33	-	-	P	H
		398.6	30.75	-15.25	46	33.99	25.89	2.12	31.25	-	-	P	H
		734.22	30.65	-15.35	46	31.52	27.43	2.94	31.24	-	-	P	H
		907.85	31.52	-14.48	46	30.73	28.64	3.33	31.18	-	-	P	H
		30	33.75	-6.25	40	38.49	26.7	0.56	32	-	-	P	V
		93.05	38.78	-4.72	43.5	51.46	18.1	0.99	31.77	100	40	P	V
		170.65	33.87	-9.63	43.5	47.08	16.89	1.34	31.44	-	-	P	V
		203.63	36.4	-7.1	43.5	50.47	15.78	1.48	31.33	-	-	P	V
		412.18	28.88	-17.12	46	32.23	25.73	2.15	31.23	-	-	P	V
		941.8	33.44	-12.56	46	32	29.26	3.38	31.2	-	-	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =  
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.