

# FCC PART 15B, CLASS B TEST REPORT

For

# BLU Products,Inc.

10814 NW 33rd St # 100 Doral, FL 33172

FCC ID: YHLBLUZ3M

**Product Type:** Report Type: Original Report Mobile Phone Sonia Zhon **Test Engineer:** Sonia Zhou Report Number: RSZ160628006-00A **Report Date:** 2016-07-07 Rocky Kang Rocky Kang Reviewed By: RF Engineer Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building Prepared By: ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

**Note**: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

Report No.: RSZ160628006-00A

# **TABLE OF CONTENTS**

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION	4
DESCRIPTION OF TEST CONFIGURATION	4
EUT Exercise Software	4
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	4
EXTERNAL I/O CABLE	
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	7
APPLICABLE STANDARD	
Measurement Uncertainty	
EUT SETUP	
EMI TEST RECEIVER SETUP.	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
CORRECTED FACTOR & MARGIN CALCULATION	8
TEST RESULTS SUMMARY	9
Test Data	9
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY	12
EUT SETUP	
EMI TEST RECEIVER SETUP	13
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	14
Test Data	15

#### **GENERAL INFORMATION**

#### **Product Description for Equipment under Test (EUT)**

The *BLU Products, Inc.*'s product, model number: Z3~M~(FCC~ID:~YHLBLUZ3M) or the "EUT" in this report was a *Mobile Phone*, which was measured approximately: 112 mm (L)  $\times$  45 mm (W)  $\times$  12 mm (H), rated with input voltage: DC 3.7 V battery or DC 5.0 V from adapter.

Report No.: RSZ160628006-00A

Adapter Information: Model: UL-SL-0550

Input: AC 100-240V, 50-60Hz, 0.15A

Output: DC 5.0V, 550mA

\*All measurement and test data in this report was gathered from production sample serial number: 1234567890123 (Assigned by applicant). The EUT supplied by the applicant was received on 2016-06-28.

#### **Objective**

This test report is prepared on behalf of *BLU Products,Inc.in* accordance with Part 2-Subpart J, Part 15-Subparts A, B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

#### Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS and Part 22H/24E PCE submissions with FCC ID: YHLBLUZ3M.

#### **Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on October 31, 2013. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15B, Class B Page 3 of 16

## **SYSTEM TEST CONFIGURATION**

#### **Description of Test Configuration**

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode: Downloading (data transfer with computer)

#### **EUT Exercise Software**

"BurnIn test v5.3" exercise software was used.

#### **Special Accessories**

No special accessory.

#### **Equipment Modifications**

No modification was made to the EUT tested.

#### **Support Equipment List and Details**

Manufacturer	Description	Model	Serial Number
DELL	PC	VOSTRO 220S	127BP2X
DELL	LCD Monitor	E178WFPC	CN-OWY564-64180-7C4-2SQH
DELL	Keyboard	L100	CNORH656658907BL05DC
DELL	Mouse	MOC5UO	G1900NKD
SAST	Modem	AEM-2100	0293
TCL	LCD Monitor	ATW22-1G	221WV
Kingston	Micro SD card	1 GB	N/A

Report No.: RSZ160628006-00A


FCC Part 15B, Class B Page 4 of 16

#### **External I/O Cable**

Cable Description	Length (m)	From/Port	То
Un-Shielding Detachable USB Cable	1.5	Host PC	Mouse
Un-Shielding Detachable Serial Cable	1.5	Host PC	Modem
Un-Shielding Detachable K/B Cable	1.5	Host PC	Keyboard
Un-Shielding Detachable VGA Cable	1.5	Host PC	LCD Monitor
Un-shielding Detachable USB Cable	1.0	EUT	PC
Un-shielding Detachable DC Cable	1.0	Modem	Modem Adapter

Report No.: RSZ160628006-00A

#### **Block Diagram of Test Setup**



FCC Part 15B, Class B Page 5 of 16

## **SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Spurious Emissions	Compliance

Report No.: RSZ160628006-00A

FCC Part 15B, Class B Page 6 of 16

### FCC §15.107 – AC LINE CONDUCTED EMISSIONS

#### **Applicable Standard**

According to FCC §15.107

#### **Measurement Uncertainty**


Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN/ISN and receiver, LISN/ISN voltage division factor, LISN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Report No.: RSZ160628006-00A

Port	Measurement uncertainty
AC Mains	3.34 dB (k=2, 95% level of confidence)
CAT 3	3.72 dB (k=2, 95% level of confidence)
CAT 5	3.74 dB (k=2, 95% level of confidence)
CAT 6	4.54 dB (k=2, 95% level of confidence)

#### **EUT Setup**



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

FCC Part 15B, Class B Page 7 of 16

#### **EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Report No.: RSZ160628006-00A

#### **Test Procedure**

During the conducted emission test, the host PC was connected to the first LISN and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

#### **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2016-06-03	2017-06-03
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2015-12-01	2016-12-01
Rohde & Schwarz	LISN	ESH2-Z5	892107/021	2016-06-09	2017-06-09
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2016-05-14	2017-05-14
Rohde & Schwarz	CE Test software	EMC 32	V8.53	NCR	NCR

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

#### **Corrected Factor & Margin Calculation**

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15B, Class B Page 8 of 16

#### **Test Results Summary**

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15.107</u>, the worst margin as below:

Report No.: RSZ160628006-00A

#### 5.2 dB at 9.255130 MHz in the Line conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{\rm (Lm)} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL.,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Sonia Zhou on 2016-07-01.


FCC Part 15B, Class B Page 9 of 16

EUT Operation Mode: Downloading

#### AC 120V/60 Hz, Line

EMI Auto Test L

Report No.: RSZ160628006-00A




Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
1.105410	39.0	20.0	56.0	17.0	QP
9.253630	44.6	20.1	60.0	15.4	QP
9.255130	45.0	20.1	60.0	15.0	QP
9.562630	42.9	20.1	60.0	17.1	QP
9.657190	45.0	20.1	60.0	15.0	QP
10.063070	44.2	20.1	60.0	15.8	QP
1.105410	38.4	20.0	46.0	7.6	Ave.
9.253630	43.7	20.1	50.0	6.3	Ave.
9.255130	44.8	20.1	50.0	5.2	Ave.
9.562630	39.7	20.1	50.0	10.3	Ave.
9.657190	44.6	20.1	50.0	5.4	Ave.
10.063070	43.1	20.1	50.0	6.9	Ave.

FCC Part 15B, Class B Page 10 of 16

#### AC 120V/60 Hz, Neutral

#### EMI Auto Test N

Report No.: RSZ160628006-00A



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
1.105410	37.4	20.0	56.0	18.6	QP
11.498970	23.8	20.1	60.0	36.2	QP
14.131670	27.5	20.1	60.0	32.5	QP
14.991430	32.2	20.1	60.0	27.8	QP
16.258490	35.9	20.1	60.0	24.1	QP
19.622430	34.7	20.1	60.0	25.3	QP
1.105410	36.6	20.0	46.0	9.4	Ave.
11.498970	15.0	20.1	50.0	35.0	Ave.
14.131670	21.0	20.1	50.0	29.0	Ave.
14.991430	27.4	20.1	50.0	22.6	Ave.
16.258490	29.3	20.1	50.0	20.7	Ave.
19.622430	30.3	20.1	50.0	19.7	Ave.

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
  3) Margin = Limit Corrected Amplitude

FCC Part 15B, Class B Page 11 of 16

#### FCC §15.109 - RADIATED SPURIOUS EMISSIONS

#### **Applicable Standard**

FCC §15.109

#### **Measurement Uncertainty**

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Report No.: RSZ160628006-00A

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown in below table. And the uncertainty will not be taken into consideration for the test data recorded in the report

Frequency	Polarity	Measurement uncertainty
30 MHz~200 MHz	Horizontal	4.04 dB (k=2, 95% level of confidence)
30 MHZ~200 MHZ	Vertical	4.52 dB (k=2, 95% level of confidence)
200 MHz∼1 GHz	Horizontal	4.72 dB (k=2, 95% level of confidence)
200 MHZ~1 GHZ	Vertical	5.81 dB (k=2, 95% level of confidence)
1 GHz~6 GHz	Horizontal/Vertical	4.64 dB (k=2, 95% level of confidence)
Above 6 GHz	Horizontal/Vertical	4.88 dB (k=2, 95% level of confidence)


#### **EUT Setup**

#### **Below 1GHz:**



FCC Part 15B, Class B Page 12 of 16

#### **Above 1GHz:**



Report No.: RSZ160628006-00A

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

#### **EMI Test Receiver Setup**

The system was investigated from 30 MHz to 12.4 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above I GHZ	1MHz	10 Hz	/	Ave.

#### **Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

FCC Part 15B, Class B Page 13 of 16

#### **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date	
HP	Amplifier	HP8447E	1937A01046	2016-05-06	2017-05-06	
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2015-12-15	2016-12-14	
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-07	2017-12-06	
Mini	Amplifier	ZVA-183-S+	5969001149	2016-04-23	2017-04-23	
A.H. System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17	
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11	
TDK	Chamber	Chamber A	2#	2013-10-15	2016-10-15	
TDK	Chamber	Chamber B	1#	2015-07-23	2016-07-22	
R&S	Auto test Software	EMC32	V9.10	NCR	NCR	
Ducommun technologies	RF Cable	UFA210A-1- 4724-30050U	MFR64369 223410-001	2016-06-15	2017-06-15	
Ducommun technologies	RF Cable	104PEA	218124002	2016-06-15	2017-06-15	
Ducommun technologies	RF Cable	RG-214	1	2016-06-15	2017-06-15	
Ducommun technologies	RF Cable	RG-214	2	2016-06-15	2017-06-15	

Report No.: RSZ160628006-00A

#### **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

#### **Test Results Summary**

According to the data in the following table, the EUT complied with the FCC §15.109 Class B, the worst margin reading as below:

#### 3.24 dB at 312.00 MHz in the Horizontal polarization mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

FCC Part 15B, Class B Page 14 of 16

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃		
Relative Humidity:	55 %		
ATM Pressure:	101.0 kPa		

The testing was performed by Sonia Zhou on 2016-07-07.

EUT Operation Mode: Downloading

#### 30 MHz – 12.4 GHz:

Frequency (MHz)	Receiver			Rx Antenna		Corrected	Corrected	FCC Part 15B	
	Reading (dBµV)	Detector (PK/QP/Ave.)	Turntable Degree	Height (m)	Polar (H/V)	Factor	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
32.59	31.81	QP	197	1.0	V	-3.3	28.51	40	11.49
71.92	42.10	QP	134	3.2	Н	-13.8	28.30	40	11.70
84.16	40.94	QP	306	4.0	Н	-12.9	28.04	40	11.96
312.00	48.46	QP	92	1.1	Н	-5.7	42.76	46	3.24
408.01	34.26	QP	75	1.0	Н	-3.8	30.46	46	15.54
419.95	46.23	QP	75	1.0	Н	-3.5	42.73	46	3.27
1735.00	46.28	PK	96	2.2	Н	-10.62	35.66	74	38.34
1735.00	30.13	Ave.	96	2.2	Н	-10.62	19.51	54	34.49
1493.26	45.69	PK	224	1.4	Н	-10.41	35.28	74	38.72
1493.26	29.75	Ave.	224	1.4	Н	-10.41	19.34	54	34.66

Report No.: RSZ160628006-00A

#### Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss amplifier factor
- 2) Corrected Amplitude = Correction Factor + Reading
- 3) Margin = Limit Corrected Amplitude

\*\*\*\*\* END OF REPORT \*\*\*\*\*

FCC Part 15B, Class B Page 15 of 16