

FCC PART 18

TEST REPORT

For

Zhongshan Donlim Weili Electrical Appliances Co., Ltd.

Fusha Industrial Park, Fusha Town, Zhongshan City, China

FCC ID: YI4DW23PX

Report Type: Product Type:

Class II Permissive Change Microwave oven

Report Number: RSZ170619555-00

Report Date: 2017-07-30

Hill He

Reviewed By: EMC Engineer

Prepared By:

Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building,

HM He

Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	3
Measurement Uncertainty:	
TEST FACILITY	
OPERATING CONDITION/TEST CONFIGURATION	5
JUSTIFICATION	5
EUT Exercise Software	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	
EXTERNAL CABLE LIST AND DETAILS	
CONFIGURATION OF TEST SETUP	
BLOCK DIAGRAM OF TEST SETUP	6
TEST EQUIPMENT LIST	7
CONDUCTED EMISSIONS	9
APPLICABLE STANDARD	9
EUT SETUP	
EMI TEST RECEIVER SETUP.	
TEST PROCEDURE	
TEST RESULTS SUMMARY	
Test Data	10
RADIATION HAZARD MEASUREMENT	13
APPLICABLE STANDARD	13
ENVIRONMENTAL CONDITIONS	
RADIATION HAZARD MEASUREMENT	
Input Power	
LOAD FOR MICROWAVE OVENS	
RF OUTPUT POWER MEASUREMENT	
OPERATING FREQUENCY MEASUREMENT	16
RADIATED EMISSIONS	19
APPLICABLE STANDARD	
EUT Setup	19
EMI TEST RECEIVER SETUP AND SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA AND PLOTS	20

Report No.: RSZ170619555-00

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Zhongshan Donlim Weili Electrical Appliances Co., Ltd.'s product, model number:23PX11(FCC ID: YI4DW23PX) or the "EUT" in this report is a Microwave Oven, which was measured approximately: 48.25cm (L) x 35.5 cm (W) x27.6 cm (H), the input power is AC 120V/60Hz. The highest operating frequency is 2450MHz.

Report No.: RSZ170619555-00

Note: The serial models 23PX27;23PX10;23PX09;23PX11-I;23PX27-I;23PX39-I;23PX10-I,23PX39 and 23PX11, the difference between them is only the shape of door frame and control box. 23PX11 was selected for fully testing, the details were explained in the attached product similarity declaration letter that stated and guaranteed by the applicant.

*All measurement and test data in this report was gathered from production sample serial number: 1706040. (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2017-06-19.

Objective

This report is prepared on behalf of *Zhongshan Donlim Weili Electrical Appliances Co., Ltd.* in accordance with Part 2-Subpart J, and Part 18-Subparts A, B and C of the Federal Communication Commissions rules and regulations.

The objective of the manufacturer is to determine compliance with FCC Part 18 limits.

This is a CIIPC application of the device; the differences between the original device and the current one are as follows:

- 1. Changing the High voltage transformer and Magnetron.
- 2. Changing the power PCB.

For the changes made to the device, all the test items were performed.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with MP-5, FCC Methods of Measurements of Radio Noise Emissions from ISM Equipment, February 1986. All measurements were performed at Bay Area Compliance Laboratory Corporation. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 18 Page 3 of 21

Measurement Uncertainty:

	Item	Expanded Measurement uncertainty	
AC Power Line Conducted Emissions			2.20 dB (k=2, 95% level of confidence)
	20MHz 200MHz	Horizontal	4.58 dB (k=2, 95% level of confidence)
	30MHz~200MHz	Vertical	4.59 dB (k=2, 95% level of confidence)
Radiated emission	l emission 200MHz~1 GHz	Horizontal	4.83 dB (k=2, 95% level of confidence)
Radiated emission	200MHZ~1 GHZ	Vertical	5.85 dB (k=2, 95% level of confidence)
	1 GHz~6 GHz	Horizontal/Vertical	4.08 dB (k=2, 95% level of confidence)
	Above 6 GHz	Horizontal/Vertical	4.59 dB (k=2, 95% level of confidence)

Report No.: RSZ170619555-00

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP(Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 18 Page 4 of 21

OPERATING CONDITION/TEST CONFIGURATION

Justification

The EUT was operated at maximum (continuous) RF output power. The loads consisted of water in a glass beaker in the amounts specified in the test procedure.

Report No.: RSZ170619555-00

EUT Exercise Software

No exercise software was used.

Equipment Modifications

No modifications were made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	Remark
N/A	Socket	N/A	140217	N/A

External Cable List and Details


Cable Description	Length (m)	From/Port	То
Un-shielding Un-detachable AC Cable	0.8	EUT	Socket
Un-shielding Un-detachable AC Cable	1.0	Mains	Socket

Configuration of Test Setup



FCC Part 18 Page 5 of 21

Block Diagram of Test Setup



FCC Part 18 Page 6 of 21

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
CONDUCTED EMISSIONS					
Rohde & Schwarz EMI Test Receiver ESCS30 10		100176	2016-10-19	2017-10-19	
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2016-12-07	2017-12-07
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-02-14	2017-08-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1- 0720-504504	2017-02-14	2017-08-15
	RADIATIO	N HAZARD MEAS	SUREMENT		
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24
GW Instek	Power Meter	GPM 8212	CL110034	2017-04-09	2018-04-09
GW Instek	AC Power Meter	GPM-8212	CH150074	2017-04-09	2018-04-09
MC	Thermometer	N/A	N/A	2016-11-01	2017-11-01
A.H.System	Horn Antenna	3115	9903-5766	NCR	NCR
ETS	Microwave Survery Meter	1501	N/A	NCR	NCR
CAMRY	Electronic Weigher	EK3820	N/A	2016-11-03	2017-11-02
Ducommun technologies	RF Cable	UFA210A-1- 4724-30050U	MFR64369 223410-001	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19
	RA	DIATED EMISSION	ONS		
HP	Amplifier	HP8447E	1937A01046	2017-05-12	2017-11-13
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-17	2017-12-17
A.H. System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-02-14	2018-02-14
TDK	Chamber	Chamber A	2#	2016-12-05	2019-12-05
TDK	Chamber	Chamber B	1#	2016-12-06	2019-12-06
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2014-12-29	2017-12-28
Ducommun technologies	Horn Antenna	ARH-4223-02	1007726-03	2014-12-29	2017-12-28
Ducommun technologies	Pre-amplifier	ALN-22093530- 01	991373-01	2017-08-03	2018-08-03
R&S	Auto test Software	EMC32	V9.10	NCR	NCR
Ducommun technologies	RF Cable	UFA210A-1- 4724-30050U	MFR64369 223410-001	2017-05-21	2017-11-19

Report No.: RSZ170619555-00

FCC Part 18 Page 7 of 21

Bay Area Compliano	Report No.: RSZ170619555-00				
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	1	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	2	2017-05-22	2017-11-22

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


FCC Part 18 Page 8 of 21

CONDUCTED EMISSIONS

Applicable Standard

FCC §18.307

EUT Setup



Report No.: RSZ170619555-00

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with MP-5: 1986 measurement procedure. Specification used was with the FCC Part 18.

The socket was connected to a 120 VAC/ 60Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

FCC Part 18 Page 9 of 21

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC PART 18,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{\rm (Lm)} \le L_{\rm lim} + U_{\rm cispr}$$

Report No.: RSZ170619555-00

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	28 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Joson Xiao on 2017-07-17.


FCC Part 18 Page 10 of 21

EUT operation mode: Boiling Water with MAX Power

AC 120V/60Hz, Line

EMI Auto Test L

Report No.: RSZ170619555-00




Frequency (MHz)	Corrected Amplitude (dBµV)	Corrected Factor (dB)	Limit (dBµV)	Margin (dB)	Remark (PK/QP/Ave.)
0.150000	43.9	20.2	66.0	22.1	QP
0.310590	33.3	20.2	60.0	26.7	QP
0.340930	32.8	20.2	59.2	26.4	QP
0.364570	31.4	20.2	58.6	27.2	QP
0.419610	28.0	20.2	57.5	29.5	QP
0.435430	28.9	20.2	57.1	28.3	QP
0.150000	31.6	20.2	56.0	24.4	Ave.
0.310590	24.6	20.2	50.0	25.4	Ave.
0.340930	24.6	20.2	49.2	24.6	Ave.
0.364570	20.8	20.2	48.6	27.9	Ave.
0.419610	15.5	20.2	47.5	31.9	Ave.
0.435430	14.1	20.2	47.1	33.1	Ave.

FCC Part 18 Page 11 of 21

AC 120V/60Hz, Neutral

EMI Auto Test N

Report No.: RSZ170619555-00



Frequency (MHz)	Corrected Amplitude (dBµV)	Corrected Factor (dB)	Limit (dBµV)	Margin (dB)	Remark (PK/QP/Ave.)
0.150000	46.8	20.2	66.0	19.2	QP
0.205500	40.5	20.2	63.4	22.9	QP
0.237500	43.4	20.2	62.2	18.8	QP
0.265500	42.2	20.2	61.3	19.0	QP
0.289500	41.2	20.2	60.5	19.3	QP
0.332990	41.8	20.2	59.4	17.6	QP
0.150000	32.5	20.2	56.0	23.5	Ave.
0.205500	24.5	20.2	53.4	28.9	Ave.
0.237500	29.7	20.2	52.2	22.5	Ave.
0.265500	27.9	20.2	51.3	23.4	Ave.
0.289500	28.0	20.2	50.5	22.6	Ave.
0.332990	24.0	20.2	49.4	25.4	Ave.

Note:

- Corrected Amplitude = Reading + Correction Factor
 Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation
- 3) Margin = Limit Corrected Amplitude

FCC Part 18 Page 12 of 21

RADIATION HAZARD MEASUREMENT

Applicable Standard

FCC §18.301

Environmental Conditions

Temperature:	26 °C	
Relative Humidity:	56 %	
ATM Pressure:	101.1 kPa	

The testing was performed by Joson Xiao on 2017-07-17.

Radiation Hazard Measurement

Radiation leakage was measured in the as-received condition with the oven door closed using a microwave leakage meter.

Report No.: RSZ170619555-00

A 275 mL water load was placed in the center of the oven and the oven was operated at maximum output power.

There was no microwave leakage exceeding a power level of 0.05mW/cm² observed at any point 5 cm or more from the external surface of the oven.

A maximum of 1.0 mW/cm² is allowed in accordance with the applicable Federal Standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed.

Input Power

Input power and current was measured using a power analyzer. A 1000 mL water load was placed in the center of the oven and the oven was operated at maximum output power. A 1000mL water load was chosen for its compatibility with the procedure commonly used by manufacturers to determine their input ratings.

Input Voltage (V _{AC} /Hz)	Input Current (Amps)	Measured Input Power (Watts)	Rated Input Power (Watts)
118.1	11.6	1370	1400

Based on the measured input power, the EUT was found to be operating within the intended specifications.

Load for Microwave ovens

For all measurements, the energy developed by the oven was absorbed by a dummy load consisting of a quantity of tap water in a beaker. If the oven was provided with a shelf or other utensil support, this support was in its initial normal position. For ovens rated at 1000 watts or less power output, the beaker contained quantities of water as listed in the following subparagraphs. For ovens rated at more than 1000 watts output, each quantity was increased by 50% for each 500watts or fraction thereof in excess of 1000 watts. Additional beakers were used if necessary.

FCC Part 18 Page 13 of 21

- Load for power output measurement: 1000 milliliters of water in the beaker located in the center of the oven.
- Load for frequency measurement: 1000 milliliters of water in the beaker located in the center of the oven.

Report No.: RSZ170619555-00

• Load for measurement of radiation on second and third harmonic: Two loads, one of 700 and the other of 300 milliliters, of water are used. Each load is tested both with the beaker located in the center of the oven and with it in the right front corner.

The RF output power is rated at 900 watts

Load used for power output measurement = 1000 milliliters of water Load used for frequency measurement = 1000 milliliters of water Load used for harmonic measurement = 700 & 300 milliliters of water Load used for other measurement = 700 milliliters of water

RF Output Power Measurement

A cylindrical container of borosilicate glass is used for the test. It has a maximum thickness of 3 mm, an external diameter of approximately 190 mm and a height of approximately 90 mm. The mass of the container is determined.

At the start of the test, the oven and the empty container are at ambient temperature. Water having an initial temperature of 25 °C \pm 1 °C is used for the test. The water temperature is measured immediately before it is poured into the container.

A quantity of 1 000 g \pm 5 g of water is added to the container and its actual mass obtained. The container is then immediately placed in the centre of the oven shelf, which is in its lowest normal position. The oven is operated and the time for the water temperature to attain 35 °C \pm 2 °C is measured. The oven is then switched off and the final water temperature is measured within 60 s.

FCC Part 18 Page 14 of 21

m _w (g)	m _c (g)	T ₀ (°C)	T ₁ (°C)	T ₂ (°C)	t (s)
1000	377.0	30	11.0	20.0	43

Report No.: RSZ170619555-00

RF Output Power = $(4.187 \text{ x} \ \underline{1000} \text{ x} \ (\underline{20} - \underline{11}) + 0.55 \text{ x} \ \underline{377.0} \text{ x} \ (\underline{20} - \underline{30})) / \underline{43} = \underline{828.13} \text{Watts}$

P is the microwave power output, in watts;

m_w is the mass of the water, in grams;

m_c is the mass of the container, in grams;

T_o is the ambient temperature, in degrees Celsius;

 T_1 is the initial temperature of the water, in degrees Celsius;

T₂ is the final temperature of the water, in degrees Celsius;

is the heating time, in seconds, excluding the magnetron filament heating-up time.

 \square The measurement output power was found to be less than 500 watts. Therefore, in accordance with Section 18.305 of Subpart-C, the measured out-of-band emissions were compared to the limit of $25\mu V/meter$ at a 300-meter measurement distance.

☑ The measured output power was found to exceed 500 watts. Therefore, in accordance with Section 18.305 of Subpart-C, the measured out-of-band emissions were compared with the limit calculated as following:

LFS = 25*SQRT (Power Output/500)

LFS = 25*SQRT (828.13/500)

LFS = 32.17

Where: LFS is the maximum allowable field strength for out-of-band emissions in $\mu V/meter$ at a 300-meter measurement distance. Power Output is the measured output power in watts.

LFS μV/m@300m	dBμV/m@300m	dBμV/m@3m		
32.17	30.15	70.15		

Note: Limit $(dB\mu V/m@3m) = Limit (dB\mu V/m@300m) + 40(dB)$

FCC Part 18 Page 15 of 21

Operating Frequency Measurement

Variation in Operating Frequency with Time

The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1000mL water load was placed in the center of the oven and the oven was operated at maximum output power. The fundamental operating frequency was monitored until the water load was reduced to 20 percent of the original load.


Report No.: RSZ170619555-00

The results of this test are as follows:

Frequency at Start time (MHz)	Frequency at End time (MHz)			
2451.50	2447.90			


Refer to data pages for details of the variation in operating frequency with time measurement.

Start time:



FCC Part 18 Page 16 of 21

End time:



Report No.: RSZ170619555-00

Variation in Operating Frequency with Line Voltage

The EUT was operated / warmed by at least 10 minutes of use with a 1000 mL water load at room temperature at the beginning of the test. Then the operating frequency was monitored as the input voltage was varied between 80 and 125 percent of the nominal rating.


The results of this test are as follows:

(Low voltage) Frequency	(High voltage) Frequency		
(MHz)	(MHz)		
2449.70	2448.50		

Please refer to following pages for details of the variation in operating frequency with line voltage measurement.


FCC Part 18 Page 17 of 21

High Voltage:



Report No.: RSZ170619555-00

Low Voltage:




FCC Part 18 Page 18 of 21

RADIATED EMISSIONS

Applicable Standard

FCC §18.305 and FCC §18.309

EUT Setup



Report No.: RSZ170619555-00

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the FCC MP - 5. The specification used was the FCC part 18 limits.

The socket was connected to 120 VAC/60 Hz power source.

EMI Test Receiver Setup and Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver and Spectrum Analyzer were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector	
30MHz – 1000 MHz	100 kHz	300 kHz	120kHz	QP	
Above 1 GHz	1MHz	3 MHz	/	PK	
	1MHz	10 Hz	/	Ave.	

FCC Part 18 Page 19 of 21

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions to ensure that the EUT complied with all installation combinations.

Report No.: RSZ170619555-00

The EUT was in the normal (naïve) operating mode during the final qualification test to represent the worst results.

The data was recorded in the Quasi-peak detection mode from 30 MHz to 1 GHz, the average detection mode for above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 18,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data and Plots

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	50 %
ATM Pressure:	101.1 kPa

The testing was performed by Joson Xiao on 2017-07-17.

FCC Part 18 Page 20 of 21

Test Mode: Boiling Water with MAX Power

30 MHz – 1 GHz:

Frequency (MHz)	Corrected Amplitude (dBµV/m)	Detector (PK/QP)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
32.780825	28.30	QP	117.0	V	285.0	-1.6	70.15	41.85
172.489850	20.30	QP	277.0	Н	43.0	-5.8	70.15	49.85
175.400800	22.39	QP	138.0	Н	161.0	-5.7	70.15	47.76
699.497600	28.65	QP	163.0	V	84.0	6.7	70.15	41.50
833.755625	30.55	QP	297.0	Н	191.0	9.0	70.15	39.60
988.894525	31.36	QP	334.0	V	309.0	9.7	70.15	38.79

Report No.: RSZ170619555-00

Above 1 GHz:

Frequency (MHz)		Detector (PK/QP/Ave.)	Turntable Degree	Height (m)	Polar (H/V)	Correction Factor (dB/m)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
9840.46	33.63	Ave.	221	2.5	Н	14.75	48.38	70.15	21.77
9813.20	32.83	Ave.	290	2.3	V	14.75	47.58	70.15	22.57
7367.48	34.20	Ave.	194	2.1	Н	13.02	47.22	70.15	22.93
7372.29	33.56	Ave.	171	2.4	V	13.02	46.58	70.15	23.57
4901.65	36.95	Ave.	264	1.1	Н	6.21	43.16	70.15	26.99
4912.83	38.05	Ave.	247	1.3	V	6.21	44.26	70.15	25.89

***** END OF REPORT *****

FCC Part 18 Page 21 of 21