



FCC PART 22H, PART 24E TEST REPORT

For

Burg Realisation Hong Kong Limited

Flat/RM 10/F Malaysia Building, 50 Gloucester Road, Wan Chai, Hong Kong

FCC ID: YIABURG12

Report Type: **Product Type:** Original Report Watch Phone leon then **Test Engineer:** Leon Chen **Report Number:** RSZ111117002-00B2 **Report Date:** 2012-09-05 Alvin Huang Di Hung **Reviewed By:** RF Leader Bay Area Compliance Laboratories Corp. (Shenzhen) **Test Laboratory:** 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "*

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	6
JUSTIFICATION	
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	7
FCC §1.1307 & §2.1093 - RF EXPOSURE	8
Applicable Standard	
TEST RESULT	
FCC §2.1047 - MODULATION CHARACTERISTIC	
FCC §2.1046, §22.913 (A) & §24.232 (C) - RF OUTPUT POWER	
APPLICABLE STANDARD	
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §22.917(A) & §24.238(A) - BAND EDGES	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
1E51 DATA	20

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY	24
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	25
TEST DATA	24

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Burg Realisation Hong Kong Limited*'s product, model number: *Burg 12 (FCC ID: YIABURG12)* (the "EUT") in this report was a *Watch Phone*, which was measured approximately: 5.5 cm (W) x 4.1 cm (D) x 1.5 cm (H), rated input voltage: DC 3.7 V Lithium battery.

Report No.: RSZ111117002-00B2

Frequency Range:

Cellular Band: 824-849 MHz (Tx), 869-894 MHz (Rx) PCS Band: 1850-1910 MHz (Tx), 1930-1990 MHz (Rx)

Bluetooth: 2402-2480 MHz (Tx/Rx)

Modulation Mode: GMSK (GSM/PCS); GFSK (Bluetooth)

Transmitter Output Power:

Cellular Band: 32.27 dBm PCS Band: 30.66 dBm Bluetooth: 1.85 dBm

Objective

This report is prepared on behalf of *Burg Realisation Hong Kong Limited* in accordance with Part 2, Subpart J, Part 22 Subpart H, and Part 24 Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS submission with FCC ID: YIABURG12

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-C, ANSI C63.4-2009.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is ± 0.96 dB, the uncertainty of any radiation on emissions measurement is ± 4.0 dB

FCC Part 22H/24E Page 4 of 26

^{*} All measurement and test data in this report was gathered from production sample serial number: 1111054 (Assigned by BACL, Shenzhen). The EUT was received on 2011-11-17.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Report No.: RSZ111117002-00B2

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at http://ts.nist.gov/Standards/scopes/2007070.htm

FCC Part 22H/24E Page 5 of 26

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-C.

The GSM/PCS item test was performed with the EUT operating at normal mode.

The GPRS item test was performed with the EUT operating at test mode.

Equipment Modifications


No modification was made to the EUT.

Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R & S	Universal Radio Communication Tester	CMU200	109038

Report No.: RSZ111117002-00B2

Block Diagram of Test Setup



FCC Part 22H/24E Page 6 of 26

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
\$2.1046; \$ 22.913 (a); \$ 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
\$ 2.1049; \$ 22.905 \$ 22.917; \$ 24.238	99% & 26 dB Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Report No.: RSZ111117002-00B2

Note: * Please refer to SAR report released by BACL, report number: R1206209-SAR.

FCC Part 22H/24E Page 7 of 26

FCC §1.1307 & §2.1093 - RF EXPOSURE

Report No.: RSZ111117002-00B2

Applicable Standard

FCC§1.1307 and §2.1093.

Test Result

Compliance, please refer to the SAR repot: R1206209-SAR.

FCC Part 22H/24E Page 8 of 26

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

Report No.: RSZ111117002-00B2

FCC Part 22H/24E Page 9 of 26

FCC §2.1046, §22.913 (a) & §24.232 (c) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.


Report No.: RSZ111117002-00B2

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-C section 2.2.17

Test Equipment List and Details

Manufacturer	nufacturer Description Mode		Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2012-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
HP	Signal Generator	HP8657A	2849U00982	2011-10-21	2012-10-20
HP	Synthesized Sweeper	8341B	2624A00116	2012-05-17	2013-05-16
COM POWER	Dipole Antenna	AD-100	041000	N/A	N/A
A.H. System	System Horn Antenna		135	2012-02-11	2013-02-10
Rohde & Schwarz Universal Radio Communication Tester		CMU200	109038	2012-04-11	2013-04-10

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements.

FCC Part 22H/24E Page 10 of 26

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Leon Chen on 2012-08-31.

Conducted Power:

Cellular Band (Part 22H)

Report No.: RSZ111117002-00B2

Mode	Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)
	128	824.2	32.16	38.45
GSM	190	836.6	32.22	38.45
	251	848.8	32.27	38.45

Mode	Frequency		Limit			
(MHz)	1 Slot	2 Slots	3 Slots	4 Slots	(dBm)	
	824.2	32.10	31.16	29.31	28.19	38.45
GPRS	836.6	32.11	31.25	29.44	28.37	38.45
	848.8	32.18	31.26	29.45	28.35	38.45

PCS Band (Part 24E)

Mode	Channel	Channel Frequency (MHz)		Limit (dBm)
	512	1850.2	30.66	33
GSM	661	1880.0	30.47	33
	810	1909.8	30.25	33

Mode	Frequency		Limit			
(MHz)	1 Slot	2 Slots	3 Slots	4 Slots	(dBm)	
	1850.2	30.21	29.72	28.11	26.88	33
GPRS	1880.0	29.90	29.43	27.78	26.62	33
	1909.8	29.53	29.21	27.41	26.30	33

FCC Part 22H/24E Page 11 of 26

ERP & EIRP:

ERP for Cellular Band (Part 22H)

Report No.: RSZ111117002-00B2

	Indicat	ed					
Channel	Measured Level (dBμV)	Ant. Polar (H/V)	S.G. Level (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
128	102.67	Н	29.3	0.0	0.42	28.88	38.4
(824.2 MHz)	105.62	V	32.3	0.0	0.42	31.88	38.4
190	101.85	Н	28.5	0.0	0.42	28.08	38.4
(836.6 MHz)	105.43	V	32.1	0.0	0.42	31.68	38.4
251	102.62	Н	29.3	0.0	0.42	28.88	38.4
(848.8 MHz)	105.87	V	32.5	0.0	0.42	32.08	38.4

EIRP for PCS Band (Part 24E)

	Indicate	ed					
Channel	Measured Level (dBμV)	Ant. Polar (H/V)	S.G. Level (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
512	96.43	Н	20.4	7.8	0.91	27.29	33
(1850.2 MHz)	99.18	V	23.1	7.8	0.91	29.99	33
661	96.25	Н	20.2	7.9	0.91	27.19	33
(1880.0 MHz)	98.72	V	22.7	7.9	0.91	29.69	33
810	95.87	Н	19.8	8.0	0.93	26.87	33
(1909.8 MHz)	98.59	V	22.5	8.0	0.93	29.57	33

FCC Part 22H/24E Page 12 of 26

FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH

Report No.: RSZ111117002-00B2


Applicable Standard

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 3 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa

The testing was performed by Leon Chen on 2012-08-31.

FCC Part 22H/24E Page 13 of 26

Cellular Band (Part 22H)

Channel	Frequency	99% Occupied Bandwidth	26 dB Bandwidth
	(MHz)	(kHz)	(kHz)
190	836.6	246.49	314.63


PCS Band (Part 24E)

Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
661	1880.0	244.49	314.63

Please refer to the following plots.

Cellular Band (Part 22H)


99% & 26 dB Emission Bandwidth



FCC Part 22H/24E Page 14 of 26

PCS Band (Part 24E)

99% & 26 dB Emission Bandwidth



FCC Part 22H/24E Page 15 of 26

FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for cellular band and 1 MHz for PCS band. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Report No.: RSZ111117002-00B2

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-12-23
Wainwright Germany	Band Reject Filter	WRCG1850/1910- 1835/1925-40/8SS	22	2012-02-28	2013-02-28
Wainwright Germany	Band Reject Filter	WRCG823/850-813/860- 40/8SS	7	2012-02-28	2013-02-28

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa


The testing was performed by Leon Chen on 2012-08-31.

Please refer to the following plots.

FCC Part 22H/24E Page 16 of 26


Cellular Band (Part 22H)

30 MHz - 10 GHz



PCS Band (Part 24E)

30 MHz - 20 GHz



FCC Part 22H/24E Page 17 of 26

FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Report No.: RSZ111117002-00B2

Applicable Standard

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in $dB = 10 \lg (TXpwr in Watts/0.001) - the absolute level$

Spurious attenuation limit in $dB = 43 + 10 \text{ Log}_{10}$ (power out in Watts)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2012-11-30
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
SUPER ULTRA	Amplifier	ZVA-213+	N/A	2011-11-24	2012-11-23
НР	Signal Generator	HP8657A	2849U00982	2011-10-21	2012-10-20
НР	Amplifier	HP8447D	2944A09795	2011-11-24	2012-11-23
HP	Synthesized Sweeper	8341B	2624A00116	2012-05-17	2013-05-16
COM POWER	Dipole Antenna	AD-100	041000	N/A	N/A
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2013-02-10
Electro-Mechanics	Horn Antenna	3116	9510-2270	2011-10-14	2012-10-13
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2012-04-11	2013-04-10

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

FCC Part 22H/24E Page 18 of 26

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Leon Chen on 2012-08-31.

EUT Operation Mode: Transmitting

Cellular Band (Part 22H)

Report No.: RSZ111117002-00B2

30 MHz ~ 10 GHz:

	Indic	ated		Substit	tuted			
Frequency (MHz)	Measured Level (dBμV)	Ant. Polar (H/V)	S.G. Level (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
	High channel (848.8 MHz)							
1697.6	60.57	V	-36.4	6.1	1.00	-31.3	-13	18.30
1697.6	58.14	Н	-40.8	6.1	1.00	-35.7	-13	22.70
2546.4	54.35	V	-42.6	7.2	1.23	-36.6	-13	23.63
2546.4	52.33	Н	-44.6	7.2	1.23	-38.6	-13	25.63

PCS Band (Part 24E)

30 MHz ~ 20 GHz:

	Indic	ated		Substit	uted			
Frequency (MHz)	Measured Level (dBµV)	Ant. Polar (H/V)	S.G. Level (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
	Low channel (1850.2 MHz)							
3700.4	54.27	V	-40.7	6.7	1.41	-35.4	-13	22.41
3700.4	52.88	Н	-42.1	6.7	1.41	-36.8	-13	23.81
5550.6	49.11	V	-43.8	8.2	1.76	-37.4	-13	24.36
5550.6	46.92	Н	-46.2	8.2	1.76	-39.8	-13	26.76

FCC Part 22H/24E Page 19 of 26

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$.


Report No.: RSZ111117002-00B2

According to \$24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 3 kHz.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Leon Chen on 2012-08-31.

Please refer to the following tables and plots.

FCC Part 22H/24E Page 20 of 26


Report No.: RSZ111117002-00B2

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.978	-20.99	-13
849.014	-19.42	-13

PCS Band (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.998	-19.91	-13
1910.022	-19.73	-13

Cellular Band, Left Band Edge




FCC Part 22H/24E Page 21 of 26

Cellular Band, Right Band Edge




PCS Band, Left Band Edge



FCC Part 22H/24E Page 22 of 26

PCS Band, Right Band Edge



FCC Part 22H/24E Page 23 of 26

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency	Tolerance fo	r Transmitters	in the	Public	Mobile Services

Report No.: RSZ111117002-00B2

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



FCC Part 22H/24E Page 24 of 26

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2011-11-24	2012-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2012-04-11	2013-04-10

Report No.: RSZ111117002-00B2

Test Data

Environmental Conditions

Temperature:	20°C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Leon Chen on 2012-08-31.

Cellular Band (Part 22H)

Middle Channel, f _o = 836.6 MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30		-33	-0.039	2.5
-20		-15	-0.018	2.5
-10		-27	-0.032	2.5
0	3.7	-43	-0.051	2.5
10		-15	-0.018	2.5
20		-6	-0.007	2.5
30		-16	-0.019	2.5
40		-20	-0.024	2.5
50		-8	-0.010	2.5
20	V _{end point} = 3.5	-23	-0.027	2.5

FCC Part 22H/24E Page 25 of 26

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements.

PCS Band (Part 24E)

Middle Channel, f _o =1880.0 MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30		48	0.026	pass
-20		41	0.022	pass
-10		29	0.015	pass
0		36	0.019	pass
10	3.7	38	0.020	pass
20		19	0.010	pass
30		24	0.013	pass
40		51	0.027	pass
50		33	0.018	pass
20	$V_{end point} = 3.5$	20	0.011	pass

***** END OF REPORT *****

FCC Part 22H/24E Page 26 of 26