



# FCC PART 15, SUBPART C IC RSS-210, ISSUE 8, DECEMBER 2010

# TEST AND MEASUREMENT REPORT

For

# Looxcie, Inc.

1196 Borregas Avenue, Suite 200, Sunnyvale, CA 94089, USA

FCC ID: YJ8-LXQ1 IC: 9087A-LXQ1

Report Type: **Product Type:** Class II Permissive Change SD Camera with Wi-Fi Cipher Chu down Test Engineer **Prepared By: Report Number:** R1406243-247 **Report Date:** 2014-08-05 Ivan Cao from Cu RF Lead **Reviewed By:** Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162 Fax: (408) 732-9164

**Note**: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by A2LA\*, NIST, or any agency of the Federal Government.

<sup>\*</sup> This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "\*"

# **TABLE OF CONTENTS**

| 1 Ge  | neral Description                                                                 | 4  |
|-------|-----------------------------------------------------------------------------------|----|
| 1.1   | Product Description for Equipment Under Test (EUT)                                |    |
| 1.2   | Mechanical Description of EUT                                                     | 4  |
| 1.3   | Objective                                                                         |    |
| 1.4   | Related Submittal(s)/Grant(s)                                                     | 4  |
| 1.5   | Test Methodology                                                                  | 4  |
| 1.6   | Measurement Uncertainty                                                           | 4  |
| 1.7   | Test Facility                                                                     | 5  |
| 2 Sys | stem Test Configuration                                                           | 7  |
| 2.1   | Justification                                                                     |    |
| 2.2   | EUT Exercise Software                                                             | 7  |
| 2.3   | Special Equipment                                                                 | 7  |
| 2.4   | Equipment Modifications                                                           | 7  |
| 2.5   | Local Support Equipment                                                           |    |
| 2.6   | EUT Internal Configuration Details                                                | 7  |
| 2.7   | Test Setup Block Diagram                                                          | 8  |
|       | mmary of Test Results                                                             |    |
| 4 FC  | CC §15.247 (i), §2.1093 & IC RSS-102 – RF Exposure                                |    |
| 4.1   | Applicable Standards                                                              |    |
| 4.2   | SAR Exemption Guidelines                                                          | 10 |
| 4.3   | Evaluation Result                                                                 |    |
| 5 FC  | CC §15.203 & IC RSS-Gen §7.1.2 – Antenna Requirements                             |    |
| 5.1   | Applicable Standards                                                              |    |
| 5.2   | Antenna List                                                                      |    |
| 6 FC  | CC §15.205, §15.209 & §15.247(d) & IC RSS-210 §A8.5 – Spurious Radiated Emissions |    |
| 6.1   | Applicable Standards                                                              |    |
| 6.2   | Test Setup                                                                        |    |
| 6.3   | Test Procedure                                                                    |    |
| 6.4   | Corrected Amplitude & Margin Calculation                                          |    |
| 6.5   | Test Equipment List and Details                                                   |    |
| 6.6   | Test Environmental Conditions                                                     |    |
| 6.7   | Summary of Test Results                                                           |    |
| 6.8   | Radiated Spurious Emissions Test Data                                             |    |
|       | hibit A – Test Setup Photographs                                                  |    |
| 7.1   | Radiated Emission below 1 GHz Front View at 3 Meter                               |    |
| 7.2   | Radiated Emission below 1 GHz Rear View at 3 Meter                                |    |
| 7.3   | Radiated Emission above 1 GHz Front View at 3 Meter                               |    |
| 7.4   | Radiated Emission above 1 GHz Rear View at 3 Meter                                |    |
|       | hibit B – EUT Photographs                                                         |    |
| 8.1   | EUT – Top View                                                                    |    |
| 8.2   | EUT – Front View                                                                  |    |
| 8.3   | EUT – Left Side View                                                              |    |
| 8.4   | EUT – Right Side View                                                             |    |
| 8.5   | EUT – Rear Side View                                                              |    |
| 8.6   | EUT – Bottom Side View                                                            |    |
| 8.7   | EUT – Open Case                                                                   |    |
| 8.8   | EUT – Motherboard Top View                                                        |    |
| 8.9   | EUT – Motherboard Bottom View                                                     |    |
| 8.10  | EUT – AC/DC Adapter                                                               |    |

## DOCUMENT REVISION HISTORY

| Revision Number Report Number |              | Description of Revision    | Date of Revision |  |
|-------------------------------|--------------|----------------------------|------------------|--|
| 0                             | R1406243-247 | Class II Permissive Change | 2014-08-05       |  |

#### 1 General Description

#### 1.1 Product Description for Equipment Under Test (EUT)

This test and measurement report was prepared on behalf of *Looxcie*, *Inc.*, and their product model: *LXQ1*; *FCC ID: YJ8-LXQ1*, IC: 9087A-LXQ1 or the "EUT" as referred to in this report. The EUT is an SD Camera with 802.11b/g Wi-Fi capability.

#### 1.2 Mechanical Description of EUT

The EUT measures approximately 8.5 cm (L) x 1.7 cm (W) x 2.5 cm (H) and weighs 21.5 g.

The test data gathered are from a typical production sample, Serial Number: 195Z21 assigned by BACL.

#### 1.3 Objective

This report is prepared on behalf of *Looxcie, Inc.* in accordance with Part 2, Subpart J, and Part 15, Subparts B and C of the Federal Communication Commission's rules.

The objective is to determine compliance with FCC Part 15.247 and IC RSS-210.

This is a CIIPC application of the device; the differences between the original device and the current one are as follows:

Antenna is changed; the new antenna is an inverted-F element printed on a PCB and uses the ground plane of the PCB.

For the changes mode to the EUT, the Radiated Spurious Emissions test was performed.

#### 1.4 Related Submittal(s)/Grant(s)

Original submission with FCC ID: YJ8-LXQ1 granted on 2013-09-30.

#### 1.5 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz and FCC KDB 558074 D01 DTS Meas Guidance: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

#### 1.6 Measurement Uncertainty

Report Number: R1406243-247

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR16-4-2:2011, The Treatment of Uncertainty in EMC Measurements, the values ranging from  $\pm 2.0$  dB for Conducted Emissions tests and  $\pm 4.0$  dB for Radiated Emissions tests are the most accurate estimates pertaining to uncertainty of EMC measurements at BACL Corp.

#### 1.7 Test Facility

Bay Area Compliance Laboratories Corp. (BACL) is:

- 1- An independent Commercial Test Laboratory accredited to **ISO 17025: 2005** by **A2LA**, in the fields of: Electromagnetic Compatibility & Telecommunications covering Emissions, Immunity, Radio, RF Exposure, Safety and Telecom. This includes NEBS (Network Equipment Building System), Wireless RF, Telecommunications Terminal Equipment (TTE); Network Equipment; Information Technology Equipment (ITE); Medical Electrical Equipment; Industrial, Commercial, and Medical Test Equipment; Professional Audio and Video Equipment; Electronic (Digital) Products; Industrial and Scientific Instruments; Cabled Distribution Systems and Energy Efficiency Lighting.
- 2- An ENERGY STAR Recognized Laboratory, for the LM80 Testing, a wide variety of Luminaires and Computers.
- 3- A NIST Designated Phase-I and Phase-II CAB including: ACMA (Australian Communication and Media Authority), BSMI (Bureau of Standards, Metrology and Inspection of Taiwan), IDA (Infocomm Development Authority of Singapore), IC (Industry Canada), Korea (Ministry of Communications Radio Research Laboratory), NCC (Formerly DGT; Directorate General of Telecommunication of Chinese Taipei) OFTA (Office of the Telecommunications Authority of Hong Kong), Vietnam, VCCI Voluntary Control Council for Interference of Japan and a designated EU CAB (Conformity Assessment Body) (Notified Body) for the EMC and R&TTE Directives.
- 4 A Product Certification Body accredited to **ISO Guide 65: 1996** by **A2LA** to certify:
- 1- Unlicensed, Licensed radio frequency devices and Telephone Terminal Equipment for the FCC. Scope A1, A2, A3, A4, B1, B2, B3, B4 & C.
- 2. Radio Standards Specifications (RSS) in the Category I Equipment Standards List and All Broadcasting Technical Standards (BETS) in Category I Equipment Standards List for Industry Canada.
- 3. Radio Communication Equipment for Singapore.

Report Number: R1406243-247

- 4. Radio Equipment Specifications, GMDSS Marine Radio Equipment Specifications, and Fixed Network Equipment Specifications for Hong Kong.
- 5. Japan MIC Telecommunication Business Law (A1, A2) and Radio Law (B1, B2 and B3).
- 6. Audio/Video, Battery Charging Systems, Computers, Displays, Enterprise Servers, Imaging Equipment, Set-Top Boxes, Telephony, Televisions, Ceiling Fans, CFLs (including GU24s), Decorative Light Strings, Integral LED Lamps, Luminaires, Residential Ventilating Fans.

The test site used by BACL Corp. to collect radiated and conducted emissions measurement data is located at its facility in Sunnyvale, California, USA.

The test site at BACL Corp. has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997, and Article 8 of the VCCI regulations on December 25, 1997. The test site also complies with the test methods and procedures set forth in CISPR 22:2008 §10.4 for measurements below 1 GHz and §10.6 for measurements above 1 GHz, as well as ANSI C63.4-2009, ANSI C63.4-2009, TIA/EIA-603 & CISPR 24:2010.

The Federal Communications Commission and Voluntary Control Council for Interference have the reports on file and they are listed under FCC registration number: 90464 and VCCI Registration No.: A-0027. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Looxcie, Inc.

Additionally, BACL Corp. is an American Association for Laboratory Accreditation (A2LA) accredited laboratory (Lab Code 3297-02). The current scope of accreditations can be found at

 $\frac{\text{http://www.a2la.org/scopepdf/3297-02.pdf?CFID=1132286\&CFTOKEN=e42a3240dac3f6ba-6DE17DCB-1851-9E57-477422F667031258\&jsessionid=8430d44f1f47cf2996124343c704b367816b}{\text{http://www.a2la.org/scopepdf/3297-02.pdf?CFID=1132286\&CFTOKEN=e42a3240dac3f6ba-6DE17DCB-1851-9E57-477422F667031258\&jsessionid=8430d44f1f47cf2996124343c704b367816b}$ 

Report Number: R1406243-247 Page 6 of 26 FCC Part 15C/IC RSS-210 Test Report

#### 2 System Test Configuration

#### 2.1 Justification

The EUT was configured for testing according to ANSI C63.4-2009 and FCC KDB 558074 D01 DTS Meas Guidance v03r01.

The EUT was tested in a testing mode to represent worst-case results during the final qualification test.

#### 2.2 EUT Exercise Software

The test utility used was *yugicon* and was provided by Looxcie, Inc., and was verified Cipher Chu to comply with the standard requirements being tested against.

#### 2.3 Special Equipment

There were no special accessories were required, included, or intended for use with EUT during these tests.

#### 2.4 Equipment Modifications

No modifications were made to the EUT.


#### 2.5 Local Support Equipment

| Manufacturer Description |  | Model | Serial Number |
|--------------------------|--|-------|---------------|
| Lenovo Laptop            |  | G550  | CBU2109946    |

#### 2.6 EUT Internal Configuration Details

| Manufacturer | Manufacturer Description |                  | Serial Number |
|--------------|--------------------------|------------------|---------------|
| Looxcie      | PCB board                | 31-2026-00 Rev 2 | -             |
| SYNergy      | Battery                  | AHB541262PS-01   | -             |

# 2.7 Test Setup Block Diagram



## 3 Summary of Test Results

Results reported relate only to the product tested.

| FCC & IC Rules                               | Description of Test                      | Results    |
|----------------------------------------------|------------------------------------------|------------|
| FCC §15.247(i), §2.1093<br>IC RSS-102        | RF Exposure                              | Compliant  |
| FCC §15.203<br>IC RSS-Gen §7.1.2             | Antenna Requirement                      | Compliant  |
| FCC §15.207(a)<br>IC RSS-Gen §7.2.4          | AC Line Conducted Emissions              | Compliant* |
| FCC §15.247 (d)<br>IC RSS-210 §A8.5          | Spurious Emissions at Antenna Port       | Compliant* |
| FCC §15.205<br>IC RSS-210 §2.2               | Restricted Bands                         | Compliant* |
| FCC §15.209, §15.247 (d)<br>IC RSS-210 §A8.5 | Radiated Spurious Emissions              | Compliant  |
| FCC §15.247(a)(2)<br>IC RSS-210 §A8.2        | 6 dB Emission Bandwidth                  | Compliant* |
| FCC §15.247(b)(3)<br>IC RSS-210 §A8.4        | Maximum Peak Output Power                | Compliant* |
| FCC §15.247(d)<br>IC RSS-210 §A8.5           | 100 kHz Bandwidth of Frequency Band Edge | Compliant* |
| FCC §15.247(e)<br>IC RSS-210 §A8.2(b)        | Power Spectral Density                   | Compliant* |

Note: Compliance\*, Please referred to FCC ID: *YJ8-LXQ1granted on 2013-09-30, report No.*: R1308012-247, which was tested by Bay Area Compliance Laboratories Corp.

#### 4 FCC §15.247 (i), §2.1093 & IC RSS-102 – RF Exposure

#### 4.1 Applicable Standards

According to FCC §15.247(i), §2.1093

#### **4.2** SAR Exemption Guidelines

According to FCC KDB 447498, § 4.3.1

 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f_{(GHz)}}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, <sup>25</sup> where

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>26</sup>
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq$  5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

According to RSS-102 §2.5.1

SAR evaluation is required if the separation distance between the user and the radiating element of the device is less than or equal to 20 cm, except when the device operates as follows:

Above 2.2 GHz and up to 3 GHz inclusively, and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 20 mW for general public use and 100 mW for controlled use;

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the output power of the device was derived.

#### 4.3 Evaluation Result

The maximum conducted output power of this device is 2.62 dBm=1.82 mW, the antenna gain is 0dBi, the maximum e.i.r.p. less than 20mW for IC,

And

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot$  [ $\sqrt{f_{\text{GHz}}}$ ]=(1.83/5)\*( $\sqrt{2.462}$ )=0.57<3 for FCC.

So SAR evaluation is not required.

#### 5 FCC §15.203 & IC RSS-Gen §7.1.2 – Antenna Requirements

#### **5.1** Applicable Standards

According to FCC §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to FCC §15.247 (b) (4), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to IC RSS-Gen §7.1.2: Transmitter Antenna

A transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. Testing shall be performed using the highest-gain antenna of each combination of transmitter and antenna type for which certification is being sought, with the transmitter output power set at the maximum level. Any antenna of the same type and having equal or lesser gain as an antenna that had been successfully tested for certification with the transmitter, will also be considered certified with the transmitter, and may be used and marketed with the transmitter. The manufacturer shall include with the application for certification a list of acceptable antenna types to be used with the transmitter.

When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. Any antenna gain in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power before using the power limits specified in RSS-210 or RSS-310 for devices of RF output powers of 10 mW or less. For devices of output powers greater than 10 mW, except devices subject to RSS-210 Annex 8 (Frequency Hopping and Digital Modulation Systems Operating in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz Bands) or RSS-210 Annex 9 (Local Area Network Devices), the total antenna gain shall be added to the measured RF output power before using the specified power limits. For devices subject to RSS-210 Annex 8 or Annex 9, the antenna gain shall not be added.

#### 5.2 Antenna List

| Manufacturers | Antenna Type/Pattern | Antenna Gain (dBi) @ 2.4 GHz |  |
|---------------|----------------------|------------------------------|--|
| Looxcie       | Internal             | 0                            |  |

The antenna consists of non-standard (UFL) connectors with less 6 dBi gain; therefore, it complies with the antenna requirement.

# 6 FCC §15.205, §15.209 & §15.247(d) & IC RSS-210 §A8.5 – Spurious Radiated Emissions

#### **6.1** Applicable Standards

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As per FCC §15.209(a) and RSS-210: Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

| Frequency<br>(MHz) | Field Strength<br>(micro volts/meter) | Measurement Distance (meters) |
|--------------------|---------------------------------------|-------------------------------|
| 0.009 - 0.490      | 2400/F(kHz)                           | 300                           |
| 0.490 - 1.705      | 24000/F(kHz)                          | 30                            |
| 1.705 - 30.0       | 30                                    | 30                            |
| 30 - 88            | 100**                                 | 3                             |
| 88 - 216           | 150**                                 | 3                             |
| 216 - 960          | 200**                                 | 3                             |
| Above 960          | 500                                   | 3                             |

<sup>\*\*</sup> Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As Per FCC §15.205(a) except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz                                                                                                                                                                                                                                                                                                                                  | MHz                                                                                                                                                                                                                                                                       | MHz                                                                                                                                                                                                                              | GHz                                                                                                                                                                                                                                              |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0.090 - 0.110<br>0.495 - 0.505<br>2.1735 - 2.1905<br>4.125 - 4.128<br>4.17725 - 4.17775<br>4.20725 - 4.20775<br>6.215 - 6.218<br>6.26775 - 6.26825<br>6.31175 - 6.31225<br>8.291 - 8.294<br>8.362 - 8.366<br>8.37625 - 8.38675<br>8.41425 - 8.41475<br>12.29 - 12.293<br>12.51975 - 12.52025<br>12.57675 - 12.57725<br>13.36 - 13.41 | 16.42 - 16.423 $16.69475 - 16.69525$ $25.5 - 25.67$ $37.5 - 38.25$ $73 - 74.6$ $74.8 - 75.2$ $108 - 121.94$ $123 - 138$ $149.9 - 150.05$ $156.52475 - 156.52525$ $156.7 - 156.9$ $162.0125 - 167.17$ $167.72 - 173.2$ $240 - 285$ $322 - 335.4$ $399.9 - 410$ $608 - 614$ | 960 - 1240<br>1300 - 1427<br>1435 - 1626.5<br>1645.5 - 1646.5<br>1660 - 1710<br>1718.8 - 1722.2<br>2200 - 2300<br>2310 - 2390<br>2483.5 - 2500<br>2690 - 2900<br>3260 - 3267<br>3.332 - 3.339<br>3 3458 - 3 358<br>3.600 - 4.400 | 4. 5 - 5. 15<br>5. 35 - 5. 46<br>7.25 - 7.75<br>8.025 - 8.5<br>9.0 - 9.2<br>9.3 - 9.5<br>10.6 - 12.7<br>13.25 - 13.4<br>14.47 - 14.5<br>15.35 - 16.2<br>17.7 - 21.4<br>22.01 - 23.12<br>23.6 - 24.0<br>31.2 - 31.8<br>36.43 - 36.5<br>Above 38.6 |

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.205(c).

As per IC RSS-210 A8.5 Out-of-band Emissions, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section A8.4 (4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

#### 6.2 Test Setup

The radiated emissions tests were performed in the 5-meter Chamber, using the setup in accordance with ANSI C63.4-2009. The specification used was the FCC 15C and IC RSS-210/RSS-Gen limits.

The spacing between the peripherals was 3 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

#### **6.3** Test Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v03r01: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 11: Emissions in non-restricted frequency bands and section 12: Emissions in restricted frequency bands. As well as ANSI C63.4: 2009 as described below:

For the radiated emissions test, the EUT host, and all support equipment power cords was connected to the AC floor outlet

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

The spectrum analyzer or receiver is set as:

Below 1000 MHz:

$$RBW = 100 \text{ kHz} / VBW = 300 \text{ kHz} / Sweep = Auto$$

Above 1000 MHz:

- (1) Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto
- (2) Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

#### 6.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude (CA) is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) to indicated Amplitude (Ai) reading. The basic equation is as follows:

$$CA = Ai + AF + CL + Atten - Ga$$

For example, a corrected amplitude of 40.3 dBuV/m = Indicated Reading (32.5 dBuV) + Antenna Factor (+23.5dB) + Cable Loss (3.7 dB) + Attenuator (10 dB) - Amplifier Gain (29.4 dB)

The "**Margin**" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Corrected Amplitude - Limit

#### 6.5 Test Equipment List and Details

| Manufacturer       | Description            | Model No.         | Serial No. | Calibration<br>Date | Calibration<br>Interval |
|--------------------|------------------------|-------------------|------------|---------------------|-------------------------|
| Sunol Science Corp | System Controller      | SC99V             | 122303-1   | N/R                 | N/R                     |
| Sunol Science Corp | Combination<br>Antenna | JB3               | A020106-3  | 2013-07-11          | 1 year                  |
| Hewlett Packard    | Pre-amplifier          | 8447D             | 2944A04374 | 2014-06-09          | 1 year                  |
| Mini-Circuits      | Pre-amplifier          | ZVA-183-S         | 570400946  | 2013-09-09          | 1 year                  |
| Agilent            | Spectrum Analyzer      | E4446A            | US44300386 | 2013-10-22          | 1 year                  |
| EMCO               | Horn Antenna           | 3115              | 9511-4627  | 2014-01-06          | 1 year                  |
| Rohde & Schwarz    | EMI Test Receiver      | ESCI 1166.5950K03 | 100337     | 2013-07-28          | 1 year                  |

Statement of Traceability: BACL attests that all calibrations have been performed per the A2LA requirements, traceable to NIST.

#### **6.6 Test Environmental Conditions**

| Temperature:              | 24 °C     |
|---------------------------|-----------|
| <b>Relative Humidity:</b> | 44 %      |
| ATM Pressure:             | 101.7 kPa |

The testing was performed by Cipher Chu on 2014-07-11 in 5 m chamber 3.

#### **6.7** Summary of Test Results

According to the data hereinafter, the EUT <u>complied with the FCC Title 47, Part 15C and IC RSS-210</u> standard's radiated emissions limits, and had the worst margin of:

#### 30-1000 MHz:

| Mode: Transmitting |                    |                                       |               |  |
|--------------------|--------------------|---------------------------------------|---------------|--|
| Margin<br>(dB)     | Frequency<br>(MHz) | Polarization<br>(Horizontal/Vertical) | Mode, Channel |  |
| -18.52             | 307.947            | Horizontal                            | 802.11 b mode |  |

#### 1-25 GHz:

| <b>Mode: Transmitting</b> | Mode: Transmitting |                                       |                               |  |  |  |
|---------------------------|--------------------|---------------------------------------|-------------------------------|--|--|--|
| Margin<br>(dB)            | Frequency<br>(MHz) | Polarization<br>(Horizontal/Vertical) | Mode, Channel                 |  |  |  |
| -1.013                    | 4924               | Horizontal                            | 802.11 b mode<br>High Channel |  |  |  |

Please refer to the following table and plots for specific test result details.

#### 6.8 Radiated Spurious Emissions Test Data

#### 1) 30 MHz-1 GHz, Measured at 3 meters, Quasi-Peak Measurements

802.11b mode

| Frequency<br>(MHz) | Corrected<br>Amplitude<br>(dBµV/m) | Antenna<br>Height<br>(cm) | Antenna<br>Polarity<br>(H/V) | Turntable<br>Azimuth<br>(degrees) | Limit<br>(dBµV/m) | Margin<br>(dB) |  |
|--------------------|------------------------------------|---------------------------|------------------------------|-----------------------------------|-------------------|----------------|--|
| 30.40725           | 15.73                              | 101                       | Н                            | 360                               | 40                | -24.27         |  |
| 475.3753           | 17.47                              | 164                       | Н                            | 355                               | 46                | -28.53         |  |
| 307.947            | 27.48                              | 100                       | Н                            | 340                               | 46                | -18.52         |  |
| 966.407            | 20.1                               | 269                       | V                            | 73                                | 54                | -33.9          |  |

802.11g mode

| Frequency<br>(MHz) | Corrected<br>Amplitude<br>(dBµV/m) | Antenna<br>Height<br>(cm) | Antenna<br>Polarity<br>(H/V) | Turntable<br>Azimuth<br>(degrees) | Limit<br>(dBµV/m) | Margin<br>(dB) |  |
|--------------------|------------------------------------|---------------------------|------------------------------|-----------------------------------|-------------------|----------------|--|
| 63.307             | 16.31                              | 200                       | Н                            | 0                                 | 40                | -23.69         |  |
| 36.445             | 15.98                              | 400                       | V                            | 0                                 | 40                | -24.02         |  |
| 130.395            | 20.03                              | 200                       | Н                            | 0                                 | 43.5              | -23.47         |  |
| 993.24             | 21.2                               | 200                       | Н                            | 0                                 | 54                | -32.8          |  |

#### 2) 1–25 GHz, Measured at 3 meters

802.11b mode

| Frequency | S.A.           | Turntable         | Test Antenna |                |               | Cable        | Pre-       | Cord.            | FC                |             |          |
|-----------|----------------|-------------------|--------------|----------------|---------------|--------------|------------|------------------|-------------------|-------------|----------|
| (MHz)     | Reading (dBµV) | Azimuth (degrees) | Height (cm)  | Polarity (H/V) | Factor (dB/m) | Loss<br>(dB) | Amp. (dB)  | Reading (dBµV/m) | Limit<br>(dBµV/m) | Margin (dB) | Comments |
|           |                |                   | Lov          | w Channe       | 1 2412 M      | Hz, meas     | sured at 3 | 3 meters         |                   |             |          |
| 2412      | 47.57          | 353               | 100          | V              | 28.956        | 3.12         | 0          | 79.646           | -                 | -           | Peak     |
| 2412      | 51.36          | 38                | 110          | Н              | 28.956        | 3.12         | 0          | 83.436           | -                 | -           | Peak     |
| 2412      | 42.98          | 353               | 100          | V              | 28.956        | 3.12         | 0          | 75.056           | -                 | -           | Ave      |
| 2412      | 47.18          | 38                | 110          | Н              | 28.956        | 3.12         | 0          | 79.256           | -                 | -           | Ave      |
| 2390      | 26.4           | 0                 | 100          | V              | 28.956        | 3.12         | 0          | 58.476           | 74                | -15.524     | Peak     |
| 2390      | 26.54          | 0                 | 100          | Н              | 28.956        | 3.12         | 0          | 58.616           | 74                | -15.384     | Peak     |
| 2390      | 12.43          | 0                 | 100          | V              | 28.956        | 3.12         | 0          | 44.506           | 54                | -9.494      | Ave      |
| 2390      | 12.41          | 0                 | 100          | Н              | 28.956        | 3.12         | 0          | 44.486           | 54                | -9.514      | Ave      |
| 4824      | 45.63          | 23                | 100          | V              | 33.097        | 4.56         | 27.7       | 55.587           | 74                | -18.413     | Peak     |
| 4824      | 44.51          | 317               | 100          | Н              | 33.097        | 4.56         | 27.7       | 54.467           | 74                | -19.533     | Peak     |
| 4824      | 39.94          | 23                | 100          | V              | 33.097        | 4.56         | 27.7       | 49.897           | 54                | -4.103      | Ave      |
| 4824      | 39.03          | 317               | 100          | Н              | 33.097        | 4.56         | 27.7       | 48.987           | 54                | -5.013      | Ave      |
| 7236      | 32.49          | 0                 | 100          | V              | 35.928        | 5.49         | 27.58      | 46.328           | 74                | -27.672     | Peak     |
| 7236      | 33.57          | 0                 | 100          | Н              | 35.928        | 5.49         | 27.58      | 47.408           | 74                | -26.592     | Peak     |
| 7236      | 18.18          | 0                 | 100          | V              | 35.928        | 5.49         | 27.58      | 32.018           | 54                | -21.982     | Ave      |
| 7236      | 18.12          | 0                 | 100          | Н              | 35.928        | 5.49         | 27.58      | 31.958           | 54                | -22.042     | Ave      |
| 9648      | 32.47          | 0                 | 100          | V              | 37.954        | 6.54         | 27.06      | 49.904           | 74                | -24.096     | Peak     |
| 9648      | 31.51          | 0                 | 100          | Н              | 37.954        | 6.54         | 27.06      | 48.944           | 74                | -25.056     | Peak     |
| 9648      | 20.27          | 0                 | 100          | V              | 37.954        | 6.54         | 27.06      | 37.704           | 54                | -16.296     | Ave      |
| 9648      | 20.99          | 0                 | 100          | Н              | 37.954        | 6.54         | 27.06      | 38.424           | 54                | -15.576     | Ave      |
|           |                |                   | Mide         | dle Chann      | el 2437 N     | Hz, me       | asured at  | t 3 meters       |                   |             | •        |
| 2437      | 49.26          | 334               | 100          | V              | 28.956        | 3.12         | 0          | 81.336           | -                 | -           | Peak     |
| 2437      | 55.66          | 35                | 107          | Н              | 28.956        | 3.12         | 0          | 87.736           | -                 | -           | Peak     |
| 2437      | 44.95          | 334               | 100          | V              | 28.956        | 3.12         | 0          | 77.026           | -                 | -           | Ave      |
| 2437      | 51.51          | 35                | 107          | Н              | 28.956        | 3.12         | 0          | 83.586           | -                 | -           | Ave      |
| 4874      | 46.12          | 23                | 100          | V              | 33.327        | 4.54         | 27.76      | 56.227           | 74                | -17.773     | Peak     |
| 4874      | 46.48          | 317               | 100          | Н              | 33.327        | 4.54         | 27.76      | 56.587           | 74                | -17.413     | Peak     |
| 4874      | 41.33          | 23                | 100          | V              | 33.327        | 4.54         | 27.76      | 51.437           | 54                | -2.563      | Ave      |
| 4874      | 41.44          | 317               | 100          | Н              | 33.327        | 4.54         | 27.76      | 51.547           | 54                | -2.453      | Ave      |
| 7311      | 32.37          | 0                 | 100          | V              | 36.369        | 5.57         | 27.51      | 46.799           | 74                | -27.201     | Peak     |
| 7311      | 33.07          | 0                 | 100          | Н              | 36.369        | 5.57         | 27.51      | 47.499           | 74                | -26.501     | Peak     |
| 7311      | 17.39          | 0                 | 100          | V              | 36.369        | 5.57         | 27.51      | 31.819           | 54                | -22.181     | Ave      |
| 7311      | 17.16          | 0                 | 100          | Н              | 36.369        | 5.57         | 27.51      | 31.589           | 54                | -22.411     | Ave      |
| 9748      | 33.02          | 0                 | 100          | V              | 38.087        | 6.62         | 26.98      | 50.747           | 74                | -23.253     | Peak     |
| 9748      | 32.32          | 0                 | 100          | Н              | 38.087        | 6.62         | 26.98      | 50.047           | 74                | -23.953     | Peak     |
| 9748      | 23.41          | 0                 | 100          | V              | 38.087        | 6.62         | 26.98      | 41.137           | 54                | -12.863     | Ave      |
| 9748      | 23.51          | 0                 | 100          | Н              | 38.087        | 6.62         | 26.98      | 41.237           | 54                | -12.763     | Ave      |

| т.                 | S.A.           | Turntable         | Т           | est Anteni        | na            | Cable     |           |                  | FCC               | /IC         |          |
|--------------------|----------------|-------------------|-------------|-------------------|---------------|-----------|-----------|------------------|-------------------|-------------|----------|
| Frequency<br>(MHz) | Reading (dBµV) | Azimuth (degrees) | Height (cm) | Polarity<br>(H/V) | Factor (dB/m) | Loss (dB) | Amp. (dB) | Reading (dBµV/m) | Limit<br>(dBµV/m) | Margin (dB) | Comments |
|                    |                |                   | High        | Channel           | 2462 MH       | z, meası  | ared at 3 | meters           |                   |             |          |
| 2462               | 46.66          | 354               | 122         | V                 | 29.155        | 3.25      | 0         | 79.065           | -                 | -           | Peak     |
| 2462               | 53.06          | 37                | 123         | Н                 | 29.155        | 3.25      | 0         | 85.465           | -                 | -           | Peak     |
| 2462               | 42.35          | 354               | 122         | V                 | 29.155        | 3.25      | 0         | 74.755           | -                 | -           | Ave      |
| 2462               | 48.91          | 37                | 123         | Н                 | 29.155        | 3.25      | 0         | 81.315           | -                 | -           | Ave      |
| 2483.5             | 26.34          | 0                 | 100         | V                 | 29.155        | 3.25      | 0         | 58.745           | 74                | -15.255     | Peak     |
| 2483.5             | 26.81          | 0                 | 100         | Н                 | 29.155        | 3.25      | 0         | 59.215           | 74                | -14.785     | Peak     |
| 2483.5             | 12.56          | 0                 | 100         | V                 | 29.155        | 3.25      | 0         | 44.965           | 54                | -9.035      | Ave      |
| 2483.5             | 12.53          | 0                 | 100         | Н                 | 29.155        | 3.25      | 0         | 44.935           | 54                | -9.065      | Ave      |
| 4924               | 48.05          | 23                | 100         | V                 | 33.327        | 4.52      | 27.75     | 58.147           | 74                | -15.853     | Peak     |
| 4924               | 47.49          | 317               | 100         | Н                 | 33.327        | 4.52      | 27.75     | 57.587           | 74                | -16.413     | Peak     |
| 4924               | 42.66          | 23                | 100         | V                 | 33.327        | 4.52      | 27.75     | 52.757           | 54                | -1.243      | Ave      |
| 4924               | 42.89          | 317               | 100         | Н                 | 33.327        | 4.52      | 27.75     | 52.987           | 54                | -1.013      | Ave      |
| 7386               | 32.54          | 0                 | 100         | V                 | 36.565        | 5.62      | 27.51     | 47.215           | 74                | -26.785     | Peak     |
| 7386               | 31.75          | 0                 | 100         | Н                 | 36.565        | 5.62      | 27.51     | 46.425           | 74                | -27.575     | Peak     |
| 7386               | 17.41          | 0                 | 100         | V                 | 36.565        | 5.62      | 27.51     | 32.085           | 54                | -21.915     | Ave      |
| 7386               | 17.13          | 0                 | 100         | Н                 | 36.565        | 5.62      | 27.51     | 31.805           | 54                | -22.195     | Ave      |
| 9848               | 34.16          | 0                 | 100         | V                 | 38.287        | 6.55      | 26.98     | 52.017           | 74                | -21.983     | Peak     |
| 9848               | 33.61          | 0                 | 100         | Н                 | 38.287        | 6.55      | 26.98     | 51.467           | 74                | -22.533     | Peak     |
| 9848               | 23.72          | 0                 | 100         | V                 | 38.287        | 6.55      | 26.98     | 41.577           | 54                | -12.423     | Ave      |
| 9848               | 23.75          | 0                 | 100         | Н                 | 38.287        | 6.55      | 26.98     | 41.607           | 54                | -12.393     | Ave      |

802.11g mode

| Frequency | S.A.           | Turntable         | Т           | est Anten         | na            | Cable     | Pre-      | Cord.            | FC                | C/IC        |          |
|-----------|----------------|-------------------|-------------|-------------------|---------------|-----------|-----------|------------------|-------------------|-------------|----------|
| (MHz)     | Reading (dBµV) | Azimuth (degrees) | Height (cm) | Polarity<br>(H/V) | Factor (dB/m) | Loss (dB) | Amp. (dB) | Reading (dBµV/m) | Limit<br>(dBµV/m) | Margin (dB) | Comments |
|           |                |                   | Lo          | w Channe          | el 2412 M     | Hz, mea   | sured at  | 3 meters         |                   |             |          |
| 2412      | 48.18          | 353               | 100         | V                 | 28.956        | 3.12      | 0         | 80.256           | -                 | -           | Peak     |
| 2412      | 54.62          | 38                | 110         | Н                 | 28.956        | 3.12      | 0         | 86.696           | -                 | -           | Peak     |
| 2412      | 36.13          | 353               | 100         | V                 | 28.956        | 3.12      | 0         | 68.206           | -                 | -           | Ave      |
| 2412      | 42.32          | 38                | 110         | Н                 | 28.956        | 3.12      | 0         | 74.396           | -                 | -           | Ave      |
| 2390      | 26.53          | 0                 | 100         | V                 | 28.956        | 3.12      | 0         | 58.606           | 74                | -15.394     | Peak     |
| 2390      | 26.1           | 0                 | 100         | Н                 | 28.956        | 3.12      | 0         | 58.176           | 74                | -15.824     | Peak     |
| 2390      | 12.33          | 0                 | 100         | V                 | 28.956        | 3.12      | 0         | 44.406           | 54                | -9.594      | Ave      |
| 2390      | 12.41          | 0                 | 100         | Н                 | 28.956        | 3.12      | 0         | 44.486           | 54                | -9.514      | Ave      |
| 4824      | 35.86          | 0                 | 100         | V                 | 33.097        | 4.56      | 27.7      | 45.817           | 74                | -28.183     | Peak     |
| 4824      | 35.46          | 0                 | 100         | Н                 | 33.097        | 4.56      | 27.7      | 45.417           | 74                | -28.583     | Peak     |
| 4824      | 21.89          | 0                 | 100         | V                 | 33.097        | 4.56      | 27.7      | 31.847           | 54                | -22.153     | Ave      |
| 4824      | 21.34          | 0                 | 100         | Н                 | 33.097        | 4.56      | 27.7      | 31.297           | 54                | -22.703     | Ave      |
| 7236      | 32.73          | 0                 | 100         | V                 | 35.928        | 5.49      | 27.58     | 46.568           | 74                | -27.432     | Peak     |
| 7236      | 32.5           | 0                 | 100         | Н                 | 35.928        | 5.49      | 27.58     | 46.338           | 74                | -27.662     | Peak     |
| 7236      | 17.72          | 0                 | 100         | V                 | 35.928        | 5.49      | 27.58     | 31.558           | 54                | -22.442     | Ave      |
| 7236      | 17.55          | 0                 | 100         | Н                 | 35.928        | 5.49      | 27.58     | 31.388           | 54                | -22.612     | Ave      |
| 9648      | 32.81          | 92                | 100         | V                 | 37.954        | 6.54      | 27.06     | 50.244           | 74                | -23.756     | Peak     |
| 9648      | 33.6           | 58                | 108         | Н                 | 37.954        | 6.54      | 27.06     | 51.034           | 74                | -22.966     | Peak     |
| 9648      | 22.28          | 92                | 100         | V                 | 37.954        | 6.54      | 27.06     | 39.714           | 54                | -14.286     | Ave      |
| 9648      | 22.49          | 58                | 108         | Н                 | 37.954        | 6.54      | 27.06     | 39.924           | 54                | -14.076     | Ave      |
|           |                |                   | Mid         | dle Chanı         | nel 2437 N    | MHz, me   | easured a | it 3 meters      |                   |             |          |
| 2437      | 48.88          | 355               | 100         | V                 | 28.956        | 3.12      | 0         | 80.956           | -                 | -           | Peak     |
| 2437      | 54.33          | 34                | 110         | Н                 | 28.956        | 3.12      | 0         | 86.406           | -                 | -           | Peak     |
| 2437      | 36.92          | 355               | 100         | V                 | 28.956        | 3.12      | 0         | 68.996           | -                 | -           | Ave      |
| 2437      | 42.83          | 34                | 110         | Н                 | 28.956        | 3.12      | 0         | 74.906           | -                 | -           | Ave      |
| 4874      | 32.89          | 0                 | 100         | V                 | 33.327        | 4.54      | 27.76     | 42.997           | 74                | -31.003     | Peak     |
| 4874      | 33.01          | 0                 | 100         | Н                 | 33.327        | 4.54      | 27.76     | 43.117           | 74                | -30.883     | Peak     |
| 4874      | 18.04          | 0                 | 100         | V                 | 33.327        | 4.54      | 27.76     | 28.147           | 54                | -25.853     | Ave      |
| 4874      | 18.09          | 0                 | 100         | Н                 | 33.327        | 4.54      | 27.76     | 28.197           | 54                | -25.803     | Ave      |
| 7311      | 32.32          | 0                 | 100         | V                 | 36.369        | 5.57      | 27.51     | 46.749           | 74                | -27.251     | Peak     |
| 7311      | 32.44          | 0                 | 100         | Н                 | 36.369        | 5.57      | 27.51     | 46.869           | 74                | -27.131     | Peak     |
| 7311      | 17.38          | 0                 | 100         | V                 | 36.369        | 5.57      | 27.51     | 31.809           | 54                | -22.191     | Ave      |
| 7311      | 17.26          | 0                 | 100         | Н                 | 36.369        | 5.57      | 27.51     | 31.689           | 54                | -22.311     | Ave      |
| 9748      | 31.06          | 0                 | 100         | V                 | 38.087        | 6.62      | 26.98     | 48.787           | 74                | -25.213     | Peak     |
| 9748      | 30.79          | 0                 | 100         | Н                 | 38.087        | 6.62      | 26.98     | 48.517           | 74                | -25.483     | Peak     |
| 9748      | 15.93          | 0                 | 100         | V                 | 38.087        | 6.62      | 26.98     | 33.657           | 54                | -20.343     | Ave      |
| 9748      | 15.9           | 0                 | 100         | Н                 | 38.087        | 6.62      | 26.98     | 33.627           | 54                | -20.373     | Ave      |

| _                  | S.A.           | Turntable         | Т           | est Anteni        | na            | Cable     | Pre-      | Cord.            | FCC               | /IC         |          |
|--------------------|----------------|-------------------|-------------|-------------------|---------------|-----------|-----------|------------------|-------------------|-------------|----------|
| Frequency<br>(MHz) | Reading (dBµV) | Azimuth (degrees) | Height (cm) | Polarity<br>(H/V) | Factor (dB/m) | Loss (dB) | Amp. (dB) | Reading (dBµV/m) | Limit<br>(dBµV/m) | Margin (dB) | Comments |
|                    |                |                   | Hig         | h Channe          | l 2462 MI     | Iz, meas  | ured at 3 | meters           |                   |             |          |
| 2462               | 50.1           | 355               | 100         | V                 | 29.155        | 3.25      | 0         | 82.505           | -                 | -           | Peak     |
| 2462               | 55.76          | 37                | 113         | Н                 | 29.155        | 3.25      | 0         | 88.165           | -                 | -           | Peak     |
| 2462               | 38.29          | 355               | 100         | V                 | 29.155        | 3.25      | 0         | 70.695           | -                 | -           | Ave      |
| 2462               | 44.56          | 37                | 113         | Н                 | 29.155        | 3.25      | 0         | 76.965           | -                 | -           | Ave      |
| 2483.5             | 26.4           | 0                 | 100         | V                 | 29.155        | 3.25      | 0         | 58.805           | 74                | -15.195     | Peak     |
| 2483.5             | 26.38          | 0                 | 100         | Н                 | 29.155        | 3.25      | 0         | 58.785           | 74                | -15.215     | Peak     |
| 2483.5             | 12.65          | 0                 | 100         | V                 | 29.155        | 3.25      | 0         | 45.055           | 54                | -8.945      | Ave      |
| 2483.5             | 12.6           | 0                 | 100         | Н                 | 29.155        | 3.25      | 0         | 45.005           | 54                | -8.995      | Ave      |
| 4924               | 36.79          | 0                 | 100         | V                 | 33.327        | 4.52      | 27.75     | 46.887           | 74                | -27.113     | Peak     |
| 4924               | 36.33          | 0                 | 100         | Н                 | 33.327        | 4.52      | 27.75     | 46.427           | 74                | -27.573     | Peak     |
| 4924               | 22.85          | 0                 | 100         | V                 | 33.327        | 4.52      | 27.75     | 32.947           | 54                | -21.053     | Ave      |
| 4924               | 22.12          | 0                 | 100         | Н                 | 33.327        | 4.52      | 27.75     | 32.217           | 54                | -21.783     | Ave      |
| 7386               | 32.05          | 0                 | 100         | V                 | 36.565        | 5.62      | 27.51     | 46.725           | 74                | -27.275     | Peak     |
| 7386               | 32.17          | 0                 | 100         | Н                 | 36.565        | 5.62      | 27.51     | 46.845           | 74                | -27.155     | Peak     |
| 7386               | 17.38          | 0                 | 100         | V                 | 36.565        | 5.62      | 27.51     | 32.055           | 54                | -21.945     | Ave      |
| 7386               | 17.23          | 0                 | 100         | Н                 | 36.565        | 5.62      | 27.51     | 31.905           | 54                | -22.095     | Ave      |
| 9848               | 34.34          | 0                 | 100         | V                 | 38.287        | 6.55      | 26.98     | 52.197           | 74                | -21.803     | Peak     |
| 9848               | 33.27          | 0                 | 100         | Н                 | 38.287        | 6.55      | 26.98     | 51.127           | 74                | -22.873     | Peak     |
| 9848               | 25.18          | 0                 | 100         | V                 | 38.287        | 6.55      | 26.98     | 43.037           | 54                | -10.963     | Ave      |
| 9848               | 25.37          | 0                 | 100         | Н                 | 38.287        | 6.55      | 26.98     | 43.227           | 54                | -10.773     | Ave      |