



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

GUARDIAN SHANGHAI CORP.

368, Min Shen Rd, SongJiang, Shanghai, China

FCC ID: YJFV2SEN


Report Type: Original Report	Product Type: Garage Door Smart Control
Test Engineer:	<u>Tyrone Wang</u> 
Report Number:	<u>RSHD190912006-00B</u>
Report Date:	<u>2021-01-27</u>
Reviewed By:	<u>Oscar Ye</u>  EMC Manager
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	5
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	9
TEST EQUIPMENT LIST	10
FCC §1.1310 & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)	11
CALCULATED FORMULARY:.....	11
FCC §15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
FACTOR & OVER LIMIT CALCULATION - BELOW 1 GHZ.....	14
CORRECTED AMPLITUDE & MARGIN CALCULATION - ABOVE 1 GHZ.....	14
TEST RESULTS SUMMARY	15
TEST DATA	15
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST DATA	38
FCC §15.247(d) – BAND EDGE.....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST DATA	42
FCC §15.247(e) - POWER SPECTRAL DENSITY	45
APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST DATA	45

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	GUARDIAN SHANGHAI CORP.
Tested Model:	V2 (sensor)
Product Type:	Garage Door Smart Control
Power Supply:	DC 3V from battery
RF Function:	BLE (1Mbps), BLE (2Mbps)
Operating Band/Frequency:	2402-2480MHz
Channel Number:	40
Channel Separation:	2 MHz
Modulation Type	GFSK
Antenna Type:	PCB Antenna
*Maximum Antenna Gain:	4.0 dBi

Note: The antenna gain was provided by the applicant.

**All measurement and test data in this report was gathered from production sample serial number: RSHD190912006-1.(Assigned by BACL, Kunshan). The EUT was received on 2019-09-12.*

Objective

This report is prepared on behalf of *GUARDIAN SHANGHAI CORP.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communications Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

Part of system submitted with FCC ID: YJFV2CRTL.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emissions	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel List for BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
18	2438	38	2478
19	2440	39	2480

EUT was tested with channel 0, 20 and 39.

Equipment Modifications

No modification was made to the EUT tested.


EUT Exercise Software


RF test software: UartAssist.exe

Power Level Setting: BLE (1Mbps): Default; BLE (2Mbps): Default

Duty Cycle:

BLE (1Mbps): High Channel



BLE (2Mbps): Middle Channel

Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
BLE (1Mbps)	51.31	2.154	0.46	2.90
BLE (2Mbps)	53.10	1.112	0.90	2.75

Note: “x” means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable (See Note1)
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Note 1: The EUT is powered by batteries.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2020-08-05	2021-08-04
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2020-08-05	2023-08-04
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Audix	Test Software	e3	V9	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2020-01-07	2023-01-06
A.H.Systems, inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
SELECTOR	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2020-08-05	2021-08-04
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2020-11-27	2021-11-26
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Guardian Shanghai Corp.	RF Cable	Guardian Shanghai Corp. C01	N/A	Each Time	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE(1Mbps)	2402~2480	4.0	2.51	-10.00	0.10	20	0.00005	1.0
BLE(2Mbps)	2402~2480	4.0	2.51	-10.00	0.10	20	0.00005	1.0

Note: The tune-up conducted power was declared by the manufacturer.

Conclusion: The device meets FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a PCB antenna for BLE, which the antenna gain is 4.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	Peak
	1MHz	3 MHz	1MHz	AVG

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Factor & Over Limit Calculation - Below 1 GHz

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Corrected Amplitude & Margin Calculation - Above 1 GHz

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	23.6~25.3℃
Relative Humidity:	50~52%
ATM Pressure:	101.1~101.7 kPa


The testing was performed by Tyrone Wang from 2021-01-18 to 2021-01-26.

Test Result: Compliant.


EUT operation mode: Transmitting

Spurious Emission Test:**BLE (1Mbps)****30MHz-1GHz**

(Pre-scan with Low channel, Middle channel, High channel of operation in the X,Y and Z axes of orientation, the worst case **middle channel of operation in X-axis of orientation** was recorded)

Horizontal:

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	30.11	22.45	-3.73	18.72	40.00	-21.28	200	153	QP
2	33.33	22.94	-6.33	16.61	40.00	-23.39	200	226	QP
3	114.92	23.13	-11.93	11.20	43.50	-32.30	100	224	QP
4	124.13	22.65	-11.14	11.51	43.50	-31.99	100	339	QP
5	138.87	23.07	-11.93	11.14	43.50	-32.36	100	50	QP
6	198.59	22.64	-11.91	10.73	43.50	-32.77	100	0	QP

Vertical:

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	30.53	21.90	-4.07	17.83	40.00	-22.17	100	315	QP
2	37.15	22.70	-9.46	13.24	40.00	-26.76	200	58	QP
3	126.33	22.20	-11.26	10.94	43.50	-32.56	200	358	QP
4	145.35	22.01	-12.08	9.93	43.50	-33.57	200	24	QP
5	203.52	21.70	-12.13	9.57	43.50	-33.93	100	271	QP
6	270.37	21.59	-11.34	10.25	46.00	-35.75	100	335	QP

1GHz-18GHz:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1062.900000	---	32.67	150.0	V	275.0	-12.1	54.00	21.33
1062.900000	37.24	---	150.0	V	275.0	-12.1	74.00	36.76
1326.400000	39.92	---	200.0	V	270.0	-10.5	74.00	34.08
1326.400000	---	28.58	200.0	V	270.0	-10.5	54.00	25.42
1686.800000	---	29.27	200.0	H	329.0	-8.8	54.00	24.73
1686.800000	40.86	---	200.0	H	329.0	-8.8	74.00	33.14
4804.000000	---	50.40	150.0	H	270.0	1.0	54.00	3.60
4804.000000	53.92	---	150.0	H	270.0	1.0	74.00	20.08
7206.000000	---	52.51	200.0	H	169.0	9.0	54.00	1.49
7206.000000	59.36	---	200.0	H	169.0	9.0	74.00	14.64
13092.100000	---	47.33	150.0	H	358.0	13.1	54.00	6.67
13092.100000	56.27	---	150.0	H	358.0	13.1	74.00	17.73
17102.400000	---	48.23	150.0	H	345.0	13.8	54.00	5.77
17102.400000	57.71	---	150.0	H	345.0	13.8	74.00	16.29

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1115.600000	---	29.12	200.0	V	0.0	-11.8	54.00	24.88
1115.600000	39.26	---	200.0	V	0.0	-11.8	74.00	34.74
1261.800000	41.46	---	200.0	V	243.0	-10.9	74.00	32.54
1261.800000	---	28.80	200.0	V	243.0	-10.9	54.00	25.20
1688.500000	---	29.04	150.0	V	301.0	-8.7	54.00	24.96
1688.500000	41.76	---	150.0	V	301.0	-8.7	74.00	32.24
4880.000000	49.36	---	150.0	H	166.0	1.1	74.00	24.64
4880.000000	---	46.19	150.0	H	166.0	1.1	54.00	7.81
7320.000000	---	52.10	200.0	H	117.0	9.1	54.00	1.90
7320.000000	57.63	---	200.0	H	117.0	9.1	74.00	16.37
16385.000000	---	48.73	200.0	V	83.0	14.0	54.00	5.27
16385.000000	58.55	---	200.0	V	83.0	14.0	74.00	15.45

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1263.500000	41.51	---	200.0	V	77.0	-10.9	74.00	32.49
1263.500000	---	28.76	150.0	H	36.0	-10.9	54.00	25.24
1593.300000	---	30.73	150.0	H	343.0	-9.1	54.00	23.27
1593.300000	43.69	---	200.0	V	166.0	-9.1	74.00	30.31
3951.200000	---	36.92	150.0	H	176.0	0.2	54.00	17.08
3951.200000	46.79	---	200.0	H	116.0	0.2	74.00	27.21
4960.000000	52.77	---	150.0	H	176.0	1.1	74.00	21.23
4960.000000	---	48.00	150.0	H	176.0	1.1	54.00	6.00
7440.000000	54.77	---	200.0	H	103.0	9.2	74.00	19.23
7440.000000	---	48.68	150.0	V	95.0	9.2	54.00	5.32
14877.100000	---	47.98	150.0	V	0.0	14.0	54.00	6.02
14877.100000	58.06	---	150.0	H	49.0	14.0	74.00	15.94

18GHz-25GHz:

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **middle channel of operation in X-axis of orientation** was recorded)

Horizontal


Date: 25.JAN.2021 20:00:13

Vertical


Date: 25.JAN.2021 19:50:39

BLE (2Mbps)**30MHz-1GHz**

(Pre-scan with Low channel, Middle channel, High channel of operation in the X,Y and Z axes of orientation, the worst case **middle channel of operation in X-axis of orientation** was recorded)

Horizontal:

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	30.21	22.92	-3.82	19.10	40.00	-20.90	200	293	Peak
2	34.16	23.13	-7.01	16.12	40.00	-23.88	200	360	Peak
3	123.70	23.44	-11.11	12.33	43.50	-31.17	200	300	Peak
4	134.09	23.10	-11.69	11.41	43.50	-32.09	100	64	Peak
5	191.75	22.65	-12.40	10.25	43.50	-33.25	200	59	Peak
6	270.38	23.51	-11.34	12.17	46.00	-33.83	200	177	Peak

Vertical:

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	30.00	22.83	-3.64	19.19	40.00	-20.81	200	346	QP
2	33.92	22.14	-6.81	15.33	40.00	-24.67	200	109	QP
3	117.36	22.20	-11.44	10.76	43.50	-32.74	200	82	QP
4	146.37	23.02	-12.09	10.93	43.50	-32.57	200	13	QP
5	204.96	22.54	-12.26	10.28	43.50	-33.22	100	156	QP
6	291.04	22.20	-10.67	11.53	46.00	-34.47	100	39	QP

1GHz-18GHz:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1263.500000	41.91	---	150.0	V	247.0	-10.9	74.00	32.09
1263.500000	---	29.43	150.0	V	247.0	-10.9	54.00	24.57
1593.300000	---	30.89	200.0	V	172.0	-9.1	54.00	23.11
1593.300000	42.97	---	200.0	V	172.0	-9.1	74.00	31.03
2921.000000	---	33.78	150.0	H	321.0	-3.6	54.00	20.22
2921.000000	43.96	---	150.0	H	321.0	-3.6	74.00	30.04
4804.000000	52.49	---	150.0	V	272.0	1.0	74.00	21.51
4804.000000	---	43.70	150.0	V	272.0	1.0	54.00	10.30
7206.000000	---	53.41	200.0	H	63.0	9.0	54.00	0.59
7206.000000	59.77	---	200.0	H	63.0	9.0	74.00	14.23
14662.900000	---	47.80	150.0	H	232.0	13.7	54.00	6.20
14662.900000	57.71	---	150.0	H	232.0	13.7	74.00	16.29
17201.000000	---	47.82	200.0	H	321.0	13.5	54.00	6.18
17201.000000	54.20	---	200.0	H	321.0	13.5	74.00	19.80

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1294.100000	40.60	---	200.0	V	63.0	-10.7	200.0	33.40
1294.100000	---	29.35	200.0	V	63.0	-10.7	150.0	24.65
1593.300000	---	31.11	200.0	V	101.0	-9.1	200.0	22.89
1593.300000	42.86	---	200.0	V	101.0	-9.1	150.0	31.14
4880.000000	---	47.42	200.0	V	114.0	1.1	200.0	6.58
4880.000000	52.17	---	200.0	V	114.0	1.1	200.0	21.83
7320.900000	---	53.67	150.0	H	74.0	9.1	150.0	0.33
7320.000000	59.83	---	150.0	H	74.0	9.1	150.0	14.17
10307.500000	---	46.05	200.0	V	0.0	12.6	200.0	7.95
10307.500000	56.12	---	200.0	V	0.0	12.6	200.0	17.88
15104.900000	---	48.81	150.0	V	299.0	13.9	150.0	5.19
15104.900000	57.10	---	150.0	V	299.0	13.9	200.0	16.90

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1326.400000	---	28.64	150.0	V	249.0	-10.5	54.00	25.36
1326.400000	42.59	---	150.0	V	249.0	-10.5	74.00	31.41
1729.300000	40.98	---	200.0	V	64.0	-8.6	74.00	33.02
1729.300000	---	30.19	200.0	V	64.0	-8.6	54.00	23.81
4960.000000	50.77	---	150.0	H	178.0	1.1	74.00	23.23
4960.000000	---	44.42	150.0	H	178.0	1.1	54.00	9.58
4993.300000	---	40.03	200.0	H	250.0	1.1	54.00	13.97
4993.300000	51.33	---	200.0	H	250.0	1.1	74.00	22.67
6195.200000	---	39.99	200.0	H	225.0	5.7	54.00	14.01
6195.200000	50.69	---	200.0	H	225.0	5.7	74.00	23.31
7440.000000	56.49	---	150.0	H	114.0	9.2	74.00	17.51
7440.000000	---	49.88	150.0	H	114.0	9.2	54.00	4.12
16590.700000	---	49.27	150.0	H	50.0	13.9	54.00	4.73
16590.700000	58.13	---	150.0	H	50.0	13.9	74.00	15.87

18GHz-25GHz:

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **middle channel of operation in X-axis of orientation** was recorded)

Horizontal

Date: 25.JAN.2021 20:17:37

Vertical

Date: 25.JAN.2021 20:06:54

Restricted Bands Emissions Test:

(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded.)

Note:



1. The test is performed with a 10dB Attenuator.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

BLE (1Mbps)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	52.15	---	200.0	H	126.0	3.8	74.00	21.85
2390.00	---	45.98	200.0	H	126.0	3.8	54.00	8.02
High Channel: 2480MHz								
2483.50	53.59	---	200.0	V	178.0	4.1	74.00	20.41
2483.50	---	46.44	200.0	V	178.0	4.1	54.00	7.56

BLE (2Mbps)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	50.98	---	150.0	V	27.0	3.7	74.00	23.02
2390.00	---	46.65	150.0	V	27.0	3.7	54.00	7.35
High Channel: 2480MHz								
2483.50	53.02	---	200.0	V	92.0	4.1	74.00	20.98
2483.50	---	46.68	200.0	V	92.0	4.1	54.00	7.32


Conducted Spurious Emissions at Antenna Port:**BLE (1Mbps)****Low Channel****Middle Channel**

High Channel




BLE (2Mbps)


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 * \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa


The testing was performed by Tyrone Wang on 2021-01-26.

Test Result: Compliant.


EUT operation mode: Transmitting

BLE (1Mbps)


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	0.751	≥ 0.5
Middle	2440	0.751	≥ 0.5
High	2480	0.751	≥ 0.5

Low Channel

Middle Channel




High Channel




BLE (2Mbps)


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	1.202	≥ 0.5
Middle	2440	1.132	≥ 0.5
High	2480	1.232	≥ 0.5

Low Channel

Middle Channel



High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW $\geq$ DTS bandwidth.
2. Set VBW $\geq 3 * \text{RBW}$.
3. Set span $\geq 3 * \text{RBW}$
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data**Environmental Conditions**

Temperature:	25.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa


The testing was performed by Tyrone Wang on 2021-01-26.

Test Result: Compliant.


EUT operation mode: Transmitting

BLE (1Mbps)


Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	-11.53	30	Pass
Middle	2440	-10.59	30	Pass
High	2480	-12.09	30	Pass

Low Channel

Middle Channel




High Channel




BLE (2Mbps)


Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	-11.63	30	Pass
Middle	2440	-10.94	30	Pass
High	2480	-10.06	30	Pass

Low Channel

Middle Channel



High Channel



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa


The testing was performed by Tyrone Wang on 2021-01-26.

Test Result: Compliant.


EUT operation mode: Transmitting

BLE (1Mbps)

Left Side




Right Side




BLE (2Mbps)

Left Side



Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa


The testing was performed by Tyrone Wang on 2021-01-26.

Test Result: Compliant.


EUT operation mode: Transmitting

BLE (1Mbps)


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-25.43	≤8
Middle	2440	-23.60	≤8
High	2480	-22.38	≤8

Low Channel

Middle Channel




High Channel




BLE (2Mbps)


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-27.73	≤ 8
Middle	2440	-27.06	≤ 8
High	2480	-26.12	≤ 8

Low Channel

Middle Channel



High Channel



Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

***** **END OF REPORT** *****