



Antenna Datasheet

APPROVAL SHEET

900Mhz Antenna
dipole antenna

Supplier : Lynxtech

382-8 Go jan Dong Nam Dong Gu, Incheon, Korea

Lynx_____

Table of Contents

1. APPLICATION SCOPE
2. OPERATING CONDITIONS
3. ELECTRONIC SPECIFICATIONS
4. APPEARANCE AND MECHANICAL SPECIFICATIONS
5. TEST METHOD AND DATA FOR ELECTRONIC SPECIFICATIONS
6. RELIABILITY ASSURANCE
7. Drawing

Specification for approval

1. APPLICATION SCOPE

THIS PRODUCT CAN BE USED IN RADIO TELECOMMUNICATION SYSTEM WITH 900MHz Band

2. OPERATING CONDITIONS

NO.	ITEMS	SPECIFICATIONS
2-1	OPERATING ENVIRONMENT	TEMPERATURE : -30~70℃ HUMIDITY : ~85% RH
2-2	STORAGE ENVIRONMENT	TEMPERATURE : -20~60℃ HUMIDITY : ~65% RH

3. ELECTRONIC SPECIFICATIONS

NO	ITEMS	SPECIFICATIONS
3-1	IMPEDANCE	50Ω
3-2	FREQUENCY RANGE	902MHz ~927MHz
3-3	PEAK GAIN	≤ 3.83dBi
3-4	VSWR	≤ 2:1

4. APPEARANCE AND MECHANICAL SPECIFICATIONS

NO.	ITEMS	SPECIFICATIONS
4-1	CONNECTOR	DIRECT SOLDERING TO BOARD
4-2	COLOR	NON
4-3	APPEARANCE AND DIMENSION	REFER TO DRAWING
4-4	WEIGHT	0.5g

Specification for approval

5. TEST METHOD AND DATA FOR ELECTRONIC SPECIFICATIONS


NO.	ITEMS	SPECIFICATIONS	CONDITION REMARK
5-1	IMPEDANCE	50Ω	902MHz~927MHz
5-2	SWR	≤ 2:1	

5-3 TEST METHOD



1. Network Analyzer
: Agilent E5071B
2. Signal Interface
: Coaxial Cable
3. SMA connector
4. Test fixture


5-4 TEST DATA (VSWR)



Specification for approval


5-5	Gain	$\leq 2\text{dBi}$	880Mhz ~960MHz
-----	------	--------------------	----------------

5-6 TEST METHOD




1. Network Analyzer
: AGILENT E5071C
2. Test Antenna
3. Signal Interface
: Coaxial Cable
4. Received Antenna
: Double Ridged Horn Antenna
5. Shield Room
: Dimension : 7.32 x 4.00 x 4.00 m,
A. Quite Zone : 30 cm,
B. Isolation : >100 dB

5-6 TEST DATA (Radiation Pattern)



Specification for approval

6. RELIABILITY ASSURANCE

NO	ITEMS	SPECIFICATIONS	
7-1	LOW TEMP EXPOSURE TEST	TEMPERATURE : -30°C TIME : 96 HOURS	AFTER 2HOURS EXPOSURE IN ORDINARY FROM TEST, ANTENNAS SHALL BE APPROVED AS SPECIFIED IN ITEM 5
7-2	HIGH TEMP EXPOSURE TEST	TEMPERATURE : 70°C TIME : 96 HOURS	
7-3	HUMIDITY EXPOSURE TEST	TEMPERATURE : $60^{\circ}\text{C} \pm 2^{\circ}\text{C}$ HUMIDITY : 85%RH TIME : 88 HOURS	
7-4	THERMAL SHOCK	Temperature($^{\circ}\text{C}$)  0 45 Min. Test cycle : 20cycles	
7-5	DROP TEST	HEIGHT : 1.5m DIRECTION : $\pm X$, $\pm Y$, $\pm Z$ DROP TIMES : THREE DROPS PER PLANE	

Specification for approval

7.Drawing

