



# Radio Exposure Evaluation Report

**FCC ID** : YL6-1438852R  
**Equipment** : Wireless Module  
**Brand Name** : ALARM.COM  
**Model Name** : ADC-WM8852-A  
**Applicant** : Alarm.com Incorporated  
8281 Greensboro Drive, Suite 100, Tysons,  
VA 22102 United States  
**Manufacturer** : Alarm.com Incorporated  
8281 Greensboro Drive, Suite 100, Tysons,  
VA 22102 United States  
**Standard** : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Feb. 06, 2025, and testing was started from Feb. 14, 2025 and completed on Feb. 26, 2025. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

**SPORTON INTERNATIONAL INC. Hsinhua Laboratory**  
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



## Table of Contents

<b>HISTORY OF THIS TEST REPORT .....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Information.....	5
1.2 Applicable Standards .....	8
1.3 Testing Location .....	8
<b>2 MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>9</b>
2.1 Limit of Maximum Permissible Exposure .....	9
2.2 RF Exposure Exempt Measurement.....	10
2.3 Multiple RF Sources Exposure.....	11
2.4 MPE Calculation Method.....	12
2.5 Calculated Result and Limit.....	13

### Photographs of EUT V01



## History of this test report



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

None

Reviewed by: Ben Tseng

Report Producer: Amber Chiu



# 1 General Description

## 1.1 Information

### 1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

### 1.1.2 Antenna Information

Source	Ant.	Brand	Model Name	Antenna Type	Connector	Support
1	1	PSA	WCBN3511L_PCA	Dipole	I-Pex	2.4G+5G
	2	PSA	WCBN3511L_PCA	Dipole	I-Pex	2.4G+5G+BT
2	3	INPAQ	RFFPA301205IMLB401	Dipole	I-Pex	2.4G+5G
	4	INPAQ	RFFPA301213IMLB401	Dipole	I-Pex	2.4G+5G
3	5	LYNwave	ALX18F-222A A4-00	Dipole	I-Pex	2.4G+5G
	6	LYNwave	ALX18F-222A A5-00	Dipole	I-Pex	2.4G+5G
4	7	LYNwave	ALX18F-222AA2-01	Dipole	I-Pex	2.4G+5G
	8	LYNwave	ALX18F-222AA3-01	Dipole	I-Pex	2.4G+5G
5	9	AWAN	ASF6P-100012	PIFA	I-Pex	2.4G+5G
	10	AWAN	ASF6P-100011	PIFA	I-Pex	2.4G+5G+BT
6	11	INPAQ	RFDPA1615SBLB818	PIFA	I-Pex	2.4G+5G
	12	INPAQ	RFDPA1615SBLB818	PIFA	I-Pex	2.4G+5G+BT



Source	Ant.	Port	Gain (dBi)		
			2.4G	5G	BT
1	1	1	5.3	5.71	-
	2	2	5.3	5.71	5.3
2	3	1	3.94	5.3	-
	4	2	3.78	4.28	-
3	5	1	4.9	5.4	-
	6	2	5.2	4.7	-
4	7	1	5.1	5.6	-
	8	2	3.5	5.5	-
5	9	1	3.3	5.7	-
	10	2	2.9	3.8	2.9
6	11	1	5.59	6.04	-
	12	2	5.59	6.04	5.59

Note 1: The EUT has twelve antennas.

Note 2: The EUT can be matched with the above antennas and Source 6 antennas were used to perform the worst configuration and result of that was recorded as the final test result.

#### For 2.4GHz function:

For IEEE 802.11 b/g/n/VHT/ax mode (2TX/2RX)

Ant. 1 (port 1) and Ant. 2 (port 2) could transmit/receive simultaneously.

Ant. 3 (port 1) and Ant. 4 (port 2) could transmit/receive simultaneously.

Ant. 5 (port 1) and Ant. 6 (port 2) could transmit/receive simultaneously.

Ant. 7 (port 1) and Ant. 8 (port 2) could transmit/receive simultaneously.

Ant. 9 (port 1) and Ant. 10 (port 2) could transmit/receive simultaneously.

Ant. 11 (port 1) and Ant. 12 (port 2) could transmit/receive simultaneously.

#### For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Ant. 2 (port 2) can be used as transmitting/receiving.

Ant. 10 (port 2) can be used as transmitting/receiving.

Ant. 12 (port 2) can be used as transmitting/receiving.

#### For 5GHz function:

For IEEE 802.11 a/n/ac/ax mode (2TX/2RX)

Ant. 1 (port 1) and Ant. 2 (port 2) could transmit/receive simultaneously.

Ant. 3 (port 1) and Ant. 4 (port 2) could transmit/receive simultaneously.

Ant. 5 (port 1) and Ant. 6 (port 2) could transmit/receive simultaneously.

Ant. 7 (port 1) and Ant. 8 (port 2) could transmit/receive simultaneously.

Ant. 9 (port 1) and Ant. 10 (port 2) could transmit/receive simultaneously.

Ant. 11 (port 1) and Ant. 12 (port 2) could transmit/receive simultaneously.



### **1.1.3 Table for Permissive Change**

This product is an extension of original one reported under Sporton project number: FA1D0419

Below is the table for the change of the product with respect to the original one.

<b>Modifications</b>	<b>Performance Checking</b>
1. Add 4 antennas (Ant 9~12)	RF Exposure was evaluated
2. Modified antennas brand and model name (Ant 7~8)	After evaluation, no RF test validations are required



## 1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

## 1.3 Testing Location

<b>Test Lab. : Sporton International Inc. Hsinhua Laboratory</b>			
<input checked="" type="checkbox"/> Hsinhua (TAF: 3785)	<b>ADD:</b> No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.) <b>TEL:</b> 886-3-327-3456	<b>FAX:</b> 886-3-327-0973	
Test site Designation No. TW3785 with FCC.			
<input type="checkbox"/> Wen 33rd.St. (TAF: 3785)	<b>ADD:</b> No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) <b>TEL:</b> 886-3-318-0787	<b>FAX:</b> 886-3-318-0287	
Test site Designation No. TW0008 with FCC.			



## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

Multiple Transmitters Condition
Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.
Co-transmitting mode:
1. Bluetooth+WLAN 2.4GHz
2. Bluetooth+WLAN 5GHz



## 2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10}\left(\frac{60}{ERP_{20cm} \sqrt{f}}\right)$ and f is in GHz $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040 f(mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060 (mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920 R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450 R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128 R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ f is in MHz; R is in m; $R > \lambda / 2\pi$



## 2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	<p>The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)</p>
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ <p>a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P, including existing exempt transmitters and those being added.</p> <p>b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.</p> <p>c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.</p> <p><math>P_i</math> = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).</p> <p><math>P_{th,i}</math> = the exemption threshold power ( <math>P_{th}</math> ) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.</p> <p><math>ERP_j</math> = the ERP of fixed, mobile, or portable RF source j.</p> <p><math>ERP_{th,j}</math> = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least <math>\lambda/2\pi</math> according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.</p> <p><math>Evaluated_k</math> = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.</p> <p><math>ExposureLimit_k</math> = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.</p>



## 2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.  
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



## 2.5 Calculated Result and Limit

### Exposure Environment: General Population / Uncontrolled Exposure

#### WLAN 2.4GHz

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	5.59	22.71	26.15	0.50	462.381	20	B	3060.0	0.1512
2.4G;D1D	5.59	21.09	24.53	0.50	318.420	20	B	3060.0	0.1041

#### WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	6.04	21.05	24.94	0.50	349.945	20	B	3060.0	0.1144
5.3G;D1D	6.04	21.08	24.97	0.50	352.371	20	B	3060.0	0.1152
5.6G;D1D	6.04	21.04	24.93	0.50	349.140	20	B	3060.0	0.1141
5.8G;D1D	6.04	21.92	25.81	0.50	427.563	20	B	3060.0	0.1398

#### Bluetooth

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	5.59	11.28	14.72	0.50	33.266	20	B	3060.0	0.0109
2.4G;BT-BR	5.59	11.09	14.53	0.50	31.842	20	B	3060.0	0.0104
2.4G;BT-EDR	5.59	10.55	13.99	0.50	28.119	20	B	3060.0	0.0092

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)



## Simultaneous Transmission Analysis Mode: WLAN 2.4GHz+WLAN 5GHz

## Bluetooth+WLAN 2.4GHz

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	5.59	22.71	26.15	0.50	462.381	20	B	3060.0	0.1512
2.4G;BT-LE	5.59	11.28	14.72	0.50	33.266	20	B	3060.0	0.0109
								Sum Ratio	0.1621
								Ratio Limit	1.00000

## Bluetooth+WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.8G;D1D	6.04	21.92	25.81	0.50	427.563	20	B	3060.0	0.1398
2.4G;BT-LE	5.59	11.28	14.72	0.50	33.266	20	B	3060.0	0.0109
								Sum Ratio	0.1507
								Ratio Limit	1.00000

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

Option	Sum TL Ratio_B	Option	Sum TL Ratio_C	Option	Sum TL Ratio_E
B	$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$	C	$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$	E	$\sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k}$

Note: The above antenna gain was declared by manufacturer.

THE END