

Innovative **Technology** for a **Connected** World

2.4 GHz Panel Antenna



The Laird Technologies S2406P antenna is designed to provide 2.4 GHz systems with an antenna offering 6+ dBi of directional gain in a package that can be easily hidden or disguised. The antenna can be wall mounted to provide directional coverage or ceiling mounted if there is a desire to direct or focus signal into a coverage area from a ceiling location.

An articulating mount is available for the antenna. This mount allows the antenna azimuth and elevation orientation. The most compelling feature of the S2406P is its compact size, convenient for mounting in very confined spaces and disguise if necessary.


FEATURES

MARKETS

- Small, easy to disguise package aesthetically neutral
- Wall and ceiling mount
- UV stabile indoor/outdoor housing

 WiMAX 	
---------------------------	--

PARAMETER	SPECIFICATION
Frequency	2400-2500 MHz
VSWR	1.8:1
Polarization	Linear
Gain	6 dBi
3 dB Beamwidth, E-Plane	65°
3 dB Beamwidth, H-Plane	70°
Mount Style	Wall/Surface
RF Connector	Type N (f)
Power	10 Watts
Weight	0.5 lbs (0.23 kg)
Dimensions	5.2 x 3.8 x 0.5 in (13.2 x 9.7 x 1.4 cm)



H-Plane

global solutions: local support ™

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-S2406P 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequid admanages of any kind. All Laird Technologies and Technologies Technologies