

#### **TEST REPORT**

**Report Number: 15020015HKG-004** 

Application
For
Original Grant of 47 CFR Part 15 Certification
New Family of RSS-213 Issue 3 Equipment Certification

Unlicensed Personal Communication Service Devices/ 2 GHz License-exempt Personal Communications Service Devices

(Base Unit)

FCC ID: YLM2161A

IC: 9101A-2161A

Prepared and Checked by: Approved by:

**Signed on File** Leung Chiu Kuen, Stanley Engineer

Nip Ming Fung, Melvin Assistant Manager April 1, 2015

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

<sup>-</sup> Intertek's standard Terms and Conditions can be obtained at our website: http://www.intertek.com/terms/.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## **GENERAL INFORMATION**

Applicant Name:	Supreme Power Ltd.
Applicant Address:	Unit 5-6, 7/F., Greenfield Tower,
	Concordia Plaza, 1 Science Museum Road,
	Tsim Sha Tsui, Kowloon, Hong Kong.
FCC Specification Standard:	FCC Part 15, October 1, 2013 Edition
FCC ID:	YLM2161A
FCC Model(s):	2161, 2161-X, 2161-XYYZV
IC Specification Standard:	RSS-213 Issue 3, March 2015
-	RSS-Gen Issue 3, December 2010
IC:	9101A-2161A
IC Model(s):	2161-1BKGA, 2161-2BKGA, 2161-3BKGA,
	2161-4BKGA
Type of EUT:	Unlicensed Personal Communications
	Service Devices
Description of EUT:	1.9GHz DECT Cordless Phone with Caller
	ID - Base Unit
Serial Number:	N/A
Sample Receipt Date:	February 02, 2015
Date of Test:	February 25, 2015 - March 5, 2015
Report Date:	April 1, 2015
Environmental Conditions:	Temperature: +10 to 40°C
	Humidity: 10 to 90%

Test Report No.: 15020015HKG-004 Page 1 of 61 FCC ID: YLM2161A

IC: 9101A-2161A

## **Table of Contents**

1.0 Test Results Summary & Statement of Compliance	
1.1 Summary of Test Results	5
1.2 Statement of Compliance	7
2.0 General Description	
2.1 Product Description	
2.2 Technical Description	9
2.3 Test Methodology	10
2.4 Test Facility	10
3.0 System Test Configuration	12
3.1 Justification	12
3.2 Conducted Emission Test Configuration	13
3.3 Conducted Monitoring and Operational Test Configuration	13
3.4 EUT Exercising Software	
3.5 Details of EUT and Description of Accessories	14
3.6 Measurement Uncertainty	
4.0 Measurement Results	16
4.1 Antenna Requirement	
4.2 Digital Modulation Techniques	
4.3 Emission Bandwidth	
4.4 Directional Gain of the Antenna	20
4.5 Peak Transmit Power	
4.6 Power Spectral Density	
4.7 Automatic Discontinuation of Transmission	
4.8 Unwanted Emission Inside the Sub-Band	
4.9 Emissions Outside the Sub-Band	
4.9.1 Radiated Emissions Configuration Photographs	
4.9.2 Radiated Emissions Data	33
4.9.3 Field Strength Calculation	
4.9.4 Average Factor Calculation and Transmitter ON Time Measurements	38
4.10 AC Power Line Conducted Emissions	
4.10.1 AC Power Line Conducted Emissions Configuration Photographs	
4.10.2 AC Power Line Conducted Emissions Data	
4.11 Frame Repetition Stability	43
4.12 Frame Period and Jitter	
4.13 Carrier Frequency Stability	
4.14 Monitoring Threshold	
4.14.1 Monitoring Threshold Limit	
4.14.2 Least Interfered Channel	48
4.14.2.1 Least Interfered Channel (LIC) Selection	49
4.14.2.2 Least Interfered Channel (LIC) Confirmation	50
4.14.2.3 Maximum Spectrum Occupance	50

Test Report No.: 15020015HKG-004 FCC ID: YLM2161A

## **Table of Contents**

4.15 Monitoring Time	51
4.16 Maximum Transmit Period	
4.17 System Acknowledgement	53
4.18 Random Waiting	
4.19 Monitoring Bandwidth	
4.20 Maximum Reaction Time	56
4.21 Monitoring Antenna	
4.22 Duplex Connections	
4.23 Alternative Monitoring Interval for Co-located Device	
4.24 Fair Access	
5.0 Equipment List	61

Test Report No.: 15020015HKG-004 FCC ID: YLM2161A

IC: 9101A-2161A

## EXHIBIT 1 TEST RESULTS SUMMARY & STATEMENT OF COMPLIANCE

Test Report No.: 15020015HKG-004 Page 4 of 61

## 1.0 Test Results Summary & Statement of Compliance

## 1.1 Summary of Test Results

General Technical Requirements						
Test Items	RSS-213 / RSS-Gen <sup>#</sup> Clause	FCC Part 15 Section	Test Procedure ANSI C63.17 / ANSI C63.4	Results	Details see section	
Antenna Requirement	7.1.2#	15.317		Pass	4.1	
Digital Modulation Techniques	5.1	15.319(b)	6.1.4	Pass	4.2	
Occupied/Emission Bandwidth	5.5	15.323(a)	6.1.3	Pass	4.3	
Directional Gain of the Antenna	4	15.319(e)	4.3.1	Pass	4.4	
Peak Transmit Power	5.6	15.319(c)	6.1.2	Pass	4.5	
Power Spectral Density	5.7	15.319(d)	6.1.5	Pass	4.6	
Automatic Discontinuation of Transmission	5.2	15.319(f)		Pass	4.7	
AC Power Line Conducted Emissions from EUT	5.4	15.315	7 *	Pass	4.10	
Security Code Information	3.3			Pass	2.2	

Test Report No.: 15020015HKG-004 Page 5 of 61 FCC ID: YLM2161A

IC: 9101A-2161A

## 1.1 Summary of Test Results (continued)

Specific Requirements for UPCS Device					
Test Items	RSS-213 Clause	FCC Part 15 Section	Test Procedure ANSI C63.17	Results	Details see section
Unwanted Emission Inside the Sub-Band	5.8.2	15.323(d)	6.1.6.1	Pass	4.8
Emissions Outside the Sub- Band	5.8.1	15.323(d)	6.1.6.2	Pass	4.9
Frame Repetition Stability	5.2(13)	15.323(e)	6.2.2	Pass	4.11
Frame Period and Jitter	5.2(13)	15.323(e)	6.2.3	Pass	4.12
Carrier Frequency Stability	5.3	15.323(f)	6.2.1	Pass	4.13
Monitoring Threshold Limit	5.2(2&9)	15.323(c2&c9)	7.3.1	NA	4.14.1
Least Interfered Channel (LIC) Selection	5.2(5)	15.323(c)(5)	7.3.2	Pass	4.14.2.1
Least Interfered Channel (LIC) Confirmation	5.2(5)	15.323(c)(5)	7.3.2	Pass	4.14.2.2
Maximum Spectrum Occupancy	5.2(5)	15.323(c)(5)		Pass	4.14.2.3
Monitoring Time	5.2(1)	15.323(c)(1)	7.3.3	Pass	4.15
Maximum Transmit Period	5.2(3)	15.323(c)(3)		Pass	4.16
System Acknowledgement	5.2(4)	15.323(c4)	8.1 or 8.2	Pass	4.17
Random Waiting	5.2(6)	15.323(c)(6)	8.1.2 or 8.1.3	Pass	4.18
Monitoring Bandwidth	5.2(7)	15.323(c)(7)	7.4	Pass	4.19
Maximum Reaction Time	5.2(7)	15.323(c)(7)	7.5	Pass	4.20
Monitoring Antenna	5.2(8)	15.323(c)(8)	4	Pass	4.21
Duplex Connections	5.2(10)	15.323(c)(10)	8.3	NA	4.22
Alternative Monitoring Interval for Co-located Device	5.2(11)	15.323(c)(11)	8.4	NA	4.23
Fair Access	5.2(12)	15.323(c)(12)		Pass	4.24

Test Report No.: 15020015HKG-004 Page 6 of 61 FCC ID: YLM2161A

IC: 9101A-2161A

## 1.2 Statement of Compliance

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2013 Edition RSS-213 Issue 3, March 2015 RSS-Gen Issue 3, December 2010

Test Report No.: 15020015HKG-004 Page 7 of 61

# EXHIBIT 2 GENERAL DESCRIPTION

Test Report No.: 15020015HKG-004 Page 8 of 61 FCC ID: YLM2161A

#### 2.0 **General Description**

#### 2.1 Product Description

The 2161 is a 1.9GHz DECT Cordless Phone with Caller ID - Base Unit. It operates at frequency range of 1921.536MHz to 1928.448MHz with 5 channels (1921.536MHz, 1923.264MHz, 1924.992MHz, 1926.720MHz and 1928.448MHz). The Base Unit is powered by an adaptor 100-240VAC to 6VDC 500mA.

The antenna used in base unit is integral, and the test sample is a prototype.

For FCC, base unit of Model(s): 2161-X, 2161-XYYZV are the same as the base unit of Model: 2161 in electrical designs, including software & firmware, PCB layout and construction design/physical design/enclosure. The only differences between these models are color, cosmetic details, model number, packing, number of handset(s) and extra charger(s) to be sold for marketing purpose. Suffix (X) indicates blank or any alphanumeric character is representing number of handset and extra charger. Suffix (Y) indicates blank or any alphanumeric character is representing different color of enclosure. Suffix (Z) indicates blank or any alphanumeric character is representing different version.

For IC, base unit of Model(s): 2161-1BKGA, 2161-2BKGA, 2161-3BKGA and 2161-4BKGA are the same as the base unit of Model: 2161 in electrical designs, including software & firmware, PCB layout and construction design/physical design/enclosure. The only differences between these models are color, cosmetic details, model number, packing, number of handset(s) and extra charger(s) to be sold for marketing purpose.

Connection between the device and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

#### 2.2 Technical Description

The circuit description and digital modulation techniques description are saved with filename: descri.pdf.

Test Report No.: 15020015HKG-004 Page 9 of 61

#### 2.3 Test Methodology

The radiated emission measurements for unintentional radiator (if any) and AC power line-conducted emission measurements were performed according to the test procedures specified in ANSI C63.4 (2009). The radiated emission measurements for intentional radiator contained in UPCS device, conducted emission measurements, Listen Before Transmit (LBT) tests, Time Frame and Frequency Stability tests were performed according to the test procedures specified in ANSI C63.17 (2013). All radiated measurements were performed in radiated emission test site. Preliminary scans were performed in the radiated emission test site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in 47 CFR Part 2 / RSS-Gen Issue 3 (2010).

#### 2.4 Test Facility

The radiated emission test site, AC power line conducted measurement facility and antenna port conducted measurement facility used to collect the radiated data, AC Power Line conducted data, and conductive data are at Intertek Testing Services Hong Kong Ltd., which is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been fully placed on file with FCC and Industry Canada.

Test Report No.: 15020015HKG-004 Page 10 of 61

# EXHIBIT 3 SYSTEM TEST CONFIGURATION

Test Report No.: 15020015HKG-004 Page 11 of 61 FCC ID: YLM2161A

IC: 9101A-2161A

#### 3.0 **System Test Configuration**

#### 3.1 Justification

For emissions testing, the equipment under test (EUT) was set up to transmit continuously in burst mode with pseudo-random data to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst-case emissions.

The Base Unit was powered by a 100-240VAC to 6VDC 500mA adaptor.

For the measurements, the EUT was attached to a plastic stand if necessary and placed on the wooden turntable. If the EUT is attached to accessories, they were connected and operational (as typical as possible).

The signal was maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization were varied during the search for maximum signal level. The antenna height was varied from 1 to 4 meters. Detector function was in peak mode. Radiated emissions are taken at three meters unless the signal level was too low for measurement at that distance. If necessary, a pre-amplifier was used and/or the test was conducted at a closer distance.

For UPCS transmitter radiated measurement, the spectrum analyzer resolution bandwidth was approximately 1% of EUT emission bandwidth, unless otherwise specified.

Radiated emission measurements for UPCS transmitter were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

For AC line conducted emission test, the EUT along with its peripherals were placed on a 1.0m(W)x1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 500hm coupling impedance for measuring instrument. The LISN housing, measuring instrument case, reference ground plane, and vertical ground plane were bounded together. The excess power cable between the EUT and the LISN was bundled.


All connecting cables of EUT and peripherals were manipulated to find the maximum emission.

All relevant operation modes have been tested, and the worst case data is included in this report.

Test Report No.: 15020015HKG-004 Page 12 of 61

#### 3.2 Conducted Emission Test Configuration

The setup and equipment setting were made in accordance with ANSI C63.17. The antenna of EUT transmitter was replaced by a coaxial cable. The impendence matching of connection, cable loss and external RF attenuator are taken into account. The EUT was arranged to communicate via a fixed carrier frequency between its transmitter and a companion device. The transmission was configured in burst mode with pseudo-random data as typical as normal operation.



**Figure 3.2.1** 

#### 3.3 Conducted Monitoring and Operation Test Configuration




Figure 3.3.1

#### 3.4 EUT Exercising Software

The EUT exercise program (if any) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

Test Report No.: 15020015HKG-004 Page 13 of 61

#### 3.5 Details of EUT and Description of Accessories

#### **Details of EUT:**

An AC adaptor (provided with the unit) was used to power the device. Their descriptions are listed below.

(1) An AC adaptor (100-240VAC to 6.0VDC 500mA, Model: S003GU0600050), Brand: Ten Pao (Supplied by Client)

#### **Description of Accessories:**

- (1) Telephone Line Simulator, Model: TLS-5C-01, S/N: 059355 (Supplied by Intertek)
- (2) 1 x 3m Telephone Line (Supplied by Intertek)
- (3) 1m Telephone Line with Termination (Supplied by Intertek)
- (4) Handset, Model: 2161, Brand: RCA, FCC ID: YLM2161A (Supplied by client)

#### 3.6 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

Test Report No.: 15020015HKG-004 Page 14 of 61

# **EXHIBIT 4 TEST RESULTS**

Test Report No.: 15020015HKG-004 Page 15 of 61 FCC ID: YLM2161A

IC: 9101A-2161A

#### 4.0 Measurement Results

4.1 Antenna Requirement, FCC Rule 15.317 / RSS-Gen Clause 7.1.2:

EUT must meet the antenna requirement of FCC Rule 15.203 / RSS-Gen Clause 7.1.2.

- [x] EUT uses permanently attached antenna(s) which is considered sufficient to comply with the provisions of this rule. Please refer to internal photos.pdf for more details.
- [ ] EUT uses unique antenna jack(s) or electrical connector(s) which is considered sufficient to comply with the provisions of this rule. Please refer to internal photos.pdf for more details.
- 4.2 Digital Modulation Techniques, FCC Rule 15.319(b) / RSS-213 Clause 5.1:

All transmissions must use only digital modulation techniques.

The requirements are made in accordance with ANSI C63.17 sub-clause 6.1.4.

#### Attestation:

Please refer to the technical description(descri.pdf) or relevant DECT standards for more details.

Test Report No.: 15020015HKG-004 Page 16 of 61

4.3 Emission Bandwidth, FCC Rule 15.323(a) / Occupied Bandwidth, RSS-213 Clause 5.5:

Operation shall be contained within the 1920 - 1930 MHz band. The emission bandwidth (B) shall be less than 2.5 MHz and greater than 50 kHz.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.3 and RSS-Gen clause 4.6.1. Test setup is shown in section 3.2 Figure 3.2.1.

#### Test Results:

#### I. Base unit - Traffic Carrier


Channel	Channel Frequency (MHz)	Measuring Signal Level	Measured Emission Bandwidth (MHz)	Results
Lowest	1921.536	26 dB down	1.49	Pass
Middle	1924.992	99% Bandwidth	1.21	Pass
Highest	1928.448	26 dB down	1.48	Pass

The plots of emission bandwidth and occupied bandwidth are saved as below.


Test Report No.: 15020015HKG-004 Page 17 of 61

#### Plots of emission bandwidth

#### Base unit, Lowest channel, Traffic carrier




#### Base unit, Highest channel, Traffic carrier



Test Report No.: 15020015HKG-004 Page 18 of 61

## Plots of occupied bandwidth





Test Report No.: 15020015HKG-004 Page 19 of 61

4.4 Directional Gain of the Antenna, FCC Rule FCC 15.319(e) / RSS-213 Clause 4:

The peak transmit power shall be reduced by the amount in dB that the maximum directional gain of the antenna exceeds 3 dBi.

The requirements are made in accordance with ANSI C63.17 sub-clause 4.3.1 / RSS-213 Clause 4.1(e).

[ × ]	Manufacturer declares that the directional gain of the antenna is less than or
	equal to 3dBi. No peak transmit power reduction is required.

[ ] Manufacturer declares that the directional gain of the antenna is greater than 3dBi. The peak transmit power shall be reduced by \_\_\_\_ dB.

Test Report No.: 15020015HKG-004 Page 20 of 61

#### 4.5 Peak Transmit Power, FCC Rule 15.319(c) / RSS-213 Clause 5.6:

The peak transmit power ( $P_{\text{EUT}}$ ) shall not exceed 100 $\mu$ W multiplied by the square root of the emission bandwidth / occupied bandwidth (B) in Hz or 5 log<sub>10</sub> B – 10 dBm. The peak transmit power shall be reduced by the amount in dB that the maximum directional gain of the antenna exceeds 3 dBi.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.2. Test setup is shown in section 3.2 Figure 3.2.1. The cable loss and/or external attenuation are included in OFFSET function of spectrum analyzer.

Calculation of Peak Transmit Power Limit ( $P_{max}$ ):

[ 
$$\times$$
 ]  $P_{\text{max}} = 5 \log_{10} B - 10 \text{ dBm}$  when  $G_A \le 3 \text{dBi}$  [ ]  $P_{\text{max}} = 5 \log_{10} B - 10 \text{ dBm} - (G_A - 3 \text{dBi})$  when  $G_A > 3 \text{dBi}$ 

Where  $G_A = EUT$  Antenna Gain: 0 dBi for Base Unit

B = Measured Emission Bandwidth / Occupied Bandwidth

#### Test Results:

#### I. Base unit - Traffic Carrier


Channel	Channel Frequency (MHz)	Measured Peak Transmit Power (dBm)	Limit (dBm)	Results
Lowest	1921.536	19.17	20.87	Pass
Middle	1924.992	19.07	20.41	Pass
Highest	1928.448	18.98	20.85	Pass

The plots of peak transmit power are saved as below.


Test Report No.: 15020015HKG-004 Page 21 of 61

## Plots of peak transmit power







## Base unit, Middle channel, Traffic carrier



Test Report No.: 15020015HKG-004

## Plots of peak transmit power





Test Report No.: 15020015HKG-004

Page 23 of 61

#### 4.6 Power Spectral Density, FCC Rule 15.319(d) / RSS-213 Clause 5.7:

Power spectral density shall not exceed 3 mW (4.8dBm) in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.5. Test setup is shown in section 3.2 Figure 3.2.1.

#### Test Results:

#### I. Base unit - Traffic Carrier


Channel	Channel Frequency (MHz)	Measured Power Spectral Density (dBm/3kHz)	Limit (dBm/3 kHz)	Results
Lowest	1921.536	-4.24	4.8	Pass
Middle	1924.992	-4.28	4.8	Pass
Highest	1928.448	-4.66	4.8	Pass

The plots of the power spectral density are as below.


Test Report No.: 15020015HKG-004 Page 24 of 61

## Plots of the power spectral density (FCC)

## Base unit, Lowest channel, Traffic carrier




## Base unit, Highest channel, Traffic carrier




Page 25 of 61

Test Report No.: 15020015HKG-004

## Plots of the power spectral density (IC)





Test Report No.: 15020015HKG-004

Page 26 of 61

4.7 Automatic Discontinuation of Transmission, FCC Rule 15.319(f) / RSS-213 Clause 5.2:

The EUT shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

The manufacturer declares that the EUT can automatically discontinue transmission in case of either absent information to transmit or operational failure. Please refer to the declaration letter for details, which is saved with filename: declaration.pdf.

Test Report No.: 15020015HKG-004 Page 27 of 61

4.8 Unwanted Emission Inside the Sub-Band, FCC Rule 15.323(d) / RSS-213 Clause 5.8.2:

Emissions inside the sub-band must comply with the following emission mask:

- 1. In the bands between 1*B* and 2*B* measured from the center of the emission bandwidth, emission shall be at least 30 dB below the permitted peak transmit power.
- 2. In the bands between 2B and 3B measured from the center of the emission bandwidth, emission shall be at least 50 dB below the permitted peak transmit power.
- 3. In the bands between 3*B* and the band edge, emission shall be at least 60 dB below the permitted peak transmit power.

Where B = emission bandwidth or occupied bandwidth in Hz

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.6.1. Test setup is shown in section 3.2 Figure 3.2.1.

#### Test Results:

I. Base unit - Traffic Carrier


Channel	Channel Frequency (MHz)	Results
Lowest	1921.536	Pass
Middle	1924.992	Pass
Highest	1928.448	Pass

The plots of the unwanted emission inside the sub-band are as below.


Test Report No.: 15020015HKG-004 Page 28 of 61

## Plots of the unwanted emission inside the sub-band (FCC)

## Base unit, Lowest channel, Traffic carrier




## Base unit, Highest channel, Traffic carrier




Test Report No.: 15020015HKG-004 Page 29 of 61

## Plots of the unwanted emission inside the sub-band (IC)

## Base unit, Lowest channel, Traffic carrier




#### Base unit, Middle channel, Traffic carrier



Test Report No.: 15020015HKG-004 Page 30 of 61

## Plots of the unwanted emission inside the sub-band (IC)





Test Report No.: 15020015HKG-004

Page 31 of 61

4.9 Emissions Outside the Sub-Band, FCC Rule 15.323(d) / RSS-213 Clause 5.8.1:

Emissions outside the sub-band shall be attenuated below a reference power of 112 mW (20.5 dBm) as follows:

- 1. 30 dB between the band edge and 1.25 MHz above or below the band;
- 2. 50 dB between 1.25 and 2.5 MHz above or below the band; and
- 3. 60 dB at 2.5 MHz or greater above or below the band, or shall meet the requirement of FCC Rule 15.319(g) which shall not exceed the limits of FCC Rule 15.209 / RSS-210 Clause 2.5.

Example: Calculation of Limit for emissions between the band edge and 1.25 MHz (1920.000 – 1918.750 MHz)

The emissions shall not exceed the Limit: 20.5 dBm - 30 dB = -9.5 dBm

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.6.2. Radiated emissions test method is used. Emissions that are directly caused by digital circuits in the transmit path and transmitter portion are measured.

#### Test Results:

Channel	Carrier Frequency (MHz)	Measured Band (MHz)	Limit (dBm)	Results
		1920.000 - 1918.750	-9.5	Pass
1	4004 500	1918.750 - 1917.500	-29.5	Pass
Lowest	1921.536	0.009 - 1917.500 & 1932.500 - 19300.000	-39.5 / RSS- 210 Clause 2.5	Pass
Highest		1930.000 - 1931.250	-9.5	Pass
	1928.448	1931.250 - 1932.500	-29.5	Pass
		0.009 – 1917.500 & 1932.500 - 19300.000	-39.5 / RSS-210 Clause 2.5	Pass

Test Report No.: 15020015HKG-004 Page 32 of 61

#### 4.9.1 Radiated Emissions Configuration Photographs:

Worst Case Radiated Emission at

Base Unit: 5764.608 MHz

The worst case radiated emission configuration photographs are saved with filename: config photos.pdf

#### 4.9.2 Radiated Emissions Data:

Data are included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data in table 1-3 list the significant emission frequencies, the limit and the margin of compliance.

Judgement:

Base Unit - Passed by 6.0 dB margin

Test Report No.: 15020015HKG-004 Page 33 of 61

Mode: Transmission

Table 1, Base Unit

# Radiated Emissions Data Pursuant To FCC Part 15 Section 15.323 (d) / RSS-213 Clause 5.8.1 Emissions Requirements

#### **Lowest Channel**

Polarization	Frequency	Measured	Power	Margin
	(MHz)	Power	Limit	(dB)
		(dBm)	(dBm)	
V	1917.101	-53.3	-39.5	-13.8
V	1917.869	-48.2	-29.5	-18.7
V	1919.850	-44.1	-9.5	-34.6
V	3843.072	-46.6	-39.5	-7.1
V	5764.608	-45.5	-39.5	-6.0
V	7686.144	-46.4	-39.5	-6.9
V	9607.680	-46.4	-39.5	-6.9
V	11529.216	-47.4	-39.5	-7.9

#### NOTES:

- 1. Peak detector is used for the emission measurement.
- 2. All measurements were made at 3 meters.
- 3. Negative value in the margin column shows emission below limit.

Test Report No.: 15020015HKG-004 Page 34 of 61

Mode: Transmission

Table 2, Base Unit

# Radiated Emissions Data Pursuant To FCC Part 15 Section 15.323 (d) / RSS-213 Clause 5.8.1 Emissions Requirements

#### **Highest Channel**

Polarization	Frequency	Measured	Power	Margin
	(MHz)	Power	Limit	(dB)
		(dBm)	(dBm)	
V	1930.013	-43.7	-9.5	-34.2
V	1931.686	-47.8	-29.5	-18.3
V	1933.471	-52.8	-39.5	-13.3
V	3856.896	-46.7	-39.5	-7.2
V	5785.344	-45.6	-39.5	-6.1
V	7713.792	-46.8	-39.5	-7.3
V	9642.240	-46.7	-39.5	-7.2
V	11570.688	-47.6	-39.5	-8.1

#### NOTES:

- 1. Peak detector is used for the emission measurement.
- 2. All measurements were made at 3 meters.
- 3. Negative value in the margin column shows emission below limit.

Test Report No.: 15020015HKG-004 Page 35 of 61

Mode: Talk

Table 3, Base Unit

# Radiated Emissions Data Pursuant To FCC Part 15 Section 15.323 (d) / RSS-213 Clause 5.8.1 Emissions Requirements

Polarization	Frequency	Measured	Power	Margin
	(MHz)	Power	Limit	(dB)
		(dBm)	(dBm)	
V	36.210	-65.7	-39.5	-26.2
V	60.320	-64.0	-39.5	-24.5
V	112.200	-65.0	-39.5	-25.5
Н	184.120	-63.1	-39.5	-23.6
Н	216.130	-63.9	-39.5	-24.4
Н	240.210	-62.9	-39.5	-23.4
Н	328.130	-61.1	-39.5	-21.6
V	480.130	-63.1	-39.5	-23.6
V	576.230	-64.3	-39.5	-24.8

### NOTES:

- 1. Peak detector is used for the emission measurement.
- 2. All measurements were made at 3 meters.
- 3. Negative value in the margin column shows emission below limit.

Test Report No.: 15020015HKG-004 Page 36 of 61

### 4.9.3 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

FS = RA + AF + CF - AG + PD + AV

Where  $FS = Field Strength in dB\mu V/m$ 

RA = Receiver Amplitude (including preamplifier) in dBμV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

#### Example

Assume a receiver reading of  $62.0~dB_{\mu}V$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29.0 dB is subtracted. The pulse desensitization factor of the spectrum analyzer is 0.0 dB, and the resultant average factor is -10.0 dB. The net field strength for comparison to the appropriate emission limit is  $32.0~dB_{\mu}V/m$ . This value in  $dB_{\mu}V/m$  is converted to its corresponding level in  $\mu V/m$ .

 $RA = 62.0 dB\mu V$ 

AF = 7.4 dB

CF = 1.6 dB

 $AG = 29.0 \, dB$ 

PD = 0.0 dB

AV = -10 dB

 $FS = 62.0 + 7.4 + 1.6 - 29.0 + 0.0 + (-10.0) = 32.0 \text{ dB}\mu\text{V/m}$ 

Level in  $\mu$ V/m = Common Antilogarithm [(32.0 dB $\mu$ V/m)/20] = 39.8  $\mu$ V/m

Test Report No.: 15020015HKG-004 Page 37 of 61

4.9.4	Average Factor Calculation and Transmitter ON Time Measurements, FCC Rule 15.35(b, c) / RSS-Gen cl 4.5
[]	The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SPAN function on the analyzer was set to ZERO. The transmitter ON time was determined from the resultant time-amplitude display:
	Please refer to the attached plots for more details:
	The plots of Transmitter ON Time Measurements are as below.
[]	Please refer to the attached transmitter timing diagram that are provided by manufacturer
[×]	Not applicable - No average factor is required.
[ ]	Please refer to Technical Description (descri.pdf) for more details

Test Report No.: 15020015HKG-004 Page 38 of 61 FCC ID: YLM2161A

IC: 9101A-2161A

4.10 AC Power Line Conducted Emissions, FCC Rule 15.315 / RSS-213 Clause 5.4:

The AC power line conducted emission shall not exceed the limits of FCC Rule 15.207 / Table 4 in RSS-Gen Clause 7.2.4.

Measurements are made in accordance with ANSI C63.4 sub-clause 7. Emissions that are directly caused by digital circuits in the transmit path and transmitter portion are measured.

[ ]	Not applicable – EUT is only powered by battery for operation.
[×]	EUT connects to AC power line. Emission Data is listed in following pages.
[ ]	Base Unit connects to AC power line and has transmission. Handset connects to AC power line (indirectly) but has no transmission. Emission Data of Base Unit is listed in following pages.
[ ]	Handset connects to AC power line (indirectly) only during charging. Emission Data is listed in following pages.

Test Report No.: 15020015HKG-004 Page 39 of 61

## 4.10.1 AC Power Line Conducted Emissions Configuration Photographs:

Worst Case AC Power Line Conducted Emission at

Base Unit: 195 kHz

The worst case AC power Line conducted emission configuration photographs are saved with filename: config photos.pdf

4.10.2 AC Power Line Conducted Emissions Data:


The plot(s) and data in the following pages list the significant emission frequencies, the limit and the worst case margin of compliance.

Judgment:

Base unit: Passed by 17.15 dB margin compared with quasi-peak limit

Test Report No.: 15020015HKG-004 Page 40 of 61

Worst Case: Talk



Date: 5.MAR.2015 05:02:23

Test Report No.: 15020015HKG-004

Page 41 of 61

Worst Case: Talk

	ED	IT PEAK LIST (Fir	nal Measurement	Results)
Tra	cel:	CF15MQP		
Tra	ce2:	CF15MAV		
Tra	ce3:			
	TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB
1	Quasi Peak	195 kHz	46.66 L1	-17.15
1	Quasi Peak	285 kHz	36.03 L1	-24.63
1	Quasi Peak	294 kHz	37.27 N	-23.13
1	Quasi Peak	541.5 kHz	27.22 N	-28.77
1	Quasi Peak	622.5 kHz	26.41 N	-29.58
1	Quasi Peak	1.0815 MHz	31.06 L1	-24.93
1	Quasi Peak	1.4505 MHz	32.91 N	-23.08
1	Quasi Peak	1.9455 MHz	34.74 L1	-21.25
1	Quasi Peak	2.157 MHz	34.08 N	-21.91
1	Quasi Peak	4.02 MHz	32.23 N	-23.76
1	Quasi Peak	4.56 MHz	30.30 N	-25.69
1	Quasi Peak	6.909 MHz	31.89 L1	-28.10
1	Quasi Peak	9.9285 MHz	36.43 N	-23.56
1	Quasi Peak	14.1315 MHz	35.24 L1	-24.75

Date: 5.MAR.2015 05:02:09

Test Report No.: 15020015HKG-004 Page 42 of 61 FCC ID: YLM2161A

IC: 9101A-2161A

- 4.11 Frame Repetition Stability, FCC Rule 15.323(e) / RSS-213 Clause 5.2.(13):
- [ ] EUT implements Time Division Duplex (TDD) (not include TDMA) in order to support duplex connection on a given frequency carrier shall maintain a frame repetition rate whereby 3 x standard deviation of the frequency stability shall not exceed 50 ppm, not including a shift of the mean.
- [x] EUT uses Time Division Multiple Access (TDMA) in order to support multiple communication links on a given frequency carrier shall maintain a frame repetition rate whereby 3 x standard deviation of the frequency stability shall not exceed 10 ppm, not including a shift of the mean.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.2.2. Test setup is shown in section 3.2 Figure 3.2.1. A spectrum analyzer measures the time duration between rising edges of two consecutive frames over a time period of at least 1000 frame periods. These measurement values are used to compute the 3 x standard deviation of the frequency stability.

#### Test Results:

#### I. Base unit

Maximum Frame Repetition Stability (ppm)	Limit (ppm)	Results
0.0701	±10	Pass

Test Report No.: 15020015HKG-004 Page 43 of 61

## 4.12 Frame Period and Jitter, FCC Rule 15.323(e) / RSS-213 Clause 5.2(13):

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of EUT operating in these sub-bands shall be 20 ms or 10 ms/X where X is a positive whole number.

The jitter (time-related, abrupt, spurious variations in the duration of the frame interval) introduced at the two ends of such a communication link shall not exceed 25  $\mu$ s for any two consecutive transmissions. Transmissions shall be continuous in every time and spectrum window during the frame period defined for EUT.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.2.3. Test setup is shown in section 3.2 Figure 3.2.1. A spectrum analyzer measures the time duration between the rising edges of two consecutive frames. The measurements are taken over 100,000 frames. These measurement values are used to compute mean value and the difference between any two consecutive frame periods. The mean value is the frame period.

#### Test Results:

#### I. Base unit

Measured Maximum Jitter (μs)	Limit (μs)	Result
-0.1881	±25	Pass

Test Report No.: 15020015HKG-004 Page 44 of 61

## 4.13 Carrier Frequency Stability, FCC Rule 15.323(f) / RSS-213 Clause 5.3:

The carrier frequency stability of EUT shall be maintained within +/-10 ppm at the following conditions:

- 1. Over 1 hour at nominal supply voltage and a temperature of +20 °C;
- 2. Over a variation in the primary supply voltage of 85 % to 115 % of nominal supply voltage at a temperature of +20 °C. This test does not apply to an EUT that is only powered by battery for operation;
- 3. Over a temperature variation of -20 °C to +50 °C or at extreme temperatures as declared by manufacturer, and at nominal supply voltage.

#### For base unit:

The nominal supply voltage: <u>115 VAC</u> and the extreme temperatures of -20°C to +50°C are declared by manufacturer.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.2.1 The EUT and CMD60 is connected with shielded coaxial cable. The EUT is controlled by DECT Radio Communication Tester, CMD60, to use a fixed frequency channel during test as well as record the frequency offset. The transmission of EUT is in burst mode with pseudo-random data. Test setup is shown as follows.



#### Test Results:

a. Carrier Frequency Stability over time

a. carrier requeries etablish ever time					
Supply Voltage	Temperature (°C)	Measured Frequency Offset Over an hour (ppm)		Limit (ppm)	Result
		Max.	Min.		
Nominal	+20°C	1.63	-0.45	±10	Pass

b. Carrier Frequency Stability over Power Supply Voltage

Supply	Temperature	Measured Frequency Offset	Limit	Results
Voltage	(°C)	(ppm)	(ppm)	
85%	+20°C	2.15	±10	Pass
115%	+20°C	2.66	±10	Pass

c. Carrier Frequency Stability over Temperature

Supply Voltage	Temperature (°C)	Measured Frequency Offset (ppm)	Limit (ppm)	Results
Nominal	-20°C	2.66	±10	Pass
Nominal	+50°C	-0.45	±10	Pass

Test Report No.: 15020015HKG-004 Page 45 of 61

## 4.14 Monitoring Threshold:

Monitoring threshold can be relaxed according to FCC Rule 15.323(c)(9) / RSS-213 Clause 5.2(9). EUT that has a power output lower than the maximum permitted under FCC Rule 15.319(c) / RSS-213 Clause 5.6 may increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

Calculation of Monitoring Threshold Limit:

Monitoring Threshold (
$$T$$
)  $\leq$  -174 + 10  $\log_{10} B + M_L + P_{max} - P_{EUT} dBm  $\leq$  15  $\log_{10} B - 184 + M_L - P_{EUT} dBm$$ 

Where B = Measured Emission Bandwidth or Occupied Bandwidth of baseunit - FCC: 1.49 x10<sup>6</sup>Hz IC: 1.21 x10<sup>6</sup>Hz

 $M_L$  = Specified by the manufacturer declared in declaration.pdf for Monitoring Threshold  $(T_1)$ 

 $P_{\text{max}} = 5 \log_{10} B - 10 \text{ dBm}$ 

P<sub>EUT</sub> = Measured Peak Transmit Power of base unit - FCC: <u>19.17</u> dBm IC: 19.07 dBm

Calculated Monitoring Threshold Limits:

#### I. Base unit

	FCC	IC
Monitoring Threshold ( $T_L + U_M$ ) in dBm	-74.6	-75.8

NA - Not applicable

Test Report No.: 15020015HKG-004 Page 46 of 61

4.14.1.1 Monitoring Threshold Limit, FCC Rule 15.323(c)(2) ) / RSS-213 Clause 5.2(2):

- [x] Not applicable EUT supports at least of 20 duplex system access channels and implements Least Interfered Channel (LIC) algorithm. Please refer to the section 4.14.2 for more details.
- [ ] The monitoring threshold must not be more than 30 dB above the thermal noise power for a bandwidth equivalent to the emission bandwidth used by EUT.

Measurements are made in accordance with ANSI C63.17: 2013 sub-clause 7.3.1. Test setup is shown in section 3.3 Figure 3.3.1. The test is performed on the carrier closest to center of the band. RF signal generators apply uniform CW interference on all EUT carriers each at level  $T_{\rm L}$  +  $U_{\rm M}$  + 10 dB. Then, the interference level is reduced uniformly on all carriers until the EUT can transmit. The interference level shall be lower than or equal to the threshold limit.

#### Test Results:

#### I. Base unit

Measured Maximum Interference Level (dBm)	Monitoring Threshold Limit (dBm) $(T_L + U_M)$		Results
Level (dBill)	FCC	IC	
NA	-74.6	-75.8	NA

NA - Not applicable

Test Report No.: 15020015HKG-004 Page 47 of 61

4.14.2	2 Least Interfered Channel, LIC, FCC Rule 15.323 RSS-213 Clause 4.3.4(b)(5):	3(c)(5)	)/
[ ]	Not implemented – EUT met lower monitoring refer to the section 4.15.1 for more details	thres	hold requirements. Please
[×]	If access to spectrum is not available as determinimum of 20 duplex system access channel time and spectrum windows with the lowest po	ls are	defined for the EUT, the
Numb	er of duplex channels per frequency channel	=_	<u>12</u>
Numb	er of frequency channel	=	<u>5</u>
Total	Duplex Channels	=	60

Test Report No.: 15020015HKG-004 Page 48 of 61 FCC ID: YLM2161A

IC: 9101A-2161A

4.14.2.1 Least Interfered Channel (LIC) Selection, FCC Rule 15.323(c)(5) / RSS-213 Clause 5.2(5):

The criteria are specified in section 4.14.2. In addition, the power measurement resolution for this comparison must be accurate to within 6 dB.

Measurements are made in accordance with ANSI C63.17 sub-clause 7.3.2. Test setup is shown in section 3.3 Figure 3.3.1. RF signal generators apply uniform CW interference on all EUT carriers except two carriers (designated  $f_1$  and  $f_2$ ), each at level  $T_L + U_M + 14$ dB (cases 1 and 2) and  $T_L + U_M + 8$ dB (cases 3 and 4). EUT can only transmit on f2 carrier (cases 1 and 3) and f1 carrier (cases 2 and 4).

Test Descriptions and Results:

#### I. LIC Procedure - Base unit

	Test Descriptions	EUT transmits on	Results
1	Apply interference on $f_1$ at level $T_L + U_M + 7$ dB. Apply interference on $f_2$ at level $T_L + U_M$ . Initiate transmission. Verify transmission on $f_2$ . Terminate transmission. Repeat 5 times.	f <sub>2</sub>	Pass
2	Apply interference on $f_1$ at level $T_L + U_M$ . Apply interference on $f_2$ at level $T_L + U_M + 7$ dB. Initiate transmission. Verify transmission on $f_1$ . Terminate transmission. Repeat 5 times.	<i>f</i> <sub>1</sub>	Pass
3	Apply interference on $f_1$ at level $T_L + U_M + 1$ dB. Apply interference on $f_2$ at level $T_L + U_M - 6$ dB. Initiate transmission. Verify transmission on $f_2$ . Terminate transmission. Repeat 5 times.	f <sub>2</sub>	Pass
4	Apply interference on $f_1$ at level $T_L + U_M$ - 6 dB. Apply interference on $f_2$ at level $T_L + U_M + 1$ dB. Initiate transmission. Verify transmission on $f_1$ . Terminate transmission. Repeat 5 times.	<i>f</i> <sub>1</sub>	Pass

NA - Not applicable

Test Report No.: 15020015HKG-004 Page 49 of 61

4.14.2.2 Least Interfered Channel (LIC) Confirmation, FCC Rule 15.323(c)(5) / RSS-213 Clause 5.2(5):

EUT utilizing the provision of FCC Rule 15.323(c)(5) / RSS-213 Clause 5.2(5) must have monitored all access channels defined for its system within the last 10 s and must verify, within the 20 ms (40 ms for EUT designed to use a 20 ms frame period) immediately preceding actual channel access that the detected power of the selected time and spectrum windows is no higher than the previously detected value.

Measurements are made in accordance with ANSI C63.17: 2013 sub-clause 7.3.3. This test is performed in section 4.15 and 4.16.

#### Results:

The tests are reported in section 4.15 and 4.16.

4.14.2.3 Maximum Spectrum Occupancy, FCC Rule 15.323(c)(5) / RSS-213 Clause 5.2(5):

No EUT or group of co-operating EUTs located within 1 meter of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively, more than one third of the time and spectrum windows defined by the EUT.

#### Attestation:

According to the technical description provided, the total number of the time and spectrum windows defined by the system is 5\*12 = 60.

During any frame period, the maximum number of time and spectrum windows occupied by the system will be 12, which is less than one third of the time and spectrum windows defined by the system.

Test Report No.: 15020015HKG-004 Page 50 of 61

4.15 Monitoring Time, FCC Rule 15.323(c)(1) / RSS-213 Clause 5.2(1):

Immediately prior to initiating transmission, EUT must monitor the combined time and spectrum windows in which they intend to transmit for a period of at least 10 ms for EUT designed to use a 10 ms or shorter frame period, or at least 20 ms for EUT designed to use a 20 ms frame period.

Measurements are made in accordance with ANSI C63.17 sub-clause 7.3.3. Test setup is shown in section 3.3 Figure 3.3.1. RF signal generators apply uniform CW interference on all system carriers except two carriers (designated  $f_1$  and  $f_2$ ), each at level  $T_L + U_{M.} + 20$ dB. EUT can only transmit on these two carriers.

## Test Descriptions and Results:

#### I. Base unit

	Test Descriptions	EUT transmits on	Results
1	Apply interference on $f_1$ at level $T_L + U_M + 20$ dB, and no interference on $f_2$ . Initiate transmission. Verify transmission on $f_2$ . Then, terminate transmission.	f <sub>2</sub>	Pass
2	Apply interference on $f_2$ at level $T_L + U_M + 20$ dB, and remove interference from $f_1$ immediately. Also immediately initiate transmission but is at least 20 ms after interference on $f_2$ is applied. Verify transmission on $f_1$ .	<i>f</i> <sub>1</sub>	Pass


Test Report No.: 15020015HKG-004 Page 51 of 61

## 4.16 Maximum Transmit Period, FCC Rule 15.323(c)(3) / RSS-213 Clause 5.2(3):

If no signal above the threshold level is detected, transmission may commence and continue with the same emission bandwidth in the monitored time and spectrum windows without further monitoring. However, occupation of the same combined time and spectrum windows by a EUT or group of co-operating EUTs continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

EUT establishes a communication channel with its companion device, which occupies the duplex pair combined time and spectrum windows. Reference RF signal generator synchronized with the sample and then generated a pulse as a time frame reference. The centre frequency of spectrum analyzer was set to the carrier frequency and the SPAN was set to ZERO. The spectrum analyzer was used to monitor the time (reference to the time signal) and spectrum of the communication channel. The occupied time or spectrum of the communication channel shall be changed over a period of time no longer than 8 hours. For a EUT with a frame period of 10/X ms, no more than 2,880,000 X frames should be transmitted without a break.

Test setup is shown as follows:



#### Test Results:

#### I. Base unit

Measured Maximum Transmission Duration (minutes)	Limit (minutes)	Results
330	480	Pass

Test Report No.: 15020015HKG-004 Page 52 of 61

## 4.17 System Acknowledgement, FCC Rule 15.323(c)(4) / RSS-213 Clause 5.2(4):

Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgment, at which time the access criteria must be repeated.

Measurements are made in accordance with ANSI C63.17 sub-clause 8.1.1 and 8.2.1. Test setup is shown in section 3.3 Figure 3.3.1.

#### Test Results:

#### I. Base Unit

## [x] Timing for EUTs using control and signaling channel type transmissions:

Conditions	nditions Transmission Duration (seconds)		Results
Time needed to repeat access criteria	1.28	30	Pass

## [x] Timing for EUTs using communications channel type transmissions:

Conditions	Transmission Duration (seconds)	Limit (seconds)	Results
Activate EUT w/ companion device off	NA	1	NA
Time needed to cease Traffic Channel	6	30	Pass

NA - Not applicable

Test Report No.: 15020015HKG-004 Page 53 of 61

## 4.18 Random Waiting, FCC Rule 15.323(c)(6) / RSS-213 Clause 5.2(6):

If the selected combined time and spectrum windows are unavailable, the EUT may either monitor and select different windows or seek to use the same windows after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 ms, commencing when the channel becomes available.

Measurements are made in accordance with ANSI C63.17 sub-clause 8.1.2 or 8.1.3. Test setup is shown in section 3.3 Figure 3.3.1.

#### Test Results:

#### I. Base unit

## [x] Random Waiting is not implemented in the EUT:

Conditions	Transmit Channel	Results
Interference applied at operating Channel, f <sub>1</sub>	f <sub>2</sub>	Pass

## [ ] Random Waiting is implemented in the EUT:

Maximum time interval from the end of interference to the start of the control channel	The distribution of the measured time intervals	Results
NA	NA	NA

## NA - Not applicable

Test Report No.: 15020015HKG-004 Page 54 of 61

4.19 Monitoring Bandwidth, FCC Rule 15.323(c)(7).1 / RSS-213 Clause 5.2(7).1:

The monitoring bandwidth must be equal to or greater than the emission bandwidth/occupied bandwidth of the intended transmission.

Measurements are made in accordance with ANSI C63.17 sub-clause 7.4. Test setup is shown in section 3.3 Figure 3.3.1.

#### Attestation:

- [x] Monitoring bandwidth of the EUT is equal to the occupied bandwidth of the intended transmission. Monitoring is made through the radio receiver used by the EUT for communication. Please refer to the section 2.2 Technical Description for more details. Designed bandwidth refers to section 4.3 Emission Bandwidth / Occupied Bandwidth.
- [ ] Compliance is demonstrated by Monitoring Bandwidth Tests as shown below.

#### Test Results:

la. Simple Compliance Test Results - Base unit

Interference from Carrier	Reaction of EUT	Results
-30% EBW / Occupied Bandwidth	NA	NA
+30% EBW / Occupied Bandwidth	NA	NA

lb. Detailed Compliance Test Results - Base unit

CW Interference from Carrier	Reaction of EUT	Results
+ 6 dB	NA	NA
+ 12 dB	NA	NA
- 6 dB	NA	NA
- 12 dB	NA	NA

A - Could Transmit

B - Could not Transmit

NA - Not applicable

\*Remarks: Detailed Compliance Test was used to show the compliance of the EUT.

Test Report No.: 15020015HKG-004 Page 55 of 61

4.20 Maximum Reaction Time, FCC Rule 15.323(c)(7).2 / RSS-213 Clause 5.2(7).2:

The monitoring system bandwidth must have a maximum reaction time less than 50 x SQRT (1.25/emission bandwidth B in MHz)  $\mu$ s for signals at the applicable threshold level but shall not be required to be less than 50  $\mu$ s. If a signal is detected that is 6 dB or more above the applicable threshold level, the maximum reaction time shall be 35 x SQRT (1.25/emission bandwidth B in MHz)  $\mu$ s but shall not be required to be less than 35  $\mu$ s.

Measurements are made in accordance with ANSI C63.17: 2013 sub-clause 7.5. Test setup is shown in section 3.3 Figure 3.3.1.

#### Test Results:

	Test	Reaction of EUT	Results
1	Apply Interference Pulse $50\mu s$ on $f_1$ at pulsed level $T_L + U_m$ , then apply a CW signal on $f_2$ at the level $T_L$	f <sub>2</sub>	Pass
2	Change Interference Pulse to 35µs on f₁ at pulsed level T <sub>L</sub> + U <sub>m</sub> + 6dB,	$f_2$	Pass

Test Report No.: 15020015HKG-004 Page 56 of 61

4.21 Monitoring Antenna, FCC Rule 15.323(c)(8) / RSS-213 Clause 5.2(8):

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

- [x] EUT uses the same antenna used for transmission and monitoring that is in compliance meet above provision.
- [ ] EUT uses difference antenna used for transmission and monitoring. It must be verified that the monitoring antenna provides coverage equivalent to that of the transmitting antenna. Measurements are made in accordance with ANSI C63.17 sub-clause 4.

Test Report No.: 15020015HKG-004 Page 57 of 61

### 4.22 Duplex Connections, FCC 15.323(c)(10) / RSS-213 Clause 5.2(10):

An initiating device may attempt to establish a duplex connection by monitoring both its intended transmit (Tx) and receive (Rx) time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

#### Attestation:

[x] The Handset Unit is the initiating device of the duplex connection

Measurements are made in accordance with ANSI C63.17: 2013 sub-clause 8.3. Test setup is shown in section 3.3 Figure 3.3.1.

#### Test Results:

#### a. Base unit

Dual Access Criteria Check for EUT not implemented the LIC algorithm and do not offer at least 20 duplex communications channels:

Interference	Reaction of EUT	Results
All Tx and Rx Window, except one for Rx Window	NA	NA
All Tx and Rx Window, except one for Tx Window	NA	NA

#### b. Base unit

[x] Dual Access Criteria Check for EUT implemented the LIC algorithm and offer at least 20 duplex communications channels:

Interference	Reaction of EUT	Results
All Tx windows with level $T_L + U_M$ & Rx windows with level $T_L + U_M + 7$ dB, except one for Tx window & one for Rx window, which are not duplex.	NA	NA
All Tx windows with level $T_L + U_M + 7 dB \& Rx$ windows with level $T_L + U_M$ , except one for Tx window & one for Rx, which are not duplex	NA	NA

## NA - Not applicable

Test Report No.: 15020015HKG-004 Page 58 of 61

4.23 Alternative Monitoring Interval for Co-located Device, FCC Rule 15.323(c)(11) / RSS-213 Clause 5.2(11):

An initiating device that is prevented from monitoring during its intended transmit window due to monitoring system blocking from the transmissions of a co-located (within one meter) transmitter of the same system, may monitor the portions of the time and spectrum windows in which they intend to receive over a period of at least 10 ms. The monitored time and spectrum window must total at least 50 % of the 10 ms frame interval and the monitored spectrum must be within the 1.25 MHz frequency channel(s) already occupied by that device or co-located co-operating devices. If the access criteria is met for the intended receive time and spectrum window under the above conditions, then transmission in the intended transmit window by the initiating device may commence.

Measurements are made in accordance with ANSI C63.17 sub-clause 8.4.

#### Attestation:

- [ ] Appropriate as it is co-located device, in which the monitoring system will be blocked from the transmissions of a co-located (Within one meter) transmitter of the same system. Please refer to attachment, 15.323(c)(11).pdf / RSS-213(b)(11).pdf, for details.
- [x] Not appropriate, as the system always monitor both the transmit and receive time/spectrum windows, it is not a co-located device.
- 4.24 Fair Access, FCC Rule 15.323(c)(12) / RSS-213 Clause 5.2(12):

The provisions of FCC Rule 15.323(c)(10) or (c)(11) / RSS-213 Clause 5.2(10) or (11) shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

#### Attestation:

The manufacturer declares that the device does not use any mechanisms as provided by Part 15.323(c)(10) or (c)(11) / RSS-213 Clause 5.2(10) or (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

Please refer to the declaration letter which is saved with filename: declaration.pdf.

Test Report No.: 15020015HKG-004 Page 59 of 61

# EXHIBIT 5 EQUIPMENT LIST

Test Report No.: 15020015HKG-004 Page 60 of 61 FCC ID: YLM2161A

IC: 9101A-2161A

## 5.0 **Equipment List**

## 1) Radiated Emissions Test

Equipment	EMI Test Receiver	Spectrum Analyzer	BiConiLog Antenna
Registration No.	EW-3095	EW-2253	EW-3061
Manufacturer	R&S	R&S	EMCO
Model No.	ESCI	FSP40	00166104
Calibration Date	Oct. 16, 2014	May 08, 2014	Jul. 17, 2014
Calibration Due Date	Oct. 16, 2015	May 08, 2015	Jul. 17, 2015

Equipment	Double Ridged Guide	Broad-Band Horn
	Antenna (1GHz -	Antenna
	18GHz)	
Registration No.	EW-1133	EW-1679
Manufacturer	EMCO	SCHWARZBECK
Model No.	3115	BBHA9170
Calibration Date	Apr. 30, 2014	Jun. 5, 2014
Calibration Due Date	Oct. 30, 2015	Jun. 5, 2015

## 2) Conducted Emissions Test

Equipment	EMI Test Receiver	LISN	
Registration No.	EW-2251	EW-2874	
Manufacturer	R&S	R&S	
Model No.	ESCI	ENV-216	
Calibration Date	Dec 4, 2014	Dec 8, 2014	
Calibration Due Date	Dec 4, 2015	Dec 8, 2015	

### 3) Conductive Measurement Test

5) Contadon o moderno mentente con			
Equipment	Coaxial directional	Spectrum Analyzer	Digital
	coupler		Radiocommunication
			Tester for DECT
Registration No.	EW-2337	EW-2466	EW-2460
Manufacturer	MAGNA	R&S	ROHDESCHWARZ
Model No.	4222-16	FSP30	CMD60
Calibration Date	Nil*	Sep. 2, 2014	Apr. 07, 2014
Calibration Due Date	Nil*	Sep. 2, 2015	Mar. 10. 2015

Equipment	Vector Signal	Temperature &	Digital Multimeter
	Generator	Humidity Chamber	
Registration No.	EW-2320	EW-2134	EW-1020
Manufacturer	R&S	GIANT FORCE	FLUKE
Model No.	SMU200A	GTH-750-40-CP-SD	87-IV
Calibration Date	Mar. 19, 2014	Oct. 10, 2014	Jun. 23, 2014
Calibration Due Date	Mar. 19, 2015	Oct. 10. 2015	Jul. 22, 2015

## **END OF TEST REPORT**

Test Report No.: 15020015HKG-004 Page 61 of 61