

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	AI translator
Model Name	S350
FCC ID	YMA-S350

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

According to the follow transmitter output power (P_t) formula :

WiFi

According to the report AGC00047180201TE05,
 $P_t = 9.75 \text{ dBm} = 9.44 \text{ mW}$

The result for RF exposure evaluation

$\text{SAR} = (9.44 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.462(\text{GHz})}] = 2.96 < 3.0 \text{ for 1-g SAR}$

4. CONCLUSION

The SAR evaluation is not required.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

