



FCC ID: YMQ-8051000

## EMI -- TEST REPORT

- FCC Part 15.225 -

Test Report No. :	<b>T34322-00-01KG</b>	03. August 2010 Date of issue
-------------------	-----------------------	----------------------------------

Type / Model Name : APEX-Reader

Product Description : Laboratory Equipment with RFID

Applicant : LRE Medical GmbH

Address : Frankfurter Ring 15  
80807 München, GERMANY

Manufacturer : AspenBio Pharma, Inc.

Address : 1585 South Perry Street, Castle Rock  
Colorado 80104-1931, USA

Licence holder : AspenBio Pharma, Inc.

Address : 1585 South Perry Street, Castle Rock  
Colorado 80104-1931, USA

<b>Test Result</b> according to the standards listed in clause 1 test standards:
--

**POSITIVE**



DAT-P-207/05-00

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: YMQ-8051000

## Contents

<b>1 TEST STANDARDS</b>	<b>3</b>
<b>2 SUMMARY</b>	<b>4</b>
<b>3 EQUIPMENT UNDER TEST</b>	<b>5</b>
3.1 Photo documentation of the EUT – See attachment A	5
3.2 Power supply system utilised	5
3.3 Short description of the equipment under test (EUT)	5
<b>4 TEST ENVIRONMENT</b>	<b>6</b>
4.1 Address of the test laboratory	6
4.2 Environmental conditions	6
4.3 Statement of the measurement uncertainty	6
4.1 Measurement Protocol for FCC, VCCI and AUSTEL	7
<b>5 TEST CONDITIONS AND RESULTS</b>	<b>8</b>
5.1 Conducted emissions	8
5.2 Field strength of the fundamental wave	12
5.3 Spurious emissions	14
5.4 Frequency tolerance	16
5.5 20 dB Bandwidth	18
5.6 Transmitter spectrum mask	21
5.7 Receiver radiated emissions	24
<b>6 USED TEST EQUIPMENT AND ACCESSORIES</b>	<b>25</b>

FCC ID: YMQ-8051000

## 1 TEST STANDARDS

The tests were performed according to following standards:

**FCC Rules and Regulations Part 15, Subpart A - General (October, 2009)**

Part 15, Subpart A, Section 15.31 Measurement standards

Part 15, Subpart A, Section 15.33 Frequency range of radiated measurements

Part 15, Subpart A, Section 15.35 Measurement detector functions and bandwidths

Part 15, Subpart A, Section 15.38 Incorporation by reference

**FCC Rules and Regulations Part 15, Subpart C - Intentional Radiators (October, 2009)**

Part 15, Subpart C, Section 15.203 Antenna requirement

Part 15, Subpart C, Section 15.204 External radio frequency power amplifiers and antenna modifications

Part 15, Subpart C, Section 15.205 Restricted bands of operation

Part 15, Subpart C, Section 15.207 Conducted limits

Part 15, Subpart C, Section 15.209 Radiated emission limits, general requirements

Part 15, Subpart C, Section 15.215 Additional provisions to the general radiated emission limitations

Part 15, Subpart C, Section 15.225 Operation within the band 13.110 - 14.010 MHz

**FCC Rules and Regulations Part 1, Subpart I - Procedures Implementing the National Environmental Policy Act of 1969**

Part 1, Subpart I, Section 1.1310 Radiofrequency radiation exposure limits

Part 1, Subpart 2, Section 2.1093 Radiofrequency radiation exposure evaluation: portable device

**OET Bulletin 65, 65A, 65B, 65C Edition 97-01, August 1997 – Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields.**

ANSI C63.4: 2009 Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

ANSI C95.1:1992 IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz

CISPR 16-4-2: 2003 Uncertainty in EMC measurement

CISPR 22: 2005  
EN 55022: 2006 Information technology equipment

FCC ID: YMQ-8051000

## **2 SUMMARY**

### **GENERAL REMARKS:**

The EUT includes 2 RFID Modules with identical electronics. Only the form of the PCB and the location is different. The working frequency of the modules is 13.56 MHz.

This test report describes the assessment for one RFID Module only. The position of this module is under the key pad and is the "worst case" module. The position of the second module is on the bottom of the unit.

The EUT is equipped with an integral antenna.

The receiver is permanently co-located within the transmitter. Therefore the receive mode is to short and was tested together with the transmitter in operating mode. There is no standby mode.

### **FINAL ASSESSMENT:**

The equipment under test **fulfills** the EMI requirements cited in clause 1 test standards.

Date of receipt of test sample	: <u>acc. to storage records</u>
Testing commenced on	: <u>5 June 2010</u>
Testing concluded on	: <u>16 June 2010</u>

Checked by:

---

Thomas Weise  
Dipl. Ing.(FH)  
Laboratory Manager

Tested by:

---

Klaus Gegenfurtner  
Dipl.-Ing.(FH)

FCC ID: YMQ-8051000

### **3 EQUIPMENT UNDER TEST**

#### **3.1 Photo documentation of the EUT – See attachment A**

#### **3.2 Power supply system utilised**

Power supply voltage : Battery 6.1 to 8.4 VDC  
AC 115 V / 60 Hz / 1φ

#### **3.3 Short description of the equipment under test (EUT)**

The ApexReader is a portable fluorescence instrument used to measure the results of tests by AspenBio Pharma. The reader is designed for use in a laboratory setting. Each test cartridge includes an RFID tag that identifies relevant parameter for evaluating the test results.

Number of tested samples: 1  
Serial number: 136

#### **EUT operation mode:**

The equipment under test was operated during the measurement under the following conditions:

- TX CW modulated

---

---

---

#### **EUT configuration:**

(The CDF filled by the applicant can be viewed at the test laboratory.)

**The following peripheral devices and interface cables were connected during the measurements:**

- None Model : \_\_\_\_\_
- \_\_\_\_\_ Model : \_\_\_\_\_
- \_\_\_\_\_ Model : \_\_\_\_\_

## **4 TEST ENVIRONMENT**

### **4.1 Address of the test laboratory**

**mikes-testingpartners gmbh**  
**Ohmstrasse 2-4**  
**94342 STRASSKIRCHEN**  
**GERMANY**

### **4.2 Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa

### **4.3 Statement of the measurement uncertainty**

The data and results referenced in this document are true and accurate. The reader may notice that tolerances within the calibration of the equipment and facilities may cause additional uncertainty. The measurement uncertainty is calculated for all measurements listed in this test report acc. to CISPR 16-4-2 „Uncertainties, statistics and limit modelling – Uncertainty in EMC measurement“ and documented in the mikes-testingpartners gmbh quality system acc. to DIN EN ISO/IEC 17025. For all measurements shown in this report, the measurement uncertainty of the test laboratory, mikes-testingpartners gmbh, is below the measurement uncertainty as defined by CISPR. Therefore, no special measures must be taken into consideration with regard to the limits according to CISPR. Furthermore, component diversity and modifications in production processes may result in additional deviation. If necessary, refer to the test lab for the actual measurement uncertainty for specific tests. The manufacturer has the sole responsibility of continued compliance of the EUT.

FCC ID: YMQ-8051000

## 4.1 Measurement Protocol for FCC, VCCI and AUSTEL

### 4.1.1 GENERAL INFORMATION

#### 4.1.1.1 Test methodology

Conducted and radiated disturbance testing is performed according to the procedures set out by the International Special Committee on Radio Interference (CISPR) Publication 22, European Standard EN 55022 as shown under section 1 of this report.

#### 4.1.1.2 Justification

The equipment under test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral using the appropriate impedance characteristic or left unterminated. Where appropriate, cables are manually manipulated with respect to each other thus obtaining maximum disturbances from the unit.

### 4.1.2 DETAILS OF TEST PROCEDURES

#### General Standard information

The test methods used comply with CISPR Publication 22, EN 55022 - "Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement" and with ANSI C63.4 - "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". In compliance with 47 CFR Part 15 Subpart A, Section 15.38 testing for FCC compliance may be achieved by following the procedures set out in ANSI C63.4 and applying the CISPR 22 limits.

## **5 TEST CONDITIONS AND RESULTS**


### **5.1 Conducted emissions**

For test instruments and accessories used see section 6 Part **A 4**.

#### **5.1.1 Description of the test location**

Test location: Shielded Room S2

#### **5.1.2 Photo documentation of the test set-up**



#### **5.1.3 Applicable standard**

According to FCC Part 15, Section 15.107(a):

Except for Class A devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the given limits.

#### **5.1.4 Description of Measurement**

The measurements are performed following the procedures set out in ANSI C63.4 described under item 4.4.3. If the minimum limit margin appears to be less than 20 dB with a peak mode measurement, the emissions are remeasured using a tuned receiver with quasi-peak and average detection and recorded on the data sheets.

FCC ID: YMQ-8051000

**5.1.5 Test result**

Frequency range: 0.15 MHz - 30 MHz

Min. limit margin 7.3 dB at 13.56 MHz

Limit according to FCC Part 15, Section 15.107(a):

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency


The requirements are **FULFILLED**.**Remarks:** For detailed test result please refer to following test protocols

FCC ID: YMQ-8051000

5.1.6 Test protocol

Test point L1  
Operation mode: TX CW modulated  
Remarks:

Frequency MHz	QP Level dB(µV)	QP Margin dB	QP Limit dB	AV Level dB(µV)	AV Margin dB	AV Limit dB
0.15	45.2	-20.8	66.0	16.2	-39.8	56.0
0.205	43.3	-20.2	63.4	30.6	-22.8	53.4
0.305	29.6	-30.5	60.1	9.6	-40.6	50.1
0.48	35.9	-20.5	56.3	22.6	-23.7	46.3
0.505	34.8	-21.2	56.0	17.8	-28.2	46.0
0.66	30.5	-25.5	56.0	13.2	-32.8	46.0
0.76	30.7	-25.3	56.0	15.1	-30.9	46.0
0.82	28.7	-27.3	56.0	13.7	-32.3	46.0
1.85	27.3	-28.7	56.0	18.7	-27.3	46.0
2.95	35.7	-20.3	56.0	14.8	-31.2	46.0
3.125	35.0	-21.0	56.0	13.6	-32.4	46.0
4.085	29.1	-26.9	56.0	14.7	-31.3	46.0
6.63	28.6	-31.4	60.0	16.7	-33.3	50.0
7.13	29.7	-30.3	60.0	17.4	-32.6	50.0
10.665	39.3	-20.7	60.0	38.0	-12.0	50.0




FCC ID: YMQ-8051000

Test point: N  
Operation mode: TX CW modulated  
Remarks:

Result: passed

Frequency MHz	QP Level dB(µV)	QP Margin dB	QP Limit dB	AV Level dB(µV)	AV Margin dB	AV Limit dB
0.15	45.1	-20.9	66.0	16.1	-39.9	56.0
0.21	39.6	-23.6	63.2	22.8	-30.5	53.2
0.325	29.5	-30.1	59.6	14.5	-35.1	49.6
0.47	34.8	-21.7	56.5	20.6	-25.9	46.5
0.505	34.8	-21.2	56.0	17.8	-28.2	46.0
0.645	29.5	-26.5	56.0	12.0	-34.0	46.0
0.76	30.7	-25.3	56.0	14.9	-31.1	46.0
0.83	28.9	-27.1	56.0	12.3	-33.7	46.0
1	22.7	-33.3	56.0	6.6	-39.4	46.0
1.96	22.3	-33.7	56.0	6.4	-39.6	46.0
2.97	37.2	-18.8	56.0	16.2	-29.8	46.0
3.125	35.1	-20.9	56.0	13.7	-32.3	46.0
4.015	30.3	-25.8	56.0	14.9	-31.1	46.0
5.05	28.6	-31.4	60.0	15.4	-34.6	50.0
6.575	29.6	-30.4	60.0	17.3	-32.7	50.0
7.13	30.0	-30.0	60.0	17.5	-32.5	50.0
8.17	28.7	-31.3	60.0	17.6	-32.4	50.0
9.69	27.7	-32.3	60.0	18.5	-31.5	50.0
13.56	52.7	-7.3	60.0	39.2	-10.8	50.0
23.995	21.7	-38.3	60.0	15.9	-34.1	50.0



FCC ID: YMQ-8051000

## 5.2 Field strength of the fundamental wave

For test instruments and accessories used see section 6 Part **CPR 1**.

### 5.2.1 Description of the test location

Test location: OATS1

Test distance: 3 metres

### 5.2.2 Photo documentation of the test set-up



FCC ID: YMQ-8051000

### 5.2.3 Applicable standard

According to FCC Part 15, Section 15.225(a):

The field strength of any emission within the band 13.553 – 13.567 MHz shall not exceed 15848  $\mu$ V/m at 30 m.

### 5.2.4 Description of Measurement

The transmitted field strength of the EUT has to be measured at an open area test site using a tuned receiver and a shielded loop antenna. The set up of the equipment under test will be in accordance with ANSI C63.4. The measurement has been performed at 3 m. The results have been compared to the limits defined at 30 m distances according to FCC Part 15C, Section 15.31(f)(2) using an inverse linear distance extrapolation factor of 40 dB/decade. The final measurement has been performed with an EMI receiver using quasi peak detector and a resolution bandwidth of 9 kHz.

### 5.2.5 Test result

a) Result at a measurement distance of 3m

Frequency (MHz)	Level (dB $\mu$ V)	Ant. factor (dB 1/m)	Field strength dB( $\mu$ V/m)
13.56	37.3	20	57.3

b) Result extrapolated to a distance of 30 m

Frequency (MHz)	Level (dB $\mu$ V)	Ant. factor (dB 1/m)	Field strength dB( $\mu$ V/m)	Limit dB( $\mu$ V/m)	Delta (dB)
13.56	-2.7	20	17.3	84	-66.7

Limit according to FCC Part 15, Section 15.225(a):

Frequency (MHz)	Field strength of fundamental wave ( $\mu$ V/m)	Measurement distance (metres)
13.553 - 13.567	15848	84

The requirements are **FULFILLED**.

Remarks:

---



---

### 5.3 Spurious emissions

For test instruments and accessories used see section 6 Part SER 1, SER 2.

#### 5.3.1 Description of the test location

Test location: OATS1

Test distance: 3 metres

#### 5.3.2 Photo documentation of the test set-up



FCC ID: YMQ-8051000

### 5.3.3 Applicable standard

According to FCC Part 15C, Section 15.209:

The emissions from an intentional radiator shall not exceed the field strength levels specified in the table below.

### 5.3.4 Description of Measurement

The spurious emissions of the EUT have to be measured at an open area test site in the frequency range from 9 kHz to 1000 MHz using a tuned EMI receiver. The set up of the equipment under test will be in accordance with ANSI C63.4. The measurement has been performed at 3 m. The results have been compared to the limits defined at 30 m or 300 m distances according to FCC Part 15C, Section 15.31(f)(2) using an inverse linear distance extrapolation factor of 40 dB/decade. The final measurement has been performed with the EMI receiver using Quasi peak detector except for the frequency bands 9 kHz to 90 kHz and 110 to 490 kHz where an average detector will be used, according to Section 15.209(d).

The resolution bandwidth during the measurement is as follows:

9 kHz – 150 kHz:	RBW: 200 Hz
150 kHz – 30 MHz:	RBW: 9 kHz
30 MHz – 1000 MHz:	RBW: 120 kHz

### 5.3.5 Test result

Results at a measurement distance of 3m

Frequency (MHz)	Level AV (dB $\mu$ V)	Level QP (dB $\mu$ V)	Ant. factor (dB)	Field strength QP dB( $\mu$ V/m)	Field strength AV dB( $\mu$ V/m)	Limit dB( $\mu$ V/m)	Delta (dB)
0.009-0.090	---						
0.090-0.110		---					
0.110-0.490	---						
0.490 - 1.705		---					
1.705 - 30.0		---					
30 - 88		---					
88 - 216		---					

Limit according to FCC Part 15 Subpart 15.209(a):

Frequency (MHz)	Field strength of spurious emissions ( $\mu$ V/m)	Measurement distance (metres)
0.009 - 0.490	2400/F(kHz)	-- 300
0.490 - 1.705	24000/F (kHz)	-- 30
1.705 - 30.0	30	29.5 30
30 - 88	100	40 3
88 - 216	150	43.5 3
216 - 960	200	46 3
Above 960	500	54 3

The requirements are **FULFILLED**.

**Remarks:** Measurement has been performed up to the 10<sup>th</sup> harmonic (135 MHz).

No undesired emissions occurred in the frequency range from 9 kHz up to 135 MHz

## 5.4 Frequency tolerance

For test instruments and accessories used see section 6 Part **FE**.

### 5.4.1 Description of the test location

Test location: AREA4 (Climatic Chamber)

### 5.4.2 Photo documentation of the test set-up



### 5.4.3 Applicable standard

According to FCC Part 15, Section 15.225(e):

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature range of  $-20\text{ }^{\circ}\text{C}$  to  $+50\text{ }^{\circ}\text{C}$  at normal supply voltage and for a variation in the primary supply voltage from 85 % to 115 % of the rated supply voltage at a temperature of  $20\text{ }^{\circ}\text{C}$ . For battery operated equipment, the equipment shall be performed using a new battery.

### 5.4.4 Description of Measurement

The frequency tolerance has been measured radiated using a spectrum analyser. The center frequency of the spectrum analyser has been set to the fundamental frequency. This is an alternative test method because the EuT can not be operated in un-modulated mode. The limit line was set to 10 dB below the carrier. The frequencies of the upper ( $f_U$ ) and lower ( $f_L$ ) points, where the displayed power envelope of the modulation including frequency drift is equal to the appropriate level, have been recorded. The centre frequency is calculated as  $f_C = (f_U + f_L)/2$ . The measurement has been performed at normal and extreme test conditions from  $-20\text{ }^{\circ}\text{C}$  to  $+50\text{ }^{\circ}\text{C}$  in steps of 10 degrees (According to FCC Part 2.1055).

**5.4.5 Test result**

Test conditions		Test result
		Frequency (MHz)
$T_{min}$ (-20)°C	$V_{min}$ (5.1 V)	13.56234
	$V_{max}$ (6.9 V)	13.56234
$T$ (-10)°C	$V_{min}$ (5.1 V)	13.56238
	$V_{max}$ (6.9 V)	13.56238
$T$ (0)°C	$V_{min}$ (5.1 V)	13.56238
	$V_{max}$ (6.9 V)	13.56238
$T$ (10)°C	$V_{min}$ (5.1 V)	13.56236
	$V_{max}$ (6.9 V)	13.56236
$T_{nom}$ (20)°C	$V_{min}$ (5.1 V)	13.56234
	$V_{nom}$ (6.0V)	13.56234
	$V_{max}$ (6.9 V)	13.56234
$T$ (30)°C	$V_{min}$ (5.1 V)	13.56232
	$V_{max}$ (6.9 V)	13.56232
$T$ (40)°C	$V_{min}$ (5.1 V)	13.56230
	$V_{max}$ (6.9 V)	13.56230
$T_{max}$ (50)°C	$V_{min}$ (5.1 V)	13.56228
	$V_{max}$ (6.9 V)	13.56228
Measurement uncertainty		± 10 Hz

 Carrier frequency:  $f_c = 13.56234$  MHz

Max. tolerance: ± 0.01 % of 13.56234 MHz = ± 1.356 kHz

 Lowest frequency:  $f_l = 13.56228$  MHz

 Lowest tolerance:  $f_l - f_c = -0.06$  kHz < - 1.356 kHz

Limit according to FCC Part 15, Section 15.225(e):

The frequency tolerance of the carrier signal shall be maintained within ±0.01 % of the operating frequency.

 The requirements are **FULFILLED**.

**Remarks:**

FCC ID: YMQ-8051000

## 5.5 20 dB Bandwidth

For test instruments and accessories used see section 6 Part **MB**.

### 5.5.1 Description of the test location

Test location: AREA4

### 5.5.2 Photo documentation of the test set-up



### 5.5.3 Applicable standard

According to FCC Part 15C, Section 15.215(c):

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in section 15.217 to 15.257, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed.

FCC ID: YMQ-8051000

#### 5.5.4 Description of Measurement

The frequency range has been measured radiated using a test fixture and a spectrum analyser. The limit line is set to 20 dB below the carrier. The frequency of the upper ( $F_H$ ) and lower ( $F_L$ ) points, where the displayed power envelope of the modulation including frequency drift is equal to the appropriate level, is recorded as the modulation bandwidth. The measurement has been performed at normal and extreme test conditions in modulated transmitting mode.

Spectrum analyzer settings:

RBW: 1 kHz  
VBW: 3 kHz  
Detector Peak

#### 5.5.5 Test result

Carrier Frequency (MHz)	( $F_L$ ) (MHz)	( $F_H$ ) (MHz)	Bandwidth (kHz)	Limit (kHz)
13.56234	13.55954	13.56614	6.6	14.0

Limit according to FCC Part 15C, Section 15.215(c):


Frequency band (MHz)	Limit 20 dB bandwidth (kHz)
13.553 - 13.567	14.0

The requirements are **FULFILLED**.

**Remarks:** For detailed test result please refer to following test protocol.

FCC ID: YMQ-8051000

### 5.5.6 Test protocol



FCC ID: YMQ-8051000

## 5.6 Transmitter spectrum mask

For test instruments and accessories used see section 6 Part **MB**.

### 5.6.1 Description of the test location

Test location: AREA4

### 5.6.2 Photo documentation of the test set-up



FCC ID: YMQ-8051000

### 5.6.3 Applicable standard

According to FCC Part 15C, Section 15.225 (a-d):

The field strength of any emission shall not exceed the limits given in FCC Part 15C, Section 15.225 (a-d)

### 5.6.4 Description of Measurement

The spectrum mask is measured using a spectrum analyser. The profile of the spectrum mask is displayed on analyser and have to be adjusted to the reference level given as maximum output power measured in OATS. The marker is set up manually to the particular maximum level at the effective limit in the frequency range and recorded. The measurement was performed radiated.

### 5.6.5 Test result

Frequency band (MHz)	Emission level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
13.110 – 13.410	≤-10	40.5
13.410 - 13.553	7.1	50.5
13.553 - 13.567	17.3	84.0
13.567 – 13.710	7.1	50.5
13.710 – 14.010	≤-10	40.5
outside of 13.110 – 14.010	≤-10	29.5

Limits according to FCC Part 15C, Section 15.225(a-d):

The absolute levels of RF power at any frequency shall not exceed the limits defined in the following table:

Frequency band (MHz)	Emission level limit at 30 m ( $\mu$ V/m)
13.110 – 13.410	106
13.410 - 13.553	334
13.553 - 13.567	15,848
13.567 – 13.710	334
13.710 – 14.010	106
outside of 13.110 – 14.010	30


The requirements are **FULFILLED**.

Remarks:

FCC ID: YMQ-8051000

### 5.6.6 Test protocol

#### Spectrum mask of modulated signal



The values of the plot are extrapolated to a measurement distance of 3 m.

FCC ID: YMQ-8051000

## 5.7 Receiver radiated emissions

### 5.7.1 Description of the test location

Test location: None

### 5.7.2 Applicable standard

According to FCC Part 15, Section 15.109(a):

The emission of an unintentional radiator shall not exceed the specified field strength level at 3 m.

**Remarks:** This test is not applicable. The receive mode is too short to make an assessment.

---

---

**FCC ID: YMQ-8051000**

## **6 USED TEST EQUIPMENT AND ACCESSORIES**

All test instruments used are calibrated and verified regularly. The calibration history is available on request.

<b>Test ID</b>	<b>Model Type</b>	<b>Equipment No.</b>	<b>Next Calib.</b>	<b>Last Calib.</b>	<b>Next Verif.</b>	<b>Next Verif.</b>
CPR 1	FMZB 1516 ESCI	Magnetic Field Antenna EMI Test Receiver		Schwarzbeck Mess-Elektronik Rohde & Schwarz München	01-02/24-01-018 02-02/03-05-004	
FE	ESCI THS730A HZ-10 WK-340/40 9543A	Spectrum Analyzer Handheld Scope Magnetic Field Antenna Climatic Chamber Power Supply		Rohde & Schwarz München Tektronix GmbH	02-02/03-05-004 02-02/13-05-001	
MB	ESCI HZ-10	Spectrum Analyzer Magnetic Field Antenna		Rohde & Schwarz München Rohde & Schwarz München	02-02/03-05-004 02-02/24-05-012	
SER 1	FMZB 1516 ESCI	Magnetic Field Antenna EMI Test Receiver		Schwarzbeck Mess-Elektronik Rohde & Schwarz München	01-02/24-01-018 02-02/03-05-004	
SER 2	ESVS 30 VULB 9168 S10162-B KK-EF393-21N-16 NW-2000-NB	EMI Test Receiver Trilog Broad Band Antenna RF Cable 33 m RF Cable 20 m RF Cable		Rohde & Schwarz München Schwarzbeck Mess-Elektronik Huber + Suhner Huber + Suhner Huber + Suhner	02-02/03-05-006 02-02/24-05-005 02-02/50-05-031 02-02/50-05-033 02-02/50-05-113	
<b>Test ID</b>	<b>Model Type</b>	<b>Equipment No.</b>	<b>Next Calib.</b>	<b>Last Calib.</b>	<b>Next Verif.</b>	<b>Last Verif.</b>
CPR 1	FMZB 1516 ESCI	01-02/24-01-018 02-02/03-05-004	02/09/2011	02/09/2010	02/15/2011	02/15/2010
FE	ESCI THS730A HZ-10 WK-340/40 LNG32-3	02-02/11-05-001 02-02/13-05-001 02-02/24-05-012 02-02/45-05-001 02-02/50-07-034	02/09/2011 09/18/2010 02/09/2010 06/17/2014 02/09/2010	02/09/2010 09/18/2009 02/09/2010 06/17/2009 02/09/2010	12/10/2010	12/10/2009
MB	ESCI HZ-10	02-02/11-05-001 02-02/24-05-012	02/09/2011	02/09/2010		
SER 1	FMZB 1516 ESCI	01-02/24-01-018 02-02/03-05-004	02/09/2011	02/09/2010	02/15/2011	02/15/2010
SER 2	ESVS 30 VULB 9168 S10162-B KK-EF393-21N-16 NW-2000-NB	02-02/03-05-006 02-02/24-05-005 02-02/50-05-031 02-02/50-05-033 02-02/50-05-113	06/11/2011 05/06/2011 05/06/2008	06/11/2010 05/06/2008	10/01/2010	04/01/2010