



FCC CERTIFICATION TEST REPORT

Applicant	:	XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO.,LTD.
Address of Applicant	:	(5/F) NO.168, QIANPU ROAD, SIMING DISTRICT, XIAMEN, CHINA
Manufacturer	:	Xiamen Healthcare Electronic Co.,Ltd.
Address of Manufacturer	:	65-66#, 62-63#Building, Siming Zone, Tongan Industrial District, Xiamen City, Fujian Province, P.R. China
Equipment under Test	:	Massage Chair
Model No.	:	EI-8701F, OP-4D Master, EI-8701C, OP-Xrest 4D
FCC ID	:	YMX-EI8701F
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10:2013
Report No.	:	DDT-RE23030924-1E01
Issue Date	:	2024/06/20
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

Table of Contents

1.	Summary of Test Results	5
2.	General Test Information.....	6
2.1.	Description of EUT.....	6
2.2.	Accessories of EUT	6
2.3.	Assistant equipment used for test	6
2.4.	Block diagram of EUT configuration for test.....	6
2.5.	Decision of final test mode	7
2.6.	Deviations of test standard	7
2.7.	Test environment conditions.....	7
2.8.	Test laboratory	7
2.9.	Measurement uncertainty	8
3	Equipment Used During Test	9
4	20 dB Bandwidth.....	10
4.1.	Block diagram of test setup	10
4.2.	Limits.....	10
4.3.	Test procedure.....	10
4.4.	Test result	10
4.5.	Original test data.....	11
5.	Radiated Emission.....	12
5.1.	Test equipment	12
5.2.	Block diagram of test setup	13
5.3.	Limits.....	13
5.4.	Assistant equipment used for test	14
5.5.	Test procedure.....	14
5.6.	Test result	15
5.7.	Test data	16
6.	Power Line Conducted Emissions.....	24
6.1.	Test equipment	24
6.2.	Block diagram of test setup	24
6.3.	Limits.....	24
6.4.	Assistant equipment used for test	24
6.5.	Test procedure.....	25
6.6.	Test result	25
6.7.	Test data	26
7	Antenna Requirements	28
8.	Test Setup Photograph.....	29
9.	Photos of the EUT	31

Test Report Declare

Applicant	:	XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO.,LTD.
Address of Applicant	:	(5/F) NO.168, QIANPU ROAD, SIMING DISTRICT, XIAMEN, CHINA
Equipment under Test	:	Massage Chair
Model No.	:	EI-8701F, OP-4D Master, EI-8701C, OP-Xrest 4D
Manufacturer	:	Xiamen Healthcare Electronic Co.,Ltd.
Address of Manufacturer	:	65-66#, 62-63#Building, Siming Zone, Tongan Industrial District, Xiamen City, Fujian Province, P.R. China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10:2013

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE23030924-1E01		
Date of Receipt:	2023/03/13	Date of Test:	2023/03/13~2024/06/20

Prepared By:

Tiger Mo

Tiger Mo/Engineer

Approved By:

Damon Hu

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/06/20	

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	20 dB Bandwidth	FCC Part 15: 15.215	/	Pass
2	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209	/	Pass
3	Power Line Conducted Emissions	FCC Part 15: 15.207(a)	/	Pass
4	Antenna Requirement	FCC Part 15: 15.203	/	Pass

Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.

2. General Test Information

2.1. Description of EUT

EUT Name	: Massage Chair
Model Number	: EI-8701F, OP-4D Master, EI-8701C, OP-Xrest 4D
Difference of models	: Above models are identical in schematic, appearance and structure, only the Model Number is different for all the models, therefore the test performed on the model EI-8701F.
EUT Function Description	: Please reference user manual of this device
Power Supply	: 110-120V~ 60Hz
Sample Number	: S23030924-01

Wireless charging Operation frequency	: 110.5 kHz - 205 kHz
Antenna Type	: Inductive loop coil antenna

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.


2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	Other
Dummy load	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test



2.5. Decision of final test mode

According pre-test, the worst test modes were reported as below:

For mode 1: Tx mode (5W load, 7.5W load, 10W load)

For mode 2: Standby mode

Note: Scan with mode 1 and mode 2, the worst case is mode 1 Tx mode (10W load) and recorded in this report

2.6. Deviations of test standard

No deviation.

2.7. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.8. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.9. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7 x 10 ⁻⁸ (Antenna couple method)
	5.5 x 10 ⁻⁸ (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.40 dB (3.6 GHz ≤ f < 8 GHz)
	1.66 dB (8 GHz ≤ f < 26.5 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	3x10 ⁻⁸
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz)
	4.40 dB (6 GHz - 18 GHz)
	3.54 dB (18 GHz - 26 GHz)
	4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 Equipment Used During Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
<input checked="" type="checkbox"/> RF Connected Test (RF Measurement System 1#)				
SIGNAL ANALYZER	R&S	FSQ26	101272	2025/03/31
Wideband Radio Communication Tester	R&S	CMW500	120259	2024/07/14
MXG Vector Signal Generator	KEYSIGHT	N5182B	MY59100192	2025/03/31
MXG Vector Signal Generator	Agilent	N5182A	MY19060405	2025/03/31
RF Control Unit	Tonsend	JS0806-2	158060010	2025/03/31
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2025/04/22
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A

4 20 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3. Test procedure

(1) Connect EUT to spectrum analyzer and use the following settings:


Centre Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	1% to 5% of the occupied bandwidth
VBW	Approximately 3xRBW
Trace	Max hold
Sweep	Auto

(2) The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

4.4. Test result

Freq. (kHz)	20 dB bandwidth Result (Hz)	Conclusion
120.12	25.96	Pass

4.5. Original test data





5. Radiated Emission

5.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2025/09/18
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2024/07/11
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2024/07/14
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31

5.2. Block diagram of test setup



5.3. Limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~ 88	3	100	40.0
88~ 216	3	150	43.5
216~ 960	3	200	46.0
960~ 1000	3	500	54.0

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 40\text{Log}(300\text{m}/3\text{m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 80$$

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40$$

5.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

5.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.


5.6. Test result

PASS. (See below detailed test result)

5.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-21 **Tested By:** Bairong
EUT: Massage Chair **Model Number:** EI-8701F
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:62.2% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report date\Q23030924-1E EI-8701F\FCC BELOW 1G 9K-30M\20230321-143103_V
Memo: parallel



Suspected Data List										
NO	Freq. [MHz]	Reading [dBµV]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.02	80.57	0.07	19.76	-30.90	69.50	119.89	50.39	PK	parallel
2	0.05	75.55	0.07	19.78	-31.19	64.21	114.18	49.97	PK	parallel
3	0.06	73.51	0.07	19.82	-31.31	62.09	112.66	50.57	PK	parallel
4	0.09	75.48	0.08	19.90	-31.79	63.67	108.23	44.56	PK	parallel
5	0.12	108.02	0.08	19.87	-32.09	95.88	106.28	10.40	PK	parallel
6	0.15	57.22	0.08	19.81	-32.49	44.62	104.24	59.62	PK	parallel


Final Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.02	69.54	0.07	19.76	-30.90	58.47	119.88	61.41	AV	parallel
2	0.05	64.88	0.07	19.78	-31.19	53.54	114.18	60.64	AV	parallel
3	0.06	62.32	0.07	19.82	-31.31	50.90	112.67	61.77	AV	parallel
4	0.09	63.11	0.08	19.90	-31.79	51.30	108.23	56.93	AV	parallel
5	0.12	99.24	0.08	19.87	-32.09	87.10	106.27	19.17	AV	parallel
6	0.15	52.64	0.08	19.81	-32.49	40.04	104.24	64.20	AV	parallel

Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-21 **Tested By:** Bairong
EUT: Massage Chair **Model Number:** EI-8701F
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:62.2% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report date\Q23030924-1E EI-8701F\FCC BELOW 1G 9K-30M\20230321-143415_V
Memo: parallel



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.23	77.54	0.08	19.72	-32.47	64.87	100.29	35.42	PK	parallel
2	0.28	70.25	0.08	19.71	-32.44	57.60	98.68	41.08	PK	parallel
3	0.35	87.73	0.08	19.74	-32.41	75.14	96.72	21.58	PK	parallel


Final Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.23	67.21	0.08	19.72	-32.47	54.54	100.28	45.74	AV	parallel
2	0.28	60.23	0.08	19.71	-32.44	47.58	98.68	51.10	AV	parallel
3	0.35	77.00	0.08	19.74	-32.41	64.41	96.72	32.31	AV	parallel
4	0.58	75.76	19.83	0.09	-32.36	63.32	72.31	8.99	QP	parallel
5	0.82	68.36	19.98	0.11	-32.33	56.12	69.36	13.24	QP	parallel
6	1.05	64.03	20.19	0.12	-32.32	52.02	67.20	15.18	QP	parallel

Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-21 **Tested By:** Bairong
EUT: Massage Chair **Model Number:** EI-8701F
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:62.2% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report date\Q23030924-1E EI-8701F\FCC BELOW 1G 9K-30M\20230321-143156_V
Memo: perpendicular



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.02	79.08	0.07	19.79	-30.86	68.08	121.06	52.98	PK	perpendicular
2	0.04	73.98	0.07	19.76	-31.13	62.68	115.09	52.41	PK	perpendicular
3	0.06	72.34	0.07	19.82	-31.31	60.92	112.65	51.73	PK	perpendicular
4	0.09	67.89	0.08	19.90	-31.79	56.08	108.22	52.14	PK	perpendicular
5	0.12	105.94	0.08	19.87	-32.09	93.80	106.28	12.48	PK	perpendicular
6	0.14	52.16	0.08	19.82	-32.37	39.69	104.82	65.13	PK	perpendicular

Final Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.02	64.32	0.07	19.79	-30.86	53.32	121.07	67.75	AV	perpendicular
2	0.04	60.23	0.07	19.76	-31.13	48.93	115.09	66.16	AV	perpendicular
3	0.06	60.17	0.07	19.82	-31.31	48.75	112.65	63.90	AV	perpendicular
4	0.09	59.62	0.08	19.90	-31.79	47.81	108.22	60.41	AV	perpendicular
5	0.12	95.10	0.08	19.87	-32.09	82.96	106.27	23.31	AV	perpendicular
6	0.14	48.86	0.08	19.82	-32.37	36.39	104.82	68.43	AV	perpendicular

Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-21

Tested By: Bairong

EUT: Massage Chair

Model Number: EI-8701F

Test Mode: TX Mode


Power Supply: AC 120V/60Hz

Condition: Temp:22.2°C;Humi:62.2%

Test Site: DDT 3# Chamber

File Path: d:\ts\2023 report date\Q23030924-1E EI-8701F\FCC BELOW 1G 9K-30M\20230321-145051_V

Memo: perpendicular



Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.28	69.30	0.08	19.71	-32.43	56.66	98.65	41.99	PK	perpendicular
2	0.35	80.45	0.08	19.74	-32.41	67.86	96.63	28.77	PK	perpendicular

Final Data List


NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.28	66.21	0.08	19.71	-32.43	53.57	98.65	45.08	AV	perpendicular
2	0.35	70.51	0.08	19.74	-32.41	57.92	96.63	38.71	AV	perpendicular
3	0.59	68.83	19.84	0.09	-32.35	56.41	72.19	15.78	QP	perpendicular
4	0.83	61.42	19.99	0.11	-32.33	49.19	69.27	20.08	QP	perpendicular
5	1.06	57.2	20.19	0.12	-32.32	45.19	67.09	21.90	QP	perpendicular
6	15.31	43.27	19.92	0.45	-32.33	31.31	69.54	38.23	QP	perpendicular

Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-21 **Tested By:** Bairong
EUT: Massage Chair **Model Number:** EI-8701F
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:62.2% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report date\Q23030924-1E EI-8701F\FCC BELOW 1G 9K-30M\20230321-143240_V
Memo: round-parallel



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.01	60.69	0.07	19.88	-30.74	49.90	125.76	75.86	PK	round-
2	0.02	78.83	0.07	19.79	-30.86	67.83	121.10	53.27	PK	round-
3	0.04	75.23	0.07	19.76	-31.13	63.93	115.07	51.14	PK	round-
4	0.06	69.87	0.07	19.85	-31.41	58.38	111.55	53.17	PK	round-
5	0.09	71.74	0.08	19.90	-31.79	59.93	108.21	48.28	PK	round-
6	0.12	106.54	0.08	19.87	-32.09	94.40	106.28	11.88	PK	round-

Final Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.01	68.25	0.07	19.88	-30.74	57.46	125.80	68.34	AV	round-
2	0.02	64.67	0.07	19.79	-30.86	53.67	121.11	67.44	AV	round-
3	0.04	62.33	0.07	19.76	-31.13	51.03	115.07	64.04	AV	round-
4	0.06	63.27	0.07	19.85	-31.41	51.78	111.56	59.78	AV	round-
5	0.09	64.52	0.08	19.90	-31.79	52.71	108.20	55.49	AV	round-
6	0.12	98.87	0.08	19.87	-32.09	86.73	106.27	19.54	AV	round-

Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-21

Tested By: Bairong

EUT: Massage Chair

Model Number: EI-8701F

Test Mode: TX Mode


Power Supply: AC 120V/60Hz

Condition: Temp:22.2°C;Humi:62.2%

Test Site: DDT 3# Chamber

File Path: d:\ts\2023 report date\Q23030924-1E EI-8701F\FCC BELOW 1G 9K-30M\20230321-145153_V

Memo: round-parallel



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.28	70.95	0.08	19.71	-32.43	58.31	98.65	40.34	PK	round-
2	0.35	80.52	0.08	19.74	-32.41	67.93	96.63	28.70	PK	round-

Final Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.28	60.58	0.08	19.71	-32.43	47.94	98.65	50.71	AV	round-
2	0.35	71.25	0.08	19.74	-32.41	58.66	96.63	37.97	AV	round-
3	0.59	68.39	19.84	0.09	-32.35	55.97	72.19	16.22	QP	round-
4	0.83	61.33	19.99	0.11	-32.33	49.10	69.27	20.17	QP	round-
5	2.27	47.57	19.89	0.15	-32.32	35.29	69.54	34.25	QP	round-
6	15.31	42.17	19.92	0.45	-32.33	30.21	69.54	39.33	QP	round-

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

Radiated Emission test (Above 30 MHz)

TR-4-E-009 Radiated Emission Test Result

Test Date:	2023-03-21	Tested By:	Bairong
EUT:	Massage Chair	Model Number:	EI-8701F
Test Mode:	TX Mode	Power Supply:	AC 120V/60Hz
Condition:	Temp:22.2°C;Humi:62.2%	Test Site:	DDT 3# Chamber
File Path:	d:\ts\2023 report date\Q23030924-1E EI-8701F\FCC BELOW 1G\20230321-142001_H		

Memo:



Final Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	57.47	35.03	12.31	0.90	-32.27	15.97	40.00	24.03	QP	Horizontal
2	96.21	40	10.52	1.36	-32.24	19.64	43.50	23.86	QP	Horizontal
3	180.84	49.63	9.28	1.89	-32.24	28.56	43.50	14.94	QP	Horizontal
4	399.94	46.78	15.40	2.86	-32.36	32.68	46.00	13.32	QP	Horizontal
5	519.86	42.33	17.30	3.22	-32.57	30.28	46.00	15.72	QP	Horizontal
6	799.58	40.45	21.20	4.13	-32.78	33.00	46.00	13.00	QP	Horizontal


Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-21 **Tested By:** Bairong
EUT: Massage Chair **Model Number:** EI-8701F
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:62.2% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report date\Q23030924-1E EI-8701F\FCC BELOW 1G\20230321-142042_V

Memo:



Final Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	55.95	46.73	12.51	0.88	-32.27	27.85	40.00	12.15	QP	Vertical
2	96.14	48.99	10.51	1.35	-32.24	28.61	43.50	14.89	QP	Vertical
3	153.47	47.48	7.65	1.72	-32.19	24.66	43.50	18.84	QP	Vertical
4	204.59	47.4	10.79	2.02	-32.26	27.95	43.50	15.55	QP	Vertical
5	479.92	47.77	16.60	3.08	-32.50	34.95	46.00	11.05	QP	Vertical
6	719.75	39.37	20.30	3.89	-32.84	30.72	46.00	15.28	QP	Vertical

Note:


1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

6. Power Line Conducted Emissions

6.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Δ -shaped artificial power network	SCHWARZBEC K	PVDC 8301	DDT-ZC03939	2025/04/01
Pulse Limiter	SCHWARZBEC K	VTSD 9561	DDT-ZC02128	2024/07/14
EMI Test Receiver	R&S	ESCI/E3	DDT-ZC01297	2024/07/11
Conducted Radiated Software	Audix	E3	DDT-ZC00562	/
Two Line V-Network	R&S	ENV216	DDT-ZC02056	2024/07/11
RF Cable	Yuhu Technology	Z806-NJ-NJ-6M	DDT-ZC02004	2024/07/14
Three-phase artificial power network	SCHWARZBEC K	NSLK 8163	DDT-ZC01572	2024/07/11
Two Line V-Network	R&S	ENV216	DDT-ZC02059	2024/07/11

6.2. Block diagram of test setup



6.3. Limits

Frequency	Quasi-Peak Level dB(mV)	Average Level dB(mV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

6.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

6.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

6.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.


Note2: “-----” means Peak detection; “-----” means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

6.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 6# Shield Room	D:\2023 Report Data\Q23030924-1E\CE-FCC.EM6	
Test Date	: 2023-03-21	Tested By	: Junchang Du
EUT	: Massage Chair	Model Number	: EI-8701F
Power Supply	: AC 120V/60Hz	Test Mode	: TX Mode
Condition	: Temp:21.8°C,Humi:59.2%	LISN	: 2022 ENV 216 3#/NEUTRAL
Memo	:		




Item (Mark)	Freq. (MHz)	Read Level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Detector	Phase
1	0.15	31.07	9.70	0.13	9.83	50.73	66.00	-15.27	QP	NEUTRAL
2	0.15	16.84	9.70	0.13	9.83	36.50	56.00	-19.50	Average	NEUTRAL
3	0.34	17.31	9.60	0.13	9.83	36.87	59.09	-22.22	QP	NEUTRAL
4	0.34	0.03	9.60	0.13	9.83	19.59	49.09	-29.50	Average	NEUTRAL
5	0.42	21.43	9.60	0.13	9.83	40.99	57.46	-16.47	QP	NEUTRAL
6	0.42	10.50	9.60	0.13	9.83	30.06	47.46	-17.40	Average	NEUTRAL
7	0.59	8.43	9.65	0.13	9.83	28.04	56.00	-27.96	QP	NEUTRAL
8	0.59	-1.70	9.65	0.13	9.83	17.91	46.00	-28.09	Average	NEUTRAL
9	12.06	9.60	9.62	0.08	9.86	29.16	60.00	-30.84	QP	NEUTRAL
10	12.06	2.77	9.62	0.08	9.86	22.33	50.00	-27.67	Average	NEUTRAL
11	24.40	2.18	10.00	0.07	9.92	22.17	60.00	-37.83	QP	NEUTRAL
12	24.40	-10.24	10.00	0.07	9.92	9.75	50.00	-40.25	Average	NEUTRAL

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 6# Shield Room	D:\2023 Report Data\Q23030924-1E\CE-FCC.EM6	
Test Date	: 2023-03-21	Tested By	: Junchang Du
EUT	: Massage Chair	Model Number	: EI-8701F
Power Supply	: AC 120V/60Hz	Test Mode	: TX Mode
Condition	: Temp:21.8°C,Humi:59.2%	LISN	: 2022 ENV 216 3#/LINE
Memo	:		



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Detector	Phase
1	0.16	30.35	9.80	0.13	9.83	50.11	65.34	-15.23	QP	LINE
2	0.16	13.65	9.80	0.13	9.83	33.41	55.34	-21.93	Average	LINE
3	0.34	19.04	9.80	0.13	9.83	38.80	59.09	-20.29	QP	LINE
4	0.34	-2.17	9.80	0.13	9.83	17.59	49.09	-31.50	Average	LINE
5	0.41	16.29	9.80	0.13	9.83	36.05	57.59	-21.54	QP	LINE
6	0.41	2.96	9.80	0.13	9.83	22.72	47.59	-24.87	Average	LINE
7	0.72	10.09	9.79	0.13	9.83	29.84	56.00	-26.16	QP	LINE
8	0.72	0.32	9.79	0.13	9.83	20.07	46.00	-25.93	Average	LINE
9	12.00	8.65	9.61	0.09	9.86	28.21	60.00	-31.79	QP	LINE
10	12.00	2.87	9.61	0.09	9.86	22.43	50.00	-27.57	Average	LINE
11	25.06	2.61	9.83	0.06	9.92	22.42	60.00	-37.58	QP	LINE
12	25.06	-11.41	9.83	0.06	9.92	8.40	50.00	-41.60	Average	LINE

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

7 Antenna Requirements

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Conclusion: The antenna used for this product is inductive loop coil antenna and that no antenna other than that furnished by the responsible party shall be used with the device.

9. Photos of the EUT

Please refer to DDT-Q23030924-1E appendix I

-----End Report-----