

FCC PART 15.247 TEST REPORT

For

Kichler Lighting

7711 E. Pleasant Valley Road Cleveland, Oh 44131-8010, USA

FCC ID: YNE-49473RZLED

Report Type: Product Name: Original Report portable lantern Lorin Bian Test Engineer: Lorin Bian Report Number: RDG170223053B **Report Date:** 2017-03-17 **Henry Ding EMC Leader** Reviewed By: **Test Laboratory:** Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
MEASUREMENT UNCERTAINTY	
Test Facility	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EQUIPMENT MODIFICATIONS	
EUT Exercise Software	
EXTERNAL CABLEBLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
Antenna Connector Construction	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
Measurement Uncertainty	11
EUT SETUP	
EMI Test Receiver Setup	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
MEASUREMENT UNCERTAINTY	
EUT SETUP.	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
Test Procedure	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
Test Results Summary	
TEST DATA	
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS TEST DATA	
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	
1 00 \$13.241 (b) (3) - WAXIMOW COMPOCIED OUTFUT FOWER	

Bay Area Compliance Laboratories Corp. (Chengdu)

APPLICABLE STANDARD	24
Test Procedure	24
TEST EQUIPMENT LIST AND DETAILS	24
TEST DATA	
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	27
APPLICABLE STANDARD	
Test Procedure	27
TEST EQUIPMENT LIST AND DETAILS	
Test Data	28
FCC §15.247(e) - POWER SPECTRAL DENSITY	30
APPLICABLE STANDARD	30
Test Procedure	30
TEST EQUIPMENT LIST AND DETAILS	30
TEST DATA	30

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Kichler Lighting*'s product, model number: *49473RZLED* (*FCC ID: YNE-49473RZLED*) or (the "EUT") in this report was a *portable lantern*, which was measured approximately: 15 cm (L) x 15 cm (W) x 48 cm (H), rated input voltage: DC3.6V from battery or DC 5V charged from adapter.

Adapter Information:

Model: HB20-0503004SPA Input: AC100-240V 50/60Hz 0.5A

Output: DC5V, 3000mA

Note: The series product, models 49473xxxLED(xxx denotes fixture finish. Example RZ, BKT, WHT, NI, OZ.) are electrically identical with 49473RZLED, the difference between them is the model name and color, we selected 49473RZLED for fully testing, the details was explained in the attached declaration letter.

*All measurement and test data in this report was gathered from final production sample, serial number: 170223053 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2017-03-01, and EUT conformed to test requirement.

Objective

This report is prepared on behalf of *Kichler Lighting* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207,15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: YNE-49473RZLED.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Chengdu). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Report No.: RDG170223053B Page 4 of 32

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Unwanted Emissions, conducted	±1.5dB
Unwanted Emissions, radiated	30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The test site used by BACL to collect test data is located in the No.5040, HuiLongWan Plaza, No. 1, ShaWan Road, JinNiu District, ChengDu, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Report No.: RDG170223053B Page 5 of 32

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404		•••
		38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

EUT Exercise Software

The software 'Bluetooth MP Tool' was used during testing, the system configured maxmum output power as default setting. The software is only for changing channel and modes.

Equipment Modifications

No modification was made to the EUT tested.


EUT Exercise Software

The test mode was configured by manufacture setting with duty cycle as below:

Test mode	T _{on}	T _{on+off}	Duty Cycle	
	(ms)	(ms)	(%)	
BLE	0.397	0.709	56%	

Report No.: RDG170223053B Page 6 of 32


Bay Area Compliance Laboratories Corp. (Chengdu)



External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
Adapter Cable	No	No	1.08	Adapter	EUT

Block Diagram of Test Setup



Report No.: RDG170223053B Page 7 of 32

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum conducted output power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Report No.: RDG170223053B Page 8 of 32

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

- mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
 - 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is 7.0 dBm (5 mW). [(max. power of channel, mW)/(min. test separation distance, mm)][$\sqrt{f(GHz)}$] = $5/5*(\sqrt{2.480})$ = 1.6<3.0

So the SAR evaluation is not necessary.

Report No.: RDG170223053B Page 9 of 32

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal antenna arrangement for BT, and the antenna gain is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

Report No.: RDG170223053B Page 10 of 32

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- -compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


- -compliance is deemed to occur if no measured disturbance level, increased by ($U_{lab} U_{cispr}$), exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Chengdu) is ±3.17 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}	
Conducted disturbance at mains port using AMN	(150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

Report No.: RDG170223053B Page 11 of 32

The setup of EUT was according to ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The power cables and external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to an AC120V/60Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,s

V_C: corrected voltage amplitude V_R: reading voltage amplitude A_c: attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "**Margin**" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Equipment List and Details

Manufacturer	Description	Model Number	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2016-12-02	2017-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	3560.6550.06	2016-12-02	2017-12-01
Rohde & Schwarz	PULSE LIMITER	ESH3Z2	357.8810.52	2016-10-31	2017-10-30
N/A	Conducted Cable	NO.5	N/A	2016-11-10	2017-11-09
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

^{*} **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions


Temperature:	18 °C
Relative Humidity:	56 %
ATM Pressure:	95.5 kPa

The testing was performed by Lorin Bian on 2017-03-15.

Report No.: RDG170223053B Page 13 of 32

Test Mode: Transmitting

AC120V/60Hz, Line




Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.450448	44.7	9.000	L1	19.7	12.2	56.9	Compliance
0.595338	51.0	9.000	L1	19.8	5.0	56.0	Compliance
0.732382	52.5	9.000	L1	19.7	3.5	56.0	Compliance
0.738241	52.3	9.000	L1	19.7	3.7	56.0	Compliance
1.441726	48.0	9.000	L1	19.7	8.0	56.0	Compliance
2.164561	45.8	9.000	L1	19.8	10.2	56.0	Compliance

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.595338	39.3	9.000	L1	19.8	6.7	46.0	Compliance
0.726569	40.0	9.000	L1	19.7	6.0	46.0	Compliance
0.738241	38.3	9.000	L1	19.7	7.7	46.0	Compliance
2.030886	33.1	9.000	L1	19.8	12.9	46.0	Compliance
2.325491	33.1	9.000	L1	19.7	12.9	46.0	Compliance
4.127365	34.1	9.000	L1	19.7	11.9	46.0	Compliance

Report No.: RDG170223053B Page 14 of 32

AC120V/60Hz, Neutral



Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.426011	42.7	9.000	N	19.6	14.6	57.3	Compliance
0.595338	48.4	9.000	N	19.6	7.6	56.0	Compliance
0.726569	49.0	9.000	N	19.6	7.0	56.0	Compliance
0.738241	49.0	9.000	N	19.6	7.0	56.0	Compliance
0.937592	40.8	9.000	N	19.7	15.2	56.0	Compliance
1.611870	41.1	9.000	N	19.7	14.9	56.0	Compliance

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.426011	29.0	9.000	N	19.6	18.3	47.3	Compliance
0.600101	32.1	9.000	N	19.6	13.9	46.0	Compliance
0.732382	35.4	9.000	N	19.6	10.6	46.0	Compliance
0.738241	36.0	9.000	N	19.6	10.0	46.0	Compliance
1.239175	33.2	9.000	N	19.6	12.8	46.0	Compliance
1.269154	31.7	9.000	N	19.6	14.3	46.0	Compliance

Report No.: RDG170223053B Page 15 of 32

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 2, then:

- -compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 2, then:

- –compliance is deemed to occur if no measured disturbance level, increased by ($U_{lab} U_{cispr}$), exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level, increased by ($U_{lab} U_{cispr}$), exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Chengdu) is:

30M~200MHz: ±4.7 dB; 200M~1GHz: ±6.0 dB; 1G~6GHz: ±5.13dB; 6G~25GHz: ±5.47 dB;


Table 2 – Values of U_{cispr}

Measurement				
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB			
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB			
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB			


Report No.: RDG170223053B Page 16 of 32

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

Report No.: RDG170223053B Page 17 of 32

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Detector	RBW	Video B/W	IF B/W	
QP	120 kHz	300 kHz	120kHz	

1GHz-25GHz:

Detector	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ava	>98%	1MHz	10 Hz
Ave.	<98%	1MHz	1/T

Note: T is minimum transmission duration

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Loss + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit - Corrected Amplitude

Report No.: RDG170223053B Page 18 of 32

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A101808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726- 0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2016-12-02	2017-12-01
EMCT	Semi-Anechoic Chamber	966	N/A	2015-04-24	2018-04-23
N/A	RF Cable (below 1GHz)	NO.1	N/A	2016-11-10	2017-11-09
N/A	RF Cable (below 1GHz)	NO.4	N/A	2016-11-10	2017-11-09
N/A	RF Cable (above 1GHz)	NO.2	N/A	2016-11-10	2017-11-09

^{*} **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247</u>.

Test Data

Environmental Conditions

Temperature:	24.6 °C	
Relative Humidity:	46 %	
ATM Pressure:	96.6 kPa	

^{*} The testing was performed by Lorin Bian on 2017-02-23.

Test Mode: Transmitting

Report No.: RDG170223053B Page 19 of 32

30MHz-25GHz:

_	Rece	eiver	Rx Aı	ntenna	Cable	Amplifier	Corrected		
Frequency (MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	, , ,		Lo	ow Chann	el: 2402	MHz			
2402	75.51	PK	Н	23.53	3.00	0.00	102.04	N/A	N/A
2402	68.41	AV	H	23.53	3.00	0.00	94.94	N/A	N/A
2402	68.61	PK	V	23.53	3.00	0.00	95.14	N/A	N/A
2402	60.49	AV	V	23.53	3.00	0.00	87.02	N/A	N/A
2390	33.66	PK	V	23.57	3.00	0.00	60.23	74	13.77
2390	19.65	AV	V	23.57	3.00	0.00	46.22	54	7.78
4804	44.68	PK	V	30.77	5.12	26.87	53.7	74	20.3
4804	34.34	AV	V	30.77	5.12	26.87	43.36	54	10.64
7206	40.30	PK	V	34.71	6.16	26.35	54.82	74	19.18
7206	30.29	AV	V	34.71	6.16	26.35	44.81	54	9.19
9608	40.76	PK	V	37.06	7.82	26.18	59.46	74	14.54
9608	29.07	AV	V	37.06	7.82	26.18	47.77	54	6.23
3119	47.76	PK	V	24.87	3.61	26.45	49.79	74	24.21
3119	37.20	AV	V	24.87	3.61	26.45	39.23	54	14.77
58.13	55.14	QP	Н	7.59	0.40	28.44	34.69	40.00	5.31
104.69	53.78	QP	H	12.11	0.61	28.24	38.26	43.50	5.24
	· ·			dle Char					
2440	75.01	PK	H	23.40	3.00	0.00	101.41	N/A	N/A
2440	66.78	AV	Н	23.40	3.00	0.00	93.18	N/A	N/A
2440	67.47	PK	V	23.40	3.00	0.00	93.87	N/A	N/A
2440	59.35	AV	V	23.40	3.00	0.00	85.75	N/A	N/A
4880	44.78	PK	V	31.02	5.09	26.87	54.02	74	19.98
4880	35.61	AV	V	31.02	5.09	26.87	44.85	54	9.15
7320	40.86	PK	V	34.94	6.22	26.40	55.62	74	18.38
7320	30.60	AV PK	V	34.94	6.22	26.40	45.36	54	8.64
9760	41.39 31.70		V	37.16 37.16	7.71 7.71	26.27 26.27	59.99 50.3	74 54	14.01 3.7
9760 2601	46.73	AV PK	V	23.40	3.08	26.79	46.42	74	27.58
2601	35.26	AV	V	23.40	3.08	26.79	34.95	54	19.05
1589	41.71	PK	V	24.24	2.74	26.42	42.27	74	31.73
1589	31.56	AV	V	24.24	2.74	26.42	32.12	54	21.88
58.13	55.41	QP	H	7.59	0.40	28.44	34.96	40.00	5.04
104.69	53.92	QP	H	12.11	0.61	28.24	38.40	43.50	5.10
101.00	00.02	<u> </u>		gh Chanr			00.10	10.00	0.10
2480	71.80	PK	Н	23.27	2.99	0.00	98.06	N/A	N/A
2480	64.62	AV	H	23.27	2.99	0.00	90.88	N/A	N/A
2480	64.73	PK	V	23.27	2.99	0.00	90.99	N/A	N/A
2480	56.23	AV	V	23.27	2.99	0.00	82.49	N/A	N/A
2483.5	35.76	PK	V	23.26	2.99	0.00	62.01	74	11.99
2483.5	21.26	AV	V	23.26	2.99	0.00	47.51	54	6.49
4960	44.15	PK	V	31.27	5.05	26.88	53.59	74	20.41
4960	34.38	AV	V	31.27	5.05	26.88	43.82	54	10.18
7440	42.27	PK	V	35.18	6.27	26.45	57.27	74	16.73
7440	32.74	AV	V	35.18	6.27	26.45	47.74	54	6.26
9920	40.73	PK	V	37.25	7.60	26.37	59.21	74	14.79
9920	30.84	AV	V	37.25	7.60	26.37	49.32	54	4.68
1659	42.03	PK	V	24.35	2.79	26.49	42.68	74	31.32
1659	30.55	AV	V	24.35	2.79	26.49	31.2	54	22.8
58.13	56.25	QP	Н	7.59	0.40	28.44	35.80	40.00	4.20
104.69	54.34	QP	Н	12.11	0.61	28.24	38.82	43.50	4.68

Report No.: RDG170223053B Page 20 of 32


FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) ≥ 3×RBW
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	1

^{*} **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	21.7 °C
Relative Humidity:	50 %
ATM Pressure:	95.4 kPa

^{*} The testing was performed by Lorin Bian on 2017-03-13.

Report No.: RDG170223053B Page 21 of 32

Bay Area Compliance Laboratories Corp. (Chengdu)

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
Low	2402	0.54	≥0.5
Middle	2440	0.54	≥0.5
High	2480	0.54	≥0.5

Low Channel




Report No.: RDG170223053B Page 22 of 32

Middle Channel



CC. 13.MARC.2017 20.30.20

High Channel




FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

- a) Set the RBW ≥ DTS bandwidth.
- b) Set VBW ≥ 3 RBW.
- c) Set span ≥ 3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	1

^{*} **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Report No.: RDG170223053B Page 24 of 32

Test Data

Environmental Conditions

Temperature:	21.7 °C	
Relative Humidity:	50 %	
ATM Pressure:	95.4 kPa	


^{*} The testing was performed by Lorin Bian on 2017-03-13.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Limit (dBm)
Low	2402	6.5	30
Middle	2440	5.19	30
High	2480	3.61	30

Low Channel



Report No.: RDG170223053B Page 25 of 32

Middle Channel



13.MMC.2017 20.33.01

High Channel



Date: 13.MAR.2017 20:56:51

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	1

^{*} Statement of Traceability: BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Report No.: RDG170223053B Page 27 of 32

Test Data

Environmental Conditions


Temperature:	21.7 °C	
Relative Humidity:	50 %	
ATM Pressure:	95.4 kPa	

^{*} The testing was performed by Lorin Bian on 2017-03-13.


Test mode: Transmitting

Test Result: Compliant. Please refer to following plots.

BLE Band Edge, Left Side



Report No.: RDG170223053B Page 28 of 32



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS channel bandwidth.
- 4. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	1

^{*} **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	21.7 °C	
Relative Humidity:	50 %	
ATM Pressure:	95.4 kPa	

^{*} The testing was performed by Lorin Bian on 2017-03-13.

Report No.: RDG170223053B Page 30 of 32


Bay Area Compliance Laboratories Corp. (Chengdu)

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-4.2	≤8
Middle	2440	-5.43	≤8
High	2480	-7.07	≤8

Low Channel




Report No.: RDG170223053B Page 31 of 32

Middle Channel



High Channel



***** END OF REPORT *****