

## **TEST REPORT**

Report No.: HK10080771-1

Goldie Marketing Pty. Ltd.

**Application** For Certification

(Original Grant)

(FCC ID: YPS-GM98323919)

**Transmitter** 

Prepared and Checked by: Approved by:

Signed On File Kung Wing Cheong, Steven **Assistant Engineer** 

Chan Chi Hung, Terry Senior Lead Engineer Date: October 13, 2010

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material product or service is or than only that the material product or service is or than only in the product or service is or the sample tested. material, product, or service is or has ever been under an Intertek certification program.

## **GENERAL INFORMATION**

# GOLDIE MARKETING PTY. LTD. MODEL: NI-233

FCC ID: YPS-GM98323919

Grantee:	Goldie Marketing Pty. Ltd.				
Grantee Address:	Unit 1,				
	51-53 Power Road,				
	Bayswater VIC 3153,				
	Melbourne, Australia.				
Contact Person:	Stephen Goldsworthy				
Tel:	61-3-97206186				
Fax:	N/A				
e-mail:	N/A				
Manufacturer:	N/A				
Manufacturer Address:	N/A				
Brand Name:	N/A				
Model:	NI-233				
Type of EUT:	Transmitter				
Description of EUT:	Radio Control Kart Large Yoshi				
Serial Number:	N/A				
FCC ID:	YPS-GM98323919				
Date of Sample	August 17, 2010				
Submitted:					
Date of Test:	August 23, 2010				
Report No.:	HK10080771-1				
Report Date:	October 13, 2010				
Environmental Conditions:	Temperature: +10 to 40°C				
	Humidity: 10 to 90%				

## **SUMMARY OF TEST RESULT**

# GOLDIE MARKETING PTY. LTD. MODEL: NI-233

FCC ID: YPS-GM98323919

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	N/A
Hopping Channel Carrier Frequencies	15.247(e) / RSS-210 A8.1	N/A
Separation		
20dB Bandwidth of the Hopping Channel	15.247(a) / RSS-210 A8.1	N/A
Number of Hopping Frequencies	15.247(e) / RSS-210 A8.1	N/A
Average Time of Occupancy of Hopping	15.247(e) / RSS-210 A8.1	N/A
Frequency		
Anteann Conducted Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
RF Exposure Compliance	15.247(i) / RSS-Gen 5.5	N/A
Transmitter Power Line Conducted	15.207 / RSS-Gen 7.2.2	N/A
Emissions		
Transmitter Field Strength	15.227 / RSS-310 3.8	N/A
Transmitter Field Strength	15.229 / RSS-210 A2.7	N/A
Transmitter Field Strength, Bandwidth	15.231(a) / RSS-210 A1.1.1	N/A
and Timing Requirement		
Transmitter Field Strength, Bandwidth	15.231(e) / RSS-210 A1.1.5	N/A
and Timing Requirement		
Transmitter Field Strength and	15.239 / RSS-210 A2.8	N/A
Bandwidth Requirement		
Transmitter Field Strength and	15.249 / RSS-210 A2.9	N/A
Bandwidth Requirement		
Transmitter Field Strength and	15.235 / RSS-310 3.9	Pass
Bandwidth Requirement		
Receiver / Digital Device Radiated	15.109 / ICES-003	N/A
Eissions		
Digital Device Conducted Emissions	15.107 / ICES-003	N/A

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.

2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

## **Table of Contents**

1.0	General Description	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants	1
1.3	Test Methodology	1
1.4	Test Facility	1
2.0	System Test Configuration	9
2.0 2.1	System Test Configuration  Justification	
2.1		
2.2	EUT Exercising Software	
	Special Accessories	
2.4	Equipment Modification	
2.5	Measurement Uncertainty	
2.6	Support Equipment List and Description	₫
3.0	Emission Results	3
3.1	Field Strength Calculation	
3.2	Radiated Emission Configuration Photograph	
3.3	Radiated Emission Data	
4.0	Equipment Photographs	6
5.0	Product Labelling	6
0.0		
6.0	Technical Specifications	6
7.0	Instruction Manual	6
8.0	Missellaneous Information	6
o.u 8.1	Miscellaneous Information Measured Bandwidth	0
o. 1 8.2		
8.2 8.3	Discussion Pulse Desensitivity	
	Calculation of Average Factor	
8.4	Emissions Test Procedures	č
9.0	Confidentiality Request	9
10.0	Equipment List	10
IU.U	Equipment List	ΞŪ

## 1.0 **General Description**

## 1.1 Product Description

The equipment under test (EUT) is a transmitter for a RC Car operating at 49.860MHz which is controlled by a crystal. The EUT is powered by a 9VDC battery. The EUT has 1 ON/OFF switch, 1 control stick and 1 control wheel. When the EUT is switched ON, the control stick is used to control the RC Car moving forward, backward and the control wheel is used to control the RC Car turning left and right.

Antenna Type: External, Telescope-type antenna (with unique antenna connector)

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

## 1.2 Related Submittal(s) Grants

The Certification procedure of receiver (with FCC ID: YPS-GM98323920) for this transmitter is being processed as the same time of this application.

## 1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.4 (2003). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

## 1.4 Test Facility

The Semi-anechoic chamber facility used to collect the radiated data is Interterk Testing Services Shenzhen Ltd. Kejiyuan Branch and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been placed on file with the FCC.

## 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The EUT was powered by a new 9VDC battery during test.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

## 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

## 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

## 2.4 Equipment Modification

Any modifications installed previous to testing by Goldie Marketing Pty. Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Interterk Testing Services Shenzhen Ltd. Kejiyuan Branch.

## 2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

## 2.6 Support Equipment List and Description

N/A.

## 3.0 **Emission Results**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

## 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where  $FS = Field Strength in dB\mu V/m$ 

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where FS = Field Strength in  $dB\mu V/m$ 

 $RR = RA - AG - AV \text{ in } dB\mu V$ 

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

 $RA = 52.0 dB\mu V/m$ 

AF = 7.4 dB  $RR = 18.0 \text{ dB}\mu\text{V}$ 

CF = 1.6 dB LF = 9.0 dB

AG = 29.0 dBAV = 5.0 dB

FS = RR + LF

 $FS = 18 + 9 = 27 \, dB\mu V/m$ 

Level in  $\mu$ V/m = Common Antilogarithm [(27 dB $\mu$ V/m)/20] = 22.4  $\mu$ V/m

## 3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission at 49.860 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

## 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 9.6 dB

Company: Goldie Marketing Pty. Ltd. Date of Test: August 23, 2010

Model: NI-233 Mode: Transmitting

Table 1

#### **Radiated Emissions**

			Pre-	Antenna	Average	Net	Limit	
Polari-	Frequency	Reading	Amp	Factor	Factor	at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(-dB)	(dBµV/m)	(dBµV/m)	(dB)
V	49.860	79.8	16	11.0	4.4	70.4	80.0	-9.6
V	99.720	33.9	16	12.0	-	29.9	43.5	-13.6
V	149.580	18.8	16	14.0	-	16.8	43.5	-26.7
V	199.440	17.8	16	16.0	-	17.8	43.5	-25.7
V	249.300	13.3	16	20.0	-	17.3	46.0	-28.7
V	299.160	13.3	16	22.0	-	19.3	46.0	-26.7
V	349.020	14.0	16	24.0	-	22.0	46.0	-24.0

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emissions over 1000MHz.

## 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

## 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

## 6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

## 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## 8.0 <u>Miscellaneous Information</u>

This miscellaneous information includes details of the measured bandwidth, the test procedure and calculation of factors such as pulse desensitization and averaging factor.

## 8.1 **Measured Bandwidth**

The plot saved in bw.pdf which shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26 dB below the carrier level. And at 49.81 & 49.91 MHz, there are at least 40.22 dB below the carrier level. It meets requirement of Section 15.235(b).

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Report No.: HK10080771-1 FCC ID: YPS-GM98323919

6

#### 8.2 Discussion of Pulse Desensitization

The effective period ( $T_{\rm eff}$ ) was approximately 9.68 ms for a digital "1" bit, as shown in the plots of Exhibit 8.3. With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB.

## 8.3 Calculation of Average Factor

Averaging factor in  $dB = 20 \log (duty \text{ cycle})$ 

The specification for output field strengths in accordance with the FCC rules specify measurements with an average detector. During testing, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation. The duty cycle is measured by placing the spectrum analyzer in zero scan (receiver mode) and linear mode at maximum bandwidth (3 MHz at 3 dB down) and viewing the resulting time domain signal output from the analyzer on a Tektronix oscilloscope. The oscilloscope is used because of its superior time base and triggering facilities.

A plot of the worst-case duty cycle as detected in this manner are saved with filename: af.pdf

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 16.10 ms Effective period of the cycle = 9.68 ms

DC = 9.68 ms / 16.10 ms = 0.60124 or 60.124%

Therefore, the averaging factor is found by 20  $log_{10}$  0.60124 = -4.4 dB

#### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

## 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

## 9.0 **Confidentiality Request**

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

# 10.0 Equipment List

## Radiated Emissions Test

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	25-Nov-09	25-May-11
SZ185-01	EMI Receiver	R&S	ESCI	100547	08-Mar-10	08-Mar-11
SZ188-01	Anechoic Chamber	ETS	RFD- F/A-100	4102	09-Jan-10	09-Jan-11
SZ062-02	RF Cable	RADIALL	RG 213U	1	19-Apr-10	19-Oct-10
SZ062-06	RF Cable	RADIALL	0.04- 26.5GHz	1	07-Apr-10	07-Oct-10
SZ061-06	Active Loop Antenna	Electro- Metrics	EM- 6876	217	27-Nov-09	27-May-11
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	18-Mar-10	18-Mar-11