



FCC PART 22H, PART 24E

MEASUREMENT AND TEST REPORT

For

ITALCOM GROUP

1728 Coral Way, Coral Gables, Miami, Florida, United States

FCC ID: YPVITALCOMKAMEO

Report Type: Original Report	Product Type: Mobile Phone
Test Engineer: <u>Dean Liu</u>	<i>Dean Liu</i>
Report Number: <u>RSZ120418002-00D</u>	
Report Date: <u>2012-05-31</u>	
Reviewed By: <u>Ivan Cao</u> <u>EMC Engineer</u>	<i>Ivan Cao</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk “★” (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	8
FCC §1.1307 & §2.1093 – RF EXPOSURE.....	9
APPLICABLE STANDARD	9
TEST RESULT	9
FCC §2.1047 – MODULATION CHARACTERISTIC	10
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) – RF OUTPUT POWER.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	11
TEST DATA	12
FCC §2.1049, §22.917, §22.905 & §24.238 – OCCUPIED BANDWIDTH	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST DATA	20
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST DATA	23
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST DATA	26
FCC §22.917(A) & §24.238(A) - BAND EDGES.....	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST EQUIPMENT LIST AND DETAILS.....	28
TEST DATA	28
FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY.....	32

APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *ITALCOM GROUP*'s product, model number: *Kameo* (FCC ID: YPVITALCOMKAMEO (the "EUT") in this report was a *Mobile Phone*, which was measured approximately: 11.3cm (L) x 6.5cm (W) x 1.5cm (H), rated input voltage: DC 3.7V Lithium battery or DC 5.0V from adapter for charging.

Adapter Information:

MODEL NO:Komeo

ENTRADA: 100-240Vca, 50/60 Hz, 0.15A

SALIDA: DC5Vcc, 500mA

Frequency Range:

GSM850: 824-849 MHz (Tx), 869-894 MHz (Rx)
PCS 1900: 1850-1910 MHz (Tx), 1930-1990 MHz (Rx)
Wifi:2412-2462MHz
Bluetooth:2402-2480MHz

Modulation Mode: GMSK (Cellular/PCS);

DSSS,OFDM(Wifi)

GFSK,8-DPSK, $\pi/4$ -DQPSK(Bluetooth)

Transmitter Output Power:

GSM: 32.8dBm (ERP)

PCS: 29.9dBm (EIRP)

BT: 5.16dBm (conducted)

Wi-Fi: 802.11b: 17.48 dBm (conducted), 802.11g: 14.96dBm (conducted)

802.11n ht 20:14.63 dBm(conducted), 802.11n ht40: 12.87dBm (conducted)

* All measurement and test data in this report was gathered from production sample serial number: 1204041 (Assigned by BACL, Shenzhen). The EUT was received on 2012-04-23.

Objective

This report is prepared on behalf of *ITALCOM GROUP* in accordance with Part 2-Subpart J, Part 22-Subpart H, and Part 24-Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submission with FCC ID: YPVITALCOMKAMEO.

FCC Part 15C DSS submission with FCC ID: YPVITALCOMKAMEO for BT.

FCC Part 15C DSS submission with FCC ID: YPVITALCOMKAMEO for WIFI.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H – Public Mobile Services

Part 24 Subpart E – Personal Communication Services

Applicable Standards: TIA/EIA 603-D-2010, ANSI C63.4-2009.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is ± 0.96 dB, the uncertainty of any radiation on emissions measurement is ± 4.0 dB

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D-2010.

The GSM/PCS item test was performed with the EUT operating at testing mode.

The GPRS item test was performed with the EUT operating at testing mode.


Equipment Modifications


No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038
Da yang	Horn Antenna	OMCDH10180	10279001A

Configuration of Test Setup



Block Diagram of Test Setup

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: * Please refer to SAR report released by BACL, report number: R1205114-SAR

FCC §1.1307 & §2.1093 – RF EXPOSURE

Applicable Standard

FCC§1.1307 and §2.1093.

Test Result

Compliance, please refer to the SAR report: R1205114-SAR

FCC §2.1047 – MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) – RF OUTPUT POWER

Applicable Standard


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 ©, mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

Test Procedure

Conducted method:

The RF output of the transmitter was connected to Universal Radio Communication Tester through sufficient attenuation.



Radiated method:

ANSI/TIA 603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-1	2012-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ 26	8386001028	2011-11-24	2012-11-23
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
HP	Signal Generator	HP8657A	3217A04699	2011-12-19	2012-12-18
HP	Synthesized Sweeper	8341B	2624A00116	2012-04-11	2013-04-10
COM POWER	Dipole Antenna	AD-100	041000	2012-02-11	2013-02-10
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2013-02-10

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Dean Liu on 2012-05-03.

Conducted Power**Cellular Band (Part 22H)& PCS Band (Part 24E)**

Band	Channel No.	Test Result(dBm)				
		GSM	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
Cellular	128	31.83	31.78	31.26	29.67	28.47
	190	31.66	31.65	31.14	29.5	28.29
	251	31.56	31.51	30.99	29.36	28.18
PCS	512	31.09	31.08	30.49	28.83	27.84
	661	30.9	30.86	30.24	28.67	27.69
	810	30.47	30.42	29.79	28.15	27.13

ERP & EIRP

ERP for Cellular Band (Part 22H)


Frequency	Polar	S.A. Reading	S.G. Level	Antenna Gain	Cable Loss	Absolute Level	Limit
	H/V	dB μ V	dBm	dBd	dB	dBm	dBm
824.2	H	125.2	34.2	0.0	3.3	30.9	38.4
	V	127.3	35.3	0.0	3.3	31.9	38.4
836.6	H	126.3	34.1	0.0	3.3	30.8	38.4
	V	128.4	36.2	0.0	3.3	32.8	38.4
848.8	H	126.2	35.0	0.0	3.3	31.7	38.4
	V	127.0	35.8	0.0	3.3	32.5	38.4

EIRP for PCS Band (Part 24E)


Frequency	Polar	S.A. Reading	S.G. Level	Antenna Gain	Cable Loss	Absolute Level	Limit
	H/V	dB μ V	dBm	dB μ	dB	dBm	dBm
1850.2	H	115.48	20.2	8.0	0.9	27.3	33.0
	V	115.67	20.4	8.0	0.9	27.5	33.0
1880	H	116.33	21.0	8.0	0.9	28.2	33.0
	V	114.37	19.1	8.0	0.9	26.2	33.0
1908.8	H	118.07	22.8	8.0	0.9	29.9	33.0
	V	115.70	20.4	8.0	0.9	27.5	33.0

GSM:


Cellular Band (Part 22H) Low channel




Cellular Band (Part 22H) Middle channel




Cellular Band (Part 22H) High channel




PCS Band (Part 24E) Low channel



PCS Band (Part 24E) Middle channel




PCS Band (Part 24E) High channel




GPRS:


Cellular Band (Part 22H) Low channel




Cellular Band (Part 22H) Middle channel




Cellular Band (Part 22H) High channel




PCS Band (Part 24E) Low channel



PCS Band (Part 24E) Middle channel



PCS Band (Part 24E) High channel



FCC §2.1049, §22.917, §22.905 & §24.238 – OCCUPIED BANDWIDTH


Applicable Standard

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 3 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ 26	8386001028	2011-11-24	2012-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa


The testing was performed by Dean Liu on 2012-05-02.

Cellular Band (Part 22H)& PCS Band (Part 24E)


Band	Channel No.	99% Occupied Bandwidth (kHz)	26 dB Occupied Bandwidth (kHz)
GSM	190	242.48	310.64
PCS	661	240.48	318.64

Please refer to the following plots.

Cellular Band (Part 22H)



PCS Band (Part 24E)



FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ 26	8386001028	2011-11-24	2012-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Dean Liu on 2012-05-09.

Please refer to the following plots.

Cellular Band (Part 22H) — Middle Channel**PCS Band (Part 24E) — Middle Channel**

FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-1	2012-11-30
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
Rohde & Schwarz	Signal Analyzer	FSIQ 26	8386001028	2011-11-24	2012-11-23
DUCOMMUN Technologies	Pre-amp	ALN-09173030-01	991396-01	2011-11-24	2012-11-23
HP	Signal Generator	HP8657A	3217A04699	2011-12-19	2012-12-18
HP	Amplifier	HP8447E	1937A01046	2011-11-24	2012-11-23
HP	Synthesized Sweeper	8341B	2624A00116	201204-11	2013-04-10
COM POWER	Dipole Antenna	AD-100	041000	N/A	N/A
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2013-02-10
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-1	2012-11-30

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Dean Liu on 2012-05-03.

EUT Operation Mode: Transmitting

Cellular Band (Part 22H)

30 MHz-10 GHz

Frequency	Polar	S.A Reading	S.G. Level	Antenna Gain	Cable Loss	Absolute Level	Limit	Margin
MHz	H/V	dB μ V	dBm	dBd/dBi	dB	dBm	dBm	dB
Low Channel, fo = 824.2 MHz								
1648.400	H	51.9	-52.4	7.3	0.9	-45.9	-13.0	32.9
1648.400	V	52.3	-50.2	7.3	0.9	-43.7	-13.0	30.7
2472.600	H	50.2	-58.9	9.8	0.9	-49.9	-13.0	36.9
2472.600	V	57.4	-58.1	9.8	0.9	-49.1	-13.0	36.1
Middle Channel, fo = 836.6 MHz								
1673.200	H	49.8	-53.3	7.3	0.9	-46.9	-13.0	33.9
1673.200	V	51.5	-49.0	7.3	0.9	-42.6	-13.0	29.6
2509.800	H	39.5	-61.2	10.1	0.9	-52.0	-13.0	39.0
2509.800	V	39.6	-56.8	10.1	0.9	-47.6	-13.0	34.6
High Channel, fo = 848.8 MHz								
1696.800	H	49.62	-54.5	7.3	0.9	-48.1	-13.0	35.1
1696.800	V	49.97	-52.8	7.3	0.9	-46.3	-13.0	33.3
2545.200	H	50.18	-58.4	10.1	0.9	-49.2	-13.0	36.2
2545.200	V	5.61	-58.1	10.1	0.9	-48.8	-13.0	35.8

PCS Band (Part 24E)
30 MHz-20 GHz

Frequency	Polar	S.A. Reading	S.G. Level	Antenna Gain	Cable Loss	Absolute Level	Limit	Margin
MHz	H/V	dB μ V	dBm	dBd/dBi	dB	dBm	dBm	dB
Low Channel, fo = 1850.2 MHz								
3700.400	H	49.41	-51.3	10.0	1.1	-42.4	-13.0	29.4
3700.400	H	44.87	-55.9	10.0	1.1	-47.0	-13.0	34.0
5550.600	H	43.42	-59.9	11.3	1.5	-50.1	-13.0	37.1
5550.600	H	46.92	-55.0	11.3	1.5	-45.2	-13.0	32.2
Middle Channel, fo = 1880.0 MHz								
3760.000	H	38.69	-58.3	10.0	1.1	-49.4	-13.0	36.4
3760.000	H	39.42	-56.7	10.0	1.1	-47.8	-13.0	34.8
5640.000	V	45.73	-46.7	11.2	1.5	-37.0	-13.0	24.0
5640.000	V	39.39	-51.8	11.2	1.5	-42.1	-13.0	29.1
High Channel, fo = 1909.8 MHz								
3816.400	V	46.62	-55.1	9.8	1.1	-46.3	-13.0	33.3
3816.400	V	48.41	-51.2	9.8	1.1	-42.4	-13.0	29.4
5729.400	V	43.27	-60.3	11.1	1.5	-50.7	-13.0	37.7
5729.400	V	49.90	-52.1	11.1	1.5	-42.5	-13.0	29.5

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 3 kHz.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
BIZI	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Dean Liu on 2012-05-02.


Please refer to the following tables and plots.

Cellular Band (Part 22H)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
128	-20.39	-13
251	-17.54	-13

PCS Band (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
512	-23.24	-13
810	-21.13	-13

Cellular Band, Left Band Edge**Cellular Band, Right Band Edge**

PCS Band, Left Band Edge



PCS Band, Right Band Edge



FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile \leq 3 watts (ppm)	Mobile \leq 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	2011-06-04	2012-06-03
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-04-11	2012-04-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa



The testing was performed by Dean Liu on 2012-05-03.

Cellular Band (Part 22H)

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	-12	-0.01	2.5
-20	3.7	-7	-0.01	2.5
-10	3.7	-8	-0.01	2.5
0	3.7	-5	-0.01	2.5
10	3.7	-2	0.00	2.5
20	3.7	-3	0.00	2.5
30	3.7	-1	0.00	2.5
40	3.7	2	0.00	2.5
50	3.7	3	0.00	2.5
25	V _{end point} = 3.5	-15	-0.02	2.5

PCS Band (Part 24E)

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-16	-0.01	Pass
-20	3.7	-15	-0.01	Pass
-10	3.7	-13	-0.01	Pass
0	3.7	-10	-0.01	Pass
10	3.7	-11	-0.01	Pass
20	3.7	-9	0.00	Pass
30	3.7	-7	0.00	Pass
40	3.7	-8	0.00	Pass
50	3.7	-9	0.00	Pass
25	$V_{\text{end point}} = 3.5$		-20	-0.01



***** END OF REPORT *****