

Test Report of FCC CFR 47 Part 15 Subpart B

On Behalf of

SUN CUPID (SHENZHEN) ELECTRONIC LTD.

FCC ID: YQB0SCI1000006
Product Description: NUU Riptide / Splash Mini / Mini Speaker
Test Model No.: RT1
Supplementary Model: RT2, RT3, M1, M2, M3
Brand Name: NUU

Prepared for: SUN CUPID (SHENZHEN) ELECTRONIC LTD.
10A, No.3 Bldg, China Academy of Sci & Tech Development, No.1
High-Tech South St., Shenzhen, China
Prepared by: Bontek Compliance Testing Laboratory Co., Ltd
1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East
Road, Nanshan, Shenzhen, China
Tel: 86-755-86337020
Fax: 86-755-86337028
Report No.: BCT14FR241E
Issue Date: June 20, 2014
Test Date: June 12-20, 2013



Tested by: 
Jiankuai.Li
Reviewed by: 
Owen Yang
Approved by: 
Kendy Wang

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST FACILITY	4
2. SYSTEM TEST CONFIGURATION.....	5
2.1 EUT CONFIGURATION	5
2.2 SUPPORT EQUIPMENTS	5
1.5m Unshielded Power Cord.....	5
1.5m Unshielded Power Cord.....	5
2.3 GENERAL TEST PROCEDURES	5
2.4 MEASUREMENT UNCERTAINTY.....	5
2.5 LIST OF MEASURING EQUIPMENTS USED.....	6
3. SUMMARY OF TEST RESULTS.....	6
4. TEST OF AC POWER LINE CONDUCTED EMISSION	7
4.1 LIMIT OF AC POWER LINE CONDUCTED EMISSION	7
4.2 EUT SETUP	7
4.3 INSTRUMENT SETUP	8
4.4 TEST PROCEDURE	8
4.5 TEST RESULT	8
5 - RADIATED DISTURBANCES	11
5.1 LIMIT OF RADIATED DISTURBANCES	11
5.2 EUT SETUP	11
5.3 TEST RECEIVER SETUP	12
5.4 TEST PROCEDURE	12
5.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	12
5.6 RADIATED EMISSIONS TEST RESULT	12

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant:	SUN CUPID (SHENZHEN) ELECTRONIC LTD.
Address of Applicant:	10A, No.3 Bldg, China Academy of Sci & Tech Development, No.1 High-Tech South St., Shenzhen, China
Manufacturer:	SUN CUPID (SHENZHEN) ELECTRONIC LTD.
Address of Manufacturer:	10A, No.3 Bldg, China Academy of Sci & Tech Development, No.1 High-Tech South St., Shenzhen, China

General Description of E.U.T

Items	Description
EUT Description:	NUU Riptide / Splash Mini / Mini Speaker
Trade Name:	NUU
Test Model No.:	RT1
Supplementary Model:	RT2, RT3, M1, M2, M3
BT Module:	V2.0+EDR
Frequency Band:	2402 MHz ~ 2480 MHz
Channel Spacing:	1 MHz
Number of Channels:	79
Type of Modulation:	GFSK, Pi/4 DAPSK, 8-DPSK
Antenna Type:	Built-in Antenna
Antenna Gain:	2dBi
Power Supply:	Battery 1#: 3.7V,750mAh, Battery 2#: 3.7V,680mAh, DC 5V from Adapter.
Battery Information:	1#:Model No: PT603040 750mAh 3.7V Manufacturer: Shenzhen Pow-Tech New Power Co., Ltd 2#:Model No: SR603040 680mAh 3.7V Manufacturer: CTE Energy CO.,Ltd.

Remark: * The test data gathered are from the production sample provided by the manufacturer.

* Supplementary models have the same circuit, but with different appearance

1.2 Test Standards

The report of EUT is prepared in accordance with FCC Rules and Regulations Part 15 Subpart B 2006
The objective of the manufacturer is to demonstrate compliance with the described above standards.

1.3 Test Facility

All measurement required was performed at laboratory of Shenzhen CTL Testing Technology Co., Ltd. at Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055.

The test facility is recognized, certified, or accredited by the following organizations:

FCC – Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December, 2013.

2. SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 Support Equipments

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

Support equipments or special accessories in test configuration:

AUX Description:	Manufacturer	Model No.	Certificate	CABLE
Host Computer	Dell	78MD82X	CE, FCC	1.5m Unshielded Power Cord
Monitor	Dell	E178Pc	CE, FCC	1.5m Unshielded Power Cord 1.8m shielded data Cable with core
Keyboard	Dell	L100	CE, FCC	1.8m shielded data Cable with core
Mouse	Dell	OCJ339	CE, FCC	1.8m shielded data Cable with core
Printer	EPSON	P330A	CE, FCC	1.2m Unshielded Power Cord 1.5m shielded data Cable

2.3 General Test Procedures

Conducted Emissions: The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 7.1 of ANSI C63.4-2003 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak detector mode.

Radiated Emissions: The EUT is placed on as turntable, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4-2003.

2.4 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Power Line Conducted Emission	+/- 2.3 dB
Radiated Emission	+/- 3.4 dB

Uncertainty figures are valid to a confidence level of 95%.

2.5 List of Measuring Equipments Used

Test equipments list of Shenzhen CTL Testing Technology Co., Ltd.

No.	Instrument no.	Equipment	Manufacturer	Model No.	S/N	Last Calculator	Due Calculator
1	BCT-EMC001	EMI Test Receiver	R&S	ESCI	100687	2014-4-25	2015-4-24
2	BCT-EMC002	EMI Test Receiver	R&S	ESPI	100097	2013-11-1	2014-10-31
3	BCT-EMC003	Amplifier	HP	8447D	1937A02492	2014-4-25	2015-4-24
4	BCT-EMC018	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	2014-4-25	2015-4-24
5	BCT-EMC021	Triple-Loop Antenna	EVERFINE	LLA-2	711002	2013-11-1	2014-10-31
6	BCT-EMC026	RF POWER AMPLIFIER	FRANKONIA	FLL-75	1020A1109	2014-4-25	2015-4-24
7	BCT-EMC029	6dB Attenuator	FRANKONIA	N/A	1001698	2014-4-25	2015-4-24
8	BCT-EMC032	10dB attenuator	ELECTRO-METRICS	EM-7600	836	2014-4-25	2015-4-24
9	BCT-EMC036	Spectrum Analyzer	R&S	FSP	100397	2013-11-1	2014-10-31
10	BCT-EMC037	Broadband preamplifier	SCH WARZBECK	BBV9718	9718-182	2014-4-25	2015-4-24
11	BCT-EMC039	Horn Antenna	SCHWARZBECK	BBHA 9120D	0437	2014-4-25	2015-4-24
12	BCT-EMC038	Horn Antenna	SCHWARZBECK	BBHA9170	0483	2014-4-25	2015-4-24

3. SUMMARY OF TEST RESULTS

Standard	Test Items	Result
FCC Part 15 Subpart B	Conduction Emission, 0.15MHz to 30MHz	Pass
FCC Part 15 Subpart B	Radiation Emission, 30MHz to 1000MHz	Pass

4. TEST OF AC POWER LINE CONDUCTED EMISSION

4.1 Limit of AC Power Line Conducted Emission

Frequency Range (MHz)	Limits (dBuV)	
	Quasi-Peak	Average
0.150~0.500	66~56	56~46
0.500~5.000	56	46
5.000~30.00	60	50

4.2 EUT Setup


The setup of EUT is according with ANSI C63.4-2003 measurement procedure. The specification used was the FCC Rules and Regulations Part 15 Subpart B limits.

The EUT was placed center and the back edge of the test table.

The AV cables were draped along the test table and bundled to 30-40cm in the middle.

The spacing between the peripherals was 10 cm.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.



Remark: The EUT was connected to a 120VAC/ 60Hz power source.

4.3 Instrument Setup

The test receiver was set with the following configurations:

Test Receiver Setting:

Frequency Range.....150 KHz to 30 MHz
Detector.....Peak & Quasi-Peak & Average
Sweep Speed.....Auto
IF Band Width.....9 KHz

4.4 Test Procedure

During the conducted emission test, the EUT power cord was connected to the auxiliary outlet of the first Artificial Mains.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance using all installation combination.

All data was recorded in the peak detection mode. Quasi-peak and Average readings were only performed when an emission was found to be marginal (within -10 dB μ V of specification limits). Quasi-peak readings are distinguished with a "QP". Average readings are distinguished with a "AV".


4.5 Test Result

Temperature (°C) : 22~23	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH): 50~54	M/N: RT1
Barometric Pressure (mbar): 950~1000	Operation Condition: Connect to PC

Conducted Emission:

EUT: NUU Riptide / Splash Mini / Mini Speaker
 M/N: RT1
 Operating Condition: Connect to PC
 Test Site: Shielded Room
 Operator: Yang
 Test Specification: AC 120V/60Hz for PC
 Comment: L Line

SCAN TABLE: "Voltage (150K-30M) FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "14FR241E04_fin"

6/17/2014 11:06AM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.352500	27.30	10.8	59	31.6	QP	L1	GND
0.447000	36.40	10.6	57	20.5	QP	L1	GND
1.266000	27.80	10.4	56	28.2	QP	L1	GND
2.094000	28.20	10.4	56	27.8	QP	L1	GND
2.134500	27.70	10.4	56	28.3	QP	L1	GND
2.787000	27.20	10.4	56	28.8	QP	L1	GND

MEASUREMENT RESULT: "14FR241E04_fin2"


6/17/2014 11:06AM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.343500	19.40	10.8	49	29.7	AV	L1	GND
0.442500	27.30	10.6	47	19.7	AV	L1	GND
1.257000	18.90	10.4	46	27.1	AV	L1	GND
2.076000	19.00	10.4	46	27.0	AV	L1	GND
2.175000	18.30	10.4	46	27.7	AV	L1	GND
2.859000	17.80	10.4	46	28.2	AV	L1	GND

Conducted Emission:

EUT: NUU Riptide / Splash Mini / Mini Speaker
 M/N: RT1
 Operating Condition: Connect to PC
 Test Site: Shielded Room
 Operator: Yang
 Test Specification: AC 120V/60Hz for PC
 Comment: N Line

SCAN TABLE: "Voltage (150K-30M) FIN"
 Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "14FR241E03_fin"

6/17/2014 11:03AM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.451500	30.30	10.6	57	26.5	QP	N	GND
0.591000	20.60	10.4	56	35.4	QP	N	GND
0.748500	13.70	10.4	56	42.3	QP	N	GND
0.789000	13.20	10.4	56	42.8	QP	N	GND
0.861000	12.60	10.4	56	43.4	QP	N	GND
1.059000	18.60	10.5	56	37.4	QP	N	GND

MEASUREMENT RESULT: "14FR241E03_fin2"

6/17/2014 11:03AM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.334500	14.00	10.9	49	35.3	AV	N	GND
0.451500	21.00	10.6	47	25.8	AV	N	GND
1.248000	12.50	10.4	46	33.5	AV	N	GND
2.058000	12.40	10.4	46	33.6	AV	N	GND
2.895000	11.90	10.4	46	34.1	AV	N	GND
3.867000	9.80	10.4	46	36.2	AV	N	GND

5 - RADIATED DISTURBANCES

5.1 Limit of Radiated Disturbances

Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dB μ V/m)
30 ~ 88	3	40
88~216	3	43.5
216 ~ 960	3	46
960 ~ 1000	3	54

Note:

- (1) The tighter limit shall apply at the edge between two frequency bands.
- (2) Distance refers to the distance in meters between the test instrument antenna and the closest point of any part of the E.U.T.


5.2 EUT Setup

The radiated emission tests were performed in the in the 3-meter anechoic chamber, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC Part 15 Subpart B limits.

The EUT was placed on the center of the test table.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.

Below 1 GHz



5.3 Test Receiver Setup

According to FCC Part 15 rule, the frequency was investigated from 30 to 1000 MHz. During the radiated emission test, the test receiver was set with the following configurations:

Test Receiver Setting:

Detector.....Peak & Quasi-Peak
IF Band Width.....120KHz
Frequency Range.....30MHz to 1000MHz
Turntable Rotated.....0 to 360 degrees

Antenna Position:

Height.....1m to 4m
Polarity.....Horizontal and Vertical

5.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the peak detection mode. Quasi-peak readings performed only when an emission was found to be marginal (within -10 dB μ V of specification limits), and are distinguished with a "QP" in the data table.

5.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB μ V means the emission is 7dB μ V below the maximum limit for Subpart B. The equation for margin calculation is as follows:

Margin = Limit – Corr. Ampl.

5.6 Radiated Emissions Test Result


Temperature (°C) : 22~23	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH): 50~54	M/N: RT1
Barometric Pressure (mbar): 950~1000	Operation Condition: Connect to PC

Radiated Emission Test Data(30~1000M):

EUT: NUU Riptide / Splash Mini / Mini Speaker
 M/N: RT1
 Operating Condition: Connect to PC
 Test Site: 3m CHAMBER
 Operator: Chen
 Test Specification: AC 120V/60Hz for PC
 Comment: Polarization: Horizontal

SWEET TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start Frequency	Stop Frequency	Detector	Meas.	IF	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Time Coupled	Bandw.	VULB9163 NEW
				100 kHz	



MEASUREMENT RESULT: "14FR241E04_red"

6/16/2014 11:10


Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
39.700000	24.00	15.8	40.0	16.0	QP	100.0	0.00	HORIZONTAL
57.160000	21.70	15.1	40.0	18.3	QP	100.0	0.00	HORIZONTAL
99.840000	23.30	17.5	43.5	20.2	QP	100.0	0.00	HORIZONTAL
305.480000	25.40	18.9	46.0	20.6	QP	100.0	0.00	HORIZONTAL
555.740000	31.90	25.1	46.0	14.1	QP	100.0	0.00	HORIZONTAL
895.240000	36.70	29.1	46.0	9.3	QP	100.0	0.00	HORIZONTAL

Radiated Emission Test Data(30~1000M):

EUT: NUU Riptide / Splash Mini / Mini Speaker
 M/N: RT1
 Operating Condition: Connect to PC
 Test Site: 3m CHAMBER
 Operator: Chen
 Test Specification: AC 120V/60Hz for PC
 Comment: Polarization: Vertical

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start Frequency	Stop Frequency	Detector	Meas.	IF	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	VULB9163 NEW



MEASUREMENT RESULT: "14FR241E03_red"

6/16/2014 11:03

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det. QP	Height cm	Azimuth deg	Polarization
47.460000	25.40	15.8	40.0	14.6	QP	100.0	0.00	VERTICAL
59.100000	22.60	14.6	40.0	17.4	QP	100.0	0.00	VERTICAL
101.780000	23.20	17.3	43.5	20.3	QP	100.0	0.00	VERTICAL
258.920000	27.90	17.3	46.0	18.1	QP	100.0	0.00	VERTICAL
553.800000	30.90	25.1	46.0	15.1	QP	100.0	0.00	VERTICAL
951.500000	36.50	29.6	46.0	9.5	QP	100.0	0.00	VERTICAL