

# Test Report of FCC CFR 47 Part 15 Subpart C

On Behalf of

## **SUN CUPID (SHENZHEN) ELECTRONIC LTD.**

**FCC ID:** YQB0SCI1000006

**Product Description:** NUU Riptide / Splash Mini / Mini Speaker

**Model No.:** RT1

**Supplementary Model:** RT2, RT3, M1, M2, M3

**Prepared for:** **SUN CUPID (SHENZHEN) ELECTRONIC LTD.**

10A, No.3 Bldg, China Academy of Sci & Tech Development, No.1  
High-Tech South st., Shenzhen, China

**Prepared by:** **Shenzhen Bontek Compliance Testing Laboratory Co., Ltd.**

1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East  
Road, Nanshan, Shenzhen, China  
Tel: 86-755-86337020  
Fax: 86-755-86337028

**Report No.:** BCT14FR241E-1

**Issue Date:** June 20, 2014


**Test Date:** June 12 ~20, 2014

**Tested by:**




Jiankuai.Li

**Reviewed by:**



Owen Yang

**Approved by:**



Kendy Wang

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
1.2 RELATED SUBMITTAL(S) / GRANT (S) AND TEST METHODOLOGY .....	5
1.3 TEST FACILITY .....	5
<b>2. SYSTEM TEST CONFIGURATION .....</b>	<b>6</b>
2.1 EUT CONFIGURATION .....	6
2.2 EUT EXERCISE .....	6
2.3 GENERAL TEST PROCEDURES .....	6
2.4 MEASUREMENT UNCERTAINTY .....	6
2.5 SUPPORT EQUIPMENTS .....	6
2.6 TEST EQUIPMENT LIST AND DETAILS .....	7
<b>3. SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>4. TEST OF AC POWER LINE CONDUCTED EMISSION.....</b>	<b>8</b>
4.1 APPLICABLE STANDARD .....	8
4.2 TEST SETUP DIAGRAM .....	8
4.3 TEST RESULT .....	8
<b>5. TEST OF HOPPING CHANNEL BANDWIDTH .....</b>	<b>11</b>
5.1 APPLICABLE STANDARD .....	11
5.2 EUT SETUP .....	11
5.3 TEST EQUIPMENT LIST AND DETAILS .....	11
5.4 TEST PROCEDURE .....	11
5.5 TEST RESULT .....	11
<b>6. TEST OF HOPPING CHANNEL SEPARATION.....</b>	<b>17</b>
6.1 APPLICABLE STANDARD .....	17
6.2 EUT SETUP .....	17
6.3 TEST EQUIPMENT LIST AND DETAILS .....	17
6.4 TEST PROCEDURE .....	17
6.5 TEST RESULT .....	17
<b>7. TEST OF NUMBER OF HOPPING FREQUENCY.....</b>	<b>24</b>
7.1 APPLICABLE STANDARD .....	24
7.2 EUT SETUP .....	24
7.3 TEST EQUIPMENT LIST AND DETAILS .....	24
7.4 TEST PROCEDURE .....	24
7.5 TEST RESULT .....	24
<b>8. TEST OF DWELL TIME OF EACH FREQUENCY.....</b>	<b>27</b>
8.1 APPLICABLE STANDARD .....	27
8.2 EUT SETUP .....	27
8.3 TEST EQUIPMENT LIST AND DETAILS .....	27
8.4 TEST PROCEDURE .....	27
8.5 TEST RESULT .....	27
<b>9. TEST OF MAXIMUM PEAK OUTPUT POWER .....</b>	<b>44</b>
9.1 APPLICABLE STANDARD .....	44
9.2 EUT SETUP .....	44
9.3 TEST EQUIPMENT LIST AND DETAILS .....	44
9.4 TEST PROCEDURE .....	44
9.5 TEST RESULT .....	44
<b>10. TEST OF BAND EDGES EMISSION .....</b>	<b>50</b>
10.1 APPLICABLE STANDARD .....	50
10.2 EUT SETUP .....	50
10.3 TEST EQUIPMENT LIST AND DETAILS .....	50
10.4 TEST PROCEDURE .....	50
10.5 TEST RESULT .....	51

<b>11. TEST OF SPURIOUS RADIATED EMISSION .....</b>	<b>57</b>
11.1 APPLICABLE STANDARD .....	57
11.2 EUT SETUP .....	57
11.3 TEST EQUIPMENT LIST AND DETAILS.....	58
11.4 TEST PROCEDURE .....	58
11.5 TEST RESULT .....	59
<b>12. ANTENNA REQUIREMENT .....</b>	<b>74</b>
12.1 STANDARD APPLICABLE .....	74
12.2 ANTENNA CONNECTED CONSTRUCTION .....	74

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant:	<b>SUN CUPID (SHENZHEN) ELECTRONIC LTD.</b>
Address of applicant:	10A, No.3 Bldg,China Academy of Sci & Tech Development, No.1 High-Tech South st., Shenzhen, China
Manufacturer :	<b>SUN CUPID (SHENZHEN) ELECTRONIC LTD.</b>
Address of manufacturer:	10A, No.3 Bldg,China Academy of Sci & Tech Development, No.1 High-Tech South st., Shenzhen, China

#### General Description of E.U.T

Items	Description
EUT Description:	NUU Riptide / Splash Mini / Mini Speaker
Model No.:	RT1
Trade Name:	NUU
Supplementary Model:	RT2, RT3, M1, M2, M3
BT Module	CSR 4.0
Frequency Band:	2402~2480MHz
Number of Channels:	79
Type of Modulation:	GFSK, Pi/4 DQPSK, 8-DPSK
Antenna Gain	0 dBi
Antenna Type:	Integral Antenna
Rated Voltage:	Battery 1#: 3.7V,750mAh, Battery 2#: 3.7V,680mAh, DC 5V from Adapter.
Battery Information:	1#:Model No: PT603040 750mAh 3.7V Manufacturer: Shenzhen Pow-Tech New Power Co., Ltd 2#:Model No: SR603040 680mAh 3.7V Manufacturer: CTE Energy CO.,Ltd.

Remark: \* The test data gathered are from the production sample provided by the manufacturer.

\* Supplementary models have the same circuit, but with different appearance

## **1.2 Related Submittal(s) / Grant (s) and Test Methodology**

The tests were performed based on the Electromagnetic Interference (EMI) tests performed on the EUT. Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 - 2003 Radiated testing was performed at an antenna to EUT distance 3 meters.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.207, 15.209 and 15.247 rules. Test was carried out according to the above mentioned FCC rules and the FCC publication notice DA 00-705: Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems

## **1.3 Test Facility**

All measurement required was performed at laboratory of Shenzhen CTL Testing Technology Co., Ltd. at Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055.

The test facility is recognized, certified, or accredited by the following organizations:

### **FCC – Registration No.: 970318**

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December, 2013.

## 2. SYstEM TEst CONFIGURATION

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT Exercise

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

### 2.3 General Test Procedures

Conducted Emissions: The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 7.1 of ANSI C63.4-2003 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak detector mode.

Radiated Emissions: The EUT is placed on as turntable, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4-2003.

### 2.4 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Power Line Conducted Emission	+/- 2.3 dB
Radiated Emission	+/- 3.4 dB

Uncertainty figures are valid to a confidence level of 95%.

### 2.5 Support Equipments

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

## 2.6 Test Equipment List and Details

Test equipments list of Shenzhen CTL Testing Technology Co., Ltd.

No.	Instrument no.	Equipment	Manufacturer	Model No.	S/N	Last Calculator	Due Calculator
1	BCT-EMC001	EMI Test Receiver	R&S	ESCI	100687	2014-4-25	2015-4-24
2	BCT-EMC002	EMI Test Receiver	R&S	ESPI	100097	2013-11-1	2014-10-31
3	BCT-EMC003	Amplifier	HP	8447D	1937A02492	2014-4-25	2015-4-24
4	BCT-EMC018	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	2014-4-25	2015-4-24
5	BCT-EMC021	Triple-Loop Antenna	EVERFINE	LLA-2	711002	2013-11-1	2014-10-31
6	BCT-EMC026	RF POWER AMPLIFIER	FRANKONIA	FLL-75	1020A1109	2014-4-25	2015-4-24
7	BCT-EMC029	6dB Attenuator	FRANKONIA	N/A	1001698	2014-4-25	2015-4-24
8	BCT-EMC032	10dB attenuator	ELECTRO-METRICS	EM-7600	836	2014-4-25	2015-4-24
9	BCT-EMC036	Spectrum Analyzer	R&S	FSP	100397	2013-11-1	2014-10-31
10	BCT-EMC037	Broadband preamplifier	SCHWARZBECK	BBV9718	9718-182	2014-4-25	2015-4-24
11	BCT-EMC039	Horn Antenna	SCHWARZBECK	BBHA 9120D	0437	2014-4-25	2015-4-24
12	BCT-EMC038	Horn Antenna	SCHWARZBECK	BBHA9170	0483	2014-4-25	2015-4-24

## 3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207	AC Power Line Conducted Emission	Pass
FCC §15.247(a)(1)	Hopping Channel Bandwidth	Pass
FCC §15.247(a)(1)	Hopping Channel Separation	Pass
FCC §15.247(a)(1)	Number of Hopping Frequency Used	Pass
FCC §15.247(a)(1)(iii)	Dwell Time of Each Frequency	Pass
FCC §15.247(b)(1)	Maximum Peak Output Power	Pass
FCC §15.247(d)	Band Edges Emission	Pass
FCC §15.247(d)	Spurious Radiated Emission	Pass
FCC §15.203/15.247(b)/(c)	Antenna Requirement	Pass

## 4. TEST OF AC POWER LINE CONDUCTED EMISSION


### 4.1 Applicable standard

Refer to FCC §15.207.

For a Low-power Radio-frequency Device is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency Range (MHz)	Limits ( dBuV)	
	Quasi-Peak	Average
0.150~0.500	66~56	56~46
0.500~5.000	56	46
5.000~30.00	60	50

### 4.2 Test Setup Diagram



Remark: The EUT was connected to a 120 VAC/ 60Hz power source.


### 4.3 Test Result

Temperature ( °C ) : 23~25	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH) : 45~58	M/N: RT1
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Tx Mode

## Conducted Emission:

EUT: NUU Riptide / Splash Mini / Mini Speaker  
 M/N: RT1  
 Operating Condition: Tx Mode  
 Test Site: Shielded Room  
 Operator: Yang  
 Test Specification: AC 120V/60Hz for adapter  
 Comment: L Line

**SCAN TABLE: "Voltage (150K-30M) FIN"**  
 Short Description: 150K-30M Voltage



### MEASUREMENT RESULT: "14FR241E01\_fin"

6/17/2014 10:42AM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Detector	Line	PE
2.067000	35.10	10.4	56	20.9	QP	L1	GND
2.445000	36.60	10.4	56	19.4	QP	L1	GND
2.872500	36.60	10.4	56	19.4	QP	L1	GND
3.322500	35.90	10.4	56	20.1	QP	L1	GND
3.619500	35.30	10.4	56	20.7	QP	L1	GND
3.723000	35.20	10.4	56	20.8	QP	L1	GND

### MEASUREMENT RESULT: "14FR241E01\_fin2"


6/17/2014 10:42AM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Detector	Line	PE
1.981500	24.00	10.4	46	22.0	AV	L1	GND
2.472000	24.50	10.4	46	21.5	AV	L1	GND
2.949000	24.70	10.4	46	21.3	AV	L1	GND
3.264000	25.20	10.4	46	20.8	AV	L1	GND
3.606000	24.40	10.4	46	21.6	AV	L1	GND
4.141500	22.80	10.4	46	23.2	AV	L1	GND

## Conducted Emission:

EUT: NUU Riptide / Splash Mini / Mini Speaker  
 M/N: RT1  
 Operating Condition: Tx Mode  
 Test Site: Shielded Room  
 Operator: Yang  
 Test Specification: AC 120V/60Hz for adapter  
 Comment: N Line

**SCAN TABLE: "Voltage(150K-30M) FIN"**  
Short Description: 150K-30M Voltage



### MEASUREMENT RESULT: "14FR241E02\_fin"

6/17/2014 10:46AM

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Detector	Line	PE
2.125500	28.60	10.4	56	27.4	QP	N	GND
2.494500	29.70	10.4	56	26.3	QP	N	GND
2.557500	29.20	10.4	56	26.8	QP	N	GND
2.931000	30.30	10.4	56	25.7	QP	N	GND
3.372000	30.10	10.4	56	25.9	QP	N	GND
3.619500	29.00	10.4	56	27.0	QP	N	GND

### MEASUREMENT RESULT: "14FR241E02\_fin2"

6/17/2014 10:46AM


Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Detector	Line	PE
0.388500	24.20	10.7	48	23.9	AV	N	GND
0.483000	22.20	10.5	46	24.1	AV	N	GND
0.645000	21.60	10.4	46	24.4	AV	N	GND
2.026500	20.90	10.4	46	25.1	AV	N	GND
2.467500	20.70	10.4	46	25.3	AV	N	GND
2.886000	20.40	10.4	46	25.6	AV	N	GND

## 5. Test of Hopping Channel Bandwidth

### 5.1 Applicable standard

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

### 5.2 EUT Setup



### 5.3 Test Equipment List and Details

See section 2.5.

### 5.4 Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Use the following spectrum analyzer settings:  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel  
 $RBW \geq 1\%$  of the 20 dB bandwidth,  $VBW \geq RBW$   
Sweep = auto  
Detector function = peak  
Trace = max hold
3. The spectrum width with level higher than 20dB below the peak level.
4. Repeat above 1~3 points for the middle and highest channel of the EUT.

### 5.5 Test Result

Temperature ( °C ) : 22~23	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH) : 50~54	M/N: RT1
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Tx Mode

## BDR 1M

Modulation Type	Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)
GFSK	Low	2402.00	912
GFSK	Middle	2441.00	924
GFSK	High	2480.00	924

## EDR 2M

Modulation Type	Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)
Pi/4 DQPSK	Low	2402.00	1224
Pi/4 DQPSK	Middle	2441.00	1220
Pi/4 DQPSK	High	2480.00	1220


## EDR 3M

Modulation Type	Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)
8-DPSK	Low	2402.00	1212
8-DPSK	Middle	2441.00	1212
8-DPSK	High	2480.00	1204


## BDR 1M Channel Low



## Channel Middle




## Channel High




## EDR 2M Channel Low



## Channel Middle




## Channel High




## EDR 3M Channel Low



## Channel Middle



## Channel High




## 6. Test of Hopping Channel Separation

### 6.1 Applicable standard

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

### 6.2 EUT Setup



### 6.3 Test Equipment List and Details

See section 2.5.

### 6.4 Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set RBW of spectrum analyzer to 30KHz and VBW to 100KHz.
3. Set Detector to Peak, Trace to Max Hold and Sweep Time is Auto.
4. The Hopping Channel Separation is defined as the separation between 2 neighboring hopping frequencies.
5. Repeat above 1~3 points for the middle and highest channel of the EUT.

### 6.5 Test Result

Temperature ( °C ) : 22~23	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH) : 50~54	M/N: RT1
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Tx Mode

**BDR 1M**

Modulation Type	Frequency (MHz)	Channel Separation (MHz)	Min. Limit (kHz)
GFSK	2402~2403	1.000	>25
GFSK	2441~2442	1.102	>25
GFSK	2479~2480	1.004	>25


**EDR 2M**

Modulation Type	Frequency (MHz)	Channel Separation (MHz)	Min. Limit (kHz)
Pi/4 DQPSK	2402~2403	1.002	>25
Pi/4 DQPSK	2441~2442	1.008	>25
Pi/4 DQPSK	2479~2480	1.008	>25


**EDR 3M**

Modulation Type	Frequency (MHz)	Channel Separation (MHz)	Min. Limit (kHz)
8-DPSK	2402~2403	1.004	>25
8-DPSK	2441~2442	1.004	>25
8-DPSK	2479~2480	1.000	>25


## BDR 1M Channel Low




## Channel Middle




## Channel High




## EDR 2M Channel Low




## Channel Middle




## Channel High




## EDR 3M Channel Low



## Channel Middle



## Channel High




## 7. Test of Number of Hopping Frequency

### 7.1 Applicable standard

Section 15.247(a)(1)(iii): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 15 non-overlapping hopping channels. Frequency hopping system which use fewer than 75 hopping frequencies may employ intelligent hopping techniques to avoid interference to other transmissions. Frequency hopping system may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 non-overlapping channels are used.

### 7.2 EUT Setup



### 7.3 Test Equipment List and Details

See section 2.5.

### 7.4 Test Procedure


1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set RBW of spectrum analyzer to 100KHz and VBW to 100KHz.
3. Set Detector to Peak, Trace to Max Hold and Sweep Time is Auto.
4. Observe frequency hopping in 2400MHz~2483.5MHz, there are at least 32 non-overlapping channels.
5. Repeat above 1~3 points for the middle and highest channel of the EUT.

### 7.5 Test Result


Temperature ( °C ) : 22~23	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH) : 50~54	M/N: RT1
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Tx Mode

Modulation Type	Frequency (MHz)	Number of Hopping Channels	Min. Limit
GFSK	2402~2480	79	≥15
Pi/4 DQPSK	2402~2480	79	≥15
8-DPSK	2402~2480	79	≥15


## BDR-1M



## EDR-2M



## EDR-3M




## 8. Test of Dwell Time of Each Frequency

### 8.1 Applicable standard

Section 15.247(a)(1)(iii): For frequency hopping systems operating in the 2400-2483.5 MHz band The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4seconds multiplied by the number of hopping channels employed.

### 8.2 EUT Setup



### 8.3 Test Equipment List and Details

See section 2.5.

### 8.4 Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set RBW of spectrum analyzer to 1000kHz and VBW to 1000kHz.
3. Set Detector to Peak, Trace to Max Hold and Sweep Time is more than once pulse time.
4. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
5. Measure the maximum time duration of one single pulse.

### 8.5 Test Result

Temperature ( °C ) : 22~23	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH) : 50~54	M/N: RT1
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Tx Mode

DH1

Dwell time=  $t*(1.6/2/79)*31.6$

DH3

Dwell time=  $t*(1.6/4/79)*31.6$

DH5

Dwell time=  $t*(1.6/6/79)*31.6$

**BDR 1M**  
**Low Channel**

Modulation Type		Reading (ms)	Dwell Time (ms)	Limit (ms)
GFSK	DH1	0.382	122.24	400
GFSK	DH3	1.646	263.32	400
GFSK	DH5	2.910	310.40	400

**Middle Channel**

Modulation Type		Reading (ms)	Dwell Time (ms)	Limit (ms)
GFSK	DH1	0.386	123.52	400
GFSK	DH3	1.656	264.96	400
GFSK	DH5	2.910	310.40	400

**High Channel**

Modulation Type		Reading (ms)	Dwell Time (ms)	Limit (ms)
GFSK	DH1	0.386	123.52	400
GFSK	DH3	1.656	264.96	400
GFSK	DH5	2.910	310.40	400

**EDR 2M**  
**Low Channel**

Modulation Type		Reading (ms)	Dwell Time (ms)	Limit (ms)
Pi/4 DQPSK	2DH1	0.388	124.16	400
Pi/4 DQPSK	2DH3	1.646	263.32	400
Pi/4 DQPSK	2DH5	2.910	310.40	400

**Middle Channel**

Modulation Type		Reading (ms)	Dwell Time (ms)	Limit (ms)
Pi/4 DQPSK	2DH1	0.388	124.16	400
Pi/4 DQPSK	2DH3	1.646	263.32	400
Pi/4 DQPSK	2DH5	2.910	310.40	400

**High Channel**

Modulation Type		Reading (ms)	Dwell Time (ms)	Limit (ms)
Pi/4 DQPSK	2DH1	0.390	124.80	400
Pi/4 DQPSK	2DH3	1.646	263.32	400
Pi/4 DQPSK	2DH5	2.910	310.40	400

**EDR 3M**  
**Low Channel**

<b>Modulation Type</b>		<b>Reading (ms)</b>	<b>Dwell Time (ms)</b>	<b>Limit (ms)</b>
8-DPSK	3DH1	0.396	126.72	400
8-DPSK	3DH3	1.636	261.76	400
8-DPSK	3DH5	2.910	310.40	400


**Middle Channel**

<b>Modulation Type</b>		<b>Reading (ms)</b>	<b>Dwell Time (ms)</b>	<b>Limit (ms)</b>
8-DPSK	3DH1	0.396	126.72	400
8-DPSK	3DH3	1.636	261.76	400
8-DPSK	3DH5	2.910	310.40	400


**High Channel**

<b>Modulation Type</b>		<b>Reading (ms)</b>	<b>Dwell Time (ms)</b>	<b>Limit (ms)</b>
8-DPSK	3DH1	0.396	126.72	400
8-DPSK	3DH3	1.636	261.76	400
8-DPSK	3DH5	2.910	310.40	400


**BDR-DH1**  
**Channel Low**




**Channel Mid**




## Channel High




## DH3 Channel Low




## Channel Middle




## Channel High




## DH5 Channel Low




## Channel Middle




## Channel High




## EDR 2M 2DH1 Channel Low




## Channel Middle




## Channel High




## EDR 2M 2DH3 Channel Low




## Channel Middle




## Channel High




## EDR 2M 2DH5 Channel Low




## Channel Middle




## Channel High




## EDR 3M 3DH1 Channel Low




## Channel Middle




## Channel High




## EDR 3M 3DH3 Channel Low




## Channel Middle




## Channel High




**EDR 3M 3DH5**  
**Channel Low**



**Channel Middle**



## Channel High




## 9. Test of Maximum Peak Output Power

### 9.1 Applicable standard

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels and The maximum peak output power shall not exceed 1 watt. For all other frequency hopping systems in this frequency band, The maximum peak output power shall not exceed 0.125 watt.

### 9.2 EUT Setup



### 9.3 Test Equipment List and Details

See section 2.5.

### 9.4 Test Procedure

1. The transmitter output was connected to the peak power meter and recorded the peak value.
2. Peak power meter parameter set to auto attenuator and filter is the same as.
3. Repeated the 1 for the middle and highest channel of the EUT.

### 9.5 Test Result

Temperature ( °C ) : 22~23	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH) : 50~54	M/N: RT1
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Tx Mode

## BDR 1M

Modulation Type	Channel No.	Frequency (MHz)	Output Power (dBm)	Limits (dBm)	Margin (dB)
GFSK	Low	2402.00	2.02	21	-18.98
GFSK	Middle	2441.00	4.20	21	-16.80
GFSK	High	2480.00	4.88	21	-16.12


## EDR 2M

Modulation Type	Channel No.	Frequency (MHz)	Output Power (dBm)	Limits (dBm)	Margin (dB)
Pi/4 DQPSK	Low	2402.00	-0.83	21	-20.17
Pi/4 DQPSK	Middle	2441.00	2.21	21	-18.79
Pi/4 DQPSK	High	2480.00	3.09	21	-17.91


## EDR 3M

Modulation Type	Channel No.	Frequency (MHz)	Output Power (dBm)	Limits (dBm)	Margin (dB)
8-DPSK	Low	2402.00	-0.58	21	-20.42
8-DPSK	Middle	2441.00	2.42	21	-18.58
8-DPSK	High	2480.00	3.34	21	-17.66


## BDR 1M Channel Low




## Channel Middle




## Channel High




## EDR 2M Channel Low




## Channel Middle




## Channel High




## EDR 3M Channel Low



## Channel Middle



## Channel High



## 10. Test of Band Edges Emission

### 10.1 Applicable standard

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions that fall in the restricted bands, as defined in Section 15.205, must also comply with the radiated emission limits specified in Section 15.209.

### 10.2 EUT Setup

Radiated Measurement Setup





Figure 2 : Frequencies measured above 1 GHz configuration

Conducted Measurement Setup



### 10.3 Test Equipment List and Details

See section 2.5.

### 10.4 Test Procedure

Conducted Measurement

1. The transmitter is set to the lowest channel.
2. The transmitter output was connected to the spectrum analyzer via a cable .

3. Set both RBW and VBW of spectrum analyzer to 100KHz with convenient frequency span including 100MHz bandwidth from lower band edge. Then detector set to peak and max hold this trace.

4. The lowest band edges emission was measured and recorded.

5. The transmitter set to the highest channel and repeated 2~4.

#### Radiated Measurement

1. Configure the EUT according to ANSI C63.4-2003

2. The turntable was rotated by 360 degrees to determine the position of the highest radiation.

3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.

4. For band edge emission, the antenna tower was scan (from 1 M to 4 M) and then the turn table was rotated (from 0 degree to 360 degrees) to find the maximum reading.

5. For band edge emission, use 1MHz VBW and 1MHz RBW for reading under AV and use 1MHz VBW and 1MHz RBW for reading under PK.

### 10.5 Test Result

Temperature ( °C ) : 22~23	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH) : 50~54	M/N: RT1
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Tx Mode

#### Radiated Test Result

##### Worst Case BDR 1M

Frequency (MHz)	Antenna Polarization	Emission Read Value (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)
2389.5	H	34.55	54
2389.5	V	35.34	54
2483.7	H	36.61	54
2483.7	V	37.76	54


##### Worst Case EDR 2M

Frequency (MHz)	Antenna Polarization	Emission Read Value (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)
2389.4	H	34.67	54
2389.4	V	35.90	54
2483.7	H	36.32	54
2483.7	V	35.64	54


**Worst Case EDR 3M**

Frequency (MHz)	Antenna Polarization	Emission Read Value (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)
2389.5	H	31.52	54
2389.5	V	33.69	54
2483.6	H	34.24	54
2483.6	V	35.75	54


**Conducted Test Result**  
**BDR 1M**  
**Low Channel**




**High Channel**




## EDR 2M Low Channel




## High Channel




## EDR 3M Low Channel




## High Channel



**Hopping Mode Worst case BDR 1M**  
**Low**



**High**



## 11. Test of Spurious Radiated Emission


### 11.1 Applicable standard

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains

the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions that fall in the restricted bands, as defined in Section 15.205, must also comply with the radiated emission limits specified in Section 15.209.

### 11.2 EUT Setup

#### Conducted Measurement Setup



Spectrum Analyzer

#### Radiated Measurement Setup




Figure 1 : Frequencies measured below 1 GHz configuration




Figure 2 : Frequencies measured above 1 GHz configuration

### 11.3 Test Equipment List and Details

See section 2.5.

### 11.4 Test Procedure

#### Conducted Measurement

1. For emission above 1GHz to 26G, conducted measurement method is used.
2. The transmitter is set to the lowest channel.
3. The transmitter output was connected to the spectrum analyzer via a cable and cable loss is used as the offset of the spectrum analyzer.
4. Set RBW to 1 MHz and VBW to 3 MHz, Then detector set to peak and max hold this trace.
5. The lowest band edges emission was measured and recorded.
6. The transmitter set to the highest channel and repeated 2~4.

#### Radiated Measurement

1. Configure the EUT according to ANSI C63.4-2003
2. The EUT was placed on the top of the turntable 0.8 meter above ground.
3. Receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable. When the frequency spectrum measured started from 9 kHz to 30 MHz, a loop antenna is used. When the frequency spectrum measured started from 30 MHz to 1000 MHz and above 1000 MHz, a broadband receiving antenna and the horn antenna are used.
4. Power on the EUT and all the supporting units.
5. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
6. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
7. For each suspected emission, the antenna tower was scanned (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.

8. According to the characteristic of the EUT crystals, the range of frequencies was investigated from 9KHz to 30MHz, 30MHz to 1GHz and 1GHz to 26GHz.

9. For emission below 1GHz, Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.

10. For emission above 1GHz, Set the RBW=1MHz,VBW=3MHz for Peak Detector while the RBW=1MHz, VBW=10Hz for Average Detector, Readings are both peak and average values.

11. The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos. The worst case data is recorded in the report. All emission not reported are much lower than the prescribed limits.

## 11.5 Test Result


Temperature ( °C ) : 22~23	EUT: NUU Riptide / Splash Mini / Mini Speaker
Humidity (%RH ): 50~54	M/N: RT1
Barometric Pressure ( mbar ): 950~1000	Operation Condition: TX Mode

The worst Spurious Emission Data BDR Mode Below 1GHz Channel Low:

EUT: NUU Riptide / Splash Mini / Mini Speaker  
M/N: RT1  
Operating Condition: TX Mode  
Test Site: 3m CHAMBER  
Operator: Chen  
Test Specification: DC 3.7V from battery  
Comment: Polarization: Horizontal

***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz
				Transducer
				VULB9163 NEW



***MEASUREMENT RESULT: "14FR24101\_red"***

6/16/2014 18:35


Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	23.50	15.8	40.0	16.5	QP	100.0	0.00	HORIZONTAL
59.100000	21.60	14.6	40.0	18.4	QP	100.0	0.00	HORIZONTAL
101.780000	23.50	17.3	43.5	20.0	QP	100.0	0.00	HORIZONTAL
299.660000	26.00	18.7	46.0	20.0	QP	100.0	0.00	HORIZONTAL
379.200000	34.50	20.9	46.0	11.5	QP	100.0	0.00	HORIZONTAL
941.800000	36.80	29.5	46.0	9.2	QP	100.0	0.00	HORIZONTAL

The worst Spurious Emission Data BDR Mode Below 1GHz Channel Low:

EUT: NUU Riptide / Splash Mini / Mini Speaker  
M/N: RT1  
Operating Condition: TX Mode  
Test Site: 3m CHAMBER  
Operator: Chen  
Test Specification: DC 3.7V from battery  
Comment: Polarization: Vertical

***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz
				Transducer
				VULB9163 NEW



***MEASUREMENT RESULT: "14FR24102\_red"***

6/16/2014 18:38


Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	27.80	15.8	40.0	12.2	QP	100.0	0.00	VERTICAL
59.100000	21.60	14.6	40.0	18.4	QP	100.0	0.00	VERTICAL
97.900000	23.20	17.4	43.5	20.3	QP	100.0	0.00	VERTICAL
293.840000	25.00	18.6	46.0	21.0	QP	100.0	0.00	VERTICAL
540.220000	31.40	24.8	46.0	14.6	QP	100.0	0.00	VERTICAL
914.640000	39.80	29.3	46.0	6.2	QP	100.0	0.00	VERTICAL

The worst Spurious Emission Data BDR Mode Below 1GHz Channel Middle:

EUT: NUU Riptide / Splash Mini / Mini Speaker  
M/N: RT1  
Operating Condition: TX Mode  
Test Site: 3m CHAMBER  
Operator: Chen  
Test Specification: DC 3.7V from battery  
Comment: Polarization: Horizontal

***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz
				Transducer
				VULB9163 NEW



***MEASUREMENT RESULT: "14FR24104\_red"***

6/16/2014 18:44


Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
39.700000	25.80	15.8	40.0	14.2	QP	100.0	0.00	HORIZONTAL
57.160000	21.30	15.1	40.0	18.7	QP	100.0	0.00	HORIZONTAL
97.900000	23.30	17.4	43.5	20.2	QP	100.0	0.00	HORIZONTAL
297.720000	24.80	18.7	46.0	21.2	QP	100.0	0.00	HORIZONTAL
544.100000	31.10	24.9	46.0	14.9	QP	100.0	0.00	HORIZONTAL
860.320000	36.00	28.7	46.0	10.0	QP	100.0	0.00	HORIZONTAL

The worst Spurious Emission Data BDR Mode Below 1GHz Channel Middle:

EUT: NUU Riptide / Splash Mini / Mini Speaker  
M/N: RT1  
Operating Condition: TX Mode  
Test Site: 3m CHAMBER  
Operator: Chen  
Test Specification: DC 3.7V from battery  
Comment: Polarization: Vertical

***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz
Transducer VULB9163 NEW				



***MEASUREMENT RESULT: "14FR24103\_red"***

6/16/2014 18:41


Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det. QP	Height cm	Azimuth deg	Polarization
47.460000	27.50	15.8	40.0	12.5	QP	100.0	0.00	VERTICAL
59.100000	22.50	14.6	40.0	17.5	QP	100.0	0.00	VERTICAL
97.900000	24.10	17.4	43.5	19.4	QP	100.0	0.00	VERTICAL
295.780000	25.30	18.6	46.0	20.7	QP	100.0	0.00	VERTICAL
544.100000	31.30	24.9	46.0	14.7	QP	100.0	0.00	VERTICAL
949.560000	36.40	29.6	46.0	9.6	QP	100.0	0.00	VERTICAL

The worst Spurious Emission Data BDR Mode Below 1GHz Channel High:

EUT: NUU Riptide / Splash Mini / Mini Speaker  
M/N: RT1  
Operating Condition: TX Mode  
Test Site: 3m CHAMBER  
Operator: Chen  
Test Specification: DC 3.7V from battery  
Comment: Polarization: Horizontal

***SWEET TABLE: "test (30M-1G)"***

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz
Transducer VULB9163 NEW				



***MEASUREMENT RESULT: "14FR24105\_red"***

6/16/2014 18:49


Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	24.40	15.8	40.0	15.6	QP	100.0	0.00	HORIZONTAL
55.220000	22.20	15.6	40.0	17.8	QP	100.0	0.00	HORIZONTAL
99.840000	23.50	17.5	43.5	20.0	QP	100.0	0.00	HORIZONTAL
291.900000	24.90	18.5	46.0	21.1	QP	100.0	0.00	HORIZONTAL
538.280000	31.50	24.7	46.0	14.5	QP	100.0	0.00	HORIZONTAL
885.540000	36.70	29.0	46.0	9.3	QP	100.0	0.00	HORIZONTAL

The worst Spurious Emission Data BDR Mode Below 1GHz Channel High:

EUT: NUU Riptide / Splash Mini / Mini Speaker  
M/N: RT1  
Operating Condition: TX Mode  
Test Site: 3m CHAMBER  
Operator: Chen  
Test Specification: DC 3.7V from battery  
Comment: Polarization: Vertical

***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz
				Transducer
				VULB9163 NEW



***MEASUREMENT RESULT: "XJD061606\_red"***

6/16/2014 18:50

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det. QP	Height cm	Azimuth deg	Polarization
47.460000	27.70	15.8	40.0	12.3	QP	100.0	0.00	VERTICAL
59.100000	21.90	14.6	40.0	18.1	QP	100.0	0.00	VERTICAL
101.780000	23.50	17.3	43.5	20.0	QP	100.0	0.00	VERTICAL
288.020000	25.40	18.4	46.0	20.6	QP	100.0	0.00	VERTICAL
551.860000	32.10	25.0	46.0	13.9	QP	100.0	0.00	VERTICAL
877.780000	36.20	28.9	46.0	9.8	QP	100.0	0.00	VERTICAL

The worst Spurious Emission Data BDR Mode Above 1GHz

Channel Low

Channel Low (2402MHz)								
Maximum Frequency (MHz)	Polarity and Level					Limit (dB $\mu$ V/m)	Margin (dB $\mu$ V/m)	Mark (P/Q/A)
	Polarity	Height (m)	Reading dB $\mu$ V	Transd	Result dB $\mu$ V/m			
2402	H	1	99.74	-7.15	92.59	N/A	N/A	P
			91.58	-7.15	84.43	N/A	N/A	A
2402	V	1	101.55	-7.15	94.4	N/A	N/A	P
			97.59	-7.15	90.44	N/A	N/A	A
4804	H	1	42.6	1.07	43.67	74	-30.33	P
			32.47	1.07	33.54	54	-20.46	A
4804	V	1	44.05	1.07	45.12	74	-28.88	P
			33.67	1.07	34.74	54	-19.26	A
7206	H	1	41.81	7.38	49.19	74	-24.81	P
			33.07	7.38	40.45	54	-13.55	A
7206	V	1	44.8	7.38	52.18	74	-21.82	P
			33.55	7.38	40.93	54	-13.07	A
9608	H	1	42.11	10.29	52.4	74	-21.6	P
			31.89	10.29	42.18	54	-11.82	A
9608	V	1	43.81	7.38	51.19	74	-22.81	P
			34.07	7.38	41.45	54	-12.55	A
12023.31	H	1	42.8	14.01	56.81	74	-17.19	P
			32.55	14.01	46.56	54	-7.44	A
12023.33	V	1	44.07	14.01	58.08	74	-15.92	P
			33.8	14.01	47.81	54	-6.19	A
25220.37	----	----	----	----	----	----	----	----

Remark: 1. Transd.=Antenna Factor+Cable Loss+Pre-amplifier  
Margin = Level-Limit  
Mark: P means Peak Value, Q means Quasi Peak Value, A means Average Value  
2. Data of measurement within this frequency range shown “-” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.  
3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz.  
4. The test limit distance is 3m limit

Channel Mid

Channel Middle (2441MHz)								
Maximum Frequency (MHz)	Polarity and Level					Limit (dB $\mu$ V/m)	Margin (dB $\mu$ V/m)	Mark (P/Q/A)
	Polarity	Height (m)	Reading dB $\mu$ V	Transd	Result dB $\mu$ V/m			
2441	H	1	100.76	-6.37	94.39	N/A	N/A	P
			92.59	-6.37	86.22	N/A	N/A	A
2441	V	1	105.57	-6.37	99.2	N/A	N/A	P
			97.1	-6.37	90.73	N/A	N/A	A
4882	H	1	41.47	1.07	42.54	74	-31.46	P
			32.06	1.07	33.13	54	-20.87	A
4882	V	1	43.76	1.07	44.83	74	-29.17	P
			33.55	1.07	34.62	54	-19.38	A
7323	H	1	42.61	7.49	50.1	74	-23.9	P
			32.76	7.49	40.25	54	-13.75	A
7323	V	1	44.8	7.49	52.29	74	-21.71	P
			33.5	7.49	40.99	54	-13.01	A
9764	H	1	42.46	10.47	52.93	74	-21.07	P
			31.58	10.47	42.05	54	-11.95	A
9764	V	1	44	10.47	54.47	74	-19.53	P
			34.06	10.47	44.53	54	-9.47	A
12168.22	H	1	42.37	14.1	56.47	74	-17.53	P
			31.97	14.1	46.07	54	-7.93	A
12168.22	V	1	44.86	14.1	58.96	74	-15.04	P
			32.6	14.1	46.7	54	-7.3	A
25380.37	----	----	----	----	----	----	----	----

Remark: 1. Transd.=Antenna Factor+Cable Loss+Pre-amplifier

Margin = Level-Limit

Mark: P means Peak Value, Q means Quasi Peak Value, A means Average Value

2. Data of measurement within this frequency range shown “-” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz.

4. The test limit distance is 3m limit

## Channel High

Channel High (2480MHz)								
Maximum Frequency (MHz)	Polarity and Level					Limit (dB $\mu$ V/m)	Margin (dB $\mu$ V/m)	Mark (P/Q/A)
	Polarity	Height (m)	Reading dB $\mu$ V	Transd	Result dB $\mu$ V/m			
2480	H	1	100.76	-6.05	94.71	N/A	N/A	P
			92.97	-6.05	86.92	N/A	N/A	A
2480	V	1	105.1	-6.05	99.05	N/A	N/A	P
			95.67	-6.05	89.62	N/A	N/A	A
4960	H	1	42.81	1.07	43.88	74	-30.12	P
			33.47	1.07	34.54	54	-19.46	A
4960	V	1	45.67	1.07	46.74	74	-27.26	P
			34.79	1.07	35.86	54	-18.14	A
7440	H	1	43.07	7.61	50.68	74	-23.32	P
			33.06	7.61	40.67	54	-13.33	A
7440	V	1	44.8	7.61	52.41	74	-21.59	P
			35.01	7.61	42.62	54	-11.38	A
9920	H	1	43.6	10.65	54.25	74	-19.75	P
			34.16	10.65	44.81	54	-9.19	A
9920	V	1	45.07	10.65	55.72	74	-18.28	P
			34.19	10.65	44.84	54	-9.16	A
12361.67	H	1	42.8	14.19	56.99	74	-17.01	P
			33	14.19	47.19	54	-6.81	A
12361.67	V	1	44.11	14.19	58.3	74	-15.7	P
			33.96	14.19	48.15	54	-5.85	A
25380.37	----	----	----	----	----	----	----	----
Remark: 1. Transd.=Antenna Factor+Cable Loss+Pre-amplifier Margin = Level-Limit Mark: P means Peak Value, Q means Quasi Peak Value, A means Average Value 2. Data of measurement within this frequency range shown “-” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. 3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz. 4. The test limit distance is 3m limit								

The worst Spurious Emission Data BDR Mode Below 30 MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Levels (dBuV/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector Mode
5.78	22.01	8.23	1.03	29.21	67	-37.79	QP
15.11	21.87	9.07	1.19	29.75	49.5	-19.75	QP
22.64	22.7	9.25	1.08	30.87	49.5	-18.63	QP
23.67	22.56	8.43	1.66	29.33	49.5	-20.17	QP


Note:

1. The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos. The worst case data is recorded in the report.
2. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
3. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
4. The other emission levels were very low against the limit.
5. Margin value = Emission level.- Limit value


#### Conducted Spurious Emission

BDR 1M


Channel Low




## Channel Mid



## Channel High




**BDR 2M**  
**Channel Low**




**Channel Middle**




## Channel High




**BDR 3M**  
**Channel Low**



## Channel Middle



## Channel High



## **12. ANTENNA REQUIREMENT**

### **12.1 standard Applicable**

Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Section 15.247(b)/(c):

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

If the intentional radiator is used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

### **12.2 Antenna Connected Construction**

The antenna is designed with permanent attachment and no consideration of replacement. The antenna used in this product is complied with standard. The maximum Gain of the antenna lower than 6.0dBi and have the definite antenna Specification.