

# RF Exposure Evaluation Report

**Product** : Bluetooth Speaker  
**Trade mark** : NUU, Whyrless, DOCKIN, ENERGY SISTEM  
**Model/Type reference** : BOOM BOX, W2. Whyrless BOOM, DOCKIN D Fine, ENERGY SISTEM BOOM BOX  
**Serial Number** : N/A  
**Report Number** : EED32I00229003  
**FCC ID** : YQB0SCI1000007  
**Date of Issue** : Oct. 18, 2016  
**Test Standards** : 47 CFR Part 1.1307(2015)  
47 CFR Part 1.1310(2015)  
KDB447498D01v06  
**Test result** : PASS

Prepared for:

**SUN CUPID (SHENZHEN) ELECTRONIC LTD**  
10A, No.3 Bldg, China Academy of Sci &Tech Development, No.1 High-Tech South St., Shenzhen, China

Prepared by:

**Centre Testing International Group Co., Ltd.**  
Hongwei Industrial Zone, Bao'an 70 District,  
Shenzhen, Guangdong, China

**TEL: +86-755-3368 3668**

**FAX: +86-755-3368 3385**

Tested By:

*Tom chen*

Tom chen (Test Project)

Compiled by:

*Ware Xin*

Ware Xin (Project Engineer)

Reviewed by:

*Kevin Yang*

Kevin yang (Reviewer)

Approved by:

*Sheek Luo*

Sheek Luo (Lab supervisor)



Oct. 18, 2016

Check No.: 2496551428

## 2 Version

Version No.	Date	Description
00	Oct. 18, 2016	Original

### 3 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION.....</b>	<b>2</b>
<b>3 CONTENTS.....</b>	<b>3</b>
<b>4 GENERAL INFORMATION.....</b>	<b>4</b>
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 TEST FACILITY.....	5
4.6 DEVIATION FROM STANDARDS.....	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
4.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
<b>5 RF EXPOSURE EVALUATION.....</b>	<b>7</b>
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	7
5.1.1 Limits.....	7
5.1.2 Test Procedure.....	7
5.1.3 EUT RF Exposure Evaluation.....	8
<b>PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....</b>	<b>9</b>

## 4 General Information

### 4.1 Client Information

Applicant:	SUN CUPID (SHENZHEN) ELECTRONIC LTD
Address of Applicant:	10A, No.3 Bldg, China Academy of Sci &Tech Development, No.1 High-Tech South St., Shenzhen, China
Manufacturer:	Foshan Sun Cupid Electronics Fty Ltd
Address of Manufacturer:	Block 7 No.127 Zhangcha 1 Road, Chancheng District, Foshan, Guangdong, China.
Factory:	Foshan Sun Cupid Electronics Fty Ltd
Address of Factory:	Block 7 No.127 Zhangcha 1 Road, Chancheng District, Foshan, Guangdong, China.

### 4.2 General Description of EUT

Product Name:	Bluetooth Speaker
Model No.(EUT):	BOOM BOX, W2. Whyrless BOOM, DOCKIN D Fine, ENERGY SISTEM BOOM BOX
Test Model No.:	BOOM BOX
Trade mark:	NUU, Whyrless, DOCKIN, ENERGY SISTEM
EUT Supports Radios application:	Bluetooth V3.0+EDR & Bluetooth V4.0 BLE

### 4.3 Product Specification subjective to this standard

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	3.0+EDR & 4.0 BLE
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Test Power Grade:	255(manufacturer declare )
Test Software of EUT:	CSR blue suite (manufacturer declare )
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
Test Voltage:	AC 120V/60Hz, AC 230V/50Hz
Conducted Peak Power:	1.941dBm
	The Power data refer to the report EED32I00229001 & EED32I00229002
Sample Received Date:	Oct. 11, 2016
Sample tested Date:	Oct. 11, 2016 to Oct. 18, 2016
The tested samples and the sample information are provided by the client.	

#### 4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 3368 3668 Fax: +86 (0) 755 3368 3385

No tests were sub-contracted.

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**CNAS-Lab Code: L1910**

Centre Testing International Group Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories..

**A2LA-Lab Cert. No. 3061.01**

Centre Testing International Group Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

**FCC-Registration No.: 886427**

Centre Testing International Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 886427.

**IC-Registration No.: 7408A-2**

The 3m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408A-2 .

**IC-Registration No.: 7408B-1**

The 10m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408B-1.

**NEMKO-Aut. No.: ELA503**

Centre Testing International Group Co., Ltd. has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA-10.

**VCCI**

The Radiation 3 & 10 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-4096.



Main Ports Conducted Interference Measurement of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-4563.

Telecommunication Ports Conducted Disturbance Measurement of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-2146.

The Radiation 3 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-758

#### **4.6 Deviation from Standards**

None.

#### **4.7 Abnormalities from Standard Conditions**

None.

#### **4.8 Other Information Requested by the Customer**

None.

## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P\*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user.

Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

Report No. : EED32I00229003

Page 8 of 9

### 5.1.3 EUT RF Exposure Evaluation

**Antenna Gain:** 0dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power(dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R (cm)	S (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Lowest	2402	1.941	0	1.941	1.56	20	0.0003	1.0	Pass

**Note:** Refer to report No. EED32I00229001 & EED32I00229002 for EUT test Max Conducted Peak Output Power value.



## **PHOTOGRAPHS OF EUT Constructional Details**

Refer to Report No. EED32I00229001 for EUT external and internal photos.

**\*\*\* End of Report \*\*\***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.