### SAR evaluation considerations for handsets with multiple transmitters and antennas

### **Procedure:**

FCC KDB 648474 v01r05 SAR evaluation considerations for handsets with multiple transmitters and antennas.

Table 1 - Output Power Thresholds for Unlicensed Transmitters

	2.45	5.15 - 5.35	5.47 - 5.85	GHz
PRef	12	6	5	mW

Table 2 – Summary of SAR Evaluation Requirements for a Cell Phone with Multiple Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	Routine evaluation required	SAR not required: Unlicensed only
Unlicensed Transmitters	When there is no simultaneous transmission — o output $\leq 60/f$ : SAR not required o output $\geq 60/f$ : stand-alone SAR required When there is simultaneous transmission — Stand-alone SAR not required when output $\leq 2 \cdot P_{Ref}$ and antenna is $\geq 5.0$ cm from other antennas output $\leq P_{Ref}$ and antenna is $\geq 2.5$ cm from other antennas output $\leq P_{Ref}$ and antenna is $\leq 2.5$ cm from other antennas, each with either output power $\leq P_{Ref}$ or 1-g SAR $\leq 1.2$ W/kg Otherwise stand-alone SAR is required When stand-alone SAR is required output channel for each wireless mode and exposure condition if SAR for highest output channel is $\geq 50\%$ of SAR limit, evaluate all channels according to normal procedures	o when stand-alone 1-g SAR is not required and antenna is ≥ 5 cm from other antennas  Licensed & Unlicensed o when the sum of the 1-g SAR is < 1.6 W/kg for all simultaneous transmitting antennas o when SAR to peak location separation ratio of simultaneous transmitting antenna pair is < 0.3  SAR required:  Licensed & Unlicensed antenna pairs with SAR to peak location separation ratio ≥ 0.3; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition  Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply
Jaw, Mouth and Nose	Flat phantom SAR required  o when measurement is required in tight regions of SAM and it is not feasible or the results can be questionable due to probe tilt calibration, positioning and orientation issues  o position rectangular and clam-shell phones according to flat phantom procedures and conduct SAR measurements for these specific locations	When simultaneous transmission SAR testing is required, contact the FCC Laboratory for interim guidance.

# **Equipment:**

A mobile phone contains GSM850/1900 transmitter and Bluetooth transmitter with FCC ID YROG152I.

### **Measurement data:**

The closest distance between the GSM850/1900 antenna and Bluetooth antenna is 33 mm.

The maximum output power of Bluetooth transmitter is 1.04 mW.

The maximum SAR value for GSM850/1900 transmitter is 0.851 W/kg (1-g).

# **Conclusion:**

Based on the output power of Bluetooth transmitter, antenna separation and the SAR value of GSM850/1900 transmitter, stand-alone Bluetooth SAR evaluation is not required.

The sum of 1-g SAR is 0.851 W/kg + 0 W/kg = 0.851 W/kg, which is less than 1.6 W/kg. Therefore, simultaneous transmission SAR evaluation is not required.