

SAR evaluation considerations for handsets with multiple transmitters and antennas

Procedure:

FCC KDB 648474 v01r05 SAR evaluation considerations for handsets with multiple transmitters and antennas.

Table 1 – Output Power Thresholds for Unlicensed Transmitters

	2.45	5.15 - 5.35	5.47 - 5.85	GHz
P _{Ref}	12	6	5	mW

Device output power should be rounded to the nearest mW to compare with values specified in this table.

Table 2 – Summary of SAR Evaluation Requirements for a Cell Phone with Multiple Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	<u>Routine evaluation required</u>	<u>SAR not required:</u> <u>Unlicensed only</u> <ul style="list-style-type: none">○ when stand-alone 1-g SAR is not required and antenna is \geq 5 cm from other antennas <u>Licensed & Unlicensed</u> <ul style="list-style-type: none">○ when the sum of the 1-g SAR is $<$ 1.6 W/kg for all simultaneous transmitting antennas○ when SAR to peak location separation ratio of simultaneous transmitting antenna pair is $<$ 0.3 <u>SAR required:</u> <u>Licensed & Unlicensed</u> <p>antenna pairs with SAR to peak location separation ratio \geq 0.3; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition</p> <p>Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply</p>
Unlicensed Transmitters	<p>When there is no simultaneous transmission –</p> <ul style="list-style-type: none">○ output \leq 60/f: SAR not required○ output $>$ 60/f: stand-alone SAR required <p>When there is simultaneous transmission –</p> <p><u>Stand-alone SAR not required when</u></p> <ul style="list-style-type: none">○ output \leq 2-P_{Ref} and antenna is \geq 5.0 cm from other antennas○ output \leq P_{Ref} and antenna is \geq 2.5 cm from other antennas○ output \leq P_{Ref} and antenna is $<$ 2.5 cm from other antennas, each with either output power \leq P_{Ref} or 1-g SAR $<$ 1.2 W/kg <p><u>Otherwise stand-alone SAR is required</u></p> <p><u>When stand-alone SAR is required</u></p> <ul style="list-style-type: none">○ test SAR on highest output channel for each wireless mode and exposure condition○ if SAR for highest output channel is $>$ 50% of SAR limit, evaluate all channels according to normal procedures	
Jaw, Mouth and Nose	<p><u>Flat phantom SAR required</u></p> <ul style="list-style-type: none">○ when measurement is required in tight regions of SAM and it is not feasible or the results can be questionable due to probe tilt, calibration, positioning and orientation issues○ position rectangular and clam-shell phones according to flat phantom procedures and conduct SAR measurements for these specific locations	When simultaneous transmission SAR testing is required, contact the FCC Laboratory for interim guidance.

Equipment:

A mobile phone contains GSM850/1900 transmitter and Bluetooth transmitter with FCC ID YROG7I.

Measurement data:

The closest distance between the GSM850/1900 antenna and Bluetooth antenna is **12 mm**.

The maximum output power of Bluetooth transmitter is **1.115 mW**.

The maximum SAR value for GSM850/1900 transmitter is **1.086 W/kg** (1-g).

Conclusion:

Based on the output power of Bluetooth transmitter, antenna separation and the SAR value of GSM850/1900 transmitter, stand-alone Bluetooth SAR evaluation is not required.

The sum of 1-g SAR is $1.086 \text{ W/kg} + 0 \text{ W/kg} = 1.086 \text{ W/kg}$, which is less than 1.6 W/kg. Therefore, simultaneous transmission SAR evaluation is not required.