

FCC PART 18

EMI MEASUREMENT AND TEST REPORT

For
Golo Chang Company Limited
4F, No.50-3, San Min Rd., LuChouCity, TaiBei Hsien, Taiwan, R.O.C.

FCC ID: YRPCANDELABRA

Sep 13, 2010

Product Name:	CFL
Model No:	G120427 & G120727
Sample	
Received Date:	July 28, 2010
Test	
Performed Date:	Aug 28, 2010
Test Engineer:	David Zhang <i>David Zhang</i>
Reviewed By:	Steven Hsu <i>Steven Hsu</i>
Prepared By:	BEST Test Service Shenzhen Co., Ltd. C, 310-316, Huameiju Business Center, 82 Block, Baoan District, Shenzhen, China TEL: +86-755-28236006 FAX: +86-755-28236249 Email: certification@bestcert.cn



NVLAP LAB CODE 200770-0

Note: The test report only allows to be revised within the retention period unless further standard or the requirement was noticed. This report is for the exclusive use of BEST's Client and is provided pursuant to the agreement between BEST and its Client. BEST's responsibility and Liability are limited to the terms and conditions of the agreement. BEST assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the BEST name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by BEST. The observations and test results in this report are relevant only to the sample tested. This report by itself does not that the material, product, of service is or has ever been under an BEST certification program. National Voluntary Laboratory Accreditation Program (NVLAP) has accredited this laboratory under ISO17025: 2005 for specific laboratory activities as listed in the NVLAP directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE.....	3
RELATED SUBMITTAL(s)/GRANT(s)	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION	4
JUSTIFICATION.....	4
SCHEMATICS / BLOCK DIAGRAM.....	4
EQUIPMENT MODIFICATIONS	4
CONFIGURATION OF TEST SYSTEM.....	4
TEST SETUP BLOCK DIAGRAM	4
CONDUCTED EMISSIONS TEST DATA.....	5
APPLICABLE STANDARD	5
MEASUREMENT UNCERTAINTY	5
EUT SETUP	5
TEST EQUIPMENTS	6
TEST PROCEDURE	6
SUMMARY OF TEST RESULTS	6
CONDUCTED EMISSIONS TEST DATA AND PLOTS	7

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Golo Chang Company Limited's model G120427 & G120727 or the "EUT" as referred to in this report is CFL, rated input voltage: AC 120V/60Hz, operation frequency between 40 KHz to 60 KHz.

Model	G120427	Electrical Power	4W
Model	G120727	Electrical Power	7W

The test data was only good for the test sample. It may have deviation for other test sample.

Objective

The following test report is prepared on behalf of Golo Chang Company Limited. in accordance with Part 2, Subpart J, and Part 18, Subparts A, B, and C of the Federal Communication Commissions rules and regulations.

The objective of the manufacturer is to demonstrate compliance with FCC Part 18 limit requirements for Industrial, Scientific, and Medical Equipment.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with MP-5 1986, FCC Method of measurements of radio noise emission from Industrial, Scientific and Medical equipments.

Test Facility

All measurement facilities used to collect the data are located at Huatongwei Building , Keji Rd, 12 S, high-Tech Park, Nanshan District, Shenzhen, China.

The sites are constructed in conformance with the requirements of ANSI C63.7/634 and CISPR 22, The site was accredited by FCC (662850), A2LA(2243.01) and CNAL (L1225)

SYSTEM TEST CONFIGURATION

Justification

The EUT was tested under normal mode as used by a common (typical) user.


Schematics / Block Diagram

N/A.


Equipment Modifications

No modifications were made by BEST TEST SERVICE Shenzhen CO., LTD. to ensure the EUT to comply with the application limits and requirements.

Configuration of Test System



Test Setup Block Diagram



CONDUCTED EMISSIONS TEST DATA

Applicable Standard

For the following equipment, when designed to be connected to the public utility (AC) power line the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies shall not exceed the limits in the following tables. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal using a 50 μ H/50 ohms line impedance stabilization network (LISN).


Frequency Range (MHz)	Max RF Voltage (uV)	Max RF Voltage (dBuV)
Non-consumer equipment		
0.45 to 1.6	1,000	60.0
1.6 to 30	3,000	69.0
Consumer equipment		
0.45 to 2.51	250	48.0
2.51 to 3.0	3000	69.0
3.0 to 30	250	48.0

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMI. The factors contributing to uncertainties are EMI Test Receiver, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMI Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BEST TEST SERVICE Shenzhen CO., LTD. is ± 2.0 dB.

EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with MP-5 measurement procedure. The specification used was the FCC Part 18 limits.

The EUT was connected to the power cord extension and placed on the left of the back edge on the test table.

The power cord extension was connected with 120 VAC/60 Hz power source.

Test Equipments

Manufacturer	Description	Model	Serial Number	Cal. Date	Cal. Due. Date
ROHDE & SCHWARZ	EMI TEST RECEIVER	ESCS30	100038	2010-08-05	2011-08-05
ROHDE & SCHWARZ	L.I.S.N	ESH2-Z5	100028	2010-08-05	2011-08-05
ROHDE & SCHWARZ	Pulse Limiter	ESHSZ2	100044	2010-08-05	2011-08-05

Statement of traceability: BEST attests that all calibrations have been performed per the CNAL /A2LA requirements, traceable to NIM China

Test Procedure

During the conducted emission test, the power cord of the power cord extension was connected to the auxiliary outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions to ensure that the EUT is compliant with all installation combination.

All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (within 4 dB μ V of specification limits). Quasi-peak readings are distinguished with a "Qp".

The EUT was tested under the normal modes during the final qualification test to represent the worst-case results.

Summary of Test Results

Pass

The EUT complied with the FCC 18 Conducted margin for industry, scientific and medical device, and with the worst margin reading of:

Conducted Emissions Test Data and Plots


BEST TEST SERVICE SHENZHEN CO., LTD

Voltage Mains Test FCC PART 18

EUT: CFL M/N:G120427
 Manufacturer: GOLO
 Operating Condition: ON
 Test Site: 3# SHIELDED ROOM
 Operator: BYRON
 Test Specification: AC 120V/60Hz
 Comment:
 Start of Test: 8/28/2010

SCAN TABLE: "FCC 18 LIGHT FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT:


Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.596000	40.60	10.4	48	7.3	QP	N	GND
0.872000	41.70	10.4	48	6.2	QP	N	GND
0.980000	41.70	10.5	48	6.2	QP	N	GND
1.104000	40.80	10.5	48	7.1	QP	N	GND
1.200000	41.80	10.5	48	6.1	QP	N	GND

BEST Test Service Shenzhen Co., Ltd**Voltage Mains Test FCC PART 18**

EUT: CFL M/N:G120427
Manufacturer: GOLO
Operating Condition: ON
Test Site: SHIELDED ROOM
Operator: Paul
Test Specification: AC 120V/60Hz
Comment:
Start of Test: 8/28/2010

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT:**


Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
1.888000	39.00	10.2	48	8.9	QP	L1	GND
1.920000	39.20	10.2	48	8.7	QP	L1	GND
1.962000	39.50	10.2	48	8.4	QP	L1	GND
2.014000	39.00	10.2	48	8.9	QP	L1	GND
2.056000	40.00	10.2	48	7.9	QP	L1	GND

BEST Test Service Shenzhen Co., Ltd**Voltage Mains Test FCC PART 18**

EUT: CFL M/N:G120727
 Manufacturer: GOLO
 Operating Condition: ON
 Test Site: SHIELDED ROOM
 Operator: Paul
 Test Specification: AC 120V/60Hz
 Comment:
 Start of Test: 8/28/2010

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT:**


Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.460000	41.30	10.1	48	6.6	QP	N	GND
0.544000	42.60	10.1	48	5.3	QP	N	GND
0.628000	41.70	10.1	48	6.2	QP	N	GND
1.872000	38.70	10.2	48	9.2	QP	N	GND
1.928000	39.20	10.2	48	8.7	QP	N	GND
1.956000	39.20	10.2	48	8.7	QP	N	GND

BEST Test Service Shenzhen Co., Ltd**Voltage Mains Test FCC PART 18**

EUT: CFL M/N:G120727
 Manufacturer: GOLO
 Operating Condition: ON
 Test Site: SHIELDED ROOM
 Operator: Paul
 Test Specification: AC 120V/60Hz
 Comment:
 Start of Test: 8/28/2010

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT:**

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.466000	39.90	10.1	48	8.0	QP	L1	GND
1.782000	34.30	10.2	48	13.6	QP	L1	GND
1.832000	34.40	10.2	48	13.5	QP	L1	GND
1.958000	37.20	10.2	48	10.7	QP	L1	GND
14.876000	37.90	10.6	48	10.0	QP	L1	GND
19.952000	38.80	11.1	48	9.1	QP	L1	GND