

Appendix D

RF Test Data for 5.5G WLAN (Conducted Measurement)

Product Name: Zettle Terminal

Trade Mark: Zettle Terminal

Test Model: Zettle Terminal


Environmental Conditions

Temperature:	22.3° C
Relative Humidity:	53.6%
ATM Pressure:	100.0 kPa
Test Engineer:	Diamond Lu
Supervised by:	Li Huan


D.1 Duty Cycle

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5580	100	0.00	0.01
11N20 SISO	5580	100	0.00	0.01
11N40 SISO	5590	100	0.00	0.01
11AC20 SISO	5580	100	0.00	0.01
11AC40 SISO	5590	100	0.00	0.01



On Time and Duty Cycle




IEEE 802.11a




IEEE 802.11n HT20







D.2 Maximum Conduct Output Power

Test Mode	Channel I	Frequency (MHz)	AVG Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	100	5500	12.64	0	12.64	24	Pass
	120	5580	12.85	0	12.85		Pass
	140	5700	12.55	0	12.55		Pass
11N20 SISO	100	5500	11.88	0	11.88	24	Pass
	120	5580	12.79	0	12.79		Pass
	140	5700	12.44	0	12.44		Pass
11N40 SISO	149	5510	12.16	0	12.16	24	Pass
	157	5590	12.81	0	12.81		Pass
	165	5670	13.11	0	13.11		Pass
11ac20 SISO	100	5500	11.97	0	11.97	24	Pass
	120	5580	12.85	0	12.85		Pass
	140	5700	12.57	0	12.57		Pass
11ac40 SISO	149	5510	12.34	0	12.34	24	Pass
	157	5590	12.94	0	12.94		Pass
	165	5670	12.65	0	12.65		Pass
11ac80 SISO	106	5530	12.71	0	12.71	24	Pass






IEEE 802.11a / Channel 120 / 5580MHz




IEEE 802.11a / Channel 140 / 5700MHz


Maximum Conducted Output Power




IEEE 802.11n20 / Channel 100 / 5500MHz




IEEE 802.11n20 / Channel 120 / 5580MHz




Maximum Conducted Output Power




IEEE 802.11n40 / Channel 102 / 5510MHz




IEEE 802.11n40 / Channel 118 / 5590MHz




IEEE 802.11n40 / Channel 134 / 5670MHz



IEEE 802.11ac20 / Channel 100 / 5500MHz




IEEE 802.11ac20 / Channel 120 / 5580MHz




IEEE 802.11ac20 / Channel 140 / 5700MHz


Maximum Conducted Output Power




IEEE 802.11ac40 / Channel 102 / 5510MHz



IEEE 802.11ac40 / Channel 118 / 5590MHz




IEEE 802.11ac40 / Channel 134 / 5670MHz




IEEE 802.11ac80 / Channel 106 / 5530MHz


D.3 Power Spectral Density

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Cycle Factor (dB)	Report Power Density (dBm/MHz)	Limit (dBm/MHz)	Verdict
11A	100	5500	2.71	0	2.71	11	Pass
	120	5580	2.75	0	2.75		Pass
	140	5700	2.51	0	2.51		Pass
11N20 SISO	100	5500	1.58	0	1.58	11	Pass
	120	5580	2.91	0	2.91		Pass
	140	5700	2.68	0	2.68		Pass
11N40 SISO	102	5510	-0.76	0	-0.76	11	Pass
	118	5590	0.84	0	0.84		Pass
	134	5670	0.52	0	0.52		Pass
11AC20 SISO	100	5500	2.10	0	2.10	11	Pass
	120	5580	2.77	0	2.77		Pass
	140	5700	2.45	0	2.45		Pass
11AC40 SISO	102	5510	-0.09	0	-0.09	11	Pass
	118	5590	-0.21	0	-0.21		Pass
	134	5670	0.34	0	0.34		Pass
11AC80 SISO	106	5530	-3.56	0	-3.56	11	Pass






IEEE 802.11a / Channel 120 / 5580MHz




IEEE 802.11a / Channel 140 / 5700MHz


Power Spectral Density




IEEE 802.11n20 / Channel 100 / 5500MHz




IEEE 802.11n20 / Channel 120 / 5580MHz




IEEE 802.11n20 / Channel 140 / 5700MHz



IEEE 802.11n40 / Channel 102 / 5510MHz




IEEE 802.11n40 / Channel 118 / 5590MHz




IEEE 802.11n40 / Channel 134 / 5670MHz


Power Spectral Density




IEEE 802.11ac20 / Channel 100 / 5500MHz




IEEE 802.11ac20 / Channel 120 / 5580MHz




IEEE 802.11ac20 / Channel 140 / 5700MHz




IEEE 802.11ac40 / Channel 102 / 5510MHz



IEEE 802.11ac40 / Channel 118 / 5590MHz





IEEE 802.11ac40 / Channel 134 / 5670MHz




D.4 Emission Bandwidth

Test Mode	Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	100	5500	20.16	No Limit	Pass
	120	5580	20.05		Pass
	140	5700	19.90		Pass
11N20 SISO	100	5500	20.03	No Limit	Pass
	120	5580	20.13		Pass
	140	5700	19.99		Pass
11N40 SISO	102	5510	40.04	No Limit	Pass
	118	5590	40.00		Pass
	134	5670	39.97		Pass
11AC20 SISO	100	5500	20.21	No Limit	Pass
	120	5580	19.86		Pass
	140	5700	19.93		Pass
11AC40 SISO	102	5510	40.09	No Limit	Pass
	118	5590	40.18		Pass
	134	5670	40.13		Pass
11AC80 SISO	106	5530	80.23	No Limit	Pass







26dB Bandwidth




IEEE 802.11n20 / Channel 100 / 5500MHz




IEEE 802.11n20 / Channel 120 / 5580MHz




IEEE 802.11n20 / Channel 140 / 5700MHz




IEEE 802.11n40 / Channel 102 / 5510MHz




IEEE 802.11n40 / Channel 118 / 5590MHz




IEEE 802.11n40 / Channel 134 / 5670MHz




IEEE 802.11ac20 / Channel 100 / 5500MHz




IEEE 802.11ac20 / Channel 120 / 5580MHz




IEEE 802.11ac20 / Channel 140 / 5700MHz




IEEE 802.11ac40 / Channel 102 / 5510MHz



IEEE 802.11ac40 / Channel 118 / 5590MHz




IEEE 802.11ac40 / Channel 134 / 5670MHz




D.5 Undesirable Emissions Measurement

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
11A	100	5460.0	-46.82	3.11	0	51.52	Peak	68.20	Pass
		5460.0	-58.13	3.11	0	40.21	Average	54.00	Pass
		5470.0	-46.43	3.11	0	51.91	Peak	68.20	Pass
		5470.0	-57.45	3.11	0	40.89	Average	54.00	Pass
	140	5725.0	-46.15	3.11	0	52.19	Peak	68.20	Pass
		5725.0	-56.34	3.11	0	42.00	Average	54.00	Pass
		5735.0	-46.83	3.11	0	51.51	Peak	68.20	Pass
		5735.0	-57.28	3.11	0	41.06	Average	54.00	Pass
11N2 O SISO	100	5460.0	-46.98	3.11	0	51.36	Peak	68.20	Pass
		5460.0	-58.18	3.11	0	40.16	Average	54.00	Pass
		5470.0	-44.90	3.11	0	53.44	Peak	68.20	Pass
		5470.0	-57.59	3.11	0	40.75	Average	54.00	Pass
	140	5725.0	-45.76	3.11	0	52.58	Peak	68.20	Pass
		5725.0	-56.40	3.11	0	41.94	Average	54.00	Pass
		5735.0	-47.22	3.11	0	51.12	Peak	68.20	Pass
		5735.0	-57.29	3.11	0	41.05	Average	54.00	Pass
11N4 O SISO	102	5460.0	-46.08	3.11	0	52.26	Peak	68.20	Pass
		5460.0	-57.21	3.11	0	41.13	Average	54.00	Pass
		5470.0	-39.48	3.11	0	58.86	Peak	68.20	Pass
		5470.0	-54.44	3.11	0	43.90	Average	54.00	Pass
	134	5725.0	-46.71	3.11	0	51.63	Peak	68.20	Pass
		5725.0	-56.53	3.11	0	41.81	Average	54.00	Pass
		5735.0	-46.86	3.11	0	51.48	Peak	68.20	Pass
		5735.0	-56.90	3.11	0	41.44	Average	54.00	Pass
11A C20 SIS O	100	5460.0	-47.22	3.11	0	51.12	Peak	68.20	Pass
		5460.0	-58.41	3.11	0	39.93	Average	54.00	Pass
		5470.0	-46.98	3.11	0	51.36	Peak	68.20	Pass
		5470.0	-57.77	3.11	0	40.57	Average	54.00	Pass
	140	5725.0	-46.23	3.11	0	52.11	Peak	68.20	Pass
		5725.0	-56.45	3.11	0	41.89	Average	54.00	Pass
		5735.0	-45.01	3.11	0	53.33	Peak	68.20	Pass
		5735.0	-57.33	3.11	0	41.01	Average	54.00	Pass
11A C40 SIS O	102	5460.0	-46.33	3.11	0	52.01	Peak	68.20	Pass
		5460.0	-57.30	3.11	0	41.04	Average	54.00	Pass
		5470.0	-42.26	3.11	0	56.08	Peak	68.20	Pass
		5470.0	-54.42	3.11	0	43.92	Average	54.00	Pass
	134	5725.0	-46.61	3.11	0	51.73	Peak	68.20	Pass
		5725.0	-56.61	3.11	0	41.73	Average	54.00	Pass
		5735.0	-45.93	3.11	0	52.41	Peak	68.20	Pass
		5735.0	-56.95	3.11	0	41.39	Average	54.00	Pass
11A C80 SIS O	106	5460.0	-41.89	3.11	0	56.45	Peak	68.20	Pass
		5460.0	-53.32	3.11	0	45.02	Average	54.00	Pass
		5470.0	-39.10	3.11	0	59.24	Peak	68.20	Pass
		5470.0	-51.17	3.11	0	47.17	Average	54.00	Pass

Undesirable Emissions Measurement




IEEE 802.11a / Channel 100 / 5500MHz / Peak




IEEE 802.11a / Channel 100 / 5500MHz / Average

Undesirable Emissions Measurement




IEEE 802.11a / Channel 140 / 5700MHz / Peak




IEEE 802.11a / Channel 140 / 5700MHz / Average

Undesirable Emissions Measurement




IEEE 802.11n20 / Channel 100 / 5500MHz / Peak




IEEE 802.11n20 / Channel 100 / 5500MHz / Average

Undesirable Emissions Measurement




IEEE 802.11n20 / Channel 140 / 5700MHz / Peak




IEEE 802.11n20 / Channel 140 / 5700MHz / Average

Undesirable Emissions Measurement




IEEE 802.11n40 / Channel 102 / 5510MHz / Peak




IEEE 802.11n40 / Channel 102 / 5510MHz / Average


Undesirable Emissions Measurement




IEEE 802.11n40 / Channel 134 / 5670MHz / Peak




IEEE 802.11n40 / Channel 134 / 5670MHz / Average




IEEE 802.11ac20 / Channel 100 / 5500MHz / Peak




IEEE 802.11ac20 / Channel 100 / 5500MHz / Average




IEEE 802.11ac20 / Channel 140 / 5700MHz / Peak




IEEE 802.11ac20 / Channel 140 / 5700MHz / Average




IEEE 802.11ac40 / Channel 102/ 5510MHz / Peak




IEEE 802.11ac40 / Channel 102 / 5510MHz / Average




IEEE 802.11ac40 / Channel 134/ 5670MHz / Peak



IEEE 802.11ac40 / Channel 134 / 5670MHz / Average



IEEE 802.11ac80 / Channel 106 / 5530MHz / Peak



IEEE 802.11ac80 / Channel 106 / 5530MHz / Average