Nexus Telecom Inc.

GSM Mobile Phone

Model: GO170 Serial Model: N/A

February 04, 2013

Report No.: 13050003-FCC-E1

(This report supersedes NONE)



Modifications made to the product: None

This Test Report is Issued Under the Authority of:

William Long	Alex. Lin	
William Long Compliance Engineer	Alex Liu Technical Manager	

This test report may be reproduced in full only. Test result presented in this test report is applicable to the representative sample only.





Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 2 of 34 www.siemic.com

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to <u>testing</u> and <u>certification</u>, SIEMIC provides initial design reviews and <u>compliance</u> <u>management</u> through out a project. Our extensive experience with <u>China</u>, <u>Asia Pacific</u>, <u>North America</u>, <u>European</u>, <u>and international</u> compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the <u>global markets</u>.

Accreditations for Conformity Assessment

i cuitations for Co	Jinul linty Assessment	
Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC, RF/Wireless, Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom, Safety
Hong Kong	OFTA , NIST	RF/Wireless ,Telecom
Australia	NATA, NIST	EMC, RF, Telecom, Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF, Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom, Safety

Accreditations for Product Certifications

Country/Region	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB , NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC, (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom



This page has been left blank intentionally.

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 4 of 34 www.siemic.com

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
3	MODIFICATION	7
4	TEST SUMMARY	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
ANI	NEX A. TEST INSTRUMENTATION & GENERAL PROCEDURES	13
ANI	NEX B. EUT AND TEST SETUP PHOTOGRAPHS	18
AN	NEX C. TEST SETUP AND SUPPORTING EQUIPMENT	29
AN	NEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	33
ANI	NEX E. DECLARATION OF SIMILARITY	34



Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 5 of 34

1 EXECUTIVE SUMMARY & EUT INFORMATION

The purpose of this test programme was to demonstrate compliance of the Nexus Telecom Inc., GSM Mobile Phone and Model: GO170 against the current Stipulated Standards. The GSM Mobile Phone has demonstrated compliance with the FCC Part 15 Subpart B Class B: 2012, ANSI C63.4: 2009.

EUT Information

EUT

Description

GSM Mobile Phone

Main Model : GO170

Serial Model N/A

Adapter

Model: GO170

Input: 100 ~ 264Vac, 200 mA

Output: 5Vdc, 500mA

Input Power : Battery

Model: GO170 Capacity: 500mAh Nominal Voltage: 3.7V Charger up Voltage: 4.2V

Classification

Per Stipulated : Class B Emission Product Per

Test Standard FCC Part 15 Subpart B Class B: 2012, ANSI C63.4: 2009

Revision Number	Report Number	Report Number Description of Revision	
0	12050087-FCC-E1	Original Report	January 08, 2013
1	13050003-FCC-E1	Amended Report	February 04, 2013

Note: This is the amended report application (13050003-FCC-E1) of the device, the original submission (12050087-FCC-E1) was granted on January 08, 2013. The difference between the original device and the current one was the SIM of the EUT. In the new model, comparing with Dual SIM model, we removed one SIM slot and relevant surrounding components. Now it's a single SIM model. It affects the Radiated Emissions. All above were explained in the attached Declaration Letter.



Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 6 of 34

2 TECHNICAL DETAILS			
Purpose	Compliance testing of GSM Mobile Phone with stipulated standards		
Applicant / Client	Nexus Telecom Inc. PO Box 873, Venterpool Plaza, Road Town, Tortola Virgin Islands(British)		
Manufacturer	Jiaxing Wingxun Electronic Technology Co., Ltd. 1# workshop,building 2,Ya Zhong Road No.777,Da Qiao town ,Nan Hu district,Jiaxing city		
Laboratory performing the tests	SIEMIC Nanjing (China) Laboratories NO.2-1, Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email:info@siemic.com		
Test report reference number	13050003-FCC-E1		
Date EUT received	December 24, 2012		
Standard applied	FCC Part 15 Subpart B Class B: 2012, ANSI C63.4: 2009		
Dates of test (from – to)	February 02, 2013		
No of Units	#1		
Equipment Category	JBP		
Trade Name	GoMobile		
RF Operating Frequency (ies)	GSM850 TX : 824.2 ~ 848.8 MHz; RX :869.2 ~ 893.8 MHz PCS1900 TX : 1850.2 ~ 1909.8 MHz; RX :1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480MHz		
Number of Channels	299CH (PCS1900) and 124CH (GSM850) Bluetooth: 79 CH		
Modulation	GSM: GMSK Bluetooth: GFSK		
FCC ID	YSEGO170		



Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 7 of 34

MODIFICATION

NONE

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 8 of 34

www.siemic.com

4 TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

Class B Emission Product

Test Results Summary

Emissions				
Test Standard Description Product Class Pass / 1				
FCC Part 15 Subpart B Class B: 2012, ANSI C63.4: 2009	Conducted Emissions	See Above	Pass	
FCC Part 15 Subpart B Class B: 2012, ANSI C63.4: 2009	Radiated Emissions	See Above	Pass	

All measurement uncertainty is not taken into consideration for all presented test result.

5 <u>MEASUREMENTS, EXAMINATION AND DERIVED</u> RESULTS

5.1 Conducted Emissions Test Result

Note:

- 1. All possible modes of operation were investigated. Only the several worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
- 2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. <u>Conducted Emissions Measurement Uncertainty</u>

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz - 30MHz (Average & Quasi-peak) is $\pm 3.86dB$.

4. Environmental Conditions Temperature 25°C

Relative Humidity 50% Atmospheric Pressure 1009mbar

5. Test date : ----

Tested By: William Long

Test Result: Pass

Note: the following test data please refer to report 12050087-FCC-E1.

5.2 Radiated Emissions Test Results

Note:

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.

2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.

3. Radiated Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30 MHz - 1 GHz (QP only @ 3m & 10m) is +6 dB/-6 dB (for EUTs < 0.5 m X 0.5m).

4. Environmental Conditions Temperature 25°C
Relative Humidity 50%
Atmospheric Pressure 1011mbar

5. Test date : February 02, 2013 Tested By : William Long


Test Result: Pass

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 11 of 34

Test Mode: Charging & Downloading

Below 1GHz

Peak Detector [
Quasi Peak Limit [



Test Data

Vertical Polarity Plot at 3m


Frequency (MHz)	Quasi Peak (dBµV/m)	Azimuth	Polarity(H /V)	Height (cm)	Factors (dB)	Limit (dBµV/m)	Margin (dB)
33.68	35.48	163.00	V	102.00	-22.85	40.00	-4.52
58.44	19.17	123.00	V	119.00	-37.62	40.00	-20.83
39.76	18.16	360.00	V	156.00	-27.65	40.00	-21.84
59.13	15.08	171.00	V	111.00	-37.82	40.00	-24.92
424.99	28.67	154.00	V	120.00	-29.40	46.00	-17.33
950.77	21.96	188.00	V	218.00	-19.67	46.00	-24.04

Report No.: 13050003-FCC-EI Issue Date: February 04, 2013 Page: 12 of 34

Test Mode: Charging & Downloading

Below 1GHz





Test Data

Horizontal Polarity Plot at 3m

Frequency (MHz)	Quasi Peak (dBµV/m)	Azimuth	Polarity(H /V)	Height (cm)	Factors (dB)	Limit (dBµV/m)	Margin (dB)
240.00	40.55	178.00	Н	107.00	-32.68	46.00	-5.45
216.40	40.64	99.00	Н	136.00	-34.02	46.00	-5.36
457.90	34.02	33.00	Н	101.00	-28.74	46.00	-11.98
143.99	33.64	190.00	Н	216.00	-32.00	43.50	-9.86
288.58	37.09	102.00	Н	104.00	-32.26	46.00	-8.91
453.33	33.99	29.00	Н	118.00	-28.93	46.00	-12.01

Note: The data above 1 GHz which below 20 dB to the limit was not recorded.

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 13 of 34

Annex A. TEST INSTRUMENTATION & GENERAL PROCEDURES

Annex A.i. TEST INSTRUMENTATION


Instrument	Model	Serial #	Calibration Date	Calibration Due Date
AC Line Conducted Emissions				
R&S EMI Test Receiver	ESPI3	101216	10/27/2012	10/26/2013
V-LISN	ESH3-Z5	838979/005	10/27/2012	10/26/2013
Com-Power Transient Limiter	LIT-153	531021	11/03/2012	11/02/2013
SIEMIC Labview Conducted Emissions software V1.0	N/A	N/A	N/A	N/A
Radiated Emissions				
Hp Spectrum Analyzer	8563E	3821A09023	01/10/2013	01/09/2014
R&S EMI Receiver	ESPI3	101216	10/27/2012	10/26/2013
Antenna (30MHz~6GHz)	JB6	A121411	12/28/2012	12/27/2013
ETS-Lindgren Antenna (1 ~18GHz)	3115	N/A	10/29/2012	10/28/2013
A-INFOMW Antenna (1 ~18GHz)	JXTXLB- 10180	J2031081120 092	06/25/2012	06/24/2013
Horn Antenna (18~40GHz)	AH-840	101013	04/22/2012	04/22/2013
Microwave Pre-Amp (18~40GHz)	PA-840	181250	05/30/2012	05/29/2013
Hp Agilent Pre-Amplifier	8447F	1937A01160	11/03/2012	11/02/2013
MITEQ Pre-Amplifier (0.1 ~ 18GHz)	AMF-7D- 00101800- 30-10P	1451709	11/03/2012	11/02/2013
Chamber	3m	N/A	04/13/2012	04/12/2013
SIEMIC Labview Radiated Emissions software V1.0	N/A	N/A	N/A	N/A

Annex A.ii. AC LINE CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
- 2. The power supply for the EUT was fed through a $50\Omega/50\mu$ H EUT LISN, connected to filtered mains.
- 3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.

4. All other supporting equipments were powered separately from another main supply.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration1

Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition.
- 2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
- 3. High peaks, relative to the limit line, were then selected.
- 4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
- 5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Description of Conducted Emission Program

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the common scan range from 150 kHz to 30 MHz; the program will first start a peak and average scan on selectable measurement time and step size. After the program complete the pre-scan, this program will perform the Quasi Peak and Average measurement, based on the pre-scan peak data reduction result.

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 15 of 34

www.siemic.com

Sample Calculation Example

At 20 MHz $limit = 250 \mu V = 47.96 dB\mu V$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = $40.00~\text{dB}\mu\text{V}$ (Calibrated for system losses)

Therefore, Q-P margin = 47.96 - 40.00 = 7.96 i.e. **7.96 dB below limit**

Annex A. iii. RADIATED EMISSIONS TEST DESCRIPTION


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8 m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred; clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS) or 3m EMC chamber.

Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5mX1.0mX0.8m high, non-metallic table.
- 2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
- 3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration2

Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

- 1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

- 1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
- 2. For emission frequencies measured below 1GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on an open test site. As the same purpose, for emission frequencies measured above 1GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below and above 1GHz, set the spectrum analyzer on a 100kHz and 1MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
- 5. Repeat step 4 until all frequencies need to be measured was complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100kHz	100kHz
Above 1000	Peak	1MHz	1MHz
Above 1000	Average	1MHz	10Hz

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

Peak = Reading + Corrected Factor

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any) And the average value is

Average = Peak Value + Duty Factor or Set RBW = 1MHz, VBW = 10Hz.

Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1GHz. And the measuring instrument is set to quasi peak detector function.

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 18 of 34

www.siemic.com

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Annex B.i. Photograph 1: EUT External Photo



EUT - Front View



EUT - Rear View



Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 19 of 34



EUT - Top View



EUT - Bottom View



Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 20 of 34



EUT - Left View



EUT - Right View



Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 21 of 34

Annex B.ii. Photograph 2: EUT Internal Photo



Cover Off - Top View



Cover Off - Bottom View

SIEMIC, INC.

Accessing gotted markets
EMC Test Report for GSM Mobile Phone
Main Model: GO170
Serial Model: N/A
To: FCC Part 15 Subpart B Class B: 2012, ANSI C63.4:2009

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 22 of 34

www.siemic.com




Battery - Top View



Battery - Bottom View



Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 23 of 34




LCD - Top View



LCD - Bottom View



Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 24 of 34




Uncover - Top View



Uncover - Bottom View

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 25 of 34


Uncover without LCD - Top View




Uncover Without Shielding - Top View



Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 26 of 34





Bluetooth Antenna - Top View

Bluetooth Antenna

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 27 of 34

Annex B.iii. Photograph 3: Test Setup Photo




Conducted Emissions Test Setup Front View




Conducted Emissions Test Setup Side View

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 28 of 34



Radiated Emissions Test Setup Below 1GHz - Front View



Radiated Emissions Test Setup Above 1GHz - Front View

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION


The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
Gateway Laptop	MS2288 & LXWHF02013951C3CA92200	N/A

Block Configuration Diagram for Conducted Emissions Mode: Charging & Downloading



Block Configuration Diagram for Radiated Emissions Mode: Charging & Downloading



Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions	Charging & Downloading

Report No.: 13050003-FCC-E1 Issue Date: February 04, 2013 Page: 33 of 34

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment

Annex E. DECLARATION OF SIMILARITY

FCC Class II Permissive Change Request Letter

Date: January 31, 2013

To FCC:

RE: FCC Permissive II Change Request for Company: Nexus Telecom Inc. FCC ID: YSEGO170

We are submitting an application for a class II permissive change to the FCC approval of the Company name: Nexus Telecom Inc., product description: GSM Mobile Phone (FCC: YSEGO170, Original Grant Date: January 30, 2013). The transmitter module itself has not changed. Here are the changes:

In the new model, comparing with Dual SIM model, we removed one SIM slot and relevant surrounding components. Now it's a single SIM model.

Sincerely,

Signature:

Name : Herbert Braun Valle

Title: Director

Company Name: Nexus Telecom Inc.

Address: PO Box 873, Venterpool Plaza, Road Town, Tortola Virgin Islands(British)

Email: hbraunvalle@gmail.com Telephone: 0050224120624