DIGITUS BIOMETRICS

RFID NETWORKED ACCESS CONTROL

Model: dbNEXIII

Sep 8th 2010

Report No.: SL10082604-DBI-001(dbNEXIII)_FCC

(This report supersedes None)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:	
David Thang	Bu
David Zhang	Leslie Bai
Test Engineer	Engineering Reviewer

EMC Test Report





 Serial#
 \$L10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 2 of 53

 www.siemic.com

This page has been left blank intentionally.

 Serial#
 \$L10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 3 of 53

 www.siemic.com

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
	TECHNICAL DETAILS	
2		
3	MODIFICATION	7
4	TEST SUMMARY	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
ANNI	EX A. TEST INSTRUMENT & METHOD	25
ANNI	EX B. TEST SETUP PHOTOGRAPHS	29
ANNI	EX B. I. EUT INTERNAL PHOTOGRAPHS	30
ANNI	EX B. II. EUT EXTERNAL PHOTOGRAPHS	31
ANNI	EX D USER MANUAL, BLOCK & CIRCUIT DIAGRAM	37
ANNI	EX E SIEMIC ACCREDITATION	38



 Serial#
 \$L10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 4 of 53

 www.siemic.com

This page has been left blank intentionally.

| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | Page | 5 of 53 | www.siemic.com | www.siemic.com |

1 Executive Summary & EUT information

The purpose of this test programmed was to demonstrate compliance of the the RFID Networked access control and model: dbNEXIII against the current Stipulated Standards.

The equipment under test radio operating frequency is 13.56 MHz.

The test has demonstrated that this unit complies with stipulated standards.

EUT Information

EUT Description

The db Nexus Solution is the networked version of the Digitus product line. Db Nexus enables security administrators to control an entire group of units – anywhere in the world – from a single location.

Each unit attaches to the respective site's computer network via a standard Ethernet interface. It then communicates with the Digitus Access Software (DAS) central control stations via Digitus' proprietary code hopping encryption protocol.

Because the db Nexus Solution adds TCP/IP connectivity to the controller, security administrators can enroll users to those units or gather reports from them at any time. The central administrator can set up and configure each networked unit, and can upload fingerprint templates to any remote networked unit in order to grant user access.

Model No : dbNEXIII
Serial No : N/A

Input Power : 18-22VDC

Classification

Per Stipulated Test Standard

RFID Reader



2 <u>TECHNICAL DETAILS</u>							
Purpose	Compliance testing of RFID Networked access control with stipulated standard						
Applicant / Client	Digitus Biometrics						
Manufacturer	Digitus Biometrics 116 A East Oglethorpe Avenue Savannah Savannah, GA 31401 USA						
Laboratory performing the tests	SIEMIC Laboratories						
Test report reference number	SL10082604-DBI-001(dbNEXIII)_FCC						
Date EUT received	Aug 30th 2010						
Standard applied	47 CFR §15.207, 15.209, 15.225: 2009						
Dates of test (from - to)	Aug 30th to Sep 08th 2010						
No of Units:	1						
Equipment Category:	DXX						
Model:	dbNEXIII						
RF Operating Frequency (ies)	13.56 MHz (RFID)						
Number of Channels :	13.56 MHz (1)						
FCC ID :	YSJDBNEX3C						



 Serial#
 \$L10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 7 of 53

 www.siemic.com

3 MODIFICATION

NONE

4 TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

RFID Reader

Test Results Summary

Test Standard	Description	Pass / Fail	
47 CFR Part 15.225: 2009	Description		
15.203	Antenna Requirement	Pass	
15.207(a)	Conducted Emissions Voltage	Pass	
15.225(a)	Limit in the band of 13.553 – 13.567 MHz	Pass	
15.225(b)	Limit in the band of 13.410 – 13.553 MHz and 13.567 – 13.710 MHz	Pass	
15.225(c)	Limit in the band of 13.110 – 13.410 MHz and 13.710 – 14.010 MHz	Pass	
15.225(d), 15.209	Limit outside the band of 13.110 – 14.010 MHz	Pass	
15.225(e)	Frequency Stability	Pass	
	Occupied Bandwidth	Pass	

ANSI C63.4: 2003

PS: All measurement uncertainties are not taken into consideration for all presented test result.

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 Antenna Requirement

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.
- 1) The RFID antenna is integral to the main board permanently to the device which meets the requirement.

SL10082604-DBI-001(dbNEXIII)_FCC Sep 8th 2010 10 of 53 Issue Date

5.2 Conducted Emissions Voltage

Requirement(s): 47 CFR §15.207

Requirement:

	Conducted limit (dBµV)		
Frequency of emission (MHz)	Quasi-peak	Average	
0.15–0.5	66 to 56*	56 to 46*	
0.5–5	56	46	
5–30	60	50	

^{*}Decreases with the logarithm of the frequency.

Procedures:

- 1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
- 2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is ±3.5dB.

Environmental Conditions Temperature 4.

28°C Relative Humidity 50%

Atmospheric Pressure 1019mbar


Test Date: Sep 06 2010 Tested By: David Zhang

Results: Pass

Test Result with AC adapter (Control unit)

Quasi-Peak Limit

Average Limit




110V, 60Hz, Neutral Line

Frequency (MHz)	QP Value (dBµV)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Avg Value (dBµV)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Line
0.35	50.53	59.11	Pass	-8.58	46.18	49.11	Pass	-2.93	N
0.49	35.30	56.10	Pass	-20.80	31.32	46.10	Pass	-14.78	N
0.31	41.32	59.94	Pass	-18.62	36.10	49.94	Pass	-13.83	N
1.75	32.58	56.00	Pass	-23.42	27.10	46.00	Pass	-18.90	N
0.19	42.45	64.19	Pass	-21.73	36.08	54.19	Pass	-18.11	N
0.79	27.14	56.00	Pass	-28.86	21.88	46.00	Pass	-24.12	N

Quasi-Peak Limit

Average Limit




110V, 60Hz, Phase Line

Frequency (MHz)	QP Value (dBµV)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Avg Value (dBµV)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Line
0.35	50.24	59.11	Pass	-8.87	45.48	49.11	Pass	-3.63	L
13.34	29.54	60.00	Pass	-30.46	18.66	50.00	Pass	-31.34	L
0.50	39.79	56.00	Pass	-16.21	37.78	46.00	Pass	-8.22	L
0.81	39.01	56.00	Pass	-16.99	34.97	46.00	Pass	-11.03	L
0.31	44.31	60.04	Pass	-15.73	38.87	50.04	Pass	-11.18	L
13.65	27.98	60.00	Pass	-32.02	19.38	50.00	Pass	-30.62	L

Test Result with DC Power supply

Quasi-Peak Limit

Average Limit




18VDC, Negative

Frequency (MHz)	QP Value (dBµV)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Avg Value (dBµV)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Line
0.35	44.26	59.11	Pass	-14.86	40.72	49.11	Pass	-8.39	Negative
4.27	39.09	56.00	Pass	-16.91	38.17	46.00	Pass	-7.83	Negative
4.01	38.74	56.00	Pass	-17.26	37.29	46.00	Pass	-8.71	Negative
3.76	36.14	56.00	Pass	-19.86	35.14	46.00	Pass	-10.86	Negative
4.52	36.69	56.00	Pass	-19.31	34.81	46.00	Pass	-11.19	Negative
4.77	36.76	56.00	Pass	-19.24	35.64	46.00	Pass	-10.36	Negative

Quasi-Peak Limit

Average Limit



18VDC, Positive

Frequency (MHz)	QP Value (dBµV)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Avg Value (dBµV)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Line
4.27	38.56	56.00	Pass	-17.44	37.67	46.00	Pass	-8.33	Positive
4.01	38.12	56.00	Pass	-17.88	36.68	46.00	Pass	-9.32	Positive
4.77	35.74	56.00	Pass	-20.26	33.56	46.00	Pass	-12.44	Positive
4.52	36.50	56.00	Pass	-19.50	34.84	46.00	Pass	-11.16	Positive
3.51	32.10	56.00	Pass	-23.90	30.48	46.00	Pass	-15.52	Positive
0.24	39.23	62.28	Pass	-23.05	33.58	52.28	Pass	-18.70	Positive

| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | Page | 15 of 53 | Water Stample com | Water Stample com | Page | Pa

5.3 Radiated Emission < 30MHz (9kHz - 30MHz, H-Field)

Requirement(s): 47 CFR §15.225

Procedures: For < 30MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the

highest output power. The EUT was set 10 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the centre of the loop. The measuring bandwidth was set to 10 kHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT.)

The limit is converted from microvolt/meter to decibel microvolt/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude (dBµV/m) + ACF (dB) + Cable Loss(dB) – Distance Correction Factor

- All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
- A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. Radiated Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, is +/-6dB.

4. Environmental Conditions Temperature 23°C

Relative Humidity 50% Atmospheric Pressure 1019mbar

Test Date: Sep 06 2010 Tested By: David Zhang


Results: Pass

Serial# SL10082604-DBI-001(dbNEXIII)_FCC Issue Date Sep 8th 2010 Page 16 of 53


100KHz ~ 1MHz

Dipole Antenna at 0 degree

General Emission Limit @ 3 Meter




Dipole Antenna at 90 degree




| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | 17 of 53 | |

1MHz ~ 30MHz Dipole Antenna at 0 degree

General Emission Limit @ 3 meter



Dipole Antenna at 90 degree



 Serial#
 SL10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 18 of 53

5.4 Radiated Emissions > 30 MHz (30MHz - 1 GHz, E-Field)

Requirement(s): 47 CFR §15.209; 47 CFR §15.225(d)

Procedures:

For > 30MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 10 meter away from the measuring antenna. The Log periodic antenna was positioned 1 meter above the ground from the centre of the antenna. The measuring bandwidth was set to 120 kHz. (Note: During testing the receive antenna was raise from 1~4 meters to maximize the emission from the

The limit is converted from microvolt/meter to decibel microvolt/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude (dBµV/m) + ACF (dB) + Cable Loss(dB) - Distance Correction Factor

- 1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
- A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. Radiated Emissions Measurement Uncertainty
 All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, is +/-6dB.

4. Environmental Conditions Temperature 23°C Relative Humidity 50%

Atmospheric Pressure 1019mbar

Test Date: Sep 06 2010 Tested By: David Zhang

Results: Pass

Test Result

Frequency (MHz)	Amplitude @ 3m	Azimuth (degree)	Antenna Polarity	Antenna Height (cm)	Limit @ 3 meter	margin (dB)
933.27	52.45	188.00	V	101.00	56.00	-3.55
596.63	52.99	182.00	Н	109.00	56.00	-3.01
569.52	51.06	187.00	Н	111.00	56.00	-4.94
399.97	46.07	29.00	Н	100.00	56.00	-9.93
40.68	38.57	116.00	V	102.00	40.00	-1.43
623.76	46.46	186.00	Н	100.00	56.00	-9.54



 Serial#
 SL10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 19 of 53

5.5 Frequency Stability

Requirement(s): 47 CFR §15.225(e)

Procedures: Frequency Stability was measured according to 47 CFR §2.1055. Measurement was taken with spectrum

analyzer. The spectrum analyzer bandwidth and span was set to read in hertz. A voltmeter was used to monitor

when varying the voltage.

Limit: $\pm 0.01\%$ of 13.56 MHz = 1356 Hz

Environmental Conditions Temperature 23°C

50% Relative Humidity

Atmospheric Pressure 1019mbar

Test Date: Sep 06 2010 Tested By: David Zhang

Results: Pass

 Serial#
 \$L10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 20 of 53

Frequency Stability versus Temperature: The Frequency tolerance of the carrier signal shall be maintained within \pm 0.01% of the operating frequency over a temperature variation of -20°C to +50°C at normal supply voltage.

Reference Frequency: 13.560171 MHz at 20°C

Temperature	Measured Freq.	Freq. Drift	Freq. Deviation	Pass/Fail
(°C)	(MHz)	(Hz)	(Limit: 0.01%)	Pass/Fall
50	13.560232	61	<0.01	Pass
40	13.560272	101	<0.01	Pass
30	13.560289	118	<0.01	Pass
20		Reference (13.560171)	MHz)	
10	13.560259	88	<0.01	Pass
0	13.560272	101	<0.01	Pass
-10	13.560266	95	<0.01	Pass
-20	13.560289	118	<0.01	Pass

Frequency Stability versus Input Voltage: The Frequency tolerance of the carrier signal shall be maintained within \pm 0.01%, the frequency of the transmitter was measured at 85% and at 115% of the rated power supply voltage at 20°C environmental temperature.

Carrier Frequency: 13.560171 MHz at 20°C at 18VDC

Measured Voltage ±15% of nominal (DC)	Measured Freq. (MHz)	Freq. Drift (Hz)	Freq. Deviation (Limit: 0.01%)	Pass/Fail
15.3	13.560264	93	<0.01	Pass
20.7	13.560236	65	<0.01	Pass

| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | Page | 21 of 53 | Water Stample com | Water Stample com | Page | Pa

5.6 Fundamental Field Strength Test Result

- 1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
- 2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. Radiated Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, is +/-6dB.

4. Environmental Conditions Temperature 23°C

Relative Humidity 50% Atmospheric Pressure 1019mbar

Test Date: Sep 06 2010 Tested By: David Zhang

Test Requirement:


13.56 MHz --- The field strength of any emissions within allowed operating band shall not exceed 10mV/m at 30 meters.

Dipole Antenna at 0 degree

General Emission Limit @ 3 meter



Dipole Antenna at 90 degree





 Serial#
 SL10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 23 of 53

5.7 Occupied Bandwidth

Requirement(s): N/A

Procedures: Measurement was taken with spectrum analyzer. The spectrum analyzer bandwidth and span was set to read in

Environmental Conditions Temperature 23°C


Relative Humidity 50% Atmospheric Pressure 1019mbar

Test Date: Sep 06 2010 Tested By: David Zhang

Results: Pass

| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | 24 of 53 | . |

Plots: 13.56 MHz



Annex A. TEST INSTRUMENT & METHOD

Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Model	Calibration Due
AC Conducted Emissions		
R&S EMI Test Receiver	ESIB40	05/19/2011
R&S LISN	ESH2-Z5	05/18/2011
CHASE LISN	MN2050B	05/18/2011
Radiated Emissions		
Spectrum Analyzer	8564E	05/19/2011
EMI Receiver	ESIB 40	05/19/2011
R&S LISN	ESH2-Z5	05/18/2011
CHASE LISN	MN2050B	05/18/2011
Antenna(1 ~18GHz)	3115	06/01/2011
Antenna (30MHz~2GHz)	JB1	06/01/2011
Chamber	3m	12/4/2010
Pre-Amplifier(1 ~ 26GHz)	8449	5/17/2011
Horn Antenna (18~40GHz)	AH-840	7/23/2013
Microwave Pre-Amp (18~40GHz)	PA-840	Every 2000 Hours

| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | Page | 26 of 53 | www.siemic.com | www.siemic.com |

Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
- 2. The power supply for the EUT was fed through a $50\Omega/50\mu$ H EUT LISN, connected to filtered mains.
- 3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
- 4. All other supporting equipments were powered separately from another main supply.

Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition.
- 2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
- 3. High peaks, relative to the limit line, were then selected.
- 4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
- 5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Sample Calculation Example

At 20 MHz $limit = 250 \mu V = 47.96 dB\mu V$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = 40.00 dBµV

(Calibrated for system losses)

Therefore, Q-P margin = 47.96 - 40.00 = 7.96 i.e. **7.96 dB below limit**

Annex A. iii RADIATED EMISSIONS TEST DESCRIPTION


EUT Characterisation

EUT characterisation, over the frequency range from 100kHz – 1GHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred; clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS) at 10m distance.

Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
- 2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
- 3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

- 1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission
- 2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

- 1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
- 2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from $0 \circ 1000$ with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
- 5. Repeat step 4 until all frequencies need to be measured were complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

Peak = Reading + Corrected Factor

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any) And the average value is

Average = Peak Value + Duty Factor or Set RBW = 1MHz, VBW = 10Hz.

Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.



 Serial#
 \$L10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 29 of 53

 www.siemic.com

TEST SETUP PHOTOGRAPHS Annex B.

Please See Attachment



Serial# SL10082604-DBI-001(dbNEXIII)_FCC Issue Date Sep 8th 2010 20 30 of 53 www.siemic.com

Annex B. i. EUT INTERNAL PHOTOGRAPHS

Please see attachment



Annex B. ii. EUT EXTERNAL PHOTOGRAPHS

Please see attachment


Annex C. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.


Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
Control Unit/ Digitus Biometrics	N/A	2 m, Bus

NOTE: No special supporting equipment are used or needed during testing to achieve compliance.


Block Configuration Diagram for Radiated Emission



Block Configuration Diagram for DC Conducted Emission



Block Configuration Diagram for Conducted Emission



Annex C. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was controlled by itself.
Others Testing	The EUT was controlled by itself.



Annex D USER MANUAL, BLOCK & CIRCUIT DIAGRAM

Please see attachment


 Serial#
 SL10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 38 of 53

Annex E SIEMIC ACCREDITATION

SIEMIC ACCREDITATION DETAILS: A2LA 17025 & ISO Guide 65: 2742.01, 2742.2



ACCREDITED LABORATORY

SIEMIC LABORATORIES

San Jose, CA

for technical competence in the field of

Electrical Testing

A2LA has accredited

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 18 June 2005).

SEAL SOREDAY AS A SELECTION OF CONTROL OF CO

Presented this 11th day of July 2008.

President
For the Accreditation Council
Certificate Number 2742.01
Valid to September 30, 2010

For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

 Serial#
 SL10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 39 of 53

 Instance of the complete compl



THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION

ACCREDITED PRODUCT CERTIFICATION BODY

A2LA has accredited

SIEMIC INC.

San Jose, CA

for technical competence as a

Product Certification Body

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 General requirements for bodies operating product certification systems. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system for a Telecommunications Certification Body (TCB) meeting FCC (U.S.), IDA (Singapore) and IC (Canada) requirements.



Presented this $9^{\rm th}$ day of January 2009.

President

For the Accreditation Council Certificate Number: 2742.02 Valid to: September 30, 2010

For the product certification schemes to which this accreditation applies, please refer to the certification body's Scope of Accreditation.

 Serial#
 \$L10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 40 of 53

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 65:1996

SIEMIC INC. 2206 Ringwood Ave. San Jose, CA 95131

Mr. Snell Leong (Authorized Representative) Phone: 408 526 1188

www.siemic.com

PRODUCT CERTIFICATION CONFORMITY ASSESSMENT BODY (CAB)

Valid to: September 30, 2010 Certificate Number: 2742.02

In recognition of the successful completion of the A2LA Certification Body Accreditation Program evaluation, including the US Federal Communications Commission (FCC), Industry Canada (IC) and Singapore (IDA) requirements for the indicated types of product certifications, accreditation is granted to this organization to perform the following product certification schemes:

<u>Economy</u> <u>Scope</u>

Federal Communication Commission - (FCC)

Unlicensed Radio Frequency Devices A1, A2, A3, A4
Licensed Radio Frequency Devices B1, B2, B3, B4
Telephone Terminal Equipment C

Industry Canada - (IC)

Radio All Radio Standards Specifications (RSS) in Category I

Equipment Standards List Radio

IDA - Singapore

Line Terminal Equipment All Technical Specifications for Line Terminal

Equipment - Table 1 of IDA MRA Recognition

Scheme: 2008, Annex 2

Radio-Communication Equipment All Technical Specifications for Radio-Communication

Equipment – Table 2 of IDA MRA Recognition

Scheme: 2008, Annex 2

^{*}Please refer to FCC TCB Program Roles and Responsibilities, v04, released February 14, 2008 detailing scopes, roles and responsibilities. http://www.fcc.gov/oet/ea/FCC-Overview-TCB-Program.pdf

^{*}Please refer to Industry Canada (IC) website at: http://www.ic.gc.ca/epic/site/smt-gst.nsf/en/h_sf01342e.html

^{*}Please refer to Info-Communication Development Authority (iDA) Singapore website at: http://www.ida.gov.sg/doc/Policies%20and%20Regulation/Policies_and_Regulation_Level2/20060609145118/MRA RecScheme.pdf

| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | Page | 41 of 53 | www.siemic.com | www.siemic.com

SIEMIC ACCREDITATION DETAILS: FCC Test Site Registration No. 783147

FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division 7435 Oakland Mills Road Columbia, MD 21046

December 20, 2007

Registration Number: 783147

SIEMIC Laboratories 2206 Ringwood Avenue, San Jose, CA 95131

Attention: Leslie Bai

Re: Measurement facility located at San Jose

3 & 10 meter site

Date of Renewal: December 20, 2007

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish Industry Analyst

| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | Page | 42 of 53 | WARN Stample com | WARN Stample com | Page | Page

SIEMIC ACCREDITATION DETAILS: Industry of Canada CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20899-

March 4, 2009

Mr. Leslie Bai SIEMIC, Inc. 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by Industry Canada (IC), under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.

Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131 USA

Identification No.: US0160

Recognized Scope: CS-03 Part I, II, V, VI, VII and VIII

You may submit test data to IC to verify that the equipment to be imported into Canada satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at http://ts.nist.gov/mra. Please contact Ms. Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov if you have any questions.

Sincerely,

David F. Alderman

Group Leader, Standards Coordination and Conformity Group

Standards Services Division

Parial In Alda

Enclosure

cc: CAB Program Manager



SL10082604-DBI-001(dbNEXIII)_FCC Serial# Issue Date Sep 8th 2010 Page

SIEMIC ACCREDITATION DETAILS: Industry of Canada Test Site Registration No. 4842-1

Industry Industrie

May 23rd, 2008

OUR FILE: 46405-4842 Submission No: 126429

Siemic Inc. 2206 Ringwood Ave. San Jose CA 95131 USA

Attention: Leslie Bai

Dear Sir/Madame:

The Bureau has received your application for the registration / renewal of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (4842A-1). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please be informed that the Bureau is now utilizing a new site numbering scheme in order to simplify the electronic filing process. Our goal is to reduce the number of secondary codes associated to one particular company. The following changes have been made to your record.

- Your primary code is: 4842
- The company number associated to the site(s) located at the above address is: 4842A
- The table below is a summary of the changes made to the unique site registration number(s):

New Site	Obsolete Site	Description of Site	Expiry Date
Number	Number		(YYYY-MM-DD)
4842A-1	4842-1	3m Chamber	2010-05-23

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 meter OATS or 3 meter chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed two years. There is no fee or form associated with an OATS filing, OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL; http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification.bureau@ic.gc.c Please reference our file and submission number above for all correspondence.

Yours sincerely,

S. Proulx

Test & Measurement Specialist Certification and Engineering Bureau 3701 Carling Ave., Building 94 Ottawa, Ontario K2H 8S2

SL10082604-DBI-001(dbNEXIII)_FCC Serial# Issue Date Sep 8th 2010

SIEMIC ACCREDITATION DETAILS: FCC DOC CAB Recognition: US1109

FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division 7435 Oakland Mills Road Columbia, MD 21046

August 28, 2008

Siemic Laboratories 2206 Ringwood Ave., San Jose, CA 95131

Attention:

Leslie Bai

Re:

Accreditation of Siemic Laboratories

Designation Number: US1109 Test Firm Registration #: 540430

Dear Sir or Madam:

We have been notified by American Association for Laboratory Accreditation that Siemic Laboratories has been accredited as a Conformity Assessment Body (CAB).

At this time Siemic Laboratories is hereby designated to perform compliance testing on equipment subject to Declaration Of Conformity (DOC) and Certification under Parts 15 and 18 of the Commission's Rules.

This designation will expire upon expiration of the accreditation or notification of withdrawal of designation.

Sincerely,

George Tannahill **Electronics Engineer**

| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | 45 of 53 | MAMU Stemic com | MAMU Stemic com | Serial# | Seri

SIEMIC ACCREDITATION DETAILS: Australia CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20899-

November 20, 2008

Mr. Leslie Bai SIEMIC, Inc. 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Australian Communications and Media Authority (ACMA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: Siemic, Inc.

Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131

Identification No.: US0160

Recognized Scope: <u>EMC</u>: AS/NZS 4251.1 (until 5/31/2009), AS/NZS 4251.2 (until 5/31/2009),

AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR 22, AS/NZS

61000.6.3, AS/NZS 61000.6.4

Radiocommunications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS

4769.2, AS/NZS 4770, AS/NZS 4771

<u>Telecommunications</u>: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/NZS 60950.1

You may submit test data to ACMA to verify that the equipment to be imported into Australia satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. Recognized CABs are listed on the NIST website at http://ts.nist.gov/mra. Please contact Ms. Ramona Saar, at (301) 975-5521 or <a href="mailto:remailt

Sincerely,

David F. Alderman

Group Leader, Standards Coordination and Conformity Group

Standards Services Division

David T. alder

Enclosure

cc:

Snell Leong, Siemic, Inc.; Ramona Saar, NIST





| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | Page | 46 of 53 | Water Stemple com-

SIEMIC ACCREDITATION DETAILS: Korea CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20899

October 1, 2008

Mr. Leslie Bai SIEMIC, Inc. 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Radio Research Agency (RRA) Korea Communications Commission (KCC) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.

Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131

Identification No.: US0160

Recognized Scope: EMI: KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI

KN22: Test Method for EMI

EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS KN24, KN-61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS Wireless: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10,

RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21,

RRL Notice 2007-80, RRL Notice 2004-68

Wired: President Notice 20664, RRL Notice 2007-30,

RRL Notice 2008-7 with attachments 1, 3, 5, 6

President Notice 20664, RRL Notice 2008-7 with attachment 4

You may submit test data to RRA/KCC to verify that the equipment to be imported into Korea satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at http://ts.nist.gov/mra. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely, Paris To alde

David F. Alderman

Group Leader, Standards Coordination and Conformity Group

Standards Services Division

Enclosure

cc: Ramona Saar



Serial# Page

SL10082604-DBI-001(dbNEXIII)_FCC Issue Date Sep 8th 2010

SIEMIC ACCREDITATION DETAILS: Taiwan BSMI Accreditation No. SL2-IN-E-1130R



UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Geithersburg, Maryland 20898-

May 3, 2006

Mr. Leslie Bai SIEMIC Laboratories 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:

SL2-IN-E-1130R (Must be applied to the test reports) BSMI number:

U.S Identification No: Scope of Designation: CNS 13438 Mr. Leslie Bai Authorized signatory:

The names of all recognized CABs will be posted on the NIST website at http://ts.nist.gov/mra. If you have any questions, please contact Mr. Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

Rund of Reden

Group Leader, Standards Coordination and Conformity Group

Jogindar Dhillon



| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | 48 of 53 | Issue Date | Sep 8th 2010 | Issue Date | Sep 8th 2010 | Issue Date | Issue

SIEMIC ACCREDITATION DETAILS: Taiwan NCC CAB ID: US0160



NATIONAL STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20899-

November 25, 2008

Mr. LeslieBai SIEMIC, Inc. 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the National Communications Commission (NCC) for the requested scope expansion under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.

Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131

Identification No.: US0160 Current Scope: LP0002

Additional Scope: PSTN01, ADSL01, ID0002, IS6100 and CNS 14336

You may submit test data to NCC to verify that the equipment to be imported into China satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at http://ts.nist.gov/mra. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely, Parist Z. ald

David F. Alderman

Group Leader, Standards Coordination and Conformity Group

Standards Services Division

Enclosure

cc: Ramona Saar





Serial# SL10082604-DBI-001(dbNEXIII)_FCC Issue Date Sep 8th 2010

Sep 8th 2010 49 of 53

Page

SIEMIC ACCREDITATION DETAILS: Mexico NOM Recognition



Laboratorio Valentín V. Rivero

México D.F. a 16 de octubre de 2006.

LESLIE BAI DIRECTOR OF CERTIFICATION SIEMIC LABORATORIES, INC. ACCESSING GLOBAL MARKETS PRESENTE

En contestación a su escrito de fecha 5 de septiembre del año en curso, le comento que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo cual adjunto a este escrito encontrara el Acuerdo en cidioma ingles y espeñol prelienado de los cuales le pido sea revisado y en su caso corregido, para que si esta de acuerdo poder firmanto para mandanto con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecho este escrito para mencionarle que nuestro intermediario gestor será la empresa fisatel de México. S. A. de C. V., empresa que ha colaborado durante mucho tiempo con nosotros en lo refacionado a la evaluación de la conformidad y que quenta con amplia experiencia en la gestoría de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.

Me despido de ustad enviêndole un cordial saludo y esperando sus comentarios al Acuerdo que nos soupa.

Atentamente:

Ing. Faustino Soriez González Gerente Poerico del Laboratorio de

CANTER.

Culturale 71 Handerene Condesa de too Maleos, D.F. e. 5204-0308 con 12 linear Fax 5364 0446

SIEMIC ACCREDITATION DETAILS: Hong Kong OFTA CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20899-

December 8, 2008

Mr. Leslie Bai SIEMIC, Inc. 2206 Ringwood Avenue San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Office of the Telecommunications Authority (OFTA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.

Physical Location: 2206 Ringwood Avenue, San Jose, California 95131 USA

Identification No.: US0160

Recognized Scope: Radio: HKTA 1002, 1007, 1008, 1010, 1015, 1016, 1020, 1022, 1026,

1027, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1039, 1041,

1042, 1043, 1044, 1046, 1047, 1048, 1049, 1051

Telecom: HKTA 2011, 2012, 2013, 2014, 2017, 2018, 2022, 2024, 2026,

2027, 2028, 2029, 2030, 2031, 2032, 2033

You may submit test data to OFTA to verify that the equipment to be imported into Hong Kong satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at http://ts.nist.gov/mra. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman

David I alden

Group Leader, Standards Coordination and Conformity Group Standards Services Division

Enclosure

cc: Ramona Saar



SL10082604-DBI-001(dbNEXIII)_FCC Issue Date Sep 8th 2010

SIEMIC ACCREDITATION DETAILS: VCCI Radiated Test Site Registration No. R-3083





CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081

Facility: SIEMIC Inc.

(Radiation

3

meter site)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

This is to certify that the following measuring facility has been registered in accordance with the Rules for Voluntary Control Measures

Registration No.: R-3083

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010





| Serial# | SL10082604-DBI-001(dbNEXIII)_FCC | Issue Date | Sep 8th 2010 | Page | 52 of 53 | State of the sep | State of the se

SIEMIC ACCREDITATION DETAILS: VCCI Conducted (Main Port) Test Site Registration No. C-3421





VCCI Council

CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081

Facility: SIEMIC Inc.

(Main Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

This is to certify that the following measuring facility has been registered in accordance with the Rules for Voluntary Control Measures

Registration No.: C-3421

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010





 Serial#
 SL10082604-DBI-001(dbNEXIII)_FCC

 Issue Date
 Sep 8th 2010

 Page
 53 of 53

SIEMIC ACCREDITATION DETAILS: VCCI Conducted (Telecom Port) Test Site Registration No. T-1597





VCCI Council

CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Telecominication Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

This is to certify that the following measuring facility has been registered in accordance with the Rules for Voluntary Control Measures

Registration No.: T-1597

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010

