

Page 1 of 35

JQA File No.: KL80170217R Issue Date: August 30, 2017

TEST REPORT (SAR EVALUATION)

Applicant : OLYMPUS CORPORATION

Address : 2951 Ishikawa-machi, Hachioji-shi, Tokyo 192-8507, Japan

Products : Smart Glasses

Model No. : EI-10
Serial No. : PP2-003
FCC ID : YSKK05

Test Standard : FCC Rules and Regulations Title 47 CFR Part 2

Test Results : Passed

Date of Test : April 27 ~ August 29, 2017



Kousei Shibata

Manager
Japan Quality Assurance Organization
KITA-KANSAI Testing Center
SAITO EMC Branch

7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

- The test results in this test report was made by using the measuring instruments which are traceable to national standards of measurement in accordance with ISO/IEC 17025.
- The applicable standard, testing condition and testing method which were used for the tests are based on the request of the applicant.
- The test results presented in this report relate only to the offered test sample.
- The contents of this test report cannot be used for the purposes, such as advertisement for consumers.
- This test report shall not be reproduced except in full without the written approval of JQA.
- VLAC does not approve, certify or warrant the product by this test report.



JQA File No. : KL80170217R

Model No. : EI-10

Standard

: FCC Rules and Regulations Title 47 CFR Part 2

Page 2 of 35

Issue Date: August 30, 2017

: YSKK05

FCC ID

TABLE OF CONTENTS

		Pag
1	Description of the Device Under Test (DUT)	3
2	Summary of Test Results	6
3	Test Procedure	7
4	Test Location	7
5	Recognition of Test Laboratory	7
6	Measurement System Diagram	8
7	System Components	9
8	Measurement Process	12
9	Measurement Uncertainties	13
10	Test Arrangement	15
11	Tissue Verification	17
12	System Performance Check	20
13	RF Output Power Measurements	22
14	SAR Measurements	24
15	Test Setup Photographs	29
16	Test Instruments	34
17	Appendix	35



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 3 of 35

1 Description of the Device Under Test (DUT)

1.1 General Information

1. Manufacturer : OLYMPUS CORPORATION

2951 Ishikawa-machi, Hachioji-shi, Tokyo 192-8507, Japan

2. Products : Smart Glasses

Model No. : EI-10
 Serial No. : PP2-003

5. Product Type : Pre-production6. Date of Manufacture : January, 2017

7. Transmitting Frequency : WLAN 2.4 GHz (DTS : 2412 MHz – 2462 MHz)

WLAN 5 GHz (U-NII 1 : 5150 MHz – 5250 MHz) WLAN 5 GHz (U-NII 2A : 5250 MHz – 5350 MHz) WLAN 5 GHz (U-NII 2C : 5470 MHz – 5725 MHz)

Bluetooth (2402 MHz - 2480 MHz)

8. Battery Option : Lithium-ion Battery Pack WHB-001 (300mAh)

9. Power Rating : 3.7VDC10. DUT Grounding : None

11. Device Category : Portable Device (§2.1093)

12. Exposure Category : General Population/Uncontrolled Exposure

13. FCC Rule Part(s) : 15.247, 15.40714. DUT Authorization : Certification

15. Received Date of DUT : January 25, 2017



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 4 of 35

1.2 Wireless Technologies

Air Interface	Description				
	Frequency band(s)	2.4 GHz			
		802.11b			
	Operating made	802.11g			
	Operating mode	802.11n [HT20]			
WLAN (DTS)		802.11n [HT40]			
	VoIP	Not supported			
	Wireless Router (Hotspot)	Not supported			
	Wi-Fi Direct	Not supported			
	Tx Diversity Configuration	N/A			
	Frequency band(s)	5 GHz			
		802.11a			
	Operating mode	802.11n [HT20]			
		802.11n [HT40]			
WLAN (U-NII)	VoIP	Not supported			
WLAIN (U-INII)	Wireless Router (Hotspot)	Not supported			
	Wi-Fi Direct	Not supported			
	TDWR (Terminal Doppler Weather Rader)	Supported			
	Band gap channel	Not supported			
	Tx Diversity Configuration	N/A			
Bluetooth	Frequency band(s)	2.4 GHz			
Diuetootii	Operating mode	Version 4.1+EDR			



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 5 of 35

1.3 Maximum Output Power

	Mode	Max. Tune-up Limit (dBm)	
		1 ~ 3 ch	8.0
	802.11b	4 ~ 7 ch	7.0
		8 ~ 11 ch	6.0
		1 ~ 3 ch	8.0
	802.11g	4 ~ 7 ch	7.0
WLAN 2.4 GHz		8 ~ 11 ch	6.0
(DTS)		1 ~ 3 ch	8.0
	802.11n HT20	4 ~ 7 ch	7.0
		8 ~ 11 ch	6.0
	802.11n HT40	3 ch	8.0
		4 ~ 7 ch	7.0
		8 ~ 9 ch	6.0
		36 ~ 64 ch	5.0
	802.11a	100 ~ 112 ch	6.5
	802.11a	116 ~ 124 ch	7.5
		128 ~ 140 ch	9.5
		36 ~ 64 ch	5.0
WLAN 5 GHz	802.11n HT20	100 ~ 112 ch	6.5
(U-NII)	802.1111 1120	116 ~ 124 ch	7.5
		128 ~ 140 ch	9.5
		38 ~ 62 ch	5.0
	009 11m IIT40	102 ~ 110 ch	6.5
	802.11n HT40	118 ch	7.5
		126 ~ 134 ch	9.5

Mode	Max. Tune-up Limit (dBm)
Bluetooth	6.0



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 6 of 35

2 Summary of Test Results

Applied Standard : FCC Rules and Regulations Title 47 CFR Part 2 - Frequency Allocations

and Radio Treaty Matters; General Rules and Regulations

§2.1093 Radiofrequency radiation exposure evaluation: poratble devices

T		Limit			
Test Configuration	Licensed	DTS	U-NII	DSS (BT)	(W/kg)
Head-worn	N/A	N/A	1.19	N/A	1.0
Simultaneous Transmission	N/A	N/A	N/A	N/A	1.6

The test results are passed for exposure limits specified in ANSI/IEEE Std. C95.1.

In the approval of test results,

- Determining compliance with the limits in this report was based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- No deviations were employed from the applied standard.

- No modifications were conducted by JQA to achieve compliance to the limitations.

Reviewed by:

Shigeru Kinoshita Assistant Manager

JQA KITA-KANSAI Testing Center

SAITO EMC Branch

Tested by:

Yasuhisa Sakai

Manager

JQA KITA-KANSAI Testing Center

SAITO EMC Branch



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 7 of 35

3 Test Procedure

The tests documented in this report were performed in accordance with FCC 47 CFR §2.1093, IEEE Std.1528–2013 and the following KDB Procedures.

- # 248227 D01 802.11 Wi-Fi SAR v02r02
- # 447498 D01 General RF Exposure Guidance v06
- # 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- # 865664 D02 RF Exposure Reporting v01r02

4 Test Location

Japan Quality Assurance Organization (JQA) KITA-KANSAI Testing Center 7-7, Ishimaru, 1-chome, Minoh-shi, Osaka, 562-0027, Japan SAITO EMC Branch 7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

5 Recognition of Test Laboratory

JQA KITA-KANSAI Testing Center SAITO EMC Branch is accredited under ISO/IEC 17025 by following accreditation bodies and the test facility is registered by the following bodies.

VLAC Accreditation No. : VLAC-001-2 (Expiry date : March 30, 2018) VCCI Registration No. : A-0002 (Expiry date : March 30, 2018)

BSMI Registration No. : SL2-IS-E-6006, SL2-IN-E-6006, SL2-R1/R2-E-6006, SL2-A1-E-6006

(Expiry date: September 14, 2019)

IC Registration No. : 2079E-3, 2079E-4 (Expiry date : June 26, 2020)

Accredited as conformity assessment body for Japan electrical appliances and material law by METI.

(Expiry date: February 22, 2019)



Model No. : EI-10 FCC ID : YSKK05


Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 8 of 35

6 Measurement System Diagram

These measurements are performed using the DASY5 automated dosimetric assessment system (manufactured by Schmid & Partner Engineering AG (SPEAG) in Zürich, Switzerland). It consists of high precision robotics system, cell controller system, DASY5 measurement server, personal computer with DASY5 software, data acquisition electronic (DAE) circuit, the Electro-optical converter (EOC), near-field probe, and the twin SAM phantom containing the equivalent tissue. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF).

The Robot is connected to the cell controller to allow software manipulation of the robot. The DAE is connected to the EOC. The DAE performs the signal amplification, signal multiplexing, A/D conversion, offset measurements, mechanical surface detection, collision detection, etc. The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY5 measurement server.





Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 9 of 35

7 System Components

7.1 Probe Specification ET3DV6

Construction : Symmetrical design with triangular core

Built-in optical fiber for surface detection system

Built-in shielding against static changes

PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

Calibration : In air form 10 MHz to 2.3 GHz

In head tissue simulating liquid (HSL) and

muscle tissue simulating liquid 835 MHz (accuracy \pm 12.0%; k=2) 900 MHz (accuracy \pm 12.0%; k=2) 1450 MHz (accuracy \pm 12.0%; k=2) 1750 MHz (accuracy \pm 12.0%; k=2) 1900 MHz (accuracy \pm 12.0%; k=2) 1950 MHz (accuracy \pm 12.0%; k=2)



Frequency : 10 MHz to 2.3 GHz

Linearity: ± 0.2 dB (30 MHz to 2.3 GHz)

Directivity : \pm 0.2 dB in HSL (rotation around probe axis)

± 0.4 dB in HSL (rotation normal to probe axis)

Dynamic Range : $5 \mu W/g$ to >100 mW/g; Linearity: \pm 0.2 dB

Surface Detection : ± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces

Dimensions : Overall length 337 mm

Tip length 16 mm
Body diameter 12 mm
Tip diameter 6.8 mm

Distance from probe tip to dipole centers 2.7 mm



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 10 of 35

7.2 Probe Specification EX3DV4

Construction : Symmetrical design with triangular core

Built-in shielding against static changes

PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

Calibration : In air form 10 MHz to 6 GHz

In head tissue simulating liquid (HSL) and

muscle tissue simulating liquid 2450 MHz (accuracy \pm 12.0%; k=2) 2600 MHz (accuracy \pm 13.1%; k=2) 5200 MHz (accuracy \pm 13.1%; k=2) 5300 MHz (accuracy \pm 13.1%; k=2) 5500 MHz (accuracy \pm 13.1%; k=2) 5600 MHz (accuracy \pm 13.1%; k=2) 5800 MHz (accuracy \pm 13.1%; k=2)



Frequency : 10 MHz to 6 GHz

Linearity: ± 0.2 dB (30 MHz to 6 GHz)

Directivity : \pm 0.3 dB in HSL (rotation around probe axis)

± 0.5 dB in tissue material (rotation normal to probe axis)

Dynamic Range : $10 \mu W/g$ to >100 mW/g; Linearity: \pm 0.2 dB (noise: typically < 1 μ W/g)

Dimensions : Overall length 337 mm

Tip length 20 mm
Body diameter 12 mm
Tip diameter 2.5 mm

Distance from probe tip to dipole centers 1 mm



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 11 of 35

7.3 Twin SAM Phantom

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.



Shell Thickness : 2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm

Filling Volume : Volume Approx. 25 liters

 $Dimensions \hspace{1.5cm} : 810 \times 1000 \times 500 \hspace{0.1cm} mm \hspace{0.1cm} (H \times L \times W)$

7.4 ELI4 Flat Phantom

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of



the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

7.5 Mounting Device for Transmitters

In combination with the Twin SAM Phantom V4.0/V4.0c or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat point).





Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 12 of 35

8 Measurement Process

Step 1 : Power Reference Measurement

The power reference job measures the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method. The minimum distance of probe sensors to surface set to 4 mm for an ET3DV6 probe, or 2 mm for EX3DV4 probe. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations in relatively coarse grids. When an area scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. If only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maxima within 2 dB of the maximum SAR value are detected, the number of zoom scans has to be increased accordingly.

Step 3: Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The zoom scan measures points specified in standards within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure.

Step 4: Z Scan

The Z scan measures points along a vertical straight line. The line runs along the Z axis of a one-dimensional grid. In order to get a reasonable extrapolation, the extrapolated distance should not be larger than the step size in Z-direction.

Step 5 : Power Drift Measurement

The power drift measurement measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The power drift measurement gives the field difference in dB from the reading conducted within the last power reference measurement. The power reference measurement and power drift measurement are for monitoring the power drift of the device under test in the batch process.



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 13 of 35

9 Measurement Uncertainties

9.1 300 MHz to 3 GHz

Uncertainty Component	Tol.	Tol. Prob. (± %) Dist.	Div	c_i	c_i	Std. Unc. (± %)		v _i
	(± /0)			(1g)	(10g)	1g	10g	
Measurement System								
Probe calibration	6.0	N	1	1	1	6.0	6.0	∞
Axial isotropy	4.7	R	√3	0.7	0.7	1.9	1.9	∞
Hemispherical isotropy	9.6	R	√3	0.7	0.7	3.9	3.9	∞
Boundary effects	1.0	R	√3	1	1	0.6	0.6	∞
Linearity	4.7	R	√3	1	1	2.7	2.7	∞
System detection limits	1.0	R	√3	1	1	0.6	0.6	∞
Modulation response	2.4	R	√3	1	1	1.4	1.4	∞
Readout electronics	0.3	N	1	1	1	0.3	0.3	∞
Response time	0.8	R	√3	1	1	0.5	0.5	∞
Integration time	2.6	R	√3	1	1	1.5	1.5	∞
RF ambient conditions – noise	3.0	R	√3	1	1	1.7	1.7	∞
RF ambient conditions – reflections	3.0	R	√3	1	1	1.7	1.7	∞
Probe positioner mechanical tolerance	0.4	R	√3	1	1	0.2	0.2	∞
Probe positioning with respect to phantom shell	2.9	R	√3	1	1	1.7	1.7	∞
Extrapolation, interpolation and integration		R	√3	1	1	1.2	1.2	∞
algorithms for max. SAR evaluation								
Test Sample Related								
Device holder uncertainty	2.9	N	1	1	1	2.9	2.9	5
Test sample positioning	3.4	N	1	1	1	3.4	3.4	23
Output power variation - SAR drift measurement	5.0	R	√3	1	1	2.9	2.9	∞
Power Scaling	0.0	R	√3	1	1	0.0	0.0	∞
Phantom and Tissue Parameters								
Phantom uncertainty	6.1	R	√3	1	1	3.5	3.5	∞
Algorithms for correcting SAR for deviations	1.9	R	√3	1	0.84	1.1	0.9	∞
Liquid Conductivity – measurement uncertainty	3.2	N	1	0.78	0.71	2.5	2.3	5
Liquid Permittivity – measurement uncertainty	3.0	N	1	0.26	0.26	0.8	0.8	5
Liquid Conductivity – temperature uncertainty	5.2	R	√3	0.78	0.71	2.3	2.1	∞
Liquid Permittivity – temperature uncertainty	0.8	R	√3	0.23	0.26	0.1	0.1	∞
Combined Standard Uncertainty		RSS				11.5	11.4	
Expanded Uncertainty (95% Confidence Interval)		k=2				22.9	22.7	

NOTES

Tol.: tolerance in influence quantity
 Prob. Dist.: probability distributions

3. N, R: normal, rectanglar

4. Div. : divisor used to obtain standard uncertainty

5. c_i : sensitivity coefficient

6. Std. Unc. : standard uncertainty

 $7.\ Measurement$ uncertainties are according to IEEE Std.1528 and IEC 62209-1



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 14 of 35

9.2 3 GHz to 6 GHz

Uncertainty Component	Tol.	Tol. Prob. (±%) Dist.	Div.	<i>c</i> _i	c _i	Std. Unc. (± %)		v _i
	(± /0)	Dist.		(1g)	(10g)	1g	10g	
Measurement System								
Probe calibration	6.6	N	1	1	1	6.6	6.6	∞
Axial isotropy	4.7	R	√3	0.7	0.7	1.9	1.9	∞
Hemispherical isotropy	9.6	R	$\sqrt{3}$	0.7	0.7	3.9	3.9	∞
Boundary effects	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Modulation response	2.4	R	$\sqrt{3}$	1	1	1.4	1.4	∞
Readout electronics	0.3	N	1	1	1	0.3	0.3	∞
Response time	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
Integration time	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
RF ambient conditions – noise	3.0	R	$\sqrt{3}$	1	1	1.7	1.7	∞
RF ambient conditions – reflections	3.0	R	√3	1	1	1.7	1.7	∞
Probe positioner mechanical tolerance	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
Probe positioning with respect to phantom shell		R	$\sqrt{3}$	1	1	3.9	3.9	∞
Extrapolation, interpolation and integration		R	$\sqrt{3}$	1	1	2.3	2.3	∞
algorithms for max. SAR evaluation								
Test Sample Related								
Device holder uncertainty	2.9	N	1	1	1	2.9	2.9	5
Test sample positioning	3.4	N	1	1	1	3.4	3.4	23
Output power variation - SAR drift measurement	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Power Scaling	0.0	R	$\sqrt{3}$	1	1	0.0	0.0	∞
Phantom and Tissue Parameters								
Phantom uncertainty	6.6	R	$\sqrt{3}$	1	1	3.8	3.8	∞
Algorithms for correcting SAR for deviations	1.9	R	$\sqrt{3}$	1	0.84	1.1	0.9	∞
Liquid Conductivity – measurement uncertainty	3.2	N	1	0.78	0.71	2.5	2.3	5
Liquid Permittivity - measurement uncertainty	3.0	N	1	0.26	0.26	0.8	0.8	5
Liquid Conductivity – temperature uncertainty	3.4	R	√3	0.78	0.71	1.5	1.4	∞
Liquid Permittivity – temperature uncertainty	0.4	R	√3	0.23	0.26	0.1	0.1	∞
Combined Standard Uncertainty		RSS				12.5	12.4	
Expanded Uncertainty (95% Confidence Interval)		k=2				24.9	24.8	

NOTES

Tol.: tolerance in influence quantity
 Prob. Dist.: probability distributions

3. N, R: normal, rectanglar

4. Div. : divisor used to obtain standard uncertainty

5. c_i : sensitivity coefficient

6. Std. Unc.: standard uncertainty

7. Measurement uncertainties are according to IEEE Std.1528 and IEC 62209-1.



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 15 of 35


10 Test Arrangement

10.1 RF Exposure Conditions

For a device that cannot be categorized as any of the other specific device types, it shall be considered to be a generic device; i.e. represented by a closed box incorporating at least one internal RF transmitter and antenna.

The SAR evaluation shall be performed for all surfaces of the DUT that are accessible during intended use. The separation distance in testing shall correspond to the intended use distance as specified in the user instructions provided by the manufacturer. If the intended use is not specified, all surfaces of the DUT shall be tested directly against the flat phantom.

The surface of the generic device (or the surface of the carry accessory holding the DUT) pointing towards the flat phantom shall be parallel to the surface of the phantom.



Test positions for a generic device





Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 16 of 35

10.2 Antenna Location and Separation Distances





WLAN/BT Antenna



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 17 of 35


11 Tissue Verification

11.1 Tissue Verification Measurement Condition

The tissue dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3-4 days of use, or earlier if dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

The temperature of the tissue-equivalent medium used during measurement must be within 18°C to 25°C and within \pm 2°C of the temperature when the tissue parameters are characterized.

It is verified by using the dielectric probe and the network analyzer.



11.2 Tissue Dielectric Properties

The tissue dielectric properties are specified in KDB 865664 D01.

Target Frequency	Frequency Head		В	ody
[MHz]	Permittivity (ε _r)	Conductivity (a)	Permittivity (er)	Conductivity (a)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

For tissue dielectric properties at other frequencies within the range, a linear interpolation method shall be used.



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 18 of 35

11.3 Composition of Ingredients for the Tissue Material Used in the SAR Tests

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Head and Body Liquids (Below 1 GHz)

Item	Head and Muscle Tissue Simulation Liquids HSL/MSL 750, HSL/MSL 900
H ₂ O	Water, 35 – 58 %
Sucrose	Sugar, white, refined, 40 – 60 %
NaCl	Sodium Chloride, 0 – 6 %
Hydroxyethyl-cellulose	Medium Viscosity (CAS# 9004-62-0), < 0.3 %
	Preservative: aqueous preparation, (CAS# 55965-84-9), containing
Preventol-D7	5-chloro-2-methyl-3(2H)-isothiazolone and 2-methyyl-3(2H)-isothiazolone,
	0.1 – 0.7 %

Head and Body Liquids (1 to 3 GHz)

Item	Head and Muscle Tissue Simulation Liquids HSL/MSL 1750, HSL/MSL 1900, HSL/MSL 2450
H ₂ O	Water, 52 – 75 %
C8H18O3	Diethylene glycol monobutyl ether (DGBE), 25 – 48%
C81118O3	(CAS-No. 112-34-5, EC-No. 203-961-6, EC-index-No. 603-096-00-8)
NaCl	Sodium Chloride, < 1.0 %

Head Liquids (3 to 6 GHz)

Item	Head Broad Band Tissue Simulation Liquids HBBL 3500-5800				
Water	50 – 65 %				
Mineral oil	10 – 30 %				
Emulsifiers	8 – 25 %				
Sodium salt	0 – 1.5 %				
Safety relevant ingredients	Safety relevant ingredients according to EU directives:				
EINECS-No 203-489-0	1.0 – 2.8 % 2-Methyl-pentane-2,4-diol (Hexylene Glycol):				
CAS-No 107-41-5	(Xi irritant, R36/38 irritant for eyes and skin)				

Body Liquids (3 to 6 GHz)

Item	Muscle Broad Band Tissue Simulation Liquids MBBL 3500-5800				
Water	60 – 80 %				
Esters, Emulsifiers,	20 – 40 %				
Inhibitors					
Sodium salt	0 – 1.5 %				
Safety relevant ingredients according to EU directives: none					
Safety relevant ingredients according to other directives:					
CAS-No 26399-02-0	10 – 28 % Oleic acid, alkylester				



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 19 of 35

11.4 Tissue Verification Results

Tissue dielectric parameters are measured at the low, middle and high frequency of each operating frequency range of the test device.

Date	Liquid	Frequency [MHz]	Parameters	Target	Measured	Deviation [%]	Limit [%]
			Permittivity (ε _r)	36.0	36.68	+1.89	± 5
		5180	Conductivity (a)	4.63	4.545	-1.84	± 5
			Permittivity (ε _r)	35.9	36.58	+1.89	± 5
4/27/2017	Head	5250	Conductivity (σ)	4.71	4.615	-2.02	± 5
			Permittivity (ε _r)	35.8	36.47	+1.87	± 5
		5320	Conductivity (a)	4.78	4.687	-1.95	± 5
		7 400	Permittivity (ε _r)	36.0	36.66	+1.83	± 5
		5180	Conductivity (o)	4.63	4.536	-2.03	± 5
1/00/0017	** 1	5050	Permittivity ($\epsilon_{\rm r}$)	35.9	36.56	+1.84	± 5
4/28/2017	Head	5250	Conductivity (a)	4.71	4.606	-2.21	± 5
		5000	Permittivity (ε _r)	35.8	36.46	+1.84	± 5
		5320	Conductivity (a)	4.78	4.675	-2.20	± 5
		5500	Permittivity (ε _r)	35.6	36.35	+2.11	± 5
		5500	Conductivity (a)	4.96	4.878	-1.65	± 5
0/97/9017	111	5000	Permittivity (ε _r)	35.5	36.21	+2.00	± 5
6/27/2017	Head	5600	Conductivity (a)	5.07	4.988	-1.62	± 5
		7700	Permittivity (ε _r)	35.4	36.05	+1.84	± 5
		5700	Conductivity (a)	5.17	5.081	-1.72	± 5
		5100	Permittivity ($\epsilon_{\rm r}$)	36.0	36.74	+2.06	± 5
		5180	Conductivity (a)	4.63	4.563	-1.45	± 5
8/28/2017	Head	5250	Permittivity (ε _r)	35.9	36.64	+2.06	± 5
0/20/2017	пеац	5230	Conductivity (a)	4.71	4.636	-1.57	± 5
		5320	Permittivity ($\epsilon_{\rm r}$)	35.8	36.53	+2.04	± 5
		5320	Conductivity (a)	4.78	4.704	-1.59	± 5
		5500	Permittivity (ε _r)	35.6	36.28	+1.91	± 5
		3300	Conductivity (a)	4.96	4.884	-1.53	± 5
8/28/2017	Head	5600	Permittivity (ε _r)	35.5	36.13	+1.77	± 5
0/20/2017	Head	5700	Conductivity (a)	5.07	4.994	-1.50	± 5
			Permittivity (ε _r)	35.4	35.99	+1.67	± 5
		3700	Conductivity (a)	5.17	5.100	-1.35	± 5



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2


Page 20 of 35

12 System Performance Check

12.1 System Performance Check Measurement Condition

The power meter PM1 (including Attenuator) measures the forward power at the location of the validation dipole connector. The signal generator is adjusted for 250 mW (100 mW for 3 to 6 GHz) at the dipole connector and the power meter PM2 is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2.

The dipole antenna is matched to be used near flat phantom filled with tissue simulating solution. A specific distance holder is used in the positioning of the antenna to ensure correct spacing between the phantom and the dipole.



12.2 Target SAR Values for System Performance Check

The target SAR values can be obtained from the calibration certificate of system validation dipoles.

System 1	System Dipole		Frequency		Target SAR Values [W/kg]		
Type	Serial	Cal. Date	[MHz]	1g/10g	Head	Body	
			5050	1g	80.4	77.8	
		9/20/2016	5250	10g	23.0	21.9	
DECH VO	1111		5000	1g	82.8	79.5	
D5GHzV2			5600	10g	23.6	22.2	
			5750	1g	81.5	77.3	
			5750	10g	23.1	21.6	



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 21 of 35

12.3 System Performance Check Results

The SAR measured with a system validation dipole, using the required tissue-equivalent medium at the test frequency, must be within 10 % of the manufacturer calibrated dipole SAR target.

Date	System I	Dipole	Liquid	Liquid Measured SAR [W/kg]		Target	Deviation	Limit
2410	Type	Serial	Ziquiu	(Nori	malized to 1 W)	Tunger	[%]	[%]
4/97/9017	D5GHzV2	1111	Head	1 g	78.10	80.4	-2.86	± 10
4/27/2017	(5.25GHz)	1111	неац	10 g	22.60	23.0	-1.74	± 10
4/00/0017	D5GHzV2	1111	77 1	1 g	78.30	80.4	-2.61	± 10
4/28/2017	(5.25GHz)	1111	Head	10 g	22.60	23.0	-1.74	± 10
0/07/0017	D5GHzV2	1111	111	1 g	81.10	82.8	-2.05	± 10
6/27/2017	(5.60GHz)	1111	Head	10 g	23.00	23.6	-2.54	± 10
0/00/0017	D5GHzV2	1111	77 1	1 g	79.40	80.4	-1.24	± 10
8/28/2017	(5.25GHz)	1111	Head	10 g	22.80	23.0	-0.87	± 10
0/00/0017	D5GHzV2	1111		1 g	84.30	82.8	+1.81	± 10
8/28/2017	(5.60GHz)	1111	Head	10 g	23.50	23.6	-0.42	± 10



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 22 of 35

13 RF Output Power Measurements

13.1 WLAN (DTS Band)

Maximum tune-up tolerance limit is 8.0 dBm from the rated nominal maximum output power. This power level qualifies for exclusion of SAR testing.

13.2 WLAN (U-NII Band)

D I	36.1	Data	C1 //	Frequency	Average Po	ower (dBm)
Band	Mode	Rate	Ch#	(MHz)	Measred	Spec. Max.
	802.11a	6 Mbps	36 - 48	5180 - 5240	Not	5.0
5.2 GHz	802.11n [HT20]	MCS 0	36 – 48	5180 - 5240	Required	5.0
(U-NII 1)	000 11 [HT40]	MCCO	38	5190	4.12	5.0
	802.11n [HT40]	MCS 0	46	5230	3.80	5.0
	802.11a	6 Mbps	52 - 64	5260 - 5320	Not	5.0
5.3 GHz	802.11n [HT20]	MCS 0	52 - 64	5260 - 5320	Required	5.0
(U-NII 2A)	000 11 [[[[[40]	MCCO	54	5270	3.11	- 0
	802.11n [HT40]	MCS 0	62	5310	3.23	5.0
			100	5500		6.5
	802.11a	6 Mbps	120	5600		7.5
			140	5700	Not	9.5
5 0 CH			100	5500	Required	6.5
5.6 GHz	802.11n [HT20]	MCS 0	120	5600		7.5
(U-NII 2C)			140	5700		9.5
			102	5510	5.38	6.5
	802.11n [HT40]	MCS 0	118	5590	6.28	7.5
			134	5670	8.37	9.5

Note(s):

Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.

- When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
- When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 23 of 35

13.3 Bluetooth

Maximum tune-up tolerance limit is 6.0 dBm from the rated nominal maximum output power. This power level qualifies for exclusion of SAR testing.

13.4 Standalone SAR Test Exclusion Considerations (KDB 447498 D01)

The 1 g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* \leq 50 mm are determined by;

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f_{(GHz)}}] \le 3.0$ for 1 g SAR and ≤ 7.5 for 10 g extremity SAR, where

- $f_{(GHz)}$ is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison.
- When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied.

D. I	Freq.	Max.	Power	Distance	m 1 11	Test
Band	(MHz)	(dBm)	(mW)	(mm)	Threshold	Exclusion
WLAN (DTS)	2462	8.0	6	< 5	1.9	YES
WLAN (U-NII)	5700	9.5	9	< 5	4.3	NO
Bluetooth	2480	6.0	4	< 5	1.3	YES



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 24 of 35

14 SAR Measurements

SAR test reduction criteria are as follows:

When 10 g extremity SAR is required, SAR values indicated below are multiplied by 2.5, i.e. the ratio of the 1 g and extremity 10 g SAR limit.

KDB 248227 D01 802.11 Wi-Fi SAR:

SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM in both 2.4 GHz and 5 GHz bands, an <u>initial test configuration</u> is first determined for each standalone and aggregated frequency band according to the maximum output power and tune-up tolerance specified for production units. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the <u>initial test configuration</u>, for each frequency band.

SAR is measured using the highest measured maximum output power channel for the determined exposure configurations. When there are multiple test channels with the same measured maximum output power, the channel closest to mid-band frequency is selected for SAR measurement. When there are multiple test channels with the same measured maximum output power and equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

An <u>initial test position</u> is applied to further reduce the number of SAR tests for devices operating in next to the ear, UMPC mini-tablet or hotspot mode exposure configurations that require multiple test positions SAR is measured in the <u>initial test position</u> using the 802.11 transmission mode configuration required by the DSSS procedure or <u>initial test configuration</u> according to the OFDM procedures. The <u>initial test position</u> procedure is described in the following:

- When the <u>reported SAR</u> of the <u>initial test position</u> is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combination within the frequency band or aggregated band.
- When the <u>reported</u> SAR of the <u>initial test position</u> is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the <u>initial test position</u> using subsequent highest extrapolated or estimated 1 g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the <u>reported</u> SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- For all positions/configurations tested using the <u>initial test position</u> and subsequent test positions, when the <u>reported</u> SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the <u>reported</u> SAR is ≤ 1.2 W/kg or all required channels are tested.

To determine the <u>initial test position</u>, Area Scans were performed to determine the position with the estimated 1 g SAR (fast SAR). The position that produced the highest fast SAR is considered the worst case position; thus used as the <u>initial test position</u>. The averaged fast SAR is scaled according to <u>reported</u> SAR requirements.



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 25 of 35

14.1 WLAN (U-NII Band)

14.1.1 5.2 GHz Band (U-NII 1)

The same maximum output power is specified for U-NII 1 and U-NII 2A band, therefore begin SAR measurement in U-NII 2A band by applying the OFDM SAR requirements.

The highest <u>reported</u> SAR for U-NII 2A band is \leq 1.2 W/kg, then the SAR is not required for U-NII 1 band.

14.1.2 5.3 GHz Band (U-NII 2A)

802.11n HT40 (802.11n HT40 (MCS 0) – Duty Cycle 100%										
DE E	Ch#	ъ.			Averaged	Power	[dBm]	1 g SAR [W/kg]		D1 .	
RF Exposure Conditions		· Hast SAR In	Tune-up Limit	Meas.	Meas.	Scaled	Plot No.				
	Inner	0	62	5310	0.000	5.0	3.23				
	Outer	0	62	5310	0.186	5.0	3.23	0.121	0.182		
	**		54	5270	0.834	5.0	3.11	0.758	1.171	1	
	Upper	0	62	5310	0.722	5.0	3.23	0.612	0.920		
	w/ Headset	0	54	5270	0.545	5.0	3.11	0.590	0.912		
Head-worn	w/ Neckband	0	54	5270	0.734	5.0	3.11	0.647	1.000		
Tieau-worn	w/ Eyewear	0	54	5270	0.609	5.0	3.11	0.601	0.929		
	w/ Neckband & Headset	0	54	5270	0.634	5.0	3.11	0.611	0.944		
	w/ Eyewear & Headset	0	54	5270	0.559	5.0	3.11	0.580	0.896		
	Lower	0	62	5310	0.001	5.0	3.23				

Note(s):

SAR is not required for <u>subsequent test configurations</u> when the highest <u>reported</u> SAR for the <u>initial test configuration</u> is adjusted by the ratio of the <u>subsequent test configuration</u> to <u>initial test configuration</u> specified maximum output power and the adjusted SAR is $\leq 1.2 \text{ W/kg}$.



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 26 of 35

14.1.3 5.6 GHz Band (U-NII 2C)

802.11n HT40 (802.11n HT40 (MCS 0) – Duty Cycle 100%									
DE E	Test	Dist		F	Averaged	Power	[dBm]	1 g SAF	[W/kg]	Plot
RF Exposure Conditions	Position	Dist. [mm]	Ch#	Freq. [MHz]	[MHz] Fast SAR T	Tune-up Limit	Meas.	Meas.	Scaled	No.
	Inner	0	134	5670	0.000	9.5	8.37			
	Outer	0	134	5670	0.253	9.5	8.37	0.222	0.288	
			102	5510	0.532	6.5	5.38			
	Upper	0	118	5590	0.677	7.5	6.28	0.672	0.890	
			134	5670	0.833	9.5	8.37	0.856	1.110	2
	w/ Headset	0	134	5670	0.737	9.5	8.37	0.843	1.094	
	w/ Neckband	0	134	5670	0.822	9.5	8.37	0.900	1.167	
Head-worn	w/ Eyewear	0	134	5670	0.669	9.5	8.37	0.777	1.008	
	w/ Neckband & Headset	0	134	5670	0.817	9.5	8.37	0.902	1.170	
	w/ Neckband & Headset (repeat #1)	0	134	5670	0.760	9.5	8.37	0.919	1.192	3
	w/ Eyewear & Headset	0	134	5670	0.688	9.5	8.37	0.811	1.052	
	Lower	0	134	5670	0.008	9.5	8.37			

Note(s):

SAR is not required for subsequent test configurations when the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is $\leq 1.2 \text{ W/kg}$.



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 27 of 35

14.2 SAR Measurement Variability

In accordance with the KDB 865664 D01, these additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The DUT should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is \geq 0.80 W/kg, repeat that measurement once.
- 3) Perform a 2nd repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a 3rd repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

14.2.1 Highest Measured SAR Configuration in Each Frequency Band

Frequency Band [MHz]	Air Interface	Standalone SAR [W/kg]
5250	WLAN 802.11a	0.758
5600	WLAN 802.11a	0.902

14.2.2 Repeated SAR Measurement Results

			Enganoman	Measured S	Largest to	
Band	Test Position	n Ch# Freque		Original	Repeated	Smallest SAR Ratio
WLAN 5.6 GHz (UNII-2C)	Upper	134	5670	0.902	0.919	1.02



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 28 of 35

14.3 Simultaneous Transmission SAR Analysis

WLAN cannot transmit simultaneously with Bluetooth since they share an antenna port.



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 34 of 35

16 Test Instruments

	Shielded Room S3									
Туре	Model	Serial No. (ID)	Manufacturer	Cal. Due						
E-Field Probe	EX3DV4	7321 (S-17)	SPEAG	2018/08/14						
DAE	DAE4	508 (S-3)	SPEAG	2018/08/03						
Robot	RX60L	F02/5R10A1/A/01 (S-7)	Stäubli	N/A						
Probe Alignment Unit	LB5/80	SE UKS 030 AA (S-13)	SPEAG	N/A						
Network Analyzer	E8357A	US41070304	Agilent	2017/10/23						
Dielectric Probe	DAK-3.5	1124 (S-32)	SPEAG	2018/08/08						
5GHz Dipole	D5GHzV2	1111 (S-31)	SPEAG	2017/09/19						
Signal Generator	MG3710A	6201171711 (B-41)	Anritsu	2017/11/06						
RF Power Amplifier	CGA020M602-2633R	B10840 (A-51)	R&K	N/A						
Directional Coupler	4226-20	03736 (D-87)	Narda Microwave	N/A						
Power Meter	E4417A	GB41290850 (B-51)	Agilent	2018/07/24						
Power Sensor	E9323A	US40411939 (B-59)	Agilent	2018/07/25						
Power Meter	ML2495A	1423001 (B-16)	Anritsu	2018/07/23						
Power Sensor	MA2411B	1339136 (B-18)	Anritsu	2018/07/23						
Attenuator	54A-10	W5675 (D-28)	Weinschel	2018/08/14						
RF Cable	SUCOFLEX102	14253/2 (C-52)	HUBER+SUHNER	2018/08/14						

NOTE: The calibration interval of the above test instruments is 12 months.



Model No. : EI-10 FCC ID : YSKK05

Standard : FCC Rules and Regulations Title 47 CFR Part 2

Page 35 of 35

17 Appendix

Refer to separated files for the following appendixes.

Appendix 1 - System Performance Check Plots

Appendix 2 - Highest SAR Test Plots

Appendix 3 - Dosimetric E-Field Probe Calibration Data

Appendix 4 – System Validation Dipole Calibration Data