



element

Exigent Sensors LLC

Omni 2.0

Antenna Pattern Measurements

Report: EXIG0024.1 Rev. 1, Issue Date: December 12, 2024



Approved by:

Johnny Candelas, Operations Manager

TABLE OF CONTENTS

| Section | Page Number |
|--|-------------|
| Revision History | 3 |
| Accreditations..... | 4 |
| Facilities | 5 |
| Product Description..... | 6 |
| Configurations | 7 |
| Modifications | 8 |
| Active 2D Antenna Pattern Measurements | 9 |
| End of Report..... | 26 |

REVISION HISTORY



| Revision Number | Description | Date (yyyy-mm-dd) | Page Number |
|-----------------|---|----------------------|-------------|
| 01 | Added picture of internal antenna | 2024-11-26 | 6 |
| | Added configurations page | 2024-11-26 | 7 |
| | Added test description page, including test equipment | 2024-11-26 | 9 |

ACCREDITATIONS AND AUTHORIZATIONS

United States

FCC - Designated by the FCC as a Telecommunications Certification Body (TCB). Certification chambers, Open Area Test Sites, and conducted measurement facilities are listed with the FCC.

A2LA - Each laboratory is accredited by A2LA to ISO / IEC 17025, and as a product certifier to ISO / IEC 17065 which allows Element to certify transmitters to FCC and IC specifications.

Canada

ISED - Recognized by Innovation, Science and Economic Development Canada as a Certification Body (CB) and as a CAB for the acceptance of test data.

European Union

European Commission – Recognized as an EU Notified Body validated for the EMCD and RED Directives.

United Kingdom

BEIS – Recognized by the UK as an Approved Body under the UK Radio Equipment and UK EMC Regulations.

Australia/New Zealand

ACMA - Recognized by ACMA as a CAB for the acceptance of test data.

Korea

MSIT / RRA - Recognized by KCC's RRA as a CAB for the acceptance of test data.

Japan

VCCI - Associate Member of the VCCI. Conducted and radiated measurement facilities are registered.

Taiwan

BSMI – Recognized by BSMI as a CAB for the acceptance of test data.

NCC - Recognized by NCC as a CAB for the acceptance of test data.

Singapore

IDA – Recognized by IDA as a CAB for the acceptance of test data.

Israel

MOC – Recognized by MOC as a CAB for the acceptance of test data.

Hong Kong

OFCA – Recognized by OFCA as a CAB for the acceptance of test data.

Vietnam

MIC – Recognized by MIC as a CAB for the acceptance of test data.

SCOPE

For details on the Scopes of our Accreditations, please visit:

[California](#)

[Minnesota](#)

[Oregon](#)

[Texas](#)

[Washington](#)



FACILITIES

Testing was performed at the following location(s)

| Location | Labs ⁽¹⁾ | Address | A2LA ⁽²⁾ | ISED ⁽³⁾ | BSMI ⁽⁴⁾ | VCCI ⁽⁵⁾ | CAB ⁽⁶⁾ | FDA ⁽⁷⁾ |
|--|---------------------|--|---------------------|---------------------|---------------------|---------------------|--------------------|--------------------|
| <input checked="" type="checkbox"/> California | OC01-17 | 41 Tesla Irvine, CA 92618 (949) 861-8918 | 3310.04 | 2834B | SL2-IN-E-1154R | A-0029 | US0158 | TL-55 |
| <input type="checkbox"/> Minnesota | MN01-11 | 9349 W Broadway Ave. Brooklyn Park, MN 55445 (612) 638-5136 | 3310.05 | 2834E | SL2-IN-E-1152R | A-0109 | US0175 | TL-57 |
| <input type="checkbox"/> Oregon | EV01-12 | 6775 NE Evergreen Pkwy #400 Hillsboro, OR 97124 (503) 844-4066 | 3310.02 | 2834D | SL2-IN-E-1017 | A-0108 | US0017 | TL-56 |
| <input type="checkbox"/> Plano Texas | PT01-15 | 1701 E Plano Pkwy, Ste 150 Plano, TX 75074 (972) 509-2566 | 214.19 | 32637 | SL2-IN-E-057R | A-0426 | US0054 | N/A |
| <input type="checkbox"/> Texas | TX01-09 | 3801 E Plano Pkwy Plano, TX 75074 (469) 304-5255 | 3310.03 | 2834G | SL2-IN-E-1158R | N/A | US0191 | TL-54 |
| <input type="checkbox"/> Washington | NC01-05 | 19201 120th Ave NE Bothell, WA 98011 (425) 984-6600 | 3310.06 | 2834F | SL2-IN-E-1153R | A-0110 | US0157 | TL-67 |
| <input type="checkbox"/> Offsite | N/A | See Product Description | N/A | N/A | N/A | N/A | N/A | N/A |

See data sheets for specific labs

- (1) The lab designations denote individual rooms within each location. (OC01, OC02, OC03, etc.)
- (2) A2LA Certificate No.
- (3) ISED Company No.
- (4) BSMI No.
- (5) VCCI Site Filing No.
- (6) CAB Identifier. Recognized Phase I CAB for ISED, ACMA, BSMI, IDA, KCC/RRA, MIC, MOC, NCC, OFCA
- (7) FDA ASCA No.



PRODUCT DESCRIPTION

Client and Equipment under Test (EUT) Information

| | |
|---------------------------------|------------------------|
| Company Name: | Exigent Sensors LLC |
| Address: | 11441 Markon Dr #1402 |
| City, State, Zip: | Garden Grove, CA 92841 |
| Test Requested By: | Chad Christensen |
| EUT: | Omni 2.0 |
| First Date of Test: | August 21, 2024 |
| Last Date of Test: | August 21, 2024 |
| Receipt Date of Samples: | August 21, 2024 |
| Equipment Design Stage: | Production |
| Equipment Condition: | No Damage |
| Purchase Authorization: | Verified |

Information Provided by the Party Requesting the Test


Functional Description of the EUT:

A photoelectric smoke and carbon monoxide alarm with a supplemental heat detector, designed for residential environments to detect dangerous levels of smoke, carbon monoxide, and heat. The device includes wireless interconnectivity, allowing it to alert nearby alarms. It operates using a proprietary radio protocol in the 902 - 928 MHz frequency band.

Testing Objective:

To obtain 3D antenna pattern measurements and calculated antenna performance values (gain, 3dB Beamwidth, etc)

Antenna Photo:



CONFIGURATIONS



Configuration EXIG0024-4

| EUT | | | |
|--------------------|---------------------|--------------------------|----------------------|
| Description | Manufacturer | Model/Part Number | Serial Number |
| OMNI 2.0 | Exigent Sensors LLC | OSSCO20AC | E7 |

MODIFICATIONS



Equipment Modifications

| Item | Date | Test | Modification | Note | Disposition of EUT |
|------|------------|---|--|---|---|
| 1 | 2024-08-21 | Active 3D Antenna Pattern Measurements | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test. |

2D ANTENNA PATTERN MEASUREMENTS



PSA-ESCI 2023.04.25.0

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data. The test data represents the configuration / operating mode/ model that produced the highest emission levels as compared to the specification limit.

MODES OF OPERATION

Sig Gen transmitting: 905.2 MHz, CW, 0 dB

Sig Gen transmitting: 913.2 MHz, CW, 0 dB

POWER SETTINGS INVESTIGATED

Battery

CONFIGURATIONS INVESTIGATED

EXIG0024-4

FREQUENCY RANGE INVESTIGATED

Start Frequency

902 MHz

Stop Frequency

915 MHz

TEST EQUIPMENT

| Description | Manufacturer | Model | ID | Last Cal. | Cal. Due |
|------------------------------|--------------------|----------------|------|------------|------------|
| Analyzer - Spectrum Analyzer | Agilent | N9010A | AFJ | 2024-02-14 | 2025-02-14 |
| Cable | ESM Cable Corp. | 30-1GHz Cables | OCW | 2023-12-29 | 2024-12-29 |
| Antenna - Biconilog | EMCO | 3142 | AXA | 2024-01-05 | 2026-01-05 |
| Antenna - Dipole | A.H. Systems, Inc. | FCC-4 | ADCA | 2023-08-23 | 2025-08-23 |
| Power Sensor | Agilent | E4412A | SQE | 2023-12-06 | 2024-12-06 |
| Meter - Power | Hewlett Packard | E4418A | SPQ | 2023-12-06 | 2024-12-06 |
| Generator - Signal | Agilent | E8257D | TGU | 2023-11-08 | 2026-11-08 |

TEST DESCRIPTION

was covered with RF absorbing cones. The reference antenna and EUT were placed on a block of approximately 1.8 m low permittivity foam.

A direct connect sample of the AUT was configured to transmit at Low and High channels. The output power of the conducted sample was measured and recorded in this report.

A signal generator was connected to the reference antenna with a low loss RF cable. To minimize the influence of the RF cable in the radiating pattern, the cable was lined with snap on ferrites at a separating distance of 10 cm.

A CW tone was then provided to the calibrated reference antenna and reference scan was then collected at the frequencies noted in this test report. The amplitude of the CW tone was measured and adjusted until it was confirmed to be the same level that was measured on the conducted sample.

Using the same test setup, the antenna under test (AUT) was placed into the chamber.

A polar plot was then collected at the antenna height of maximum field strength. This plot was then compared to the reference antenna scan. Using the antenna gain (dBi) of the reference antenna the absolute gain of the AUT was calculated.

RELATIVE GAIN



EmiR5 2023.08.29.0

PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 905.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency (MHz) **905.2**

Maximum Amplitude (dBuV/m) **92.63156**



Azimuth at Maximum **343°**

Minimum Amplitude (dBuV/m) **63.03156**

Azimuth at Minimum **66°**

3 dB Beamwidth **54°**

| | | | | | | | |
|-------|----|-------------------|---|-------------------|-----|--|--|
| Run # | 44 | Test Distance (m) | 3 | Antenna Height(s) | 1.5 | | |
|-------|----|-------------------|---|-------------------|-----|--|--|



RELATIVE GAIN



EmiR5 2023.08.29.0

PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 913.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency (MHz) 913.2

Maximum Amplitude (dBuV/m) 92.64096



Azimuth at Maximum 342°

Minimum Amplitude (dBuV/m) 54.94096

Azimuth at Minimum 66°

3 dB Beamwidth 50°

| | | | | | | | |
|-------|----|-------------------|---|-------------------|-----|--|--|
| Run # | 45 | Test Distance (m) | 3 | Antenna Height(s) | 1.5 | | |
|-------|----|-------------------|---|-------------------|-----|--|--|



RELATIVE GAIN



EmiR5 2023.08.29.0

PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 905.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency (MHz) **905.2**

Maximum Amplitude (dBuV/m) **89.53156**



Azimuth at Maximum **270°**

Minimum Amplitude (dBuV/m) **86.83156**

Azimuth at Minimum **140°**

Measurement Antenna Polarity **Vertical**
Antenna Under Test (AUT) Polarity **Vertical**

| | | | | | | | |
|-------|----|-------------------|---|-------------------|-----|--|--|
| Run # | 46 | Test Distance (m) | 3 | Antenna Height(s) | 1.5 | | |
|-------|----|-------------------|---|-------------------|-----|--|--|



RELATIVE GAIN



EmiR5 2023.08.29.0

PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 913.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency (MHz) **913.2**

Maximum Amplitude (dBuV/m) **90.04096**



Azimuth at Maximum **271°**

Minimum Amplitude (dBuV/m) **87.64096**

Azimuth at Minimum **293°**

Measurement Antenna Polarity **Vertical**
Antenna Under Test (AUT) Polarity **Vertical**

| | | | | | | | |
|-------|----|-------------------|---|-------------------|-----|--|--|
| Run # | 47 | Test Distance (m) | 3 | Antenna Height(s) | 1.5 | | |
|-------|----|-------------------|---|-------------------|-----|--|--|



ABSOLUTE GAIN



EmiR5 2023.08.29.0



PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 905.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency **905.2**
 Measurement Antenna Polarity **Horizontal**
 Antenna Under Test (AUT) Polarity **Horizontal**
 Maximum Absolute Gain of AUT (dBi) **1.05**
 Average Absolute Gain of AUT (dBi) **-5.85**

Absolute Gain of Reference Antenna (dBi) **0.95**
 Reference Antenna Relative Gain Max (dBuV/m) **92.63**
 AUT Relative Gain Max (dBuV/m) **92.63**
 Difference (Reference Antenna - AUT) (dB) **0.00**
 AUT Setup Loss (dB) **0.1**
 Correction Factor (Convert Relative to Absolute Gain) (dB) **91.58**

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN



EmiR5 2023.08.29.0



PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 905.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency **905.2**
 Measurement Antenna Polarity **Vertical**
 Antenna Under Test (AUT) Polarity **Horizontal**
 Maximum Absolute Gain of AUT (dBi) **-3.25**
 Average Absolute Gain of AUT (dBi) **-13.42**

Absolute Gain of Reference Antenna (dBi) **0.95**
 Reference Antenna Relative Gain Max (dBuV/m) **89.53**
 AUT Relative Gain Max (dBuV/m) **85.23**
 Difference (Reference Antenna - AUT) (dB) **4.30**
 AUT Setup Loss (dB) **0.1**
 Correction Factor (Convert Relative to Absolute Gain) (dB) **88.48**

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN



EmiR5 2023.08.29.0



PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 913.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency **913.2**
 Measurement Antenna Polarity **Horizontal**
 Antenna Under Test (AUT) Polarity **Horizontal**
 Maximum Absolute Gain of AUT (dBi) **-2.13**
 Average Absolute Gain of AUT (dBi) **-9.28**

Absolute Gain of Reference Antenna (dBi) **0.87**
 Reference Antenna Relative Gain Max (dBuV/m) **92.64**
 AUT Relative Gain Max (dBuV/m) **89.54**
 Difference (Reference Antenna - AUT) (dB) **3.10**
 AUT Setup Loss (dB) **0.1**
 Correction Factor (Convert Relative to Absolute Gain) (dB) **91.67**

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN



EmiR5 2023.08.29.0



PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 913.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency **913.2**
 Measurement Antenna Polarity **Vertical**
 Antenna Under Test (AUT) Polarity **Horizontal**
 Maximum Absolute Gain of AUT (dBi) **-5.23**
 Average Absolute Gain of AUT (dBi) **-14.52**

Absolute Gain of Reference Antenna (dBi) **0.87**
 Reference Antenna Relative Gain Max (dBuV/m) **90.04**
 AUT Relative Gain Max (dBuV/m) **83.94**
 Difference (Reference Antenna - AUT) (dB) **6.10**
 AUT Setup Loss (dB) **0**
 Correction Factor (Convert Relative to Absolute Gain) (dB) **89.17**

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN



EmiR5 2023.08.29.0



PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 905.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency **905.2**
 Measurement Antenna Polarity **Horizontal**
 Antenna Under Test (AUT) Polarity **Vertical**
 Maximum Absolute Gain of AUT (dBi) **-13.45**
 Average Absolute Gain of AUT (dBi) **-20.91**

Absolute Gain of Reference Antenna (dBi) **0.95**
 Reference Antenna Relative Gain Max (dBuV/m) **92.63**
 AUT Relative Gain Max (dBuV/m) **78.23**
 Difference (Reference Antenna - AUT) (dB) **14.40**
 AUT Setup Loss (dB) **0**
 Correction Factor (Convert Relative to Absolute Gain) (dB) **91.68**

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN



EmiR5 2023.08.29.0



PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 905.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency **905.2**
 Measurement Antenna Polarity **Vertical**
 Antenna Under Test (AUT) Polarity **Vertical**
 Maximum Absolute Gain of AUT (dBi) **2.85**
 Average Absolute Gain of AUT (dBi) **0.20**

Absolute Gain of Reference Antenna (dBi) **0.95**
 Reference Antenna Relative Gain Max (dBuV/m) **89.53**
 AUT Relative Gain Max (dBuV/m) **91.43**
 Difference (Reference Antenna - AUT) (dB) **-1.90**
 AUT Setup Loss (dB) **0**
 Correction Factor (Convert Relative to Absolute Gain) (dB) **88.58**

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN



EmiR5 2023.08.29.0



PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 913.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency **913.2**
 Measurement Antenna Polarity **Horizontal**
 Antenna Under Test (AUT) Polarity **Vertical**
 Maximum Absolute Gain of AUT (dBi) **-14.23**
 Average Absolute Gain of AUT (dBi) **-21.21**

Absolute Gain of Reference Antenna (dBi) **0.87**
 Reference Antenna Relative Gain Max (dBuV/m) **92.64**
 AUT Relative Gain Max (dBuV/m) **77.54**
 Difference (Reference Antenna - AUT) (dB) **15.10**
 AUT Setup Loss (dB) **0**
 Correction Factor (Convert Relative to Absolute Gain) (dB) **91.77**

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN





EmiR5 2023.08.29.0

PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 913.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

| | | | |
|------------------------------------|----------|--|-------|
| Frequency | 913.2 | Absolute Gain of Reference Antenna (dBi) | 0.87 |
| Measurement Antenna Polarity | Vertical | Reference Antenna Relative Gain Max (dBuV/m) | 90.04 |
| Antenna Under Test (AUT) Polarity | Vertical | AUT Relative Gain Max (dBuV/m) | 90.74 |
| Maximum Absolute Gain of AUT (dBi) | 1.57 | Difference (Reference Antenna - AUT) (dB) | -0.70 |
| Average Absolute Gain of AUT (dBi) | -1.31 | AUT Setup Loss (dB) | 0 |
| 3 dB Beamwidth | 125° | Correction Factor (Convert Relative to Absolute Gain) (dB) | 89.17 |

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN



EmiR5 2023.08.29.0



PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 905.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency **905.2**
 Measurement Antenna Polarity **Horizontal**
 Antenna Under Test (AUT) Polarity **on Side**
 Maximum Absolute Gain of AUT (dBi) **-4.35**
 Average Absolute Gain of AUT (dBi) **-13.10**

Absolute Gain of Reference Antenna (dBi) **0.95**
 Reference Antenna Relative Gain Max (dBuV/m) **92.63**
 AUT Relative Gain Max (dBuV/m) **87.33**
 Difference (Reference Antenna - AUT) (dB) **5.30**
 AUT Setup Loss (dB) **0**
 Correction Factor (Convert Relative to Absolute Gain) (dB) **91.68**

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN





EmiR5 2023.08.29.0

PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 24.9°C | |
| Job Site: | OC07 | Humidity: | 43.80% | |
| Serial Number: | E7 | Barometric Pres.: | 1013 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 905.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

| | | | |
|------------------------------------|----------|--|-------|
| Frequency | 905.2 | Absolute Gain of Reference Antenna (dBi) | 0.95 |
| Measurement Antenna Polarity | Vertical | Reference Antenna Relative Gain Max (dBuV/m) | 89.53 |
| Antenna Under Test (AUT) Polarity | on Side | AUT Relative Gain Max (dBuV/m) | 84.23 |
| Maximum Absolute Gain of AUT (dBi) | -4.35 | Difference (Reference Antenna - AUT) (dB) | 5.30 |
| Average Absolute Gain of AUT (dBi) | -11.00 | AUT Setup Loss (dB) | 0 |
| 3 dB Beamwidth | 38° | Correction Factor (Convert Relative to Absolute Gain) (dB) | 88.58 |

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN



EmiR5 2023.08.29.0



PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 26.1°C | |
| Job Site: | OC07 | Humidity: | 43.30% | |
| Serial Number: | E7 | Barometric Pres.: | 1012 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Sig Gen transmitting: 913.2 MHz, CW, 0 dB | | | |
| Deviations: | None | | | |
| Comments: | 6 dB attenuator | | | |

Frequency **913.2**
 Measurement Antenna Polarity **Horizontal**
 Antenna Under Test (AUT) Polarity **on Side**
 Maximum Absolute Gain of AUT (dBi) **-6.23**
 Average Absolute Gain of AUT (dBi) **-14.99**

Absolute Gain of Reference Antenna (dBi) **0.87**
 Reference Antenna Relative Gain Max (dBuV/m) **92.64**
 AUT Relative Gain Max (dBuV/m) **85.54**
 Difference (Reference Antenna - AUT) (dB) **7.10**
 AUT Setup Loss (dB) **0**
 Correction Factor (Convert Relative to Absolute Gain) (dB) **91.77**

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



ABSOLUTE GAIN





EmiR5 2023.08.29.0

PSA-ESCI 2023.12.23.0

| | | | | |
|-----------------|---|-------------------|------------|---|
| Work Order: | EXIG0024 | Date: | 2024-08-21 |  |
| Project: | None | Temperature: | 26.1°C | |
| Job Site: | OC07 | Humidity: | 43.30% | |
| Serial Number: | E7 | Barometric Pres.: | 1012 mbar | Tested by: Nolan De Ramos |
| EUT: | Omni 2.0 | | | |
| Configuration: | EXIG0024-4 | | | |
| Customer: | Exigent Sensors LLC | | | |
| Attendees: | Kevin Tain | | | |
| EUT Power: | Battery | | | |
| Operating Mode: | Transmitting: Low Channel 905.2 MHz, High Channel 913.2 MHz, Data Rate: FSK 10, Power Setting: 0XC0 | | | |
| Deviations: | None | | | |
| Comments: | None | | | |

| | | | |
|------------------------------------|----------|--|-------|
| Frequency | 913.2 | Absolute Gain of Reference Antenna (dBi) | 0.87 |
| Measurement Antenna Polarity | Vertical | Reference Antenna Relative Gain Max (dBuV/m) | 90.04 |
| Antenna Under Test (AUT) Polarity | on Side | AUT Relative Gain Max (dBuV/m) | 81.54 |
| Maximum Absolute Gain of AUT (dBi) | -7.63 | Difference (Reference Antenna - AUT) (dB) | 8.50 |
| Average Absolute Gain of AUT (dBi) | -13.37 | AUT Setup Loss (dB) | 0 |
| 3 dB Beamwidth | 37° | Correction Factor (Convert Relative to Absolute Gain) (dB) | 89.17 |

| Run # | Test Distance (m) | Antenna Height(s) | Results |
|-------|-------------------|-------------------|---------|
| | | | NA |



End of Test Report